

FINAL ANALYTICAL TEST REPORT

Envirolab Job Number: 17/08335
Issue Number: 1
Date: 14 December, 2017

Client: Geocon Site Investigations Ltd
15 Belmont Drive
Marple Bridge
Stockport
UK
SK6 5EA

Project Manager: Ian Walker; Jon Lord, Andrew Dickinson
Project Name: Finchley Road
Project Ref: GSI 0548
Order No: PO 17/0605
Date Samples Received: 07/12/17
Date Instructions Received: 08/12/17
Date Analysis Completed: 13/12/17

Prepared by:



Holly Neary-King
Administrative Assistant

Approved by:



Richard Wong
Client Manager

Envirolab Job Number: 17/08335

Client Project Name: Finchley Road

Client Project Ref: GSI 0548

Lab Sample ID	17/08335/1	17/08335/2							Units	Method ref
Client Sample No										
Client Sample ID	HP01	HP02								
Depth to Top	0.30	0.50								
Depth To Bottom										
Date Sampled	05-Dec-17	05-Dec-17								
Sample Type	Soil - ES	Soil - ES								
Sample Matrix Code	6	6AE								
% Stones >10mm _A	<0.1	4.6							% w/w	A-T-044
Total Organic Carbon _D ^{M#}	1.47	2.38							% w/w	A-T-032s
Chromium (hexavalent) _D	<1	<1							mg/kg	A-T-040s

Envirolab Job Number: 17/08335

Client Project Name: Finchley Road

Client Project Ref: GSI 0548

Lab Sample ID	17/08335/1	17/08335/2							Units	Method ref
Client Sample No										
Client Sample ID	HP01	HP02								
Depth to Top	0.30	0.50								
Depth To Bottom										
Date Sampled	05-Dec-17	05-Dec-17								
Sample Type	Soil - ES	Soil - ES								
Sample Matrix Code	6	6AE								
Asbestos in Soil (inc. matrix)										
Asbestos in soil [#]	NAD	NAD								A-T-045
Asbestos ACM - Suitable for Water Absorption Test?	N/A	N/A								

REPORT NOTES

General:

This report shall not be reproduced, except in full, without written approval from Envirolab.

All samples contained within this report, and any received with the same delivery, will be disposed of one month after the date of this report.

Analytical results reflect the quality of the sample at the time of analysis only.

Opinions and interpretations expressed are outside the scope of our accreditation.

If results are in italic font they are associated with an AQC failure and there is insufficient sample to repeat the analysis. These are not accredited and are unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling and, as a result, may be invalid.

Soil chemical analysis:

All results are reported as dry weight (<40°C).

For samples with Matrix Codes 1 - 6 natural stones, brick and concrete fragments >10mm and any extraneous material (visible glass, metal or twigs) are removed and excluded from the sample prior to analysis and reported results corrected to a whole sample basis. This is reported as '% stones >10mm'.

For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis and this supersedes any "A" subscripts

All analysis is performed on the sample as received for soil samples which are positive for asbestos or the client has informed asbestos may be present and/or if they are from outside the European Union and this supersedes any "D" subscripts.

TPH analysis of water by method A-T-007:

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

Electrical Conductivity of water by Method A-T-037:

Results greater than 12900µS/cm @ 25°C / 11550µS/cm @ 20°C fall outside the calibration range and as such are unaccredited.

Asbestos:

Asbestos in soil analysis is performed on a dried aliquot of the submitted sample and cannot guarantee to identify asbestos if only present in small numbers as discrete fibres/fragments in the original sample.

Stones etc. are not removed from the sample prior to analysis.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified as being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

Predominant Matrix Codes:

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER, 8 = Asbestos bulk ID sample.

Samples with Matrix Code 7 & 8 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our BSEN 17025 or MCERTS accreditations, with the exception of bulk asbestos which are BSEN 17025 accredited.

Secondary Matrix Codes:

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal,

E = contains roots/twigs.

Key:

IS indicates Insufficient Sample for analysis.

US indicates Unsuitable Sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Superscript "M" indicates method accredited to MCERTS.

Subscript "A" indicates analysis performed on the sample as received.

Subscript "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve

Please contact us if you need any further information.