



Robin O'Sullivan 33 Oppidans Road London NW3 3AG GTec Windows Limited 1st Floor Allied Sainif House 412 Greenford Road, Greenford Middlesex, UB6 9AH

Customer number: 80

Offer number: 20170043

Clerk in charge: Gipi Sagoo
Telephone No.:

EMail: qsaqoo.qtec@hotmail.com

Offer Robin O'Sullivan Date: 27.11.2017

<u>Internorm home pure / Timber/alu window HF210</u>

Cozy timber surface inside, protective aluminium outside

Gapless all around gluing of glass panes (I-tec glazing) ensures excellent stability, burglary protection as well as thermal insulation and sound reduction

Three continuous gaskets prevent water from entering on to the timber surface.



Symbolic photo

Your elements have the following common characteristics:

Glass spacer: Aluminium Glass coating: Light

Glazing: Double 24mm coated clear 4toughened/16Ar/b4toughened (1.1W/m²K, 32dB)

(2UA-AL_)

Hardware: Fully concealed hardware (V)

handle inside: designer handle G80 lockable in F1 (36400)

colour inside: spruce FI509 (FI509)

colour outside: Traffic white RAL9016 matt (M916)

Thermal insulation value window*: 1,20 W/m²K Sound insulation value window*: 33dB

*According to standard EN ISO 12567 or 10077 referring to a standard test window size of 1230x1480. Georgian/feature bars, thresholds etc. are not taken into consideration.

Deviations to this information are listed in the positions descriptions!

Internorm

Offer number: 20170043

Pos.	Quantity	Description	Price per unit GBP	Total price GBP
100	2,00 Pcs.	HF210 1-piece sash Internorm timber/aluminium window – home pure width: 1185mm, height: 1170mm, frame system: NR - frame 76mm, 1st sash Turn/tilt sash Opening direction: right, handle height from sash bottom bead: 398mm, Accessories hardware: with turn lock, key: 1, faulty operation safety device, slam protection,		
		Element version: connection bead/building connection hard foam plate (30PU) Extras: drainage towards bottom (or Pre-drilled f. screw fitting (21) Altitude up to 900 m		
2,00 Pcs.		HF210 1-piece sash Internorm timber/aluminium v width: 1185mm, height: 1170mr frame system: NR - frame 76mm,		1,886.46
		1st sash Turn/tilt sash Opening direction: left, handle height from sash bottom bead: 398mm, Accessories hardware: with turn lock, key: 1, faulty operation safety device, slam protection,		
		Element version: connection bead/building connection hard foam plate (30PU) Extras: drainage towards bottom (or Pre-drilled f. screw fitting (21) Altitude up to 900 m		
120	2,00 Pcs.	Timber/wood coupling profile system: HF210 Internorm timber/a length: 1170mm	18.60 Iu window - Home Pure	37.20

Offer number: 20170043

colour: Traffic white RAL9016 matt (M916)


Type of coupling: Coupling profile

130 9,00 Pcs.

Timber cover profile 30/11 fingerjointed 35,29

317,61

========



length: 3500mm,

colour inside: spruce FI509 (FI509),

SUM total		5,943.28
20,00 %	VAT	990.55
Sub total		4,952.73
Installation		825.00
Sub total		4,127.73

We would like to thank you for your enquiry

Please note that there may be internal plastering involved – this not included in the quote and would be an extra.

Payment Terms

40% initial payment (pre-order)

40% stage payment (on manufacture and delivery of goods from Austria)

20% final payment on completion of works.