LEGEND

External Finishes - The Yard - Ground Floor Level

T1: Granite Stone Sett Paving various rotation. Lengths between 100-250mm Width x 100 Depth. 24% Stirling Red/Grey (availability of Stirling red TBC by quarry) ,38% Millennium Green, 38% Sea Black 10mm joints 40mm bed



T2: Sea black setts. The setting-out of the setts within the perimeter of the fan is indicative and should be developed with the paving subcontractor along traditional laying techniques.

SEE DRAWING (90)-5003 FOR TYPICAL 'FAN' PAVING LAYOUTS TYP 1,2,3



T3: Lightly Sawn and Textured Granite Setts - Source from site. Lengths between 100-250mm x 80-125mm Width x APPROX. 100 Depth Sawn + Textured (Tolerance +/- 2mm). (sizes will be limited to available existing sett sizes & numbers.)

T5: Rough Reclaimed Granite Setts - Source from site Lengths between 100-250mm x 80-125mm Width x Appox 100 Depth Reclaimed, cleaned + laid with no finish. (sizes will be limited to available existing sett sizes & numbers.)

T6: Blue Engineering Brick Edge Strip. Size to match existing viaduct face. Wienerberger Staffordshire smooth blue perforated bricks 65mm x 215mm x 103mm

T7: Sea black paving zone to mark original ECD Viaduct footprint. Two rows border around periphery

T8: Tactile Granite Corduroy Paving of milled granite to match surrounding paving (Sea black). 800mm Length x 400mm Width x 50mm depth

T9: Single line of new granite setts threshold 100x100 Width x 100 Depth. Colour to match T1. **T9B**: Triple line of new granite setts threshold 100x100 Width x 100 Depth. Colour to match T1. Slot Drain - C250

Slot Drain - D400

Concrete encasing for Slot Drain Concrete encasing for Slot Drain

CF: Compressible filler

MJ: Expansion joint in paving See Structural Engineers Details

--- Fall lines shown indicatively , slopes to be executed with soft blends, no setts to be cut

SOP Setting out position for paving

Continuation on drawing (90) - 400402 Netrocoffer SN N 183507425 E 530008444 21.400 T1 N 183513277 E 529997291

DO NOT SCALE FROM THIS DRAWING - ALL DIMENSIONS TO BE CHECKED ON SITE

NOTES:

1. This drawing shows design intent only & is subject to detailed design specialists. 2. Figured dimensions only are to be taken from this drawing. All contractors must visit site & are responsible for taking & checking all dimensions relating to their work. BAM Design to be advised of any variation between drawings & site conditions.

3. All vertical dimensions to be taken from FFL, please note that all manufacturing schedules are to take this into account.

4. All dimensions are in millimetres unless noted otherwise. 5. All levels in meters unless noted otherwise. To be read in conjunction with -

ARUP drawings for structural frame, openings, supports


TO BE READ IN CONJUCTION WITH ALL ARCH DETAILS & SPECIFICATIONS


 Material finishes all to approved samples • Areas stated are approximate for pricing excercise only and are total area of BAMC scope of works boundary as indicated on drawing 4389-A-20-001

• Existing services covers in new / re-instated paving to be re-aligned with paving where possible - individual covers to be reviewed on site To be read in conjunction with -ARUP Structural Engineers drawings for sub base information

 ARUP / PBA drawings for drainage layouts BAMD Electrical Engineers drawings for services, lighting layouts • BAMD for waterproofing details (23 - Series)

• Miler Druck for paving finishes / cut patterns PBA - Drainage levels





KEY PLAN





project COAL DROPS YARD

DO NOT SCALE FROM THIS DRAWING.

SERIES OF DRAWINGS

ALL DIMENSIONS TO BE CHECKED ON SITE.

FOR REFERENCED VIEWS REFER TO KXC- 12- 001- A- ((90))

External Paving Layout - I2 WRA - L00 Yard Level - Sheet 05

scale As indicated @ A1

date 03/08/16 drg / doc ref. KXC-I2- 001-BD4389-A- (90)-400405 003