

office: 30 gratton tce., london, nw2 6qe telephone: 44 (0)208 450 5703 facsimile: 44 (0)208 450 5703 email: info@capeconstruction.net web: www.capeconstruction.net

34 Great James Street London WC1N 3HB

Method Statement the Renovation of the Existing Wall Panelling and the installation of the Replacement Panelling.



office: 30 gratton tce., london, nw2 6qe telephone: 44 (0)208 450 5703 facsimile: 44 (0)208 450 5703 email: info@capeconstruction.net web: www.capeconstruction.net

Cape Construction

Address: 30 Gratton Terrace, NW2 6QE

Tel: 02084505703

Project / Contract	34 Great James Street
Contractor	Cape Construction
Contact Details	Fatmir Paloja
Site Address	34 Great James Street

Emergency Contact Details		
Contact	Fatmir Paloja	Epameinondas Papaspyridakos
Tel	02035986354	02035986354
Mobile	07983572641	07950958626



office: 30 gratton tce., london, nw2 6qe telephone: 44 (0)208 450 5703 facsimile: 44 (0)208 450 5703 email: info@capeconstruction.net

web: www.capeconstruction.net

Task Description

This method statement describes the work process for the following:

- Renovation of the existing partitioning/panelling.
- Fabrication and construction of partitioning/panelling as per approved drawings and schedule of finishes for the project.
- Setting out of doorways.

Preparation for the Works

- Report to site office and inform site manager of arrival, collect permit to work where required.
- Attend any induction as required by the Principal Contractor.
- Put on your personal protective equipment.
- Take tools, equipment and materials to work area.
- Cordon off work area, if required to do so.
- Ensure the area to be worked and exit points are clear of obstruction and that safe access and egress is maintained.
- Check any electrical or hand tools for damage or faults; faulty or damaged tools must be removed from service immediately.
- Do not leave tools and equipment unattended at any time.
- Ensure operatives are fully aware of method statement and that all required approved drawings and specifications have been provided to the operatives.
- Site Foreman to be present and ensure all fabrication and installation of panelling is carried out in accordance with approved drawings, specification and approved method statement.
- All tools and equipment will be cleared to secure storage at the end of each shift.
- Staff will leave area clean and tidy at end of shift.
- · Report to site office and sign off permit to work where necessary.

Pre-Installation Setting out and Fabrication works

- Carefully remove the existing panelling and set aside for reuse.
- Using small tools carefully remove for storage and reinstatement existing wall.
- Existing wall panelling to be measured for reinstallation in accordance with set out drawing.
- New wall panelling to be measured for reinstallation in accordance with set out drawing.
- Check partitioning is level before installation of panelling.
- Existing skirting to be replaced with new, where required.
- Temporarily fix panelling, line up and check alignment (floor/ceiling and panels) and presence of any gaps.
- Make adjustments (i.e. fill any gaps) as necessary; no joints should be visible.



office: 30 gratton tce., london, nw2 6qe telephone: 44 (0)208 450 5703 facsimile: 44 (0)208 450 5703 email: info@capeconstruction.net web: www.capeconstruction.net

Lifting and Positioning

- All lifting work will be properly planned and supervised.
- Slinging work to be carried out by competent personnel.
- Loads will have a hand line attached.
- Slung loads will be guided into position and positioned by two men working from suitable access
 equipment.

Finishing

- Sand and fill, the surface should be smooth plain.
- Apply primer coat allow to dry for 2-3 hours sand any gaps or cracks and apply 2nd coat of primer.
- · Check again for any cracks or gaps and make even.
- Apply an intumescent paper faced with white fire card (ES/MP/900) to the inset panels using 1A
 adhesive. The stiles and rails of the panelling will be painted with 2 coats of HW02 clear intumescent
 paint and 1 coat of HW Enviroclear protective coat.
- Apply a thinned first coat of Trade Vinyl Silk (up to 1 part clean water to 5 parts paint.
- Apply 2 coats of Trade Vinyl Silk.

QA/QC Checks

- Operatives to co-ordinate with Site Forman to check wall panelling is installed as per client and listed building status requirements.
- Check for no scratches and damage to panels.
- Check all panels are aligned properly.
- Checks all panels are even and straight.
- Check for any gaps between panels.
- Check for cleanliness and avoid any dust particles.

Plant/ Equipment Required

PLANT required:	PLANT Certification required
Small Hand tools	Plant Inspection Tickets Electrical PAT Tested Toolbox Talks
Metal Grinder/Cutter	
Electrical Extension Cables	
Safety Harness	
Hand Wood Saw	
Drills	