

**Structural Calculations**  
**for a proposed new basement at**  
**10, Downside Crescent**  
**Belsize Park, London**  
**NW3**

**rodriguesassociates**  
1 Amwell Street  
London  
EC1R 1UL  
Telephone 020 7837 1133  
[www.rodriguesassociates.com](http://www.rodriguesassociates.com)  
May 2018

Structural Calculations

for

10, Downside Crescent  
Belsize Park, London NW3  
for

Asif Noor and Sabina Khan  
10 Downside Crescent, London  
NW3 2AP

Job No 1411

Rev	Date	Notes
-	01.05.18	First issue

## CONTENTS

Calculation plan	1
Resources	2
Area loads	3
Loads on side retaining wall toward No.12 Downside Crescent	4
Existing loads take down	5.1
Proposed loads take down	5.2
Water uplift check	6.1
Ground floor slab	6.2
Retaining wall under party wall	6.3
Rear retaining wall under rear extension	6.4
Side retaining wall under rear extension	6.5
Side retaining wall under rear extension – top beam	6.5B
Retaining wall under main building side wall	6.6
Structural methodology	Annex A
Movement monitoring specification and target location	Annex B

# 1. CALCULATION PLAN

This report contains the structural engineering initial calculations for a proposed new basement at No.10 Downside Crescent.

The development consists of a new basement built mostly under an existing semi-detached house and partially under a new rear extension. The extension over the basement will be single storey with flat roof. The access to the new basement and rear extension will be provided creating a new opening in the existing building back wall and a new flight under the main stair at ground floor. At the ground floor of the main building are also proposed internal alteration and demolition of existing partitions.

## 1.1. SUMMARY OF STRUCTURE

Proposed plan area – extension

Maximum plan dimensions	14.7m by 8.9m, say
Footprint area	114m <sup>2</sup>
Storeys	Basement, Ground, First & Second floor
Rear extension maximum height	3.6m over ground level
Basement maximum depth	3.5m below ground level

## 1.2. IMPOSED LOADS

The following imposed loads have been used

Typical imposed loads on pitched roofs	0.75 kN/m <sup>2</sup>
Typical imposed loads on floors	1.50 kN/m <sup>2</sup>
Partitions loads on floors (as imposed loads)	1.00 kN/m <sup>2</sup>
Typical imposed loads on flat roofs allowing for maintenance	1.50 kN/m <sup>2</sup>

## 1.3. REAR EXTENSION AND BASEMENT

The basement box will be realized with reinforced concrete walls and slabs. Rear extension walls at ground floor walls will be constructed as cavity block wall and the roof will be mainly built in timber elements and steel beams.

## **2. RESOURCES**

### **2.1 CODES & REFERENCES**

BS6399 Pt1 Loadings for buildings. Code of practice for dead and imposed loads.

BS6399 Pt2 Loadings for buildings. Code of practice for wind loads.

BS6399 Pt3 Loadings for buildings. Code of practice for imposed roof loads.

BS5269 Pt2 Structural use of Timber. Code of practice for permissible stress design, materials and workmanship.

BS5628 Pt1 Use of masonry. Structural use of unreinforced masonry.

BS5950 Pt1 Structural use of steelwork in building. Code of practice for design in simple and continuous construction hot rolled sections.

BS8110 Pt1 Structural use of concrete

Manual for the design of plain masonry in building structures – The Institution of Structural Engineers. July 1997.

### **2.2 SOFTWARE**

Tekla Structural Designer suite of design and analysis tools.

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>3. 1</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations:	<b>Area loads</b>	Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>
<u>Existing pitched roof</u>				
Dead	Tiles			0.77 kN/m <sup>2</sup>
	Battens and felt			0.05 kN/m <sup>2</sup>
	Rafters			0.15 kN/m <sup>2</sup>
	Insulation			0.01 kN/m <sup>2</sup>
	Services			0.05 kN/m <sup>2</sup>
	Plasterboard and skim coat			0.15 kN/m <sup>2</sup>
				<hr/> 1.18 kN/m <sup>2</sup>
	Roof Angle	51 °		1.88 kN/m <sup>2</sup>
Imposed				0.75 kN/m <sup>2</sup>
<u>Existing typical floor</u>				
Dead	Finishes			0.15 kN/m <sup>2</sup>
	Boarding			0.14 kN/m <sup>2</sup>
	Joists			0.15 kN/m <sup>2</sup>
	Insulation			0.05 kN/m <sup>2</sup>
	Services			0.05 kN/m <sup>2</sup>
	Lath and plaster			0.25 kN/m <sup>2</sup>
				<hr/> 0.79 kN/m <sup>2</sup>
Dead with tiles as finishes				0.96 kN/m <sup>2</sup>
Imposed				1.50 kN/m <sup>2</sup>
	Partitions			1.00 kN/m <sup>2</sup>
				<hr/> 2.50 kN/m <sup>2</sup>
<u>External brick wall</u>				
Dead	External render			0.60 kN/m <sup>2</sup>
	215mm brickwork			4.73 kN/m <sup>2</sup>
	Plaster			0.25 kN/m <sup>2</sup>
				<hr/> 5.58 kN/m <sup>2</sup>
<u>Internal loadbearing stud walls</u>				
Dead	Lath and plaster (both sides)			0.50 kN/m <sup>2</sup>
	Studs and blocking			0.15 kN/m <sup>2</sup>
				<hr/> 0.65 kN/m <sup>2</sup>
<u>Internal brick walls</u>				
Dead	Lath and plaster (both sides)			0.50 kN/m <sup>2</sup>
	102.5mm brickwork			2.24 kN/m <sup>2</sup>
				<hr/> 2.74 kN/m <sup>2</sup>

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>3. 2</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations:	<b>Area loads</b>	Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>
<u>Proposed ground floor slab</u>				
Dead	Finishes		0.30 kN/m <sup>2</sup>	
	Screed 50mm		1.00 kN/m <sup>2</sup>	
	Insulation		0.05 kN/m <sup>2</sup>	
	200mm slab		4.80 kN/m <sup>2</sup>	
	Services		0.15 kN/m <sup>2</sup>	
	Allowance for possible down-stand beams		0.50 kN/m <sup>2</sup>	
			<hr/>	
			6.80 kN/m <sup>2</sup>	
Patio	Stone slab as finishes		7.25 kN/m <sup>2</sup>	
Imposed			1.50 kN/m <sup>2</sup>	
	Partitions		1.00 kN/m <sup>2</sup>	
			<hr/>	
			2.50 kN/m <sup>2</sup>	
<u>Proposed basement floor slab</u>				
Dead	Finishes		0.15 kN/m <sup>2</sup>	
	Screed		1.80 kN/m <sup>2</sup>	
	Insulation		0.05 kN/m <sup>2</sup>	
	400mm slab		9.60 kN/m <sup>2</sup>	
	Services		0.15 kN/m <sup>2</sup>	
			<hr/>	
			11.75 kN/m <sup>2</sup>	
Imposed			1.50 kN/m <sup>2</sup>	
	Partitions		1.00 kN/m <sup>2</sup>	
			<hr/>	
			2.50 kN/m <sup>2</sup>	
<u>Proposed flat roof</u>				
Dead	Asphalt		0.40 kN/m <sup>2</sup>	
	Boarding		0.14 kN/m <sup>2</sup>	
	Insulation		0.05 kN/m <sup>2</sup>	
	Joists		0.15 kN/m <sup>2</sup>	
	Services		0.05 kN/m <sup>2</sup>	
	Plasterboard and skim coat		0.15 kN/m <sup>2</sup>	
			<hr/>	
			0.94 kN/m <sup>2</sup>	
	Imposed (allowing for maintenance of structure above)		1.50 kN/m <sup>2</sup>	
<u>Glazing</u>				
Dead	Glazing (Double)		0.65 kN/m <sup>2</sup>	
	Framing		0.20 kN/m <sup>2</sup>	
			<hr/>	
			0.85 kN/m <sup>2</sup>	
	Imposed (for horizontal glazing accounting for snow)		0.75 kN/m <sup>2</sup>	

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>	Job No.: 1411	Sheet No.: 3. 3	Rev.: -
Job title: 10 Downside Crescent			
Calculations: Area loads	Designed: ab	Date: 05/04/2018	Ckd: -

### Proposed external wall

Dead	External render	0.60 kN/m <sup>2</sup>
	100mm blockwork	1.50 kN/m <sup>2</sup>
	Insulation	0.05 kN/m <sup>2</sup>
	100mm block work	1.50 kN/m <sup>2</sup>
	Plasterboard and skim coat	0.15 kN/m <sup>2</sup>
		<hr/> 3.80 kN/m <sup>2</sup>



<b>rodriquesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriquesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>4. 1</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Loads on elements</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
Retaining wall in rear extension toward No.12										
Assumed load at foundation level of rear extension wall at No.12										
Flat roof/terrace @ N.12		0.94	1.50	2000			1.88	3.00		
External wall SW		5.58		3200			17.86			
TOT							19.74	3.00		

Assuming a distribution of the load at 45degree and a distance between this wall and the new retaining wall of 2m we can consider the following surcharge at 2.2m depth ( refer to image below )

$$(DL + LL) / (2m * 2) = 5.68 \text{ kN/m}^2$$


Assumed load at foundation level of party wall with No.12

External wall SW	4.73	2100	9.93
------------------	------	------	------

Assuming a distribution of the load at 45degree and a distance between this wall and the new retaining wall of 0.8m we can consider the following surcharge at 1m depth( refer to image below )

$$(DL + LL) / (0.8m * 2) = 6.21 \text{ kN/m}^2$$

For the retaining wall design will be considered a surcharge of 12 kN/m<sup>2</sup>.



<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>4. 2</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Loads on elements</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span  mm	Area loads		Width  mm	Location		UDL		Point loads			
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN		
Retaining wall under main building toward No.12												
Assumed load at foundation level of external wall at No.12												
roof		1.18	0.75	2000							2.36	1.50
attic		0.79	2.50	2000							1.58	5.00
wall SW at "f		4.98		3000							14.94	0.00
2F		0.79	2.50	2000							1.58	5.00
wall SW at 1F		4.98		3000							14.94	0.00
1F		0.79	2.50	2000							1.58	5.00
wall SW at GF		7.51		3000							22.53	0.00
TOT											59.51	16.50

Assuming a distribution of the load at 45degree and a distance between this wall and the new retaining wall of 2.4m we can consider the following surcharge at 2.7m depth ( refer to image below )

$$( DL + LL ) / ( 2m * 2 ) = 19.00 \text{ kN/m}^2$$


Assumed load at foundation level of party wall with No.12

External wall SW	4.73	2100	9.93
------------------	------	------	------

Assuming a distribution of the load at 45degree and a distance between this wall and the new retaining wall of 1.3m we can consider the following surcharge at 1.5m depth ( refer to image below )


$$( DL + LL ) / ( 1.3m * 2 ) = 3.82 \text{ kN/m}^2$$

For the retaining wall design will be considered a conservative surcharge of 25 kN/m<sup>2</sup> at the top.



<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>	Job No.: 1411	Sheet No.: 5.1. 1	Rev.: -
Job title: 10 Downside Crescent			
Calculations: Existing loads take down	Designed: ab	Date: 05/04/2018	Ckd: -

Picture below shows existing loaded walls at ground floor



WALL / PIER	DEAD LOAD kN/m	IMPOSED LOAD kN/m
1	73.00	4.00
2	17.00	4.00
3	11.00	2.00
4	50.00	4.00
5	50.00	6.00
6	46.00	2.00
7	36.00	4.00
8	41.00	14.00
9	40.00	10.00
10	20.00	24.00
11	24.00	20.00
12	66.00	13.00
13	38.00	5.00
14	59.00	4.00

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.1. 2</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Existing loads take down</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>WALL 1</b> ( assumed 330 thk party wall )										
roof ( both side )		1.88	0.75	2000			3.75	1.50		
2F ( both side )		0.79	2.50	350			0.28	0.88		
1F ( both side )		0.79	2.50	350			0.28	0.88		
party wall SW		7.76		8800			68.29	0.00		
							72.59	3.25		
<b>WALL 2</b> ( assumed 103 thk brick wall )										
roof		1.88	0.75	2250			4.22	1.69		
2F		0.79	2.50	350			0.28	0.88		
1F		0.79	2.50	350			0.28	0.88		
stud wall at 2F		0.65		2700			1.76	0.00		
stud wall at 1F		0.65		2900			1.89	0.00		
wall SW at GF		2.74		3000			8.23	0.00		
							16.64	3.44		
<b>WALL 3</b> ( assumed 103 thk brick wall )										
roof		1.88	0.75	0			0.00	0.00		
2F		0.79	2.50	350			0.28	0.88		
1F		0.79	2.50	350			0.28	0.88		
stud wall at 2F		0.65		0			0.00	0.00		
stud wall at 1F		0.65		2900			1.89	0.00		
wall SW at GF		2.74		3000			8.23	0.00		
							10.67	1.75		
<b>WALL 4</b> ( assumed 330 thk brick wall )										
roof		1.88	0.75	1000			1.88	0.75		
2F		0.79	2.50	0			0.00	0.00		
1F		0.79	2.50	1200			0.95	3.00		
wall SW		7.76		6000			46.56	0.00		
							49.38	3.75		
<b>WALL 5</b> ( assumed 330 thk brick wall )										
roof		1.88	0.75	1000			1.88	0.75		
2F		0.79	2.50	350			0.28	0.88		
1F		0.79	2.50	1550			1.22	3.88		
wall SW		7.76		6000			46.56	0.00		
							49.94	5.50		

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.1. 3</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Existing loads take down</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>


Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>WALL 6</b> ( assumed 215 thk brick wall )										
roof		1.88	0.75	1125			2.11	0.84		
2F		0.79	2.50	175			0.14	0.44		
1F		0.79	2.50	175			0.14	0.44		
wall SW		5.58		7800			43.52	0.00		
							45.91	1.72		
<b>WALL 7</b> ( assumed 215 thk brick wall )										
roof		1.88	0.75	350			0.66	0.26		
2F		0.79	2.50	0			0.00	0.00		
1F		0.79	2.50	1200			0.95	3.00		
wall SW		5.58		6000			33.48	0.00		
							35.08	3.26		
<b>WALL 8</b> ( assumed 215 thk brick wall )										
roof		1.88	0.75	1500			2.81	1.13		
2F		0.79	2.50	2450			1.94	6.13		
1F		0.79	2.50	2450			1.94	6.13		
wall SW		5.58		6000			33.48	0.00		
							40.16	13.38		
<b>WALL 9</b> ( assumed 215 thk brick wall )										
roof		1.88	0.75	1500			2.81	1.13		
2F		0.79	2.50	1750			1.38	4.38		
1F		0.79	2.50	1750			1.38	4.38		
wall SW		5.58		6000			33.48	0.00		
							39.06	9.88		
<b>WALL 10</b> ( assumed 103 thk brick wall )										
roof		1.88	0.75	200			0.38	0.15		
2F		0.79	2.50	4700			3.71	11.75		
1F		0.79	2.50	4700			3.71	11.75		
stud wall at 2F		0.65		2700			1.76	0.00		
stud wall at 1F		0.65		2900			1.89	0.00		
wall SW at GF		2.74		3000			8.23	0.00		
							19.67	23.65		

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.1. 4</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Existing loads take down</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>WALL 11</b> ( assumed 103 thk brick wall )										
roof		1.88	0.75	3500			6.56	2.63		
2F		0.79	2.50	3400			2.69	8.50		
1F		0.79	2.50	3400			2.69	8.50		
stud wall at 2F		0.65		2700			1.76	0.00		
stud wall at 1F		0.65		2900			1.89	0.00		
wall SW at GF		2.74		3000			8.23	0.00		
							23.81	19.63		
<b>WALL 12</b> ( assumed 330 thk brick wall )										
roof		1.88	0.75	1000			1.88	0.75		
2F		0.79	2.50	2300			1.82	5.75		
1F		0.79	2.50	2300			1.82	5.75		
wall SW		7.51		8000			60.08	0.00		
							65.59	12.25		
<b>WALL 13</b> ( assumed 330 thk brick wall )										
roof		1.88	0.75	1500			2.81	1.13		
2F		0.79	2.50	1000			0.79	2.50		
1F		0.79	2.50	350			0.28	0.88		
wall SW		7.51		4500			33.80	0.00		
							37.67	4.50		
<b>WALL 14</b> ( assumed 330 thk party wall )										
roof ( both side )		1.88	0.75	2000			3.75	1.50		
2F ( both side )		0.79	2.50	350			0.28	0.88		
1F ( both side )		0.79	2.50	350			0.28	0.88		
party wall SW		7.76		7000			54.32	0.00		
							58.62	3.25		

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>	Job No.: 1411	Sheet No.: 5.2. 1	Rev.: -
Job title: 10 Downside Crescent			
Calculations: Proposed loads take down	Designed: ab	Date: 05/04/2018	Ckd: -

Picture below shows proposed loaded walls at basement floor



WALL / PIER	DEAD LOAD kN/m - kN	IMPOSED LOAD kN/m - kN
1	32.00	3.00
2	108.00	6.00
3	94.00	6.00
4	52.00	12.00
5	119.00 kN	46.00 kN
6	45.00	9.00
7	60.00	10.00
8	78.00	10.00
9	86.00	8.00
10	27.00	0.00
11	84.00	5.00
12	73.00	7.00
13	37.00	4.00
14	43.00	6.00
15	89.00 kN	21.00 kN
16	28.00	4.00
17	114.00 kN	33.00 kN
18	54.00	24.00
19	54.00	30.00
20	103.00	16.00
21	72.00	7.00
22	99.00	14.00

11.71



<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.2. 3</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations:	<b>Proposed loads take down</b>	Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>PIER 5</b> from existing wall 8 (see sheet 5.1) from existing wall 9 @1F (see sheet 5.1) GF 6.80 2.50									58.24 49.10 10.88 118.22	19.39 21.73 4.00 45.12
<b>WALL 6</b> ( assumed 150 thk rc wall ) from existing wall 2 (see sheet 5.1) GF wall SW 6.80 2.50 3.75				2200 3500			16.64 14.96 13.13 44.73	3.44 5.50		
<b>WALL 7</b> ( assumed 330 thk rc wall ) from existing wall 3 (see sheet 5.1) GF wall SW 6.80 2.50 8.25				2950 3500			10.67 20.06 28.88 59.61	1.75 7.38		
<b>WALL 8</b> ( assumed 150 thk rc wall ) from existing wall 4 (see sheet 5.1) GF wall SW 6.80 2.50 3.75				2250 3500			49.38 15.30 13.13 77.81	3.75 5.63		
<b>WALL 9</b> ( assumed 330 thk rc wall ) from existing wall 5 (see sheet 5.1) GF wall SW 6.80 2.50 8.25				1000 3500			49.94 6.80 28.88 85.61	5.50 2.50		
<b>WALL 10</b> ( assumed 300 thk rc wall ) wall SW 7.50				3500			26.25	8.00		

<b>rodrigueassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodrigueassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.2. 4</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Proposed loads take down</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>


Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>WALL 11</b> ( assumed 330 thk rc wall ) from existing wall 6 (see sheet 5.1)							45.91	1.72		
GF		6.80	2.50	1250			8.50	3.13		
wall SW		8.25		3500			28.88			
							83.28	4.84		
<b>WALL 12</b> ( assumed 330 thk rc wall ) from existing wall 7 (see sheet 5.1)							35.08	3.26		
GF		6.80	2.50	1250			8.50	3.13		
wall SW		8.25		3500			28.88			
							72.46	6.39		
<b>WALL 13</b> ( assumed 300 thk rc wall )							9.86	3.63		
GF		6.80	2.50	1450			26.25			
wall SW		7.50		3500			36.11	3.63		
<b>WALL 14</b> ( assumed 300 thk rc wall )							15.98	5.88		
GF		6.80	2.50	2350			26.25			
wall SW		7.50		3500			42.23	5.88		
<b>PIER 15</b> from existing wall 8 (see sheet 5.1)									58.24	19.39
pier SW		7.50		3500					26.25	
GF		6.80	2.50						4.08	1.50
									88.57	20.89
<b>WALL 16</b> ( assumed 200 thk rc wall )							9.86	3.63		
GF		6.80	2.50	1450			17.50			
wall SW		5.00		3500			27.36	3.63		

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>5.2. 5</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations:	<b>Proposed loads take down</b>	Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads	
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN
<b>PIER 17</b>										
from existing wall 9 @ 1F (see sheet 5.1)									49.10	21.73
GF		6.80	2.50						6.80	2.50
new flat roof	2350	0.94	1.50	2250					4.97	7.93
cavity wall at GF	2350	3.80		3000					26.79	
pier SW		7.50		3500					26.25	
									113.91	32.16
<b>WALL 18</b>										
( assumed 200 thk rc wall )										
from existing wall 11 @ GF (see sheet 5.1)							23.81	19.63		
GF		6.80	2.50	1725			11.73	4.31		
wall SW		5.00		3500			17.50			
							53.04	23.94		
<b>WALL 19</b>										
( assumed 200 thk rc wall )										
from existing wall 10 @ GF (see sheet 5.1)							19.67	23.65		
GF		6.80	2.50	2400			16.32	6.00		
wall SW		5.00		3500			17.50			
							53.49	29.65		
<b>WALL 20</b>										
( assumed 330 thk rc wall )										
from existing wall 12 @ GF (see sheet 5.1)							65.59	12.25		
GF		6.80	2.50	1150			7.82	2.88		
wall SW		8.25		3500			28.88			
							102.28	15.13		
<b>WALL 21</b>										
( assumed 330 thk rc wall )										
from existing wall 13 @ GF (see sheet 5.1)							37.67	4.50		
GF		6.80	2.50	800			5.44	2.00		
wall SW		8.25		3500			28.88			
							71.99	6.50		
<b>WALL 22</b>										
( assumed 330 thk rc wall )										
from existing wall 12 @ GF (see sheet 5.1)							65.59	12.25		
GF		6.80	2.50	550			3.74	1.38		
wall SW		8.25		3500			28.88			
							98.20	13.63		

<b>rodriguesassociates</b> <b>1 Amwell Street, London, EC1R 1UL</b> <b>t: 020 7837 1133, e: www.rodriguesassociates.com</b>		Job No.: <b>1411</b>	Sheet No.: <b>6. 1</b>	Rev.: <b>-</b>
Job title: <b>10 Downside Crescent</b>				
Calculations: <b>Water uplift check</b>		Designed: <b>ab</b>	Date: <b>05/04/2018</b>	Ckd: <b>-</b>

Beam & Load description	Span mm	Area loads		Width mm	Location		UDL		Point loads		
		DL kN/m <sup>2</sup>	LL kN/m <sup>2</sup>		from mm	to mm	DL kN/m	LL kN/m	DL kN	LL kN	
<b>Check under main building</b>											
<u>Water uplift force</u>											
3m high water table	7600	30.00		9500					<b>2166.0</b>		
<u>Gravitational load</u>											
roof DL	7600	1.88		9500					135.4		
2F DL	7600	0.79		9500					57.0		
1F ext walls SW		22.00	kN/m3	22.06	m3				485.3		
1F DL	7600	0.79		9500					57.0		
GF side&spine wall SW		22.00	kN/m3	12.65	m3				278.4		
GF DL	7600	6.80		9500					491.0		
BF walls SW		24.00	kN/m3	26.79	m3				643.0		
BF DL	7600	11.75		9500					848.4		
TOT									<b>2995.4</b>	<b>PASS</b>	
<b>Check under rear extension</b>											
<u>Water uplift force</u>											
3m high water table	5100	30.00		6500					<b>994.5</b>		
<u>Gravitational load</u>											
roof DL	5100	0.94		5300					25.4		
GF walls SW	2800	3.80		6900					73.4		
GF DL	5300	6.80		6200					223.4		
BF walls SW		24.00	kN/m3	11.934	m3				286.4		
BF DL	5100	11.75		6500					389.5		
TOT									<b>998.2</b>	<b>PASS</b>	
<b>Check under rear courtyard</b>											
<u>Water uplift force</u>											
3m high water table	5000	30.00		3100					<b>465.0</b>		
<u>Gravitational load</u>											
GF DL	3800	6.80		3100					80.1		
BF walls SW		24.00	kN/m3	10.38	m3				249.1		
BF DL	5000	11.75		3100					182.1		
TOT									<b>511.3</b>	<b>PASS</b>	

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for GF slab				Start page no./Revision 6.2. 1	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

## RC SLAB DESIGN (BS8110:PART1:1997)

TEDDS calculation version 1.0.04

### TWO WAY SPANNING SLAB DEFINITION – SIMPLY SUPPORTED

Overall depth of slab  $h = 200$  mm

Outer sagging steel

Cover to outer tension reinforcement resisting sagging  $c_{sag} = 25$  mm

Trial bar diameter  $D_{tryx} = 10$  mm

Depth to outer tension steel (resisting sagging)

$$d_x = h - c_{sag} - D_{tryx}/2 = 170 \text{ mm}$$

Inner sagging steel

Trial bar diameter  $D_{tryy} = 10$  mm



Depth to inner tension steel (resisting sagging)

$$d_y = h - c_{sag} - D_{tryx} - D_{tryy}/2 = 160 \text{ mm}$$

Materials

Characteristic strength of reinforcement  $f_y = 500$  N/mm<sup>2</sup>

Characteristic strength of concrete  $f_{cu} = 40$  N/mm<sup>2</sup>




### **Two-way spanning slab (simple)**

### MAXIMUM DESIGN MOMENTS

Length of shorter side of slab  $l_x = 4.300$  m

Length of longer side of slab  $l_y = 4.800$  m

Design ultimate load per unit area  $n_s = 13.5$  kN/m<sup>2</sup>

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for GF slab				Start page no./Revision 6.2. 2	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

#### Moment coefficients

$$\alpha_{sx} = (l_y / l_x)^4 / (8 \times (1 + (l_y / l_x)^4)) = \mathbf{0.076}$$

$$\alpha_{sy} = (l_y / l_x)^2 / (8 \times (1 + (l_y / l_x)^4)) = \mathbf{0.061}$$

#### Maximum moments per unit width - simply supported slabs

$$m_{sx} = \alpha_{sx} \times n_s \times l_x^2 = \mathbf{19.0 \text{ kNm/m}}$$

$$m_{sy} = \alpha_{sy} \times n_s \times l_x^2 = \mathbf{15.2 \text{ kNm/m}}$$

#### **CONCRETE SLAB DESIGN – SAGGING – OUTER LAYER OF STEEL (CL 3.5.4)**

Design sagging moment (per m width of slab)  $m_{sx} = \mathbf{19.0 \text{ kNm/m}}$

Moment Redistribution Factor  $\beta_{bx} = \mathbf{1.0}$

#### **Area of reinforcement required**

$$K_x = \text{abs}(m_{sx}) / (d_x^2 \times f_{cu}) = \mathbf{0.016}$$

$$K'_x = \min(0.156, (0.402 \times (\beta_{bx} - 0.4)) - (0.18 \times (\beta_{bx} - 0.4)^2)) = \mathbf{0.156}$$

*Outer compression steel not required to resist sagging*

#### **Slab requiring outer tension steel only - bars (sagging)**

$$z_x = \min((0.95 \times d_x), (d_x \times (0.5 + \sqrt{(0.25 - K_x / 0.9)}))) = \mathbf{162 \text{ mm}}$$

$$\text{Neutral axis depth } x_x = (d_x - z_x) / 0.45 = \mathbf{19 \text{ mm}}$$

#### Area of tension steel required

$$A_{sx\_req} = \text{abs}(m_{sx}) / (1/\gamma_{ms} \times f_y \times z_x) = \mathbf{270 \text{ mm}^2/\text{m}}$$

#### **Tension steel**

**Provide 10 dia bars @ 200 centres outer tension steel resisting sagging**

$$A_{sx\_prov} = A_{sx} = \mathbf{393 \text{ mm}^2/\text{m}}$$

*Area of outer tension steel provided sufficient to resist sagging*

#### **Concrete Slab Design - Sagging - Inner layer of steel (cl. 3.5.4)**

Design sagging moment (per m width of slab)  $m_{sy} = \mathbf{15.2 \text{ kNm/m}}$

Moment Redistribution Factor  $\beta_{by} = \mathbf{1.0}$

#### **Area of reinforcement required**

$$K_y = \text{abs}(m_{sy}) / (d_y^2 \times f_{cu}) = \mathbf{0.015}$$

$$K'_y = \min(0.156, (0.402 \times (\beta_{by} - 0.4)) - (0.18 \times (\beta_{by} - 0.4)^2)) = \mathbf{0.156}$$


*Inner compression steel not required to resist sagging*

#### **Slab requiring inner tension steel only - bars (sagging)**

$$z_y = \min((0.95 \times d_y), (d_y \times (0.5 + \sqrt{(0.25 - K_y / 0.9)}))) = \mathbf{152 \text{ mm}}$$

$$\text{Neutral axis depth } x_y = (d_y - z_y) / 0.45 = \mathbf{18 \text{ mm}}$$

#### Area of tension steel required

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for GF slab				Start page no./Revision 6.2. 3	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

$$A_{sy\_req} = \text{abs}(m_{sy}) / (1/\gamma_{ms} \times f_y \times z_y) = 230 \text{ mm}^2/\text{m}$$

#### Tension steel

**Provide 10 dia bars @ 200 centres inner tension steel resisting sagging**

$$A_{sy\_prov} = A_{sy} = 393 \text{ mm}^2/\text{m}$$

**Area of inner tension steel provided sufficient to resist sagging**

#### **Check min and max areas of steel resisting sagging**

Total area of concrete  $A_c = h = 200000 \text{ mm}^2/\text{m}$

Minimum % reinforcement  $k = 0.13 \%$

$$A_{st\_min} = k \times A_c = 260 \text{ mm}^2/\text{m}$$

$$A_{st\_max} = 4 \% \times A_c = 8000 \text{ mm}^2/\text{m}$$

Steel defined:

Outer steel resisting sagging  $A_{sx\_prov} = 393 \text{ mm}^2/\text{m}$

**Area of outer steel provided (sagging) OK**

Inner steel resisting sagging  $A_{sy\_prov} = 393 \text{ mm}^2/\text{m}$

**Area of inner steel provided (sagging) OK**

#### **SHEAR RESISTANCE OF CONCRETE SLABS (CL 3.5.5)**

##### **Outer tension steel resisting sagging moments**

Depth to tension steel from compression face  $d_x = 170 \text{ mm}$

Area of tension reinforcement provided (per m width of slab)  $A_{sx\_prov} = 393 \text{ mm}^2/\text{m}$

Design ultimate shear force (per m width of slab)  $V_x = 29 \text{ kN/m}$

Characteristic strength of concrete  $f_{cu} = 40 \text{ N/mm}^2$

##### **Applied shear stress**

$$v_x = V_x / d_x = 0.17 \text{ N/mm}^2$$

##### **Check shear stress to clause 3.5.5.2**

$$v_{allowable} = \min((0.8 \text{ N}^{1/2}/\text{mm}) \times \sqrt{f_{cu}}, 5 \text{ N/mm}^2) = 5.00 \text{ N/mm}^2$$

**Shear stress - OK**

##### **Shear stresses to clause 3.5.5.3**

##### **Design shear stress**

$$f_{cu\_ratio} = \text{if } (f_{cu} > 40 \text{ N/mm}^2, 40/25, f_{cu}/(25 \text{ N/mm}^2)) = 1.600$$


$$v_{cx} = 0.79 \text{ N/mm}^2 \times \min(3, 100 \times A_{sx\_prov} / d_x)^{1/3} \times \max(0.67, (400 \text{ mm} / d_x)^{1/4}) / 1.25 \times f_{cu\_ratio}^{1/3}$$

$$v_{cx} = 0.56 \text{ N/mm}^2$$

Applied shear stress

$$v_x = 0.17 \text{ N/mm}^2$$

**No shear reinforcement required**

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for GF slab				Start page no./Revision 6.2. 4	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

### **SHEAR RESISTANCE OF CONCRETE SLABS (CL 3.5.5)**

#### **Inner tension steel resisting sagging moments**

Depth to tension steel from compression face  $d_y = 160$  mm

Area of tension reinforcement provided (per m width of slab)  $A_{sy\_prov} = 393$  mm<sup>2</sup>/m

Design ultimate shear force (per m width of slab)  $V_y = 32$  kN/m

Characteristic strength of concrete  $f_{cu} = 40$  N/mm<sup>2</sup>

#### **Applied shear stress**

$v_y = V_y / d_y = 0.20$  N/mm<sup>2</sup>

#### **Check shear stress to clause 3.5.5.2**

$V_{allowable} = \min((0.8 \text{ N}^{1/2}/\text{mm}) \times \sqrt{f_{cu}}, 5 \text{ N/mm}^2) = 5.00$  N/mm<sup>2</sup>

**Shear stress - OK**

#### **Shear stresses to clause 3.5.5.3**

##### **Design shear stress**

$f_{cu\_ratio} = \text{if } (f_{cu} > 40 \text{ N/mm}^2, 40/25, f_{cu}/(25 \text{ N/mm}^2)) = 1.600$

$v_{cy} = 0.79 \text{ N/mm}^2 \times \min(3, 100 \times A_{sy\_prov} / d_y)^{1/3} \times \max(0.67, (400 \text{ mm}) / d_y)^{1/4} / 1.25 \times f_{cu\_ratio}^{1/3}$

$v_{cy} = 0.58$  N/mm<sup>2</sup>

Applied shear stress

$v_y = 0.20$  N/mm<sup>2</sup>

**No shear reinforcement required**

### **CONCRETE SLAB DEFLECTION CHECK (CL 3.5.7)**

Slab span length  $l_x = 4.300$  m

Design ultimate moment in shorter span per m width  $m_{sx} = 19$  kNm/m

Depth to outer tension steel  $d_x = 170$  mm

#### **Tension steel**

Area of outer tension reinforcement provided  $A_{sx\_prov} = 393$  mm<sup>2</sup>/m

Area of tension reinforcement required  $A_{sx\_req} = 270$  mm<sup>2</sup>/m

Moment Redistribution Factor  $\beta_{bx} = 1.00$

#### **Modification Factors**

Basic span / effective depth ratio (Table 3.9)  $\text{ratio}_{\text{span\_depth}} = 20$


The modification factor for spans in excess of 10m (ref. cl 3.4.6.4) has not been included.

$f_s = 2 \times f_y \times A_{sx\_req} / (3 \times A_{sx\_prov} \times \beta_{bx}) = 229.3$  N/mm<sup>2</sup>

$\text{factor}_{\text{tens}} = \min(2, 0.55 + (477 \text{ N/mm}^2 - f_s) / (120 \times (0.9 \text{ N/mm}^2 + m_{sx} / d_x^2))) = 1.876$

#### **Calculate Maximum Span**



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for GF slab				Start page no./Revision 6.2. 5	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

This is a simplified approach and further attention should be given where special circumstances exist. Refer to clauses 3.4.6.4 and 3.4.6.7.

$$\text{Maximum span } l_{\max} = \text{ratio}_{\text{span\_depth}} \times \text{factor}_{\text{tens}} \times d_x = \mathbf{6.38 \text{ m}}$$

#### Check the actual beam span

$$\text{Actual span/depth ratio } l_x / d_x = \mathbf{25.29}$$

$$\text{Span depth limit } \text{ratio}_{\text{span\_depth}} \times \text{factor}_{\text{tens}} = \mathbf{37.52}$$

**Span/Depth ratio check satisfied**

#### CHECK OF NOMINAL COVER (SAGGING) – (BS8110:PT 1, TABLE 3.4)

$$\text{Slab thickness } h = \mathbf{200 \text{ mm}}$$

$$\text{Effective depth to bottom outer tension reinforcement } d_x = \mathbf{170.0 \text{ mm}}$$

$$\text{Diameter of tension reinforcement } D_x = \mathbf{10 \text{ mm}}$$

$$\text{Diameter of links } L_{\text{diat}} = \mathbf{0 \text{ mm}}$$

Cover to outer tension reinforcement

$$C_{\text{tenx}} = h - d_x - D_x / 2 = \mathbf{25.0 \text{ mm}}$$


Nominal cover to links steel

$$C_{\text{nomx}} = C_{\text{tenx}} - L_{\text{diat}} = \mathbf{25.0 \text{ mm}}$$

Permissible minimum nominal cover to all reinforcement (Table 3.4)


$$C_{\min} = \mathbf{25 \text{ mm}}$$

**Cover over steel resisting sagging OK**

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	retaining wall under party wall				6.3. 1	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

## RETAINING WALL ANALYSIS (BS 8002:1994)

TEDDS calculation version 1.2.01.06



### Wall details

Retaining wall type  
Height of retaining wall stem  
Thickness of wall stem  
Length of toe  
Length of heel  
Overall length of base  
Thickness of base  
Depth of downstand  
Position of downstand  
Thickness of downstand  
Height of retaining wall  
Depth of cover in front of wall  
Depth of unplanned excavation  
Height of ground water behind wall  
Height of saturated fill above base  
Density of wall construction  
Density of base construction  
Angle of rear face of wall  
Angle of soil surface behind wall  
Effective height at virtual back of wall


### Cantilever propped at both

$h_{\text{stem}} = 3100$  mm  
 $t_{\text{wall}} = 330$  mm  
 $l_{\text{toe}} = 650$  mm  
 $l_{\text{heel}} = 0$  mm  
 $l_{\text{base}} = l_{\text{toe}} + l_{\text{heel}} + t_{\text{wall}} = 980$  mm  
 $t_{\text{base}} = 400$  mm  
 $d_{\text{ds}} = 0$  mm  
 $l_{\text{ds}} = 15$  mm  
 $t_{\text{ds}} = 400$  mm  
 $h_{\text{wall}} = h_{\text{stem}} + t_{\text{base}} + d_{\text{ds}} = 3500$  mm  
 $d_{\text{cover}} = 0$  mm  
 $d_{\text{exc}} = 0$  mm  
 $h_{\text{water}} = 3000$  mm  
 $h_{\text{sat}} = \max(h_{\text{water}} - t_{\text{base}} - d_{\text{ds}}, 0 \text{ mm}) = 2600$  mm  
 $\gamma_{\text{wall}} = 23.6$  kN/m<sup>3</sup>  
 $\gamma_{\text{base}} = 23.6$  kN/m<sup>3</sup>  
 $\alpha = 90.0$  deg  
 $\beta = 0.0$  deg  
 $h_{\text{eff}} = h_{\text{wall}} + l_{\text{heel}} \times \tan(\beta) = 3500$  mm

### Retained material details

Mobilisation factor  
Moist density of retained material

$M = 1.5$   
 $\gamma_m = 18.0$  kN/m<sup>3</sup>

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>retaining wall under party wall</b>				Start page no./Revision <b>6.3. 2</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

Saturated density of retained material

$$\gamma_s = 21.0 \text{ kN/m}^3$$

Design shear strength

$$\phi' = 18.6 \text{ deg}$$

Angle of wall friction

$$\delta = 0.0 \text{ deg}$$

#### Base material details

Firm clay

Moist density

$$\gamma_{mb} = 18.0 \text{ kN/m}^3$$

Design shear strength

$$\phi'_b = 16.5 \text{ deg}$$

Design base friction

$$\delta_b = 18.6 \text{ deg}$$

Allowable bearing pressure

$$P_{\text{bearing}} = 150 \text{ kN/m}^2$$

#### Using Coulomb theory

Active pressure coefficient for retained material

$$K_a = \sin(\alpha + \phi')^2 / (\sin(\alpha)^2 \times \sin(\alpha - \delta) \times [1 + \sqrt{(\sin(\phi' + \delta) \times \sin(\phi' - \beta) / (\sin(\alpha - \delta) \times \sin(\alpha + \beta)))})^2] = 0.516$$

Passive pressure coefficient for base material

$$K_p = \sin(90 - \phi'_b)^2 / (\sin(90 - \delta_b) \times [1 - \sqrt{(\sin(\phi'_b + \delta_b) \times \sin(\phi'_b) / (\sin(90 + \delta_b)))})^2] = 2.835$$

#### At-rest pressure

At-rest pressure for retained material

$$K_0 = 1 - \sin(\phi') = 0.681$$

#### Loading details

Surcharge load on plan

$$\text{Surcharge} = 10.0 \text{ kN/m}^2$$

Applied vertical dead load on wall

$$W_{\text{dead}} = 79.0 \text{ kN/m}$$

Applied vertical live load on wall

$$W_{\text{live}} = 5.6 \text{ kN/m}$$

Position of applied vertical load on wall

$$l_{\text{load}} = 815 \text{ mm}$$

Applied horizontal dead load on wall


$$F_{\text{dead}} = 0.0 \text{ kN/m}$$

Applied horizontal live load on wall


$$F_{\text{live}} = 0.0 \text{ kN/m}$$

Height of applied horizontal load on wall

$$h_{\text{load}} = 0 \text{ mm}$$



Loads shown in kN/m, pressures shown in kN/m²

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	retaining wall under party wall				6.3. 3	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

### Vertical forces on wall

Wall stem	$W_{wall} = h_{stem} \times t_{wall} \times \gamma_{wall} = 24.1 \text{ kN/m}$
Wall base	$W_{base} = l_{base} \times t_{base} \times \gamma_{base} = 9.3 \text{ kN/m}$
Applied vertical load	$W_v = W_{dead} + W_{live} = 84.6 \text{ kN/m}$
Total vertical load	$W_{total} = W_{wall} + W_{base} + W_v = 118 \text{ kN/m}$

### Horizontal forces on wall

Surcharge	$F_{sur} = K_a \times \text{Surcharge} \times h_{eff} = 18.1 \text{ kN/m}$
Moist backfill above water table	$F_{m\_a} = 0.5 \times K_a \times \gamma_m \times (h_{eff} - h_{water})^2 = 1.2 \text{ kN/m}$
Moist backfill below water table	$F_{m\_b} = K_a \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = 13.9 \text{ kN/m}$
Saturated backfill	$F_s = 0.5 \times K_a \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = 26 \text{ kN/m}$
Water	$F_{water} = 0.5 \times h_{water}^2 \times \gamma_{water} = 44.1 \text{ kN/m}$
Total horizontal load	$F_{total} = F_{sur} + F_{m\_a} + F_{m\_b} + F_s + F_{water} = 103.3 \text{ kN/m}$

### Calculate total propping force

Passive resistance of soil in front of wall	$F_p = 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = 3.9 \text{ kN/m}$
Propping force	$F_{prop} = \max(F_{total} - F_p - (W_{total} - W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$
	$F_{prop} = 61.6 \text{ kN/m}$

### Overturning moments

Surcharge	$M_{sur} = F_{sur} \times (h_{eff} - 2 \times d_{ds}) / 2 = 31.6 \text{ kNm/m}$
Moist backfill above water table	$M_{m\_a} = F_{m\_a} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = 3.7 \text{ kNm/m}$
Moist backfill below water table	$M_{m\_b} = F_{m\_b} \times (h_{water} - 2 \times d_{ds}) / 2 = 20.9 \text{ kNm/m}$
Saturated backfill	$M_s = F_s \times (h_{water} - 3 \times d_{ds}) / 3 = 26 \text{ kNm/m}$
Water	$M_{water} = F_{water} \times (h_{water} - 3 \times d_{ds}) / 3 = 44.1 \text{ kNm/m}$
Total overturning moment	$M_{ot} = M_{sur} + M_{m\_a} + M_{m\_b} + M_s + M_{water} = 126.4 \text{ kNm/m}$

### Restoring moments

Wall stem	$M_{wall} = W_{wall} \times (l_{toe} + t_{wall} / 2) = 19.7 \text{ kNm/m}$
Wall base	$M_{base} = W_{base} \times l_{base} / 2 = 4.5 \text{ kNm/m}$
Design vertical dead load	$M_{dead} = W_{dead} \times l_{load} = 64.4 \text{ kNm/m}$
Total restoring moment	$M_{rest} = M_{wall} + M_{base} + M_{dead} = 88.6 \text{ kNm/m}$

### Check bearing pressure

Total vertical reaction	$R = W_{total} = 118.0 \text{ kN/m}$
Distance to reaction	$x_{bar} = l_{base} / 2 = 490 \text{ mm}$
Eccentricity of reaction	$e = \text{abs}((l_{base} / 2) - x_{bar}) = 0 \text{ mm}$


**Reaction acts within middle third of base**

Bearing pressure at toe	$p_{toe} = (R / l_{base}) - (6 \times R \times e / l_{base}^2) = 120.4 \text{ kN/m}^2$
Bearing pressure at heel	$p_{heel} = (R / l_{base}) + (6 \times R \times e / l_{base}^2) = 120.4 \text{ kN/m}^2$

**PASS - Maximum bearing pressure is less than allowable bearing pressure**

### Calculate propping forces to top and base of wall

Propping force to top of wall	$F_{prop\_top} = (M_{ot} - M_{rest} + R \times l_{base} / 2 - F_{prop} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = 25.230 \text{ kN/m}$
Propping force to base of wall	$F_{prop\_base} = F_{prop} - F_{prop\_top} = 36.396 \text{ kN/m}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	retaining wall under party wall				6.3. 4	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

## RETAINING WALL DESIGN (BS 8002:1994)

TEDDS calculation version 1.2.01.06

### Ultimate limit state load factors

Dead load factor  $\gamma_{f_d} = 1.4$

Live load factor  $\gamma_{f_l} = 1.6$

Earth and water pressure factor  $\gamma_{f_e} = 1.4$

### Factored vertical forces on wall

Wall stem  $W_{wall_f} = \gamma_{f_d} \times h_{stem} \times t_{wall} \times \gamma_{wall} = 33.8 \text{ kN/m}$

Wall base  $W_{base_f} = \gamma_{f_d} \times l_{base} \times t_{base} \times \gamma_{base} = 13 \text{ kN/m}$

Applied vertical load  $W_{v_f} = \gamma_{f_d} \times W_{dead} + \gamma_{f_l} \times W_{live} = 119.6 \text{ kN/m}$

Total vertical load  $W_{total_f} = W_{wall_f} + W_{base_f} + W_{v_f} = 166.3 \text{ kN/m}$

### Factored horizontal at-rest forces on wall

Surcharge  $F_{sur_f} = \gamma_{f_l} \times K_0 \times \text{Surcharge} \times h_{eff} = 38.1 \text{ kN/m}$

Moist backfill above water table  $F_{m_a_f} = \gamma_{f_e} \times 0.5 \times K_0 \times \gamma_m \times (h_{eff} - h_{water})^2 = 2.1 \text{ kN/m}$

Moist backfill below water table  $F_{m_b_f} = \gamma_{f_e} \times K_0 \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = 25.7 \text{ kN/m}$

Saturated backfill  $F_{s_f} = \gamma_{f_e} \times 0.5 \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = 48 \text{ kN/m}$

Water  $F_{water_f} = \gamma_{f_e} \times 0.5 \times h_{water}^2 \times \gamma_{water} = 61.8 \text{ kN/m}$

Total horizontal load  $F_{total_f} = F_{sur_f} + F_{m_a_f} + F_{m_b_f} + F_{s_f} + F_{water_f} = 175.8 \text{ kN/m}$

### Calculate total propping force

Passive resistance of soil in front of wall  $F_{p_f} = \gamma_{f_e} \times 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = 5.4 \text{ kN/m}$

Propping force  $F_{prop_f} = \max(F_{total_f} - F_{p_f} - (W_{total_f} - \gamma_{f_l} \times W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$

$F_{prop_f} = 117.5 \text{ kN/m}$

### Factored overturning moments

Surcharge  $M_{sur_f} = F_{sur_f} \times (h_{eff} - 2 \times d_{ds}) / 2 = 66.7 \text{ kNm/m}$

Moist backfill above water table  $M_{m_a_f} = F_{m_a_f} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = 6.8 \text{ kNm/m}$

Moist backfill below water table  $M_{m_b_f} = F_{m_b_f} \times (h_{water} - 2 \times d_{ds}) / 2 = 38.6 \text{ kNm/m}$

Saturated backfill  $M_{s_f} = F_{s_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 48 \text{ kNm/m}$

Water  $M_{water_f} = F_{water_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 61.8 \text{ kNm/m}$

Total overturning moment  $M_{ot_f} = M_{sur_f} + M_{m_a_f} + M_{m_b_f} + M_{s_f} + M_{water_f} = 222 \text{ kNm/m}$

### Restoring moments

Wall stem  $M_{wall_f} = W_{wall_f} \times (l_{toe} + t_{wall} / 2) = 27.5 \text{ kNm/m}$

Wall base  $M_{base_f} = W_{base_f} \times l_{base} / 2 = 6.3 \text{ kNm/m}$

Design vertical load  $M_{v_f} = W_{v_f} \times l_{load} = 97.4 \text{ kNm/m}$

Total restoring moment  $M_{rest_f} = M_{wall_f} + M_{base_f} + M_{v_f} = 131.3 \text{ kNm/m}$

### Factored bearing pressure

Total vertical reaction  $R_f = W_{total_f} = 166.3 \text{ kN/m}$

Distance to reaction  $x_{bar_f} = l_{base} / 2 = 490 \text{ mm}$

Eccentricity of reaction  $e_f = \text{abs}((l_{base} / 2) - x_{bar_f}) = 0 \text{ mm}$


**Reaction acts within middle third of base**

Bearing pressure at toe  $p_{toe_f} = (R_f / l_{base}) - (6 \times R_f \times e_f / l_{base}^2) = 169.7 \text{ kN/m}^2$

Bearing pressure at heel  $p_{heel_f} = (R_f / l_{base}) + (6 \times R_f \times e_f / l_{base}^2) = 169.7 \text{ kN/m}^2$

Rate of change of base reaction  $\text{rate} = (p_{toe_f} - p_{heel_f}) / l_{base} = 0.00 \text{ kN/m}^2/\text{m}$

Bearing pressure at stem / toe  $p_{stem\_toe_f} = \max(p_{toe_f} - (\text{rate} \times l_{toe}), 0 \text{ kN/m}^2) = 169.7 \text{ kN/m}^2$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	retaining wall under party wall				6.3. 5	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

Bearing pressure at mid stem

$$p_{\text{stem\_mid\_f}} = \max(p_{\text{toe\_f}} - (\text{rate} \times (l_{\text{toe}} + t_{\text{wall}} / 2)), 0 \text{ kN/m}^2) = \mathbf{169.7 \text{ kN/m}^2}$$

Bearing pressure at stem / heel

$$p_{\text{stem\_heel\_f}} = \max(p_{\text{toe\_f}} - (\text{rate} \times (l_{\text{toe}} + t_{\text{wall}})), 0 \text{ kN/m}^2) = \mathbf{169.7 \text{ kN/m}^2}$$

### Calculate propping forces to top and base of wall

Propping force to top of wall

$$F_{\text{prop\_top\_f}} = (M_{\text{ot\_f}} - M_{\text{rest\_f}} + R_f \times l_{\text{base}} / 2 - F_{\text{prop\_f}} \times t_{\text{base}} / 2) / (h_{\text{stem}} + t_{\text{base}} / 2) = \mathbf{45.039 \text{ kN/m}}$$

Propping force to base of wall

$$F_{\text{prop\_base\_f}} = F_{\text{prop\_f}} - F_{\text{prop\_top\_f}} = \mathbf{72.430 \text{ kN/m}}$$

### Design of reinforced concrete retaining wall toe (BS 8002:1994)

#### Material properties

Characteristic strength of concrete

$$f_{\text{cu}} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

#### Base details

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in toe

$$c_{\text{toe}} = \mathbf{45 \text{ mm}}$$

#### Calculate shear for toe design

Shear from bearing pressure

$$V_{\text{toe\_bear}} = (p_{\text{toe\_f}} + p_{\text{stem\_toe\_f}}) \times l_{\text{toe}} / 2 = \mathbf{110.3 \text{ kN/m}}$$

Shear from weight of base

$$V_{\text{toe\_wt\_base}} = \gamma_{\text{f\_d}} \times \gamma_{\text{base}} \times l_{\text{toe}} \times t_{\text{base}} = \mathbf{8.6 \text{ kN/m}}$$

Total shear for toe design

$$V_{\text{toe}} = V_{\text{toe\_bear}} - V_{\text{toe\_wt\_base}} = \mathbf{101.7 \text{ kN/m}}$$

#### Calculate moment for toe design

Moment from bearing pressure


$$M_{\text{toe\_bear}} = (2 \times p_{\text{toe\_f}} + p_{\text{stem\_mid\_f}}) \times (l_{\text{toe}} + t_{\text{wall}} / 2)^2 / 6 = \mathbf{56.4 \text{ kNm/m}}$$

Moment from weight of base

$$M_{\text{toe\_wt\_base}} = (\gamma_{\text{f\_d}} \times \gamma_{\text{base}} \times t_{\text{base}} \times (l_{\text{toe}} + t_{\text{wall}} / 2)^2 / 2) = \mathbf{4.4 \text{ kNm/m}}$$

Total moment for toe design

$$M_{\text{toe}} = M_{\text{toe\_bear}} - M_{\text{toe\_wt\_base}} = \mathbf{52 \text{ kNm/m}}$$



#### Check toe in bending

Width of toe

$$b = \mathbf{1000 \text{ mm/m}}$$

Depth of reinforcement

$$d_{\text{toe}} = t_{\text{base}} - c_{\text{toe}} - (\phi_{\text{toe}} / 2) = \mathbf{349.0 \text{ mm}}$$

Constant

$$K_{\text{toe}} = M_{\text{toe}} / (b \times d_{\text{toe}}^2 \times f_{\text{cu}}) = \mathbf{0.011}$$

**Compression reinforcement is not required**

Lever arm

$$z_{\text{toe}} = \min(0.5 + \sqrt{(0.25 - (\min(K_{\text{toe}}, 0.225) / 0.9))}, 0.95) \times d_{\text{toe}}$$

$$z_{\text{toe}} = \mathbf{332 \text{ mm}}$$

Area of tension reinforcement required

$$A_{\text{s\_toe\_des}} = M_{\text{toe}} / (0.87 \times f_y \times z_{\text{toe}}) = \mathbf{360 \text{ mm}^2/\text{m}}$$

Minimum area of tension reinforcement

$$A_{\text{s\_toe\_min}} = k \times b \times t_{\text{base}} = \mathbf{520 \text{ mm}^2/\text{m}}$$

Area of tension reinforcement required


$$A_{\text{s\_toe\_req}} = \text{Max}(A_{\text{s\_toe\_des}}, A_{\text{s\_toe\_min}}) = \mathbf{520 \text{ mm}^2/\text{m}}$$

Reinforcement provided

$$\mathbf{12 \text{ mm dia. bars @ 200 mm centres}}$$

Area of reinforcement provided

$$A_{\text{s\_toe\_prov}} = \mathbf{565 \text{ mm}^2/\text{m}}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>retaining wall under party wall</b>				Start page no./Revision <b>6.3. 6</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

**PASS - Reinforcement provided at the retaining wall toe is adequate**

**Check shear resistance at toe**

Design shear stress

$$V_{toe} = V_{toe} / (b \times d_{toe}) = \mathbf{0.291 \text{ N/mm}^2}$$

Allowable shear stress

$$V_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = \mathbf{5.000 \text{ N/mm}^2}$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$V_{c\_toe} = \mathbf{0.417 \text{ N/mm}^2}$$

**$V_{toe} < V_{c\_toe}$  - No shear reinforcement required**

**Design of reinforced concrete retaining wall stem (BS 8002:1994)**

**Material properties**

Characteristic strength of concrete

$$f_{cu} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

**Wall details**

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in stem

$$C_{stem} = \mathbf{45 \text{ mm}}$$

Cover to reinforcement in wall

$$C_{wall} = \mathbf{45 \text{ mm}}$$

**Factored horizontal at-rest forces on stem**

Surcharge

$$F_{s\_sur\_f} = \gamma_{f\_l} \times K_0 \times \text{Surcharge} \times (h_{eff} - t_{base} - d_{ds}) = \mathbf{33.8 \text{ kN/m}}$$

Moist backfill above water table

$$F_{s\_m\_a\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat})^2 = \mathbf{2.1 \text{ kN/m}}$$

Moist backfill below water table

$$F_{s\_m\_b\_f} = \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat}) \times h_{sat} = \mathbf{22.3 \text{ kN/m}}$$

Saturated backfill

$$F_{s\_s\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{sat}^2 = \mathbf{36.1 \text{ kN/m}}$$

Water

$$F_{s\_water\_f} = 0.5 \times \gamma_{f\_e} \times \gamma_{water} \times h_{sat}^2 = \mathbf{46.4 \text{ kN/m}}$$

**Calculate shear for stem design**

Surcharge

$$V_{s\_sur\_f} = 5 \times F_{s\_sur\_f} / 8 = \mathbf{21.1 \text{ kN/m}}$$

Moist backfill above water table

$$V_{s\_m\_a\_f} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - b_l^2) / (5 \times L^3) = \mathbf{0.3 \text{ kN/m}}$$

Moist backfill below water table

$$V_{s\_m\_b\_f} = F_{s\_m\_b\_f} \times (8 - (n^2 \times (4 - n))) / 8 = \mathbf{16 \text{ kN/m}}$$

Saturated backfill

$$V_{s\_s\_f} = F_{s\_s\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{30.7 \text{ kN/m}}$$

Water

$$V_{s\_water\_f} = F_{s\_water\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{39.5 \text{ kN/m}}$$

Total shear for stem design

$$V_{stem} = V_{s\_sur\_f} + V_{s\_m\_a\_f} + V_{s\_m\_b\_f} + V_{s\_s\_f} + V_{s\_water\_f} = \mathbf{107.6 \text{ kN/m}}$$

**Calculate moment for stem design**

Surcharge

$$M_{s\_sur} = F_{s\_sur\_f} \times L / 8 = \mathbf{13.9 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{s\_m\_a} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - (3 \times b_l^2)) / (15 \times L^2) = \mathbf{0.4 \text{ kNm/m}}$$

Moist backfill below water table

$$M_{s\_m\_b} = F_{s\_m\_b\_f} \times a_l \times (2 - n)^2 / 8 = \mathbf{10.4 \text{ kNm/m}}$$

Saturated backfill

$$M_{s\_s} = F_{s\_s\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{15.9 \text{ kNm/m}}$$

Water

$$M_{s\_water} = F_{s\_water\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{20.4 \text{ kNm/m}}$$

kNm/m

Total moment for stem design

$$M_{stem} = M_{s\_sur} + M_{s\_m\_a} + M_{s\_m\_b} + M_{s\_s} + M_{s\_water} = \mathbf{60.9 \text{ kNm/m}}$$

**Calculate moment for wall design**

Surcharge

$$M_{w\_sur} = 9 \times F_{s\_sur\_f} \times L / 128 = \mathbf{7.8 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{w\_m\_a} = F_{s\_m\_a\_f} \times 0.577 \times b_l \times [(b_l^3 + 5 \times a_l \times L^2) / (5 \times L^3) - 0.577^2 / 3] = \mathbf{0.5 \text{ kNm/m}}$$


kNm/m

Moist backfill below water table

$$M_{w\_m\_b} = F_{s\_m\_b\_f} \times a_l \times [((8 - n^2 \times (4 - n))^2 / 16) - 4 \times n \times (4 - n)] / 8 = \mathbf{5.7 \text{ kNm/m}}$$

Saturated backfill

$$M_{w\_s} = F_{s\_s\_f} \times [a_l^2 \times x \times ((5 \times L) - a_l) / (20 \times L^3) - (x - b_l)^3 / (3 \times a_l^2)] = \mathbf{6.6 \text{ kNm/m}}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for retaining wall under party wall				Start page no./Revision 6.3. 7	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

Water


kNm/m

Total moment for wall design

$$M_{w\_water} = F_{s\_water\_f} \times [a_1^2 \times x \times ((5 \times L) - a_1) / (20 \times L^3) - (x - b_1)^3 / (3 \times a_1^2)] = 8.5$$

$$M_{wall} = M_{w\_sur} + M_{w\_m\_a} + M_{w\_m\_b} + M_{w\_s} + M_{w\_water} = 29 \text{ kNm/m}$$

← 200 →



#### Check wall stem in bending

Width of wall stem

$$b = 1000 \text{ mm/m}$$

Depth of reinforcement

$$d_{stem} = t_{wall} - c_{stem} - (\phi_{stem} / 2) = 279.0 \text{ mm}$$

Constant

$$K_{stem} = M_{stem} / (b \times d_{stem}^2 \times f_{cu}) = 0.020$$

**Compression reinforcement is not required**

Lever arm

$$z_{stem} = \min(0.5 + \sqrt{(0.25 - (\min(K_{stem}, 0.225) / 0.9))}, 0.95) \times d_{stem}$$

$$z_{stem} = 265 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_stem\_des} = M_{stem} / (0.87 \times f_y \times z_{stem}) = 529 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_stem\_min} = k \times b \times t_{wall} = 429 \text{ mm}^2/\text{m}$$

Area of tension reinforcement required

$$A_{s\_stem\_req} = \text{Max}(A_{s\_stem\_des}, A_{s\_stem\_min}) = 529 \text{ mm}^2/\text{m}$$

Reinforcement provided

**12 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_stem\_prov} = 565 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided at the retaining wall stem is adequate**

#### Check shear resistance at wall stem

Design shear stress

$$v_{stem} = V_{stem} / (b \times d_{stem}) = 0.386 \text{ N/mm}^2$$

Allowable shear stress

$$v_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = 5.000 \text{ N/mm}^2$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$v_{c\_stem} = 0.475 \text{ N/mm}^2$$

**$v_{stem} < v_{c\_stem}$  - No shear reinforcement required**

#### Check mid height of wall in bending

Depth of reinforcement

$$d_{wall} = t_{wall} - c_{wall} - (\phi_{wall} / 2) = 279.0 \text{ mm}$$

Constant

$$K_{wall} = M_{wall} / (b \times d_{wall}^2 \times f_{cu}) = 0.009$$

**Compression reinforcement is not required**

Lever arm

$$z_{wall} = \min(0.5 + \sqrt{(0.25 - (\min(K_{wall}, 0.225) / 0.9))}, 0.95) \times d_{wall}$$

$$z_{wall} = 265 \text{ mm}$$


Area of tension reinforcement required

$$A_{s\_wall\_des} = M_{wall} / (0.87 \times f_y \times z_{wall}) = 252 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_wall\_min} = k \times b \times t_{wall} = 429 \text{ mm}^2/\text{m}$$



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for retaining wall under party wall				Start page no./Revision 6.3. 8	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

Area of tension reinforcement required

$$A_{s\_wall\_req} = \text{Max}(A_{s\_wall\_des}, A_{s\_wall\_min}) = 429 \text{ mm}^2/\text{m}$$

Reinforcement provided

**12 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_wall\_prov} = 565 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided to the retaining wall at mid height is adequate**

#### Check retaining wall deflection

Basic span/effective depth ratio

$$\text{ratio}_{bas} = 20$$

Design service stress

$$f_s = 2 \times f_y \times A_{s\_stem\_req} / (3 \times A_{s\_stem\_prov}) = 311.6 \text{ N/mm}^2$$

Modification factor

$$\text{factor}_{tens} = \min(0.55 + (477 \text{ N/mm}^2 - f_s) / (120 \times (0.9 \text{ N/mm}^2 + (M_{stem} / (b \times d_{stem}^2)))), 2) = 1.37$$

Maximum span/effective depth ratio

$$\text{ratio}_{max} = \text{ratio}_{bas} \times \text{factor}_{tens} = 27.38$$


Actual span/effective depth ratio

$$\text{ratio}_{act} = h_{stem} / d_{stem} = 11.11$$


**PASS - Span to depth ratio is acceptable**

<div> <div> <div>Tekla</div> <div>Tedds</div> </div> <div> <div>RODRIGUES ASSOCIATES</div> <div>1 AMWELL STREET</div> <div>LONDON</div> <div>EC1R 1UL</div> </div> </div>	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	retaining wall under party wall				6.3. 9	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

Indicative retaining wall reinforcement diagram




- Toe bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Wall bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Stem bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	rear retaining wall under rear extension				6.4. 1	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				

## RETAINING WALL ANALYSIS (BS 8002:1994)

TEDDS calculation version 1.2.01.06



### Wall details

Retaining wall type  
Height of retaining wall stem  
Thickness of wall stem  
Length of toe  
Length of heel  
Overall length of base  
Thickness of base  
Depth of downstand  
Position of downstand  
Thickness of downstand  
Height of retaining wall  
Depth of cover in front of wall  
Depth of unplanned excavation  
Height of ground water behind wall  
Height of saturated fill above base  
Density of wall construction  
Density of base construction  
Angle of rear face of wall  
Angle of soil surface behind wall  
Effective height at virtual back of wall


### Cantilever propped at both

$h_{\text{stem}} = 3100$  mm  
 $t_{\text{wall}} = 300$  mm  
 $l_{\text{toe}} = 650$  mm  
 $l_{\text{heel}} = 0$  mm  
 $l_{\text{base}} = l_{\text{toe}} + l_{\text{heel}} + t_{\text{wall}} = 950$  mm  
 $t_{\text{base}} = 400$  mm  
 $d_{\text{ds}} = 0$  mm  
 $l_{\text{ds}} = 15$  mm  
 $t_{\text{ds}} = 400$  mm  
 $h_{\text{wall}} = h_{\text{stem}} + t_{\text{base}} + d_{\text{ds}} = 3500$  mm  
 $d_{\text{cover}} = 0$  mm  
 $d_{\text{exc}} = 0$  mm  
 $h_{\text{water}} = 3000$  mm  
 $h_{\text{sat}} = \max(h_{\text{water}} - t_{\text{base}} - d_{\text{ds}}, 0 \text{ mm}) = 2600$  mm  
 $\gamma_{\text{wall}} = 23.6$  kN/m<sup>3</sup>  
 $\gamma_{\text{base}} = 23.6$  kN/m<sup>3</sup>  
 $\alpha = 90.0$  deg  
 $\beta = 0.0$  deg  
 $h_{\text{eff}} = h_{\text{wall}} + l_{\text{heel}} \times \tan(\beta) = 3500$  mm

### Retained material details

Mobilisation factor  
Moist density of retained material

$M = 1.5$   
 $\gamma_m = 18.0$  kN/m<sup>3</sup>

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>rear retaining wall under rear extension</b>				Start page no./Revision <b>6.4. 2</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

Saturated density of retained material

$$\gamma_s = 21.0 \text{ kN/m}^3$$

Design shear strength

$$\phi' = 18.6 \text{ deg}$$

Angle of wall friction

$$\delta = 0.0 \text{ deg}$$

#### Base material details

Firm clay

Moist density

$$\gamma_{mb} = 18.0 \text{ kN/m}^3$$

Design shear strength

$$\phi'_b = 16.5 \text{ deg}$$

Design base friction

$$\delta_b = 18.6 \text{ deg}$$

Allowable bearing pressure

$$P_{\text{bearing}} = 150 \text{ kN/m}^2$$

#### Using Coulomb theory

Active pressure coefficient for retained material

$$K_a = \sin(\alpha + \phi')^2 / (\sin(\alpha)^2 \times \sin(\alpha - \delta) \times [1 + \sqrt{(\sin(\phi' + \delta) \times \sin(\phi' - \beta) / (\sin(\alpha - \delta) \times \sin(\alpha + \beta)))})^2) = 0.516$$

Passive pressure coefficient for base material

$$K_p = \sin(90 - \phi'_b)^2 / (\sin(90 - \delta_b) \times [1 - \sqrt{(\sin(\phi'_b + \delta_b) \times \sin(\phi'_b) / (\sin(90 + \delta_b)))})^2) = 2.835$$

#### At-rest pressure

At-rest pressure for retained material

$$K_0 = 1 - \sin(\phi') = 0.681$$

#### Loading details

Surcharge load on plan

$$\text{Surcharge} = 10.0 \text{ kN/m}^2$$

Applied vertical dead load on wall

$$W_{\text{dead}} = 43.0 \text{ kN/m}$$

Applied vertical live load on wall

$$W_{\text{live}} = 6.0 \text{ kN/m}$$

Position of applied vertical load on wall

$$l_{\text{load}} = 800 \text{ mm}$$

Applied horizontal dead load on wall


$$F_{\text{dead}} = 0.0 \text{ kN/m}$$

Applied horizontal live load on wall


$$F_{\text{live}} = 0.0 \text{ kN/m}$$

Height of applied horizontal load on wall

$$h_{\text{load}} = 0 \text{ mm}$$



Loads shown in kN/m, pressures shown in kN/m²

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>rear retaining wall under rear extension</b>				Start page no./Revision <b>6.4. 3</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

### Vertical forces on wall

Wall stem	$W_{wall} = h_{stem} \times t_{wall} \times \gamma_{wall} = \mathbf{21.9 \text{ kN/m}}$
Wall base	$W_{base} = l_{base} \times t_{base} \times \gamma_{base} = \mathbf{9 \text{ kN/m}}$
Applied vertical load	$W_v = W_{dead} + W_{live} = \mathbf{49 \text{ kN/m}}$
Total vertical load	$W_{total} = W_{wall} + W_{base} + W_v = \mathbf{79.9 \text{ kN/m}}$

### Horizontal forces on wall

Surcharge	$F_{sur} = K_a \times \text{Surcharge} \times h_{eff} = \mathbf{18.1 \text{ kN/m}}$
Moist backfill above water table	$F_{m\_a} = 0.5 \times K_a \times \gamma_m \times (h_{eff} - h_{water})^2 = \mathbf{1.2 \text{ kN/m}}$
Moist backfill below water table	$F_{m\_b} = K_a \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = \mathbf{13.9 \text{ kN/m}}$
Saturated backfill	$F_s = 0.5 \times K_a \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = \mathbf{26 \text{ kN/m}}$
Water	$F_{water} = 0.5 \times h_{water}^2 \times \gamma_{water} = \mathbf{44.1 \text{ kN/m}}$
Total horizontal load	$F_{total} = F_{sur} + F_{m\_a} + F_{m\_b} + F_s + F_{water} = \mathbf{103.3 \text{ kN/m}}$

### Calculate total propping force

Passive resistance of soil in front of wall	$F_p = 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = \mathbf{3.9 \text{ kN/m}}$
Propping force	$F_{prop} = \max(F_{total} - F_p - (W_{total} - W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$ $F_{prop} = \mathbf{74.6 \text{ kN/m}}$

### Overturning moments

Surcharge	$M_{sur} = F_{sur} \times (h_{eff} - 2 \times d_{ds}) / 2 = \mathbf{31.6 \text{ kNm/m}}$
Moist backfill above water table	$M_{m\_a} = F_{m\_a} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = \mathbf{3.7 \text{ kNm/m}}$
Moist backfill below water table	$M_{m\_b} = F_{m\_b} \times (h_{water} - 2 \times d_{ds}) / 2 = \mathbf{20.9 \text{ kNm/m}}$
Saturated backfill	$M_s = F_s \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{26 \text{ kNm/m}}$
Water	$M_{water} = F_{water} \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{44.1 \text{ kNm/m}}$
Total overturning moment	$M_{ot} = M_{sur} + M_{m\_a} + M_{m\_b} + M_s + M_{water} = \mathbf{126.4 \text{ kNm/m}}$

### Restoring moments

Wall stem	$M_{wall} = W_{wall} \times (l_{toe} + t_{wall} / 2) = \mathbf{17.6 \text{ kNm/m}}$
Wall base	$M_{base} = W_{base} \times l_{base} / 2 = \mathbf{4.3 \text{ kNm/m}}$
Design vertical dead load	$M_{dead} = W_{dead} \times l_{load} = \mathbf{34.4 \text{ kNm/m}}$
Total restoring moment	$M_{rest} = M_{wall} + M_{base} + M_{dead} = \mathbf{56.2 \text{ kNm/m}}$

### Check bearing pressure

Total vertical reaction	$R = W_{total} = \mathbf{79.9 \text{ kN/m}}$
Distance to reaction	$x_{bar} = l_{base} / 2 = \mathbf{475 \text{ mm}}$
Eccentricity of reaction	$e = \text{abs}((l_{base} / 2) - x_{bar}) = \mathbf{0 \text{ mm}}$


**Reaction acts within middle third of base**

Bearing pressure at toe	$p_{toe} = (R / l_{base}) - (6 \times R \times e / l_{base}^2) = \mathbf{84.1 \text{ kN/m}^2}$
Bearing pressure at heel	$p_{heel} = (R / l_{base}) + (6 \times R \times e / l_{base}^2) = \mathbf{84.1 \text{ kN/m}^2}$

**PASS - Maximum bearing pressure is less than allowable bearing pressure**

### Calculate propping forces to top and base of wall

Propping force to top of wall	$F_{prop\_top} = (M_{ot} - M_{rest} + R \times l_{base} / 2 - F_{prop} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = \mathbf{28.239 \text{ kN/m}}$
Propping force to base of wall	$F_{prop\_base} = F_{prop} - F_{prop\_top} = \mathbf{46.336 \text{ kN/m}}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>rear retaining wall under rear extension</b>				Start page no./Revision <b>6.4. 4</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

## **RETAINING WALL DESIGN (BS 8002:1994)**

TEDDS calculation version 1.2.01.06

### **Ultimate limit state load factors**

Dead load factor  $\gamma_{f_d} = 1.4$

Live load factor  $\gamma_{f_l} = 1.6$

Earth and water pressure factor  $\gamma_{f_e} = 1.4$

### **Factored vertical forces on wall**

Wall stem  $W_{wall_f} = \gamma_{f_d} \times h_{stem} \times t_{wall} \times \gamma_{wall} = 30.7 \text{ kN/m}$

Wall base  $W_{base_f} = \gamma_{f_d} \times l_{base} \times t_{base} \times \gamma_{base} = 12.6 \text{ kN/m}$

Applied vertical load  $W_{v_f} = \gamma_{f_d} \times W_{dead} + \gamma_{f_l} \times W_{live} = 69.8 \text{ kN/m}$

Total vertical load  $W_{total_f} = W_{wall_f} + W_{base_f} + W_{v_f} = 113.1 \text{ kN/m}$

### **Factored horizontal at-rest forces on wall**

Surcharge  $F_{sur_f} = \gamma_{f_l} \times K_0 \times \text{Surcharge} \times h_{eff} = 38.1 \text{ kN/m}$

Moist backfill above water table  $F_{m_a_f} = \gamma_{f_e} \times 0.5 \times K_0 \times \gamma_m \times (h_{eff} - h_{water})^2 = 2.1 \text{ kN/m}$

Moist backfill below water table  $F_{m_b_f} = \gamma_{f_e} \times K_0 \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = 25.7 \text{ kN/m}$

Saturated backfill  $F_{s_f} = \gamma_{f_e} \times 0.5 \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = 48 \text{ kN/m}$

Water  $F_{water_f} = \gamma_{f_e} \times 0.5 \times h_{water}^2 \times \gamma_{water} = 61.8 \text{ kN/m}$

Total horizontal load  $F_{total_f} = F_{sur_f} + F_{m_a_f} + F_{m_b_f} + F_{s_f} + F_{water_f} = 175.8 \text{ kN/m}$

### **Calculate total propping force**

Passive resistance of soil in front of wall  
kN/m  $F_{p_f} = \gamma_{f_e} \times 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = 5.4$

Propping force  $F_{prop_f} = \max(F_{total_f} - F_{p_f} - (W_{total_f} - \gamma_{f_l} \times W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$

$F_{prop_f} = 135.6 \text{ kN/m}$

### **Factored overturning moments**

Surcharge  $M_{sur_f} = F_{sur_f} \times (h_{eff} - 2 \times d_{ds}) / 2 = 66.7 \text{ kNm/m}$

Moist backfill above water table  $M_{m_a_f} = F_{m_a_f} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = 6.8 \text{ kNm/m}$

Moist backfill below water table  $M_{m_b_f} = F_{m_b_f} \times (h_{water} - 2 \times d_{ds}) / 2 = 38.6 \text{ kNm/m}$

Saturated backfill  $M_{s_f} = F_{s_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 48 \text{ kNm/m}$

Water  $M_{water_f} = F_{water_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 61.8 \text{ kNm/m}$

Total overturning moment  $M_{ot_f} = M_{sur_f} + M_{m_a_f} + M_{m_b_f} + M_{s_f} + M_{water_f} = 222 \text{ kNm/m}$

### **Restoring moments**

Wall stem  $M_{wall_f} = W_{wall_f} \times (l_{toe} + t_{wall} / 2) = 24.6 \text{ kNm/m}$

Wall base  $M_{base_f} = W_{base_f} \times l_{base} / 2 = 6 \text{ kNm/m}$

Design vertical load  $M_{v_f} = W_{v_f} \times l_{load} = 55.8 \text{ kNm/m}$

Total restoring moment  $M_{rest_f} = M_{wall_f} + M_{base_f} + M_{v_f} = 86.4 \text{ kNm/m}$

### **Factored bearing pressure**

Total vertical reaction  $R_f = W_{total_f} = 113.1 \text{ kN/m}$

Distance to reaction  $x_{bar_f} = l_{base} / 2 = 475 \text{ mm}$

Eccentricity of reaction  $e_f = \text{abs}((l_{base} / 2) - x_{bar_f}) = 0 \text{ mm}$


**Reaction acts within middle third of base**

Bearing pressure at toe  $p_{toe_f} = (R_f / l_{base}) - (6 \times R_f \times e_f / l_{base}^2) = 119 \text{ kN/m}^2$

Bearing pressure at heel  $p_{heel_f} = (R_f / l_{base}) + (6 \times R_f \times e_f / l_{base}^2) = 119 \text{ kN/m}^2$

Rate of change of base reaction  $\text{rate} = (p_{toe_f} - p_{heel_f}) / l_{base} = 0.00 \text{ kN/m}^2/\text{m}$

Bearing pressure at stem / toe  $p_{stem\_toe_f} = \max(p_{toe_f} - (\text{rate} \times l_{toe}), 0 \text{ kN/m}^2) = 119 \text{ kN/m}^2$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>rear retaining wall under rear extension</b>				Start page no./Revision <b>6.4. 5</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

Bearing pressure at mid stem

$$p_{\text{stem\_mid\_f}} = \max(p_{\text{toe\_f}} - (\text{rate} \times (l_{\text{toe}} + t_{\text{wall}} / 2)), 0 \text{ kN/m}^2) = \mathbf{119 \text{ kN/m}^2}$$

Bearing pressure at stem / heel

$$p_{\text{stem\_heel\_f}} = \max(p_{\text{toe\_f}} - (\text{rate} \times (l_{\text{toe}} + t_{\text{wall}})), 0 \text{ kN/m}^2) = \mathbf{119 \text{ kN/m}^2}$$

### Calculate propping forces to top and base of wall

Propping force to top of wall

$$F_{\text{prop\_top\_f}} = (M_{\text{ot\_f}} - M_{\text{rest\_f}} + R_f \times l_{\text{base}} / 2 - F_{\text{prop\_f}} \times t_{\text{base}} / 2) / (h_{\text{stem}} + t_{\text{base}} / 2) = \mathbf{49.144 \text{ kN/m}}$$

Propping force to base of wall

$$F_{\text{prop\_base\_f}} = F_{\text{prop\_f}} - F_{\text{prop\_top\_f}} = \mathbf{86.454 \text{ kN/m}}$$

### Design of reinforced concrete retaining wall toe (BS 8002:1994)

#### Material properties

Characteristic strength of concrete

$$f_{\text{cu}} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

#### Base details

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in toe

$$c_{\text{toe}} = \mathbf{45 \text{ mm}}$$

#### Calculate shear for toe design

Shear from bearing pressure

$$V_{\text{toe\_bear}} = (p_{\text{toe\_f}} + p_{\text{stem\_toe\_f}}) \times l_{\text{toe}} / 2 = \mathbf{77.4 \text{ kN/m}}$$

Shear from weight of base

$$V_{\text{toe\_wt\_base}} = \gamma_{\text{f\_d}} \times \gamma_{\text{base}} \times l_{\text{toe}} \times t_{\text{base}} = \mathbf{8.6 \text{ kN/m}}$$

Total shear for toe design

$$V_{\text{toe}} = V_{\text{toe\_bear}} - V_{\text{toe\_wt\_base}} = \mathbf{68.8 \text{ kN/m}}$$

#### Calculate moment for toe design

Moment from bearing pressure


$$M_{\text{toe\_bear}} = (2 \times p_{\text{toe\_f}} + p_{\text{stem\_mid\_f}}) \times (l_{\text{toe}} + t_{\text{wall}} / 2)^2 / 6 = \mathbf{38.1 \text{ kNm/m}}$$

Moment from weight of base

$$M_{\text{toe\_wt\_base}} = (\gamma_{\text{f\_d}} \times \gamma_{\text{base}} \times t_{\text{base}} \times (l_{\text{toe}} + t_{\text{wall}} / 2)^2 / 2) = \mathbf{4.2 \text{ kNm/m}}$$

Total moment for toe design

$$M_{\text{toe}} = M_{\text{toe\_bear}} - M_{\text{toe\_wt\_base}} = \mathbf{33.9 \text{ kNm/m}}$$



#### Check toe in bending

Width of toe

$$b = \mathbf{1000 \text{ mm/m}}$$

Depth of reinforcement

$$d_{\text{toe}} = t_{\text{base}} - c_{\text{toe}} - (\phi_{\text{toe}} / 2) = \mathbf{349.0 \text{ mm}}$$

Constant

$$K_{\text{toe}} = M_{\text{toe}} / (b \times d_{\text{toe}}^2 \times f_{\text{cu}}) = \mathbf{0.007}$$

**Compression reinforcement is not required**

Lever arm

$$z_{\text{toe}} = \min(0.5 + \sqrt{(0.25 - (\min(K_{\text{toe}}, 0.225) / 0.9))}, 0.95) \times d_{\text{toe}}$$

$$z_{\text{toe}} = \mathbf{332 \text{ mm}}$$

Area of tension reinforcement required

$$A_{\text{s\_toe\_des}} = M_{\text{toe}} / (0.87 \times f_y \times z_{\text{toe}}) = \mathbf{235 \text{ mm}^2/\text{m}}$$

Minimum area of tension reinforcement

$$A_{\text{s\_toe\_min}} = k \times b \times t_{\text{base}} = \mathbf{520 \text{ mm}^2/\text{m}}$$

Area of tension reinforcement required


$$A_{\text{s\_toe\_req}} = \text{Max}(A_{\text{s\_toe\_des}}, A_{\text{s\_toe\_min}}) = \mathbf{520 \text{ mm}^2/\text{m}}$$

Reinforcement provided

$$\mathbf{12 \text{ mm dia. bars @ 200 mm centres}}$$

Area of reinforcement provided

$$A_{\text{s\_toe\_prov}} = \mathbf{565 \text{ mm}^2/\text{m}}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>rear retaining wall under rear extension</b>				Start page no./Revision <b>6.4. 6</b>	
	Calcs by <b>ab</b>	Calcs date <b>20/04/2018</b>	Checked by	Checked date	Approved by	Approved date

**PASS - Reinforcement provided at the retaining wall toe is adequate**

**Check shear resistance at toe**

Design shear stress

$$V_{toe} = V_{toe} / (b \times d_{toe}) = \mathbf{0.197 \text{ N/mm}^2}$$

Allowable shear stress

$$V_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = \mathbf{5.000 \text{ N/mm}^2}$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$V_{c\_toe} = \mathbf{0.417 \text{ N/mm}^2}$$

**$V_{toe} < V_{c\_toe}$  - No shear reinforcement required**

**Design of reinforced concrete retaining wall stem (BS 8002:1994)**

**Material properties**

Characteristic strength of concrete

$$f_{cu} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

**Wall details**

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in stem

$$C_{stem} = \mathbf{45 \text{ mm}}$$

Cover to reinforcement in wall

$$C_{wall} = \mathbf{45 \text{ mm}}$$

**Factored horizontal at-rest forces on stem**

Surcharge

$$F_{s\_sur\_f} = \gamma_{f\_l} \times K_0 \times \text{Surcharge} \times (h_{eff} - t_{base} - d_{ds}) = \mathbf{33.8 \text{ kN/m}}$$

Moist backfill above water table

$$F_{s\_m\_a\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat})^2 = \mathbf{2.1 \text{ kN/m}}$$

Moist backfill below water table

$$F_{s\_m\_b\_f} = \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat}) \times h_{sat} = \mathbf{22.3 \text{ kN/m}}$$

Saturated backfill

$$F_{s\_s\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{sat}^2 = \mathbf{36.1 \text{ kN/m}}$$

Water

$$F_{s\_water\_f} = 0.5 \times \gamma_{f\_e} \times \gamma_{water} \times h_{sat}^2 = \mathbf{46.4 \text{ kN/m}}$$

**Calculate shear for stem design**

Surcharge

$$V_{s\_sur\_f} = 5 \times F_{s\_sur\_f} / 8 = \mathbf{21.1 \text{ kN/m}}$$

Moist backfill above water table

$$V_{s\_m\_a\_f} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - b_l^2) / (5 \times L^3) = \mathbf{0.3 \text{ kN/m}}$$

Moist backfill below water table

$$V_{s\_m\_b\_f} = F_{s\_m\_b\_f} \times (8 - (n^2 \times (4 - n))) / 8 = \mathbf{16 \text{ kN/m}}$$

Saturated backfill

$$V_{s\_s\_f} = F_{s\_s\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{30.7 \text{ kN/m}}$$

Water

$$V_{s\_water\_f} = F_{s\_water\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{39.5 \text{ kN/m}}$$

Total shear for stem design

$$V_{stem} = V_{s\_sur\_f} + V_{s\_m\_a\_f} + V_{s\_m\_b\_f} + V_{s\_s\_f} + V_{s\_water\_f} = \mathbf{107.6 \text{ kN/m}}$$

**Calculate moment for stem design**

Surcharge

$$M_{s\_sur} = F_{s\_sur\_f} \times L / 8 = \mathbf{13.9 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{s\_m\_a} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - (3 \times b_l^2)) / (15 \times L^2) = \mathbf{0.4 \text{ kNm/m}}$$

Moist backfill below water table

$$M_{s\_m\_b} = F_{s\_m\_b\_f} \times a_l \times (2 - n)^2 / 8 = \mathbf{10.4 \text{ kNm/m}}$$

Saturated backfill

$$M_{s\_s} = F_{s\_s\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{15.9 \text{ kNm/m}}$$

Water

$$M_{s\_water} = F_{s\_water\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{20.4 \text{ kNm/m}}$$

kNm/m

Total moment for stem design

$$M_{stem} = M_{s\_sur} + M_{s\_m\_a} + M_{s\_m\_b} + M_{s\_s} + M_{s\_water} = \mathbf{60.9 \text{ kNm/m}}$$

**Calculate moment for wall design**

Surcharge

$$M_{w\_sur} = 9 \times F_{s\_sur\_f} \times L / 128 = \mathbf{7.8 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{w\_m\_a} = F_{s\_m\_a\_f} \times 0.577 \times b_l \times [(b_l^3 + 5 \times a_l \times L^2) / (5 \times L^3) - 0.577^2 / 3] = \mathbf{0.5 \text{ kNm/m}}$$

kNm/m


Moist backfill below water table

$$M_{w\_m\_b} = F_{s\_m\_b\_f} \times a_l \times [((8 - n^2 \times (4 - n))^2 / 16) - 4 \times n \times (4 - n)] / 8 = \mathbf{5.7 \text{ kNm/m}}$$

Saturated backfill

$$M_{w\_s} = F_{s\_s\_f} \times [a_l^2 \times x \times ((5 \times L) - a_l) / (20 \times L^3) - (x - b_l)^3 / (3 \times a_l^2)] = \mathbf{6.6 \text{ kNm/m}}$$



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for rear retaining wall under rear extension				Start page no./Revision 6.4. 7	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date


Water  
kNm/m

Total moment for wall design

$$M_{w\_water} = F_{s\_water\_f} \times [a_1^2 \times x \times ((5 \times L) - a_1) / (20 \times L^3) - (x - b_1)^3 / (3 \times a_1^2)] = 8.5$$

$$M_{wall} = M_{w\_sur} + M_{w\_m\_a} + M_{w\_m\_b} + M_{w\_s} + M_{w\_water} = 29 \text{ kNm/m}$$

← 200 →



#### Check wall stem in bending

Width of wall stem

$$b = 1000 \text{ mm/m}$$

Depth of reinforcement

$$d_{stem} = t_{wall} - c_{stem} - (\phi_{stem} / 2) = 247.0 \text{ mm}$$

Constant

$$K_{stem} = M_{stem} / (b \times d_{stem}^2 \times f_{cu}) = 0.025$$

**Compression reinforcement is not required**

Lever arm

$$z_{stem} = \min(0.5 + \sqrt{(0.25 - (\min(K_{stem}, 0.225) / 0.9))}, 0.95) \times d_{stem}$$

$$z_{stem} = 235 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_stem\_des} = M_{stem} / (0.87 \times f_y \times z_{stem}) = 597 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_stem\_min} = k \times b \times t_{wall} = 390 \text{ mm}^2/\text{m}$$

Area of tension reinforcement required

$$A_{s\_stem\_req} = \text{Max}(A_{s\_stem\_des}, A_{s\_stem\_min}) = 597 \text{ mm}^2/\text{m}$$

Reinforcement provided

**16 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_stem\_prov} = 1005 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided at the retaining wall stem is adequate**

#### Check shear resistance at wall stem

Design shear stress

$$v_{stem} = V_{stem} / (b \times d_{stem}) = 0.436 \text{ N/mm}^2$$

Allowable shear stress

$$v_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = 5.000 \text{ N/mm}^2$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$v_{c\_stem} = 0.618 \text{ N/mm}^2$$

**$v_{stem} < v_{c\_stem}$  - No shear reinforcement required**

#### Check mid height of wall in bending

Depth of reinforcement

$$d_{wall} = t_{wall} - c_{wall} - (\phi_{wall} / 2) = 249.0 \text{ mm}$$

Constant

$$K_{wall} = M_{wall} / (b \times d_{wall}^2 \times f_{cu}) = 0.012$$

**Compression reinforcement is not required**

Lever arm

$$z_{wall} = \min(0.5 + \sqrt{(0.25 - (\min(K_{wall}, 0.225) / 0.9))}, 0.95) \times d_{wall}$$


$$z_{wall} = 237 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_wall\_des} = M_{wall} / (0.87 \times f_y \times z_{wall}) = 282 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_wall\_min} = k \times b \times t_{wall} = 390 \text{ mm}^2/\text{m}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for rear retaining wall under rear extension				Start page no./Revision 6.4. 8	
	Calcs by ab	Calcs date 20/04/2018	Checked by	Checked date	Approved by	Approved date

Area of tension reinforcement required

$$A_{s\_wall\_req} = \text{Max}(A_{s\_wall\_des}, A_{s\_wall\_min}) = 390 \text{ mm}^2/\text{m}$$

Reinforcement provided

**12 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_wall\_prov} = 565 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided to the retaining wall at mid height is adequate**

#### Check retaining wall deflection

Basic span/effective depth ratio

$$\text{ratio}_{\text{bas}} = 20$$

Design service stress

$$f_s = 2 \times f_y \times A_{s\_stem\_req} / (3 \times A_{s\_stem\_prov}) = 198.0 \text{ N/mm}^2$$

Modification factor

$$\text{factor}_{\text{tens}} = \min(0.55 + (477 \text{ N/mm}^2 - f_s) / (120 \times (0.9 \text{ N/mm}^2 + (M_{\text{stem}} / (b \times d_{\text{stem}}^2)))), 2) = 1.77$$

Maximum span/effective depth ratio

$$\text{ratio}_{\text{max}} = \text{ratio}_{\text{bas}} \times \text{factor}_{\text{tens}} = 35.49$$


Actual span/effective depth ratio

$$\text{ratio}_{\text{act}} = h_{\text{stem}} / d_{\text{stem}} = 12.55$$

**PASS - Span to depth ratio is acceptable**

<div> <div> <div>Tekla</div> <div>Tedds</div> </div> <div> <div>RODRIGUES ASSOCIATES</div> <div>1 AMWELL STREET</div> <div>LONDON</div> <div>EC1R 1UL</div> </div> </div>	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	rear retaining wall under rear extension				6.4. 9	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	20/04/2018				


Indicative retaining wall reinforcement diagram



- Toe bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Wall bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Stem bars - 16 mm dia.@ 200 mm centres - (1005 mm<sup>2</sup>/m)

## RETAINING WALL ANALYSIS (BS 8002:1994)

TEDDS calculation version 1.2.01.06



### Wall details

Retaining wall type

Height of retaining wall stem

Thickness of wall stem

Length of toe

Length of heel

Overall length of base

Thickness of base

Depth of downstand

Position of downstand

Thickness of downstand

Height of retaining wall

Depth of cover in front of wall

Depth of unplanned excavation

Height of ground water behind wall

Height of saturated fill above base

Density of wall construction

Density of base construction

Angle of rear face of wall

Angle of soil surface behind wall

Effective height at virtual back of wall

### Cantilever propped at both

$h_{\text{stem}} = 3100 \text{ mm}$

$t_{\text{wall}} = 300 \text{ mm}$

$l_{\text{toe}} = 650 \text{ mm}$

$l_{\text{heel}} = 0 \text{ mm}$

$l_{\text{base}} = l_{\text{toe}} + l_{\text{heel}} + t_{\text{wall}} = 950 \text{ mm}$

$t_{\text{base}} = 400 \text{ mm}$

$d_{\text{ds}} = 0 \text{ mm}$

$l_{\text{ds}} = 15 \text{ mm}$

$t_{\text{ds}} = 400 \text{ mm}$

$h_{\text{wall}} = h_{\text{stem}} + t_{\text{base}} + d_{\text{ds}} = 3500 \text{ mm}$

$d_{\text{cover}} = 0 \text{ mm}$

$d_{\text{exc}} = 0 \text{ mm}$

$h_{\text{water}} = 3000 \text{ mm}$

$h_{\text{sat}} = \max(h_{\text{water}} - t_{\text{base}} - d_{\text{ds}}, 0 \text{ mm}) = 2600 \text{ mm}$

$\gamma_{\text{wall}} = 23.6 \text{ kN/m}^3$

$\gamma_{\text{base}} = 23.6 \text{ kN/m}^3$

$\alpha = 90.0 \text{ deg}$

$\beta = 0.0 \text{ deg}$

$h_{\text{eff}} = h_{\text{wall}} + l_{\text{heel}} \times \tan(\beta) = 3500 \text{ mm}$


### Retained material details

Mobilisation factor

$M = 1.5$

Moist density of retained material

$\gamma_m = 18.0 \text{ kN/m}^3$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	side retaining wall under rear extension				6.5. 2	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	01/05/2018				

Saturated density of retained material

$$\gamma_s = 21.0 \text{ kN/m}^3$$

Design shear strength

$$\phi' = 18.6 \text{ deg}$$

Angle of wall friction

$$\delta = 0.0 \text{ deg}$$

#### Base material details

Firm clay

Moist density

$$\gamma_{mb} = 18.0 \text{ kN/m}^3$$

Design shear strength

$$\phi'_b = 16.5 \text{ deg}$$

Design base friction

$$\delta_b = 18.6 \text{ deg}$$

Allowable bearing pressure

$$P_{\text{bearing}} = 150 \text{ kN/m}^2$$

#### Using Coulomb theory

Active pressure coefficient for retained material

$$K_a = \sin(\alpha + \phi')^2 / (\sin(\alpha)^2 \times \sin(\alpha - \delta) \times [1 + \sqrt{(\sin(\phi' + \delta) \times \sin(\phi' - \beta) / (\sin(\alpha - \delta) \times \sin(\alpha + \beta)))})^2] = 0.516$$

Passive pressure coefficient for base material

$$K_p = \sin(90 - \phi'_b)^2 / (\sin(90 - \delta_b) \times [1 - \sqrt{(\sin(\phi'_b + \delta_b) \times \sin(\phi'_b) / (\sin(90 + \delta_b)))})^2] = 2.835$$

#### At-rest pressure

At-rest pressure for retained material

$$K_0 = 1 - \sin(\phi') = 0.681$$

#### Loading details

Surcharge load on plan

$$\text{Surcharge} = 12.0 \text{ kN/m}^2$$

Applied vertical dead load on wall

$$W_{\text{dead}} = 0.0 \text{ kN/m}$$

Applied vertical live load on wall

$$W_{\text{live}} = 0.0 \text{ kN/m}$$

Position of applied vertical load on wall

$$l_{\text{load}} = 0 \text{ mm}$$

Applied horizontal dead load on wall


$$F_{\text{dead}} = 0.0 \text{ kN/m}$$

Applied horizontal live load on wall


$$F_{\text{live}} = 0.0 \text{ kN/m}$$

Height of applied horizontal load on wall

$$h_{\text{load}} = 0 \text{ mm}$$



Loads shown in kN/m, pressures shown in kN/m²

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>side retaining wall under rear extension</b>				Start page no./Revision <b>6.5. 3</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

### Vertical forces on wall

Wall stem  $W_{wall} = h_{stem} \times t_{wall} \times \gamma_{wall} = \mathbf{21.9 \text{ kN/m}}$

Wall base  $W_{base} = l_{base} \times t_{base} \times \gamma_{base} = \mathbf{9 \text{ kN/m}}$

Total vertical load  $W_{total} = W_{wall} + W_{base} = \mathbf{30.9 \text{ kN/m}}$

### Horizontal forces on wall

Surcharge  $F_{sur} = K_a \times \text{Surcharge} \times h_{eff} = \mathbf{21.7 \text{ kN/m}}$

Moist backfill above water table  $F_{m\_a} = 0.5 \times K_a \times \gamma_m \times (h_{eff} - h_{water})^2 = \mathbf{1.2 \text{ kN/m}}$

Moist backfill below water table  $F_{m\_b} = K_a \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = \mathbf{13.9 \text{ kN/m}}$

Saturated backfill  $F_s = 0.5 \times K_a \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = \mathbf{26 \text{ kN/m}}$

Water  $F_{water} = 0.5 \times h_{water}^2 \times \gamma_{water} = \mathbf{44.1 \text{ kN/m}}$

Total horizontal load  $F_{total} = F_{sur} + F_{m\_a} + F_{m\_b} + F_s + F_{water} = \mathbf{106.9 \text{ kN/m}}$

### Calculate total propping force

Passive resistance of soil in front of wall  $F_p = 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = \mathbf{3.9 \text{ kN/m}}$

Propping force  $F_{prop} = \max(F_{total} - F_p - (W_{total}) \times \tan(\delta_b), 0 \text{ kN/m})$

$F_{prop} = \mathbf{92.7 \text{ kN/m}}$

### Overturning moments

Surcharge  $M_{sur} = F_{sur} \times (h_{eff} - 2 \times d_{ds}) / 2 = \mathbf{38 \text{ kNm/m}}$

Moist backfill above water table  $M_{m\_a} = F_{m\_a} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = \mathbf{3.7 \text{ kNm/m}}$

Moist backfill below water table  $M_{m\_b} = F_{m\_b} \times (h_{water} - 2 \times d_{ds}) / 2 = \mathbf{20.9 \text{ kNm/m}}$

Saturated backfill  $M_s = F_s \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{26 \text{ kNm/m}}$

Water  $M_{water} = F_{water} \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{44.1 \text{ kNm/m}}$

Total overturning moment  $M_{ot} = M_{sur} + M_{m\_a} + M_{m\_b} + M_s + M_{water} = \mathbf{132.7 \text{ kNm/m}}$

### Restoring moments

Wall stem  $M_{wall} = W_{wall} \times (l_{toe} + t_{wall} / 2) = \mathbf{17.6 \text{ kNm/m}}$

Wall base  $M_{base} = W_{base} \times l_{base} / 2 = \mathbf{4.3 \text{ kNm/m}}$

Total restoring moment  $M_{rest} = M_{wall} + M_{base} = \mathbf{21.8 \text{ kNm/m}}$

### Check bearing pressure

Total vertical reaction  $R = W_{total} = \mathbf{30.9 \text{ kN/m}}$

Distance to reaction  $x_{bar} = l_{base} / 2 = \mathbf{475 \text{ mm}}$

Eccentricity of reaction  $e = \text{abs}((l_{base} / 2) - x_{bar}) = \mathbf{0 \text{ mm}}$

**Reaction acts within middle third of base**

Bearing pressure at toe  $p_{toe} = (R / l_{base}) - (6 \times R \times e / l_{base}^2) = \mathbf{32.5 \text{ kN/m}^2}$

Bearing pressure at heel  $p_{heel} = (R / l_{base}) + (6 \times R \times e / l_{base}^2) = \mathbf{32.5 \text{ kN/m}^2}$

**PASS - Maximum bearing pressure is less than allowable bearing pressure**


### Calculate propping forces to top and base of wall

Propping force to top of wall

$F_{prop\_top} = (M_{ot} - M_{rest} + R \times l_{base} / 2 - F_{prop} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = \mathbf{32.431 \text{ kN/m}}$

Propping force to base of wall

$F_{prop\_base} = F_{prop} - F_{prop\_top} = \mathbf{60.230 \text{ kN/m}}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>side retaining wall under rear extension</b>				Start page no./Revision <b>6.5. 4</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

## **RETAINING WALL DESIGN (BS 8002:1994)**

TEDDS calculation version 1.2.01.06

### **Ultimate limit state load factors**

Dead load factor  $\gamma_{f_d} = 1.4$

Live load factor  $\gamma_{f_l} = 1.6$

Earth and water pressure factor  $\gamma_{f_e} = 1.4$

### **Factored vertical forces on wall**

Wall stem  $W_{wall_f} = \gamma_{f_d} \times h_{stem} \times t_{wall} \times \gamma_{wall} = 30.7 \text{ kN/m}$

Wall base  $W_{base_f} = \gamma_{f_d} \times l_{base} \times t_{base} \times \gamma_{base} = 12.6 \text{ kN/m}$

Total vertical load  $W_{total_f} = W_{wall_f} + W_{base_f} = 43.3 \text{ kN/m}$

### **Factored horizontal at-rest forces on wall**

Surcharge  $F_{sur_f} = \gamma_{f_l} \times K_0 \times \text{Surcharge} \times h_{eff} = 45.8 \text{ kN/m}$

Moist backfill above water table  $F_{m_a_f} = \gamma_{f_e} \times 0.5 \times K_0 \times \gamma_m \times (h_{eff} - h_{water})^2 = 2.1 \text{ kN/m}$

Moist backfill below water table  $F_{m_b_f} = \gamma_{f_e} \times K_0 \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = 25.7 \text{ kN/m}$

Saturated backfill  $F_{s_f} = \gamma_{f_e} \times 0.5 \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = 48 \text{ kN/m}$

Water  $F_{water_f} = \gamma_{f_e} \times 0.5 \times h_{water}^2 \times \gamma_{water} = 61.8 \text{ kN/m}$

Total horizontal load  $F_{total_f} = F_{sur_f} + F_{m_a_f} + F_{m_b_f} + F_{s_f} + F_{water_f} = 183.5 \text{ kN/m}$

### **Calculate total propping force**

Passive resistance of soil in front of wall  $F_{p_f} = \gamma_{f_e} \times 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = 5.4 \text{ kN/m}$

Propping force  $F_{prop_f} = \max(F_{total_f} - F_{p_f} - (W_{total_f}) \times \tan(\delta_b), 0 \text{ kN/m})$

$F_{prop_f} = 163.5 \text{ kN/m}$

### **Factored overturning moments**

Surcharge  $M_{sur_f} = F_{sur_f} \times (h_{eff} - 2 \times d_{ds}) / 2 = 80.1 \text{ kNm/m}$

Moist backfill above water table  $M_{m_a_f} = F_{m_a_f} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = 6.8 \text{ kNm/m}$

Moist backfill below water table  $M_{m_b_f} = F_{m_b_f} \times (h_{water} - 2 \times d_{ds}) / 2 = 38.6 \text{ kNm/m}$

Saturated backfill  $M_{s_f} = F_{s_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 48 \text{ kNm/m}$

Water  $M_{water_f} = F_{water_f} \times (h_{water} - 3 \times d_{ds}) / 3 = 61.8 \text{ kNm/m}$

Total overturning moment  $M_{ot_f} = M_{sur_f} + M_{m_a_f} + M_{m_b_f} + M_{s_f} + M_{water_f} = 235.3 \text{ kNm/m}$

### **Restoring moments**

Wall stem  $M_{wall_f} = W_{wall_f} \times (l_{toe} + t_{wall} / 2) = 24.6 \text{ kNm/m}$

Wall base  $M_{base_f} = W_{base_f} \times l_{base} / 2 = 6 \text{ kNm/m}$

Total restoring moment  $M_{rest_f} = M_{wall_f} + M_{base_f} = 30.5 \text{ kNm/m}$

### **Factored bearing pressure**

Total vertical reaction  $R_f = W_{total_f} = 43.3 \text{ kN/m}$

Distance to reaction  $x_{bar_f} = l_{base} / 2 = 475 \text{ mm}$

Eccentricity of reaction  $e_f = \text{abs}((l_{base} / 2) - x_{bar_f}) = 0 \text{ mm}$

**Reaction acts within middle third of base**

Bearing pressure at toe  $p_{toe_f} = (R_f / l_{base}) - (6 \times R_f \times e_f / l_{base}^2) = 45.6 \text{ kN/m}^2$


Bearing pressure at heel  $p_{heel_f} = (R_f / l_{base}) + (6 \times R_f \times e_f / l_{base}^2) = 45.6 \text{ kN/m}^2$

Rate of change of base reaction  $\text{rate} = (p_{toe_f} - p_{heel_f}) / l_{base} = 0.00 \text{ kN/m}^2/\text{m}$

Bearing pressure at stem / toe  $p_{stem\_toe_f} = \max(p_{toe_f} - (\text{rate} \times l_{toe}), 0 \text{ kN/m}^2) = 45.6 \text{ kN/m}^2$

Bearing pressure at mid stem  $p_{stem\_mid_f} = \max(p_{toe_f} - (\text{rate} \times (l_{toe} + t_{wall} / 2)), 0 \text{ kN/m}^2) = 45.6 \text{ kN/m}^2$

Bearing pressure at stem / heel  $p_{stem\_heel_f} = \max(p_{toe_f} - (\text{rate} \times (l_{toe} + t_{wall})), 0 \text{ kN/m}^2) = 45.6 \text{ kN/m}^2$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for side retaining wall under rear extension				Start page no./Revision 6.5. 5	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

### Calculate propping forces to top and base of wall

Propping force to top of wall

$$F_{prop\_top\_f} = (M_{ot\_f} - M_{rest\_f} + R_f \times l_{base} / 2 - F_{prop\_f} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = \mathbf{58.373 \text{ kN/m}}$$

Propping force to base of wall

$$F_{prop\_base\_f} = F_{prop\_f} - F_{prop\_top\_f} = \mathbf{105.113 \text{ kN/m}}$$

### Design of reinforced concrete retaining wall toe (BS 8002:1994)

#### Material properties

Characteristic strength of concrete

$$f_{cu} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

#### Base details

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in toe

$$c_{toe} = \mathbf{45 \text{ mm}}$$

#### Calculate shear for toe design

Shear from bearing pressure

$$V_{toe\_bear} = (p_{toe\_f} + p_{stem\_toe\_f}) \times l_{toe} / 2 = \mathbf{29.6 \text{ kN/m}}$$

Shear from weight of base

$$V_{toe\_wt\_base} = \gamma_{f\_d} \times \gamma_{base} \times l_{toe} \times t_{base} = \mathbf{8.6 \text{ kN/m}}$$

Total shear for toe design

$$V_{toe} = V_{toe\_bear} - V_{toe\_wt\_base} = \mathbf{21 \text{ kN/m}}$$

#### Calculate moment for toe design

Moment from bearing pressure


$$M_{toe\_bear} = (2 \times p_{toe\_f} + p_{stem\_mid\_f}) \times (l_{toe} + t_{wall} / 2)^2 / 6 = \mathbf{14.6 \text{ kNm/m}}$$

Moment from weight of base

$$M_{toe\_wt\_base} = (\gamma_{f\_d} \times \gamma_{base} \times t_{base} \times (l_{toe} + t_{wall} / 2)^2 / 2) = \mathbf{4.2 \text{ kNm/m}}$$

Total moment for toe design

$$M_{toe} = M_{toe\_bear} - M_{toe\_wt\_base} = \mathbf{10.4 \text{ kNm/m}}$$



#### Check toe in bending

Width of toe

$$b = \mathbf{1000 \text{ mm/m}}$$

Depth of reinforcement

$$d_{toe} = t_{base} - c_{toe} - (\phi_{toe} / 2) = \mathbf{349.0 \text{ mm}}$$

Constant

$$K_{toe} = M_{toe} / (b \times d_{toe}^2 \times f_{cu}) = \mathbf{0.002}$$

**Compression reinforcement is not required**

Lever arm

$$z_{toe} = \min(0.5 + \sqrt{(0.25 - (\min(K_{toe}, 0.225) / 0.9))}, 0.95) \times d_{toe}$$

$$z_{toe} = \mathbf{332 \text{ mm}}$$

Area of tension reinforcement required

$$A_{s\_toe\_des} = M_{toe} / (0.87 \times f_y \times z_{toe}) = \mathbf{72 \text{ mm}^2/\text{m}}$$

Minimum area of tension reinforcement

$$A_{s\_toe\_min} = k \times b \times t_{base} = \mathbf{520 \text{ mm}^2/\text{m}}$$

Area of tension reinforcement required

$$A_{s\_toe\_req} = \text{Max}(A_{s\_toe\_des}, A_{s\_toe\_min}) = \mathbf{520 \text{ mm}^2/\text{m}}$$

Reinforcement provided


$$\mathbf{12 \text{ mm dia. bars @ 200 mm centres}}$$

Area of reinforcement provided

$$A_{s\_toe\_prov} = \mathbf{565 \text{ mm}^2/\text{m}}$$

**PASS - Reinforcement provided at the retaining wall toe is adequate**



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for side retaining wall under rear extension				Start page no./Revision 6.5. 6	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

### Check shear resistance at toe

Design shear stress

$$V_{toe} = V_{toe} / (b \times d_{toe}) = \mathbf{0.060 \text{ N/mm}^2}$$

Allowable shear stress

$$V_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = \mathbf{5.000 \text{ N/mm}^2}$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$V_{c\_toe} = \mathbf{0.417 \text{ N/mm}^2}$$

**$V_{toe} < V_{c\_toe}$  - No shear reinforcement required**

### Design of reinforced concrete retaining wall stem (BS 8002:1994)

#### Material properties

Characteristic strength of concrete

$$f_{cu} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

#### Wall details

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in stem

$$C_{stem} = \mathbf{45 \text{ mm}}$$

Cover to reinforcement in wall

$$C_{wall} = \mathbf{45 \text{ mm}}$$

#### Factored horizontal at-rest forces on stem

Surcharge

$$F_{s\_sur\_f} = \gamma_{f\_l} \times K_0 \times \text{Surcharge} \times (h_{eff} - t_{base} - d_{ds}) = \mathbf{40.5 \text{ kN/m}}$$

Moist backfill above water table

$$F_{s\_m\_a\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat})^2 = \mathbf{2.1 \text{ kN/m}}$$

Moist backfill below water table

$$F_{s\_m\_b\_f} = \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat}) \times h_{sat} = \mathbf{22.3 \text{ kN/m}}$$

Saturated backfill

$$F_{s\_s\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{sat}^2 = \mathbf{36.1 \text{ kN/m}}$$

Water

$$F_{s\_water\_f} = 0.5 \times \gamma_{f\_e} \times \gamma_{water} \times h_{sat}^2 = \mathbf{46.4 \text{ kN/m}}$$

#### Calculate shear for stem design

Surcharge

$$V_{s\_sur\_f} = 5 \times F_{s\_sur\_f} / 8 = \mathbf{25.3 \text{ kN/m}}$$

Moist backfill above water table

$$V_{s\_m\_a\_f} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - b_l^2) / (5 \times L^3) = \mathbf{0.3 \text{ kN/m}}$$

Moist backfill below water table

$$V_{s\_m\_b\_f} = F_{s\_m\_b\_f} \times (8 - (n^2 \times (4 - n))) / 8 = \mathbf{16 \text{ kN/m}}$$

Saturated backfill

$$V_{s\_s\_f} = F_{s\_s\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{30.7 \text{ kN/m}}$$

Water

$$V_{s\_water\_f} = F_{s\_water\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{39.5 \text{ kN/m}}$$

Total shear for stem design

$$V_{stem} = V_{s\_sur\_f} + V_{s\_m\_a\_f} + V_{s\_m\_b\_f} + V_{s\_s\_f} + V_{s\_water\_f} = \mathbf{111.8 \text{ kN/m}}$$

#### Calculate moment for stem design

Surcharge

$$M_{s\_sur} = F_{s\_sur\_f} \times L / 8 = \mathbf{16.7 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{s\_m\_a} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - (3 \times b_l^2)) / (15 \times L^2) = \mathbf{0.4 \text{ kNm/m}}$$

Moist backfill below water table

$$M_{s\_m\_b} = F_{s\_m\_b\_f} \times a_l \times (2 - n)^2 / 8 = \mathbf{10.4 \text{ kNm/m}}$$

Saturated backfill

$$M_{s\_s} = F_{s\_s\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{15.9 \text{ kNm/m}}$$

Water

$$M_{s\_water} = F_{s\_water\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{20.4 \text{ kNm/m}}$$

kNm/m

Total moment for stem design

$$M_{stem} = M_{s\_sur} + M_{s\_m\_a} + M_{s\_m\_b} + M_{s\_s} + M_{s\_water} = \mathbf{63.7 \text{ kNm/m}}$$

#### Calculate moment for wall design

Surcharge

$$M_{w\_sur} = 9 \times F_{s\_sur\_f} \times L / 128 = \mathbf{9.4 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{w\_m\_a} = F_{s\_m\_a\_f} \times 0.577 \times b_l \times [(b_l^3 + 5 \times a_l \times L^2) / (5 \times L^3) - 0.577^2 / 3] = \mathbf{0.5 \text{ kNm/m}}$$

kNm/m

Moist backfill below water table

$$M_{w\_m\_b} = F_{s\_m\_b\_f} \times a_l \times [(8 - n^2 \times (4 - n))^2 / 16 - 4 + n \times (4 - n)] / 8 = \mathbf{5.7 \text{ kNm/m}}$$


Saturated backfill

$$M_{w\_s} = F_{s\_s\_f} \times [a_l^2 \times x \times ((5 \times L) - a_l) / (20 \times L^3) - (x - b_l)^3 / (3 \times a_l^2)] = \mathbf{6.6 \text{ kNm/m}}$$

Water


$$M_{w\_water} = F_{s\_water\_f} \times [a_l^2 \times x \times ((5 \times L) - a_l) / (20 \times L^3) - (x - b_l)^3 / (3 \times a_l^2)] = \mathbf{8.5 \text{ kNm/m}}$$

kNm/m

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for side retaining wall under rear extension				Start page no./Revision 6.5. 7	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Total moment for wall design

$$M_{wall} = M_{w\_sur} + M_{w\_m\_a} + M_{w\_m\_b} + M_{w\_s} + M_{w\_water} = 30.6 \text{ kNm/m}$$



#### Check wall stem in bending

Width of wall stem

$$b = 1000 \text{ mm/m}$$

Depth of reinforcement

$$d_{stem} = t_{wall} - c_{stem} - (\phi_{stem} / 2) = 247.0 \text{ mm}$$

Constant

$$K_{stem} = M_{stem} / (b \times d_{stem}^2 \times f_{cu}) = 0.026$$

**Compression reinforcement is not required**

Lever arm

$$z_{stem} = \min(0.5 + \sqrt{(0.25 - (\min(K_{stem}, 0.225) / 0.9))}, 0.95) \times d_{stem}$$

$$z_{stem} = 235 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_stem\_des} = M_{stem} / (0.87 \times f_y \times z_{stem}) = 624 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_stem\_min} = k \times b \times t_{wall} = 390 \text{ mm}^2/\text{m}$$

Area of tension reinforcement required

$$A_{s\_stem\_req} = \max(A_{s\_stem\_des}, A_{s\_stem\_min}) = 624 \text{ mm}^2/\text{m}$$

Reinforcement provided

$$16 \text{ mm dia. bars @ 200 mm centres}$$

Area of reinforcement provided

$$A_{s\_stem\_prov} = 1005 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided at the retaining wall stem is adequate**

#### Check shear resistance at wall stem

Design shear stress

$$v_{stem} = V_{stem} / (b \times d_{stem}) = 0.453 \text{ N/mm}^2$$

Allowable shear stress

$$v_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = 5.000 \text{ N/mm}^2$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$v_{c\_stem} = 0.618 \text{ N/mm}^2$$

**$v_{stem} < v_{c\_stem}$  - No shear reinforcement required**

#### Check mid height of wall in bending

Depth of reinforcement

$$d_{wall} = t_{wall} - c_{wall} - (\phi_{wall} / 2) = 249.0 \text{ mm}$$

Constant

$$K_{wall} = M_{wall} / (b \times d_{wall}^2 \times f_{cu}) = 0.012$$

**Compression reinforcement is not required**

Lever arm

$$z_{wall} = \min(0.5 + \sqrt{(0.25 - (\min(K_{wall}, 0.225) / 0.9))}, 0.95) \times d_{wall}$$

$$z_{wall} = 237 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_wall\_des} = M_{wall} / (0.87 \times f_y \times z_{wall}) = 297 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement


$$A_{s\_wall\_min} = k \times b \times t_{wall} = 390 \text{ mm}^2/\text{m}$$

Area of tension reinforcement required

$$A_{s\_wall\_req} = \max(A_{s\_wall\_des}, A_{s\_wall\_min}) = 390 \text{ mm}^2/\text{m}$$

Reinforcement provided

$$12 \text{ mm dia. bars @ 200 mm centres}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for side retaining wall under rear extension				Start page no./Revision 6.5. 8	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Area of reinforcement provided

$$A_{s\_wall\_prov} = 565 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided to the retaining wall at mid height is adequate**

**Check retaining wall deflection**

Basic span/effective depth ratio

$$\text{ratio}_{bas} = 20$$

Design service stress

$$f_s = 2 \times f_y \times A_{s\_stem\_req} / (3 \times A_{s\_stem\_prov}) = 207.0 \text{ N/mm}^2$$

Modification factor

$$\text{factor}_{tens} = \min(0.55 + (477 \text{ N/mm}^2 - f_s) / (120 \times (0.9 \text{ N/mm}^2 + (M_{stem} / (b \times d_{stem}^2)))), 2) = 1.71$$

Maximum span/effective depth ratio

$$\text{ratio}_{max} = \text{ratio}_{bas} \times \text{factor}_{tens} = 34.14$$


Actual span/effective depth ratio

$$\text{ratio}_{act} = h_{stem} / d_{stem} = 12.55$$

**PASS - Span to depth ratio is acceptable**

<div> <div> <div>Tekla</div> <div>Tedds</div> </div> <div> <div>RODRIGUES ASSOCIATES</div> <div>1 AMWELL STREET</div> <div>LONDON</div> <div>EC1R 1UL</div> </div> </div>	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for				Start page no./Revision	
	side retaining wall under rear extension				6.5. 9	
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date
	ab	01/05/2018				

Indicative retaining wall reinforcement diagram




- Toe bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Wall bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Stem bars - 16 mm dia.@ 200 mm centres - (1005 mm<sup>2</sup>/m)

Project 10 Downside Crescent				Job no. 1411	
Calcs for side retaining wall under rear extension top beam				Start page no./Revision 6.5B. 1	
Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

## RC BEAM ANALYSIS & DESIGN BS8110

TEDDS calculation version 2.1.12



### Support conditions

Support A

Vertically restrained

Rotationally free

Support B

Vertically restrained

Rotationally free

### Applied loading

Dead self weight of beam  $\times 0$

Dead full UDL 58.4 kN/m

### Load combinations

Load combination 1

Support A

Dead  $\times 1.00$

Imposed  $\times 1.00$

Span 1

Dead  $\times 1.00$

Imposed  $\times 1.00$

Support B

Dead  $\times 1.00$

Imposed  $\times 1.00$

### Analysis results

Maximum moment support A


$M_{A\_max} = 0 \text{ kNm}$

$M_{A\_red} = 0 \text{ kNm}$

Maximum moment span 1 at 2400 mm

$M_{s1\_max} = 168 \text{ kNm}$


$M_{s1\_red} = 168 \text{ kNm}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>side retaining wall under rear extension top beam</b>				Start page no./Revision <b>6.5B. 2</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

Maximum moment support B	$M_{B\_max} = 0 \text{ kNm}$	$M_{B\_red} = 0 \text{ kNm}$
Maximum shear support A	$V_{A\_max} = 140 \text{ kN}$	$V_{A\_red} = 140 \text{ kN}$
Maximum shear support A span 1 at 293 mm	$V_{A\_s1\_max} = 124 \text{ kN}$	$V_{A\_s1\_red} = 124 \text{ kN}$
Maximum shear support B	$V_{B\_max} = -140 \text{ kN}$	$V_{B\_red} = -140 \text{ kN}$
Maximum shear support B span 1 at 4507 mm	$V_{B\_s1\_max} = -124 \text{ kN}$	$V_{B\_s1\_red} = -124 \text{ kN}$
Maximum reaction at support A	$R_A = 140 \text{ kN}$	
Unfactored dead load reaction at support A	$R_{A\_Dead} = 140 \text{ kN}$	
Maximum reaction at support B	$R_B = 140 \text{ kN}$	
Unfactored dead load reaction at support B	$R_{B\_Dead} = 140 \text{ kN}$	

#### Rectangular section details

Section width	$b = 300 \text{ mm}$
Section depth	$h = 350 \text{ mm}$



#### Concrete details

Concrete strength class	<b>C32/40</b>
Characteristic compressive cube strength	$f_{cu} = 40 \text{ N/mm}^2$
Modulus of elasticity of concrete	$E_c = 20 \text{ kN/mm}^2 + 200 \times f_{cu} = 28000 \text{ N/mm}^2$
Maximum aggregate size	$h_{agg} = 20 \text{ mm}$


#### Reinforcement details


Characteristic yield strength of reinforcement	$f_y = 500 \text{ N/mm}^2$
Characteristic yield strength of shear reinforcement	$f_{yv} = 500 \text{ N/mm}^2$

#### Nominal cover to reinforcement

Nominal cover to top reinforcement	$C_{nom\_t} = 35 \text{ mm}$
Nominal cover to bottom reinforcement	$C_{nom\_b} = 35 \text{ mm}$
Nominal cover to side reinforcement	$C_{nom\_s} = 35 \text{ mm}$

#### Support A



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for side retaining wall under rear extension top beam				Start page no./Revision 6.5B. 3	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

### Rectangular section in shear

Design shear force span 1 at 293 mm

$$V = \max(V_{A_{s1\_max}}, V_{A_{s1\_red}}) = 124 \text{ kN}$$

Design shear stress

$$v = V / (b \times d) = 1.409 \text{ N/mm}^2$$

Design concrete shear stress

$$v_c = 0.79 \times \min(3, [100 \times A_{s,prov} / (b \times d)]^{1/3}) \times \max(1, (400 / d)^{1/4}) \times$$

$$(\min(f_{cu}, 40) / 25)^{1/3} / \gamma_m$$

$$v_c = 1.046 \text{ N/mm}^2$$

Allowable design shear stress

$$v_{max} = \min(0.8 \text{ N/mm}^2 \times (f_{cu} / 1 \text{ N/mm}^2)^{0.5}, 5 \text{ N/mm}^2) = 5.000 \text{ N/mm}^2$$

**PASS - Design shear stress is less than maximum allowable**

Value of  $v$  from Table 3.7

$$0.5 \times v_c < v < (v_c + 0.4 \text{ N/mm}^2)$$

Design shear resistance required

$$v_s = \max(v - v_c, 0.4 \text{ N/mm}^2) = 0.400 \text{ N/mm}^2$$

Area of shear reinforcement required

$$A_{sv,req} = v_s \times b / (0.87 \times f_{yv}) = 276 \text{ mm}^2/\text{m}$$

Shear reinforcement provided

$$2 \times 10\phi \text{ legs at } 200 \text{ c/c}$$

Area of shear reinforcement provided

$$A_{sv,prov} = 785 \text{ mm}^2/\text{m}$$


**PASS - Area of shear reinforcement provided exceeds minimum required**

Maximum longitudinal spacing

$$s_{vl,max} = 0.75 \times d = 219 \text{ mm}$$

**PASS - Longitudinal spacing of shear reinforcement provided is less than maximum**

### Mid span 1



### Design moment resistance of rectangular section (cl. 3.4.4) - Positive moment

Design bending moment

$$M = \text{abs}(M_{s1\_red}) = 168 \text{ kNm}$$

Depth to tension reinforcement

$$d = h - c_{nom\_b} - \phi_v - \phi_{bot} / 2 = 293 \text{ mm}$$

Redistribution ratio

$$\beta_b = \min(1 - m_{rs1}, 1) = 1.000$$

$$K = M / (b \times d^2 \times f_{cu}) = 0.164$$

$$K' = 0.156$$

**K > K' - Compression reinforcement is required**

Lever arm

$$z = d \times (0.5 + (0.25 - K' / 0.9)^{0.5}) = 227 \text{ mm}$$

Depth of neutral axis

$$x = (d - z) / 0.45 = 145 \text{ mm}$$

Depth of compression reinforcement

$$d_2 = c_{nom\_t} + \phi_v + \phi_{top} / 2 = 51 \text{ mm}$$

Area of compression reinforcement required

$$A_{s2,req} = (K - K') \times f_{cu} \times b \times d^2 / (0.87 \times f_y \times (d - d_2)) = 76 \text{ mm}^2$$

Compression reinforcement provided

$$3 \times 12\phi \text{ bars}$$

Area of compression reinforcement provided

$$A_{s2,prov} = 339 \text{ mm}^2$$

Maximum area of reinforcement (cl.9.2.1.1(3))

$$A_{s,max} = 0.04 \times b \times h = 4200 \text{ mm}^2$$

**PASS - Area of reinforcement provided is greater than area of reinforcement required**

Area of tension reinforcement required


$$A_{s,req} = K' \times f_{cu} \times b \times d^2 / (0.87 \times f_y \times z) + A_{s2,req} = 1697 \text{ mm}^2$$

Tension reinforcement provided

$$4 \times 25\phi \text{ bars}$$

Area of tension reinforcement provided

$$A_{s,prov} = 1963 \text{ mm}^2$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for side retaining wall under rear extension top beam				Start page no./Revision 6.5B. 4	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Minimum area of reinforcement (exp.9.1N)  $A_{s,min} = 0.0013 \times b \times h = 137 \text{ mm}^2$

**PASS - Area of reinforcement provided is greater than area of reinforcement required**

#### Rectangular section in shear

Shear reinforcement provided  $2 \times 10\phi$  legs at 200 c/c

Area of shear reinforcement provided  $A_{sv,prov} = 785 \text{ mm}^2/\text{m}$

Minimum area of shear reinforcement (Table 3.7)  $A_{sv,min} = 0.4\text{N}/\text{mm}^2 \times b / (0.87 \times f_{yv}) = 276 \text{ mm}^2/\text{m}$

**PASS - Area of shear reinforcement provided exceeds minimum required**

Maximum longitudinal spacing (cl. 3.4.5.5)  $s_{vl,max} = 0.75 \times d = 219 \text{ mm}$

**PASS - Longitudinal spacing of shear reinforcement provided is less than maximum**

Design concrete shear stress  $v_c = 0.79\text{N}/\text{mm}^2 \times \min(3, [100 \times A_{s,prov} / (b \times d)]^{1/3}) \times \max(1, (400\text{mm} / d)^{1/4}) \times (\min(f_{cu}, 40\text{N}/\text{mm}^2) / 25\text{N}/\text{mm}^2)^{1/3} / \gamma_m = 1.046 \text{ N}/\text{mm}^2$

Design shear resistance provided  $V_{s,prov} = A_{sv,prov} \times 0.87 \times f_{yv} / b = 1.139 \text{ N}/\text{mm}^2$

Design shear stress provided  $V_{prov} = V_{s,prov} + v_c = 2.184 \text{ N}/\text{mm}^2$

Design shear resistance  $V_{prov} = V_{prov} \times (b \times d) = 191.7 \text{ kN}$

**Shear links provided valid between 0 mm and 4800 mm with tension reinforcement of 1963 mm<sup>2</sup>**

#### Spacing of reinforcement (cl 3.12.11)

Actual distance between bars in tension  $s = (b - 2 \times (c_{nom,s} + \phi_v + \phi_{bot}/2)) / (N_{bot} - 1) - \phi_{bot} = 37 \text{ mm}$

#### Minimum distance between bars in tension (cl 3.12.11.1)

Minimum distance between bars in tension  $s_{min} = h_{agg} + 5 \text{ mm} = 25 \text{ mm}$

**PASS - Satisfies the minimum spacing criteria**

#### Maximum distance between bars in tension (cl 3.12.11.2)

Design service stress  $f_s = (2 \times f_y \times A_{s,req}) / (3 \times A_{s,prov} \times \beta_b) = 288.0 \text{ N}/\text{mm}^2$

Maximum distance between bars in tension  $s_{max} = \min(47000 \text{ N}/\text{mm} / f_s, 300 \text{ mm}) = 163 \text{ mm}$

**PASS - Satisfies the maximum spacing criteria**

#### Span to depth ratio (cl. 3.4.6)

Basic span to depth ratio (Table 3.9)  $\text{span\_to\_depth}_{basic} = 20.0$

Design service stress in tension reinforcement  $f_s = (2 \times f_y \times A_{s,req}) / (3 \times A_{s,prov} \times \beta_b) = 288.0 \text{ N}/\text{mm}^2$

Modification for tension reinforcement

$$f_{tens} = \min(2.0, 0.55 + (477\text{N}/\text{mm}^2 - f_s) / (120 \times (0.9\text{N}/\text{mm}^2 + (M / (b \times d^2)))) = 0.761$$

Modification for compression reinforcement

$$f_{comp} = \min(1.5, 1 + (100 \times A_{s2,prov} / (b \times d)) / (3 + (100 \times A_{s2,prov} / (b \times d)))) = 1.114$$

Modification for span length

$$f_{long} = 1.000$$

Allowable span to depth ratio


$$\text{span\_to\_depth}_{allow} = \text{span\_to\_depth}_{basic} \times f_{tens} \times f_{comp} = 17.0$$

Actual span to depth ratio


$$\text{span\_to\_depth}_{actual} = L_{s1} / d = 16.4$$

**PASS - Actual span to depth ratio is within the allowable limit**



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>side retaining wall under rear extension top beam</b>				Start page no./Revision <b>6.5B. 5</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

### Support B



### **Rectangular section in shear**

Design shear force span 1 at 4507 mm

$$V = \text{abs}(\min(V_{B\_s1\_max}, V_{B\_s1\_red})) = \mathbf{124 \text{ kN}}$$

Design shear stress

$$v = V / (b \times d) = \mathbf{1.409 \text{ N/mm}^2}$$

Design concrete shear stress

$$v_c = 0.79 \times \min(3, [100 \times A_{s,prov} / (b \times d)]^{1/3}) \times \max(1, (400/d)^{1/4}) \times$$

$$(\min(f_{cu}, 40) / 25)^{1/3} / \gamma_m$$

$$v_c = \mathbf{1.046 \text{ N/mm}^2}$$

Allowable design shear stress

$$v_{max} = \min(0.8 \text{ N/mm}^2 \times (f_{cu}/1 \text{ N/mm}^2)^{0.5}, 5 \text{ N/mm}^2) = \mathbf{5.000 \text{ N/mm}^2}$$

**PASS - Design shear stress is less than maximum allowable**

Value of v from Table 3.7

$$0.5 \times v_c < v < (v_c + 0.4 \text{ N/mm}^2)$$

Design shear resistance required

$$v_s = \max(v - v_c, 0.4 \text{ N/mm}^2) = \mathbf{0.400 \text{ N/mm}^2}$$

Area of shear reinforcement required

$$A_{sv,req} = v_s \times b / (0.87 \times f_{yv}) = \mathbf{276 \text{ mm}^2/\text{m}}$$

Shear reinforcement provided

$$2 \times 10\phi \text{ legs at } 200 \text{ c/c}$$

Area of shear reinforcement provided

$$A_{sv,prov} = \mathbf{785 \text{ mm}^2/\text{m}}$$

**PASS - Area of shear reinforcement provided exceeds minimum required**


Maximum longitudinal spacing

$$s_{vl,max} = 0.75 \times d = \mathbf{219 \text{ mm}}$$

**PASS - Longitudinal spacing of shear reinforcement provided is less than maximum**

## RETAINING WALL ANALYSIS (BS 8002:1994)

TEDDS calculation version 1.2.01.06



### Wall details

Retaining wall type

Height of retaining wall stem

Thickness of wall stem

Length of toe

Length of heel

Overall length of base

Thickness of base

Depth of downstand

Position of downstand

Thickness of downstand

Height of retaining wall

Depth of cover in front of wall

Depth of unplanned excavation

Height of ground water behind wall

Height of saturated fill above base

Density of wall construction

Density of base construction

Angle of rear face of wall

Angle of soil surface behind wall

Effective height at virtual back of wall

### Cantilever propped at both

$h_{\text{stem}} = 3100 \text{ mm}$

$t_{\text{wall}} = 330 \text{ mm}$

$l_{\text{toe}} = 650 \text{ mm}$

$l_{\text{heel}} = 0 \text{ mm}$

$l_{\text{base}} = l_{\text{toe}} + l_{\text{heel}} + t_{\text{wall}} = 980 \text{ mm}$

$t_{\text{base}} = 400 \text{ mm}$

$d_{\text{ds}} = 0 \text{ mm}$

$l_{\text{ds}} = 15 \text{ mm}$

$t_{\text{ds}} = 400 \text{ mm}$

$h_{\text{wall}} = h_{\text{stem}} + t_{\text{base}} + d_{\text{ds}} = 3500 \text{ mm}$

$d_{\text{cover}} = 0 \text{ mm}$

$d_{\text{exc}} = 0 \text{ mm}$

$h_{\text{water}} = 3000 \text{ mm}$

$h_{\text{sat}} = \max(h_{\text{water}} - t_{\text{base}} - d_{\text{ds}}, 0 \text{ mm}) = 2600 \text{ mm}$

$\gamma_{\text{wall}} = 23.6 \text{ kN/m}^3$

$\gamma_{\text{base}} = 23.6 \text{ kN/m}^3$

$\alpha = 90.0 \text{ deg}$

$\beta = 0.0 \text{ deg}$

$h_{\text{eff}} = h_{\text{wall}} + l_{\text{heel}} \times \tan(\beta) = 3500 \text{ mm}$


### Retained material details

Mobilisation factor

$M = 1.5$

Moist density of retained material

$\gamma_m = 18.0 \text{ kN/m}^3$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>retaining wall under main building side wall</b>				Start page no./Revision <b>6.6. 2</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

Saturated density of retained material  $\gamma_s = 21.0 \text{ kN/m}^3$

Design shear strength  $\phi' = 18.6 \text{ deg}$

Angle of wall friction  $\delta = 0.0 \text{ deg}$

#### Base material details

Firm clay

Moist density  $\gamma_{mb} = 18.0 \text{ kN/m}^3$

Design shear strength  $\phi'_b = 16.5 \text{ deg}$

Design base friction  $\delta_b = 18.6 \text{ deg}$

Allowable bearing pressure  $P_{\text{bearing}} = 150 \text{ kN/m}^2$

#### Using Coulomb theory

Active pressure coefficient for retained material

$$K_a = \sin(\alpha + \phi')^2 / (\sin(\alpha)^2 \times \sin(\alpha - \delta) \times [1 + \sqrt{(\sin(\phi' + \delta) \times \sin(\phi' - \beta) / (\sin(\alpha - \delta) \times \sin(\alpha + \beta)))^2}] = 0.516$$

Passive pressure coefficient for base material

$$K_p = \sin(90 - \phi'_b)^2 / (\sin(90 - \delta_b) \times [1 - \sqrt{(\sin(\phi'_b + \delta_b) \times \sin(\phi'_b) / (\sin(90 + \delta_b)))^2}] = 2.835$$

#### At-rest pressure

At-rest pressure for retained material  $K_0 = 1 - \sin(\phi') = 0.681$

#### Loading details

Surcharge load on plan **Surcharge = 25.0 kN/m<sup>2</sup>**

Applied vertical dead load on wall  $W_{\text{dead}} = 80.7 \text{ kN/m}$


Applied vertical live load on wall  $W_{\text{live}} = 4.8 \text{ kN/m}$

Position of applied vertical load on wall  $l_{\text{load}} = 815 \text{ mm}$


Applied horizontal dead load on wall  $F_{\text{dead}} = 0.0 \text{ kN/m}$

Applied horizontal live load on wall  $F_{\text{live}} = 0.0 \text{ kN/m}$

Height of applied horizontal load on wall  $h_{\text{load}} = 0 \text{ mm}$



Loads shown in kN/m, pressures shown in kN/m<sup>2</sup>

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for retaining wall under main building side wall				Start page no./Revision 6.6. 3	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

### Vertical forces on wall

Wall stem	$W_{wall} = h_{stem} \times t_{wall} \times \gamma_{wall} = 24.1 \text{ kN/m}$
Wall base	$W_{base} = l_{base} \times t_{base} \times \gamma_{base} = 9.3 \text{ kN/m}$
Applied vertical load	$W_v = W_{dead} + W_{live} = 85.5 \text{ kN/m}$
Total vertical load	$W_{total} = W_{wall} + W_{base} + W_v = 118.9 \text{ kN/m}$

### Horizontal forces on wall

Surcharge	$F_{sur} = K_a \times \text{Surcharge} \times h_{eff} = 45.2 \text{ kN/m}$
Moist backfill above water table	$F_{m\_a} = 0.5 \times K_a \times \gamma_m \times (h_{eff} - h_{water})^2 = 1.2 \text{ kN/m}$
Moist backfill below water table	$F_{m\_b} = K_a \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = 13.9 \text{ kN/m}$
Saturated backfill	$F_s = 0.5 \times K_a \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = 26 \text{ kN/m}$
Water	$F_{water} = 0.5 \times h_{water}^2 \times \gamma_{water} = 44.1 \text{ kN/m}$
Total horizontal load	$F_{total} = F_{sur} + F_{m\_a} + F_{m\_b} + F_s + F_{water} = 130.4 \text{ kN/m}$

### Calculate total propping force

Passive resistance of soil in front of wall	$F_p = 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = 3.9 \text{ kN/m}$
Propping force	$F_{prop} = \max(F_{total} - F_p - (W_{total} - W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$ $F_{prop} = 88.2 \text{ kN/m}$

### Overturning moments

Surcharge	$M_{sur} = F_{sur} \times (h_{eff} - 2 \times d_{ds}) / 2 = 79.1 \text{ kNm/m}$
Moist backfill above water table	$M_{m\_a} = F_{m\_a} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = 3.7 \text{ kNm/m}$
Moist backfill below water table	$M_{m\_b} = F_{m\_b} \times (h_{water} - 2 \times d_{ds}) / 2 = 20.9 \text{ kNm/m}$
Saturated backfill	$M_s = F_s \times (h_{water} - 3 \times d_{ds}) / 3 = 26 \text{ kNm/m}$
Water	$M_{water} = F_{water} \times (h_{water} - 3 \times d_{ds}) / 3 = 44.1 \text{ kNm/m}$
Total overturning moment	$M_{ot} = M_{sur} + M_{m\_a} + M_{m\_b} + M_s + M_{water} = 173.8 \text{ kNm/m}$

### Restoring moments

Wall stem	$M_{wall} = W_{wall} \times (l_{toe} + t_{wall} / 2) = 19.7 \text{ kNm/m}$
Wall base	$M_{base} = W_{base} \times l_{base} / 2 = 4.5 \text{ kNm/m}$
Design vertical dead load	$M_{dead} = W_{dead} \times l_{load} = 65.8 \text{ kNm/m}$
Total restoring moment	$M_{rest} = M_{wall} + M_{base} + M_{dead} = 90 \text{ kNm/m}$

### Check bearing pressure

Total vertical reaction	$R = W_{total} = 118.9 \text{ kN/m}$
Distance to reaction	$x_{bar} = l_{base} / 2 = 490 \text{ mm}$
Eccentricity of reaction	$e = \text{abs}((l_{base} / 2) - x_{bar}) = 0 \text{ mm}$


**Reaction acts within middle third of base**

Bearing pressure at toe	$p_{toe} = (R / l_{base}) - (6 \times R \times e / l_{base}^2) = 121.3 \text{ kN/m}^2$
Bearing pressure at heel	$p_{heel} = (R / l_{base}) + (6 \times R \times e / l_{base}^2) = 121.3 \text{ kN/m}^2$

**PASS - Maximum bearing pressure is less than allowable bearing pressure**

### Calculate propping forces to top and base of wall

Propping force to top of wall	$F_{prop\_top} = (M_{ot} - M_{rest} + R \times l_{base} / 2 - F_{prop} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = 37.711 \text{ kN/m}$
Propping force to base of wall	$F_{prop\_base} = F_{prop} - F_{prop\_top} = 50.451 \text{ kN/m}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>retaining wall under main building side wall</b>				Start page no./Revision <b>6.6. 4</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

## **RETAINING WALL DESIGN (BS 8002:1994)**

TEDDS calculation version 1.2.01.06

### **Ultimate limit state load factors**

Dead load factor  $\gamma_{f_d} = \mathbf{1.4}$

Live load factor  $\gamma_{f_l} = \mathbf{1.6}$

Earth and water pressure factor  $\gamma_{f_e} = \mathbf{1.4}$

### **Factored vertical forces on wall**

Wall stem  $W_{wall\_f} = \gamma_{f_d} \times h_{stem} \times t_{wall} \times \gamma_{wall} = \mathbf{33.8 \text{ kN/m}}$

Wall base  $W_{base\_f} = \gamma_{f_d} \times l_{base} \times t_{base} \times \gamma_{base} = \mathbf{13 \text{ kN/m}}$

Applied vertical load  $W_{v\_f} = \gamma_{f_d} \times W_{dead} + \gamma_{f_l} \times W_{live} = \mathbf{120.7 \text{ kN/m}}$

Total vertical load  $W_{total\_f} = W_{wall\_f} + W_{base\_f} + W_{v\_f} = \mathbf{167.4 \text{ kN/m}}$

### **Factored horizontal at-rest forces on wall**

Surcharge  $F_{sur\_f} = \gamma_{f_l} \times K_0 \times \text{Surcharge} \times h_{eff} = \mathbf{95.3 \text{ kN/m}}$

Moist backfill above water table  $F_{m\_a\_f} = \gamma_{f_e} \times 0.5 \times K_0 \times \gamma_m \times (h_{eff} - h_{water})^2 = \mathbf{2.1 \text{ kN/m}}$

Moist backfill below water table  $F_{m\_b\_f} = \gamma_{f_e} \times K_0 \times \gamma_m \times (h_{eff} - h_{water}) \times h_{water} = \mathbf{25.7 \text{ kN/m}}$

Saturated backfill  $F_{s\_f} = \gamma_{f_e} \times 0.5 \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{water}^2 = \mathbf{48 \text{ kN/m}}$

Water  $F_{water\_f} = \gamma_{f_e} \times 0.5 \times h_{water}^2 \times \gamma_{water} = \mathbf{61.8 \text{ kN/m}}$

Total horizontal load  $F_{total\_f} = F_{sur\_f} + F_{m\_a\_f} + F_{m\_b\_f} + F_{s\_f} + F_{water\_f} = \mathbf{233 \text{ kN/m}}$

### **Calculate total propping force**

Passive resistance of soil in front of wall  
kN/m  $F_{p\_f} = \gamma_{f_e} \times 0.5 \times K_p \times \cos(\delta_b) \times (d_{cover} + t_{base} + d_{ds} - d_{exc})^2 \times \gamma_{mb} = \mathbf{5.4}$

Propping force  $F_{prop\_f} = \max(F_{total\_f} - F_{p\_f} - (W_{total\_f} - \gamma_{f_l} \times W_{live}) \times \tan(\delta_b), 0 \text{ kN/m})$

$F_{prop\_f} = \mathbf{173.9 \text{ kN/m}}$

### **Factored overturning moments**

Surcharge  $M_{sur\_f} = F_{sur\_f} \times (h_{eff} - 2 \times d_{ds}) / 2 = \mathbf{166.9 \text{ kNm/m}}$

Moist backfill above water table  $M_{m\_a\_f} = F_{m\_a\_f} \times (h_{eff} + 2 \times h_{water} - 3 \times d_{ds}) / 3 = \mathbf{6.8 \text{ kNm/m}}$

Moist backfill below water table  $M_{m\_b\_f} = F_{m\_b\_f} \times (h_{water} - 2 \times d_{ds}) / 2 = \mathbf{38.6 \text{ kNm/m}}$

Saturated backfill  $M_{s\_f} = F_{s\_f} \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{48 \text{ kNm/m}}$

Water  $M_{water\_f} = F_{water\_f} \times (h_{water} - 3 \times d_{ds}) / 3 = \mathbf{61.8 \text{ kNm/m}}$

Total overturning moment  $M_{ot\_f} = M_{sur\_f} + M_{m\_a\_f} + M_{m\_b\_f} + M_{s\_f} + M_{water\_f} = \mathbf{322.1 \text{ kNm/m}}$

### **Restoring moments**

Wall stem  $M_{wall\_f} = W_{wall\_f} \times (l_{toe} + t_{wall} / 2) = \mathbf{27.5 \text{ kNm/m}}$

Wall base  $M_{base\_f} = W_{base\_f} \times l_{base} / 2 = \mathbf{6.3 \text{ kNm/m}}$

Design vertical load  $M_{v\_f} = W_{v\_f} \times l_{load} = \mathbf{98.3 \text{ kNm/m}}$

Total restoring moment  $M_{rest\_f} = M_{wall\_f} + M_{base\_f} + M_{v\_f} = \mathbf{132.2 \text{ kNm/m}}$

### **Factored bearing pressure**

Total vertical reaction  $R_f = W_{total\_f} = \mathbf{167.4 \text{ kN/m}}$

Distance to reaction  $x_{bar\_f} = l_{base} / 2 = \mathbf{490 \text{ mm}}$

Eccentricity of reaction  $e_f = \text{abs}((l_{base} / 2) - x_{bar\_f}) = \mathbf{0 \text{ mm}}$


**Reaction acts within middle third of base**

Bearing pressure at toe  $p_{toe\_f} = (R_f / l_{base}) - (6 \times R_f \times e_f / l_{base}^2) = \mathbf{170.8 \text{ kN/m}^2}$

Bearing pressure at heel  $p_{heel\_f} = (R_f / l_{base}) + (6 \times R_f \times e_f / l_{base}^2) = \mathbf{170.8 \text{ kN/m}^2}$

Rate of change of base reaction  $\text{rate} = (p_{toe\_f} - p_{heel\_f}) / l_{base} = \mathbf{0.00 \text{ kN/m}^2/\text{m}}$

Bearing pressure at stem / toe  $p_{stem\_toe\_f} = \max(p_{toe\_f} - (\text{rate} \times l_{toe}), 0 \text{ kN/m}^2) = \mathbf{170.8 \text{ kN/m}^2}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project <b>10 Downside Crescent</b>				Job no. <b>1411</b>	
	Calcs for <b>retaining wall under main building side wall</b>				Start page no./Revision <b>6.6. 5</b>	
	Calcs by <b>ab</b>	Calcs date <b>01/05/2018</b>	Checked by	Checked date	Approved by	Approved date

Bearing pressure at mid stem  $p_{stem\_mid\_f} = \max(p_{toe\_f} - (\text{rate} \times (l_{toe} + t_{wall} / 2)), 0 \text{ kN/m}^2) = \mathbf{170.8 \text{ kN/m}^2}$

Bearing pressure at stem / heel  $p_{stem\_heel\_f} = \max(p_{toe\_f} - (\text{rate} \times (l_{toe} + t_{wall})), 0 \text{ kN/m}^2) = \mathbf{170.8 \text{ kN/m}^2}$

### Calculate propping forces to top and base of wall

Propping force to top of wall

$$F_{prop\_top\_f} = (M_{ot\_f} - M_{rest\_f} + R_f \times l_{base} / 2 - F_{prop\_f} \times t_{base} / 2) / (h_{stem} + t_{base} / 2) = \mathbf{71.849 \text{ kN/m}}$$

Propping force to base of wall

$$F_{prop\_base\_f} = F_{prop\_f} - F_{prop\_top\_f} = \mathbf{102.026 \text{ kN/m}}$$

### Design of reinforced concrete retaining wall toe (BS 8002:1994)

#### Material properties

Characteristic strength of concrete  $f_{cu} = \mathbf{40 \text{ N/mm}^2}$

Characteristic strength of reinforcement  $f_y = \mathbf{500 \text{ N/mm}^2}$

#### Base details

Minimum area of reinforcement  $k = \mathbf{0.13 \%}$

Cover to reinforcement in toe  $c_{toe} = \mathbf{45 \text{ mm}}$

#### Calculate shear for toe design

Shear from bearing pressure  $V_{toe\_bear} = (p_{toe\_f} + p_{stem\_toe\_f}) \times l_{toe} / 2 = \mathbf{111 \text{ kN/m}}$

Shear from weight of base  $V_{toe\_wt\_base} = \gamma_{f\_d} \times \gamma_{base} \times l_{toe} \times t_{base} = \mathbf{8.6 \text{ kN/m}}$


Total shear for toe design  $V_{toe} = V_{toe\_bear} - V_{toe\_wt\_base} = \mathbf{102.4 \text{ kN/m}}$

#### Calculate moment for toe design

Moment from bearing pressure  $M_{toe\_bear} = (2 \times p_{toe\_f} + p_{stem\_mid\_f}) \times (l_{toe} + t_{wall} / 2)^2 / 6 = \mathbf{56.7 \text{ kNm/m}}$

Moment from weight of base  $M_{toe\_wt\_base} = (\gamma_{f\_d} \times \gamma_{base} \times t_{base} \times (l_{toe} + t_{wall} / 2)^2 / 2) = \mathbf{4.4 \text{ kNm/m}}$

Total moment for toe design  $M_{toe} = M_{toe\_bear} - M_{toe\_wt\_base} = \mathbf{52.3 \text{ kNm/m}}$



#### Check toe in bending

Width of toe  $b = \mathbf{1000 \text{ mm/m}}$

Depth of reinforcement  $d_{toe} = t_{base} - c_{toe} - (\phi_{toe} / 2) = \mathbf{349.0 \text{ mm}}$

Constant  $K_{toe} = M_{toe} / (b \times d_{toe}^2 \times f_{cu}) = \mathbf{0.011}$

**Compression reinforcement is not required**

Lever arm  $z_{toe} = \min(0.5 + \sqrt{(0.25 - (\min(K_{toe}, 0.225) / 0.9))}, 0.95) \times d_{toe}$

$$z_{toe} = \mathbf{332 \text{ mm}}$$


Area of tension reinforcement required  $A_{s\_toe\_des} = M_{toe} / (0.87 \times f_y \times z_{toe}) = \mathbf{363 \text{ mm}^2/\text{m}}$

Minimum area of tension reinforcement  $A_{s\_toe\_min} = k \times b \times t_{base} = \mathbf{520 \text{ mm}^2/\text{m}}$

Area of tension reinforcement required  $A_{s\_toe\_req} = \text{Max}(A_{s\_toe\_des}, A_{s\_toe\_min}) = \mathbf{520 \text{ mm}^2/\text{m}}$

Reinforcement provided **12 mm dia.bars @ 200 mm centres**

Area of reinforcement provided  $A_{s\_toe\_prov} = \mathbf{565 \text{ mm}^2/\text{m}}$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for retaining wall under main building side wall				Start page no./Revision 6.6. 6	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

**PASS - Reinforcement provided at the retaining wall toe is adequate**

**Check shear resistance at toe**

Design shear stress

$$V_{toe} = V_{toe} / (b \times d_{toe}) = \mathbf{0.294 \text{ N/mm}^2}$$

Allowable shear stress

$$V_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = \mathbf{5.000 \text{ N/mm}^2}$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$V_{c\_toe} = \mathbf{0.417 \text{ N/mm}^2}$$

**$V_{toe} < V_{c\_toe}$  - No shear reinforcement required**

**Design of reinforced concrete retaining wall stem (BS 8002:1994)**

**Material properties**

Characteristic strength of concrete

$$f_{cu} = \mathbf{40 \text{ N/mm}^2}$$

Characteristic strength of reinforcement

$$f_y = \mathbf{500 \text{ N/mm}^2}$$

**Wall details**

Minimum area of reinforcement

$$k = \mathbf{0.13 \%}$$

Cover to reinforcement in stem

$$C_{stem} = \mathbf{45 \text{ mm}}$$

Cover to reinforcement in wall

$$C_{wall} = \mathbf{45 \text{ mm}}$$

**Factored horizontal at-rest forces on stem**

Surcharge

$$F_{s\_sur\_f} = \gamma_{f\_e} \times K_0 \times \text{Surcharge} \times (h_{eff} - t_{base} - d_{ds}) = \mathbf{84.4 \text{ kN/m}}$$

Moist backfill above water table

$$F_{s\_m\_a\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat})^2 = \mathbf{2.1 \text{ kN/m}}$$

Moist backfill below water table

$$F_{s\_m\_b\_f} = \gamma_{f\_e} \times K_0 \times \gamma_m \times (h_{eff} - t_{base} - d_{ds} - h_{sat}) \times h_{sat} = \mathbf{22.3 \text{ kN/m}}$$

Saturated backfill

$$F_{s\_s\_f} = 0.5 \times \gamma_{f\_e} \times K_0 \times (\gamma_s - \gamma_{water}) \times h_{sat}^2 = \mathbf{36.1 \text{ kN/m}}$$

Water

$$F_{s\_water\_f} = 0.5 \times \gamma_{f\_e} \times \gamma_{water} \times h_{sat}^2 = \mathbf{46.4 \text{ kN/m}}$$

**Calculate shear for stem design**

Surcharge

$$V_{s\_sur\_f} = 5 \times F_{s\_sur\_f} / 8 = \mathbf{52.8 \text{ kN/m}}$$

Moist backfill above water table

$$V_{s\_m\_a\_f} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - b_l^2) / (5 \times L^3) = \mathbf{0.3 \text{ kN/m}}$$

Moist backfill below water table

$$V_{s\_m\_b\_f} = F_{s\_m\_b\_f} \times (8 - (n^2 \times (4 - n))) / 8 = \mathbf{16 \text{ kN/m}}$$

Saturated backfill

$$V_{s\_s\_f} = F_{s\_s\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{30.7 \text{ kN/m}}$$

Water

$$V_{s\_water\_f} = F_{s\_water\_f} \times (1 - (a^2 \times ((5 \times L) - a_l) / (20 \times L^3))) = \mathbf{39.5 \text{ kN/m}}$$

Total shear for stem design

$$V_{stem} = V_{s\_sur\_f} + V_{s\_m\_a\_f} + V_{s\_m\_b\_f} + V_{s\_s\_f} + V_{s\_water\_f} = \mathbf{139.2 \text{ kN/m}}$$

**Calculate moment for stem design**

Surcharge

$$M_{s\_sur} = F_{s\_sur\_f} \times L / 8 = \mathbf{34.8 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{s\_m\_a} = F_{s\_m\_a\_f} \times b_l \times ((5 \times L^2) - (3 \times b_l^2)) / (15 \times L^2) = \mathbf{0.4 \text{ kNm/m}}$$

Moist backfill below water table

$$M_{s\_m\_b} = F_{s\_m\_b\_f} \times a_l \times (2 - n)^2 / 8 = \mathbf{10.4 \text{ kNm/m}}$$

Saturated backfill

$$M_{s\_s} = F_{s\_s\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{15.9 \text{ kNm/m}}$$

Water

$$M_{s\_water} = F_{s\_water\_f} \times a_l \times ((3 \times a_l^2) - (15 \times a_l \times L) + (20 \times L^2)) / (60 \times L^2) = \mathbf{20.4 \text{ kNm/m}}$$

kNm/m

Total moment for stem design

$$M_{stem} = M_{s\_sur} + M_{s\_m\_a} + M_{s\_m\_b} + M_{s\_s} + M_{s\_water} = \mathbf{81.8 \text{ kNm/m}}$$

**Calculate moment for wall design**

Surcharge

$$M_{w\_sur} = 9 \times F_{s\_sur\_f} \times L / 128 = \mathbf{19.6 \text{ kNm/m}}$$

Moist backfill above water table

$$M_{w\_m\_a} = F_{s\_m\_a\_f} \times 0.577 \times b_l \times [(b_l^3 + 5 \times a_l \times L^2) / (5 \times L^3) - 0.577^2 / 3] = \mathbf{0.5 \text{ kNm/m}}$$


kNm/m

Moist backfill below water table

$$M_{w\_m\_b} = F_{s\_m\_b\_f} \times a_l \times [((8 - n^2 \times (4 - n))^2 / 16) - 4 \times n \times (4 - n)] / 8 = \mathbf{5.7 \text{ kNm/m}}$$

Saturated backfill

$$M_{w\_s} = F_{s\_s\_f} \times [a_l^2 \times x \times ((5 \times L) - a_l) / (20 \times L^3) - (x - b_l)^3 / (3 \times a_l^2)] = \mathbf{6.6 \text{ kNm/m}}$$

 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for retaining wall under main building side wall				Start page no./Revision 6.6. 7	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Water


kNm/m

Total moment for wall design

$$M_{w\_water} = F_{s\_water\_f} \times [a_1^2 \times x \times ((5 \times L) - a_1) / (20 \times L^3) - (x - b_1)^3 / (3 \times a_1^2)] = 8.5$$

$$M_{wall} = M_{w\_sur} + M_{w\_m\_a} + M_{w\_m\_b} + M_{w\_s} + M_{w\_water} = 40.8 \text{ kNm/m}$$

← 200 →



#### Check wall stem in bending

Width of wall stem

$$b = 1000 \text{ mm/m}$$

Depth of reinforcement

$$d_{stem} = t_{wall} - c_{stem} - (\phi_{stem} / 2) = 277.0 \text{ mm}$$

Constant

$$K_{stem} = M_{stem} / (b \times d_{stem}^2 \times f_{cu}) = 0.027$$

**Compression reinforcement is not required**

Lever arm

$$z_{stem} = \min(0.5 + \sqrt{(0.25 - (\min(K_{stem}, 0.225) / 0.9))}, 0.95) \times d_{stem}$$

$$z_{stem} = 263 \text{ mm}$$

Area of tension reinforcement required

$$A_{s\_stem\_des} = M_{stem} / (0.87 \times f_y \times z_{stem}) = 715 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_stem\_min} = k \times b \times t_{wall} = 429 \text{ mm}^2/\text{m}$$

Area of tension reinforcement required

$$A_{s\_stem\_req} = \text{Max}(A_{s\_stem\_des}, A_{s\_stem\_min}) = 715 \text{ mm}^2/\text{m}$$

Reinforcement provided

**16 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_stem\_prov} = 1005 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided at the retaining wall stem is adequate**

#### Check shear resistance at wall stem

Design shear stress

$$v_{stem} = V_{stem} / (b \times d_{stem}) = 0.503 \text{ N/mm}^2$$

Allowable shear stress

$$v_{adm} = \min(0.8 \times \sqrt{f_{cu}} / 1 \text{ N/mm}^2, 5) \times 1 \text{ N/mm}^2 = 5.000 \text{ N/mm}^2$$

**PASS - Design shear stress is less than maximum shear stress**

**From BS8110:Part 1:1997 – Table 3.8**

Design concrete shear stress

$$v_{c\_stem} = 0.578 \text{ N/mm}^2$$

**$v_{stem} < v_{c\_stem}$  - No shear reinforcement required**

#### Check mid height of wall in bending

Depth of reinforcement

$$d_{wall} = t_{wall} - c_{wall} - (\phi_{wall} / 2) = 279.0 \text{ mm}$$

Constant

$$K_{wall} = M_{wall} / (b \times d_{wall}^2 \times f_{cu}) = 0.013$$

**Compression reinforcement is not required**

Lever arm

$$z_{wall} = \min(0.5 + \sqrt{(0.25 - (\min(K_{wall}, 0.225) / 0.9))}, 0.95) \times d_{wall}$$

$$z_{wall} = 265 \text{ mm}$$


Area of tension reinforcement required

$$A_{s\_wall\_des} = M_{wall} / (0.87 \times f_y \times z_{wall}) = 354 \text{ mm}^2/\text{m}$$

Minimum area of tension reinforcement

$$A_{s\_wall\_min} = k \times b \times t_{wall} = 429 \text{ mm}^2/\text{m}$$



 <b>RODRIGUES ASSOCIATES</b> 1 AMWELL STREET LONDON EC1R 1UL	Project 10 Downside Crescent				Job no. 1411	
	Calcs for retaining wall under main building side wall				Start page no./Revision 6.6. 8	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Area of tension reinforcement required

$$A_{s\_wall\_req} = \text{Max}(A_{s\_wall\_des}, A_{s\_wall\_min}) = 429 \text{ mm}^2/\text{m}$$

Reinforcement provided

**12 mm dia.bars @ 200 mm centres**

Area of reinforcement provided

$$A_{s\_wall\_prov} = 565 \text{ mm}^2/\text{m}$$

**PASS - Reinforcement provided to the retaining wall at mid height is adequate**

#### Check retaining wall deflection

Basic span/effective depth ratio

$$\text{ratio}_{bas} = 20$$

Design service stress

$$f_s = 2 \times f_y \times A_{s\_stem\_req} / (3 \times A_{s\_stem\_prov}) = 237.1 \text{ N/mm}^2$$

Modification factor

$$\text{factor}_{tens} = \min(0.55 + (477 \text{ N/mm}^2 - f_s) / (120 \times (0.9 \text{ N/mm}^2 + (M_{stem} / (b \times d_{stem}^2)))), 2) = 1.57$$


Maximum span/effective depth ratio

$$\text{ratio}_{max} = \text{ratio}_{bas} \times \text{factor}_{tens} = 31.33$$


Actual span/effective depth ratio

$$\text{ratio}_{act} = h_{stem} / d_{stem} = 11.19$$

**PASS - Span to depth ratio is acceptable**

<div>  </div> <div> RODRIGUES ASSOCIATES  1 AMWELL STREET  LONDON  EC1R 1UL </div>	Project				Job no.	
	10 Downside Crescent				1411	
	Calcs for retaining wall under main building side wall				Start page no./Revision 6.6. 9	
	Calcs by ab	Calcs date 01/05/2018	Checked by	Checked date	Approved by	Approved date

Indicative retaining wall reinforcement diagram



- Toe bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Wall bars - 12 mm dia.@ 200 mm centres - (565 mm<sup>2</sup>/m)
- Stem bars - 16 mm dia.@ 200 mm centres - (1005 mm<sup>2</sup>/m)

## **Annex A - Structural methodology**

### **Introduction**

This document sets out the structural methodology for the construction of the basement at 10, Downside Crescent.

### **Details of the stages**

This methodology includes the drawings 1411-31 which is included in the drawings package. Reference should also be made to the other drawings in the contract.

#### **PRE SITE START**

1. Install monitoring positions on walls and do baseline survey. Monitoring to be carried out in accordance with movement monitoring specification thereafter, during structural works.

#### **STAGE 1**

2. Saw cut any existing ground floor screed, where it is present, to its full depth parallel to the party wall with No.8 as close to it as feasible and remove the portion against the party wall to limit vibration born noise through the party wall during demolition.
3. Demolish side infill with party wall toward No.12, observing the main house walls for any movement as demolition proceeds.

#### **STAGE 2**

4. Install underpinning to the party wall with No.8 and under main building walls where indicated on plan, in an agreed sequence.
5. Only ASUC registered underpinning specialists to be used to carry out the work.
6. Excavate for the pin, each excavation to be no more than 1 m wide. Excavations to be temporarily shored as they progress down in accordance with good practice. The line of the rear face of the excavation under the party wall is to be carefully set out to be at the face of the adjoining owner's wall above (allowing for the corbel to overhang). The rear face is to be shored with sacrificial cement board shutters. A lean mix cementitious grout is to be poured down the back of these boards as they are placed to fill any voids.
7. Carefully remove any existing mass concrete footing if present, clean off the underside of the existing original footing and repair any damaged brickwork.
8. Clean and blind the base of the excavation, put in the reinforcement and cast the toe and kicker of the pin with continuity reinforcement pushed into the surrounding soil to give the required lap for the next pins or using couplers.

#### **STAGE 3**

9. To allow for continuity of the reinforced concrete in the wall and suspended slab, carefully saw cut a section of the brickwork vertically on the line of the party wall boundary at the centre of the wall. The use of percussion tools to remove the brickwork will not be permitted.
10. Reinforce the pin and cast the wall up to 75mm below the footing level or underside of prepared brickwork, with continuity reinforcement or couplers as for its toe.
11. Dry pack the back half of the pin to the underside of the brickwork.

12. Cast the small remaining section of the front half of the pin.
13. Dry pack the front half of the pin to the underside of the cut brickwork.
14. Leave excavation to pin fully shored and proceed with the next pin in the sequence.

#### STAGE 4

15. Excavate trench for basement rear wall. Excavations to be temporarily shored as they progress down in accordance with good practice.
16. Clean and blind the base of the excavation, put in the reinforcement and cast the toe and kicker of the pin with continuity reinforcement pushed into the surrounding soil to give the required lap for the base slab and returning walls or using couplers.
17. When the concrete has gained sufficient strength place reinforcements and cast the wall up to the underside of the future ground floor slab.

#### STAGE 5

18. For the side walls of the new basement under the rear extension install first temporary sheet piles to secure excavation and adjoining walls at No. 12.
19. Prop top of piles, over future ground floor slab level, using horizontal waling beam and soldiers.
20. Dig trenches supported by shoring and cast side walls toe and stem first.
21. When the concrete has gained sufficient strength place reinforcements and cast the walls up to the underside of the future ground floor slab.
22. Install temporary needles and steelwork to support back and internal walls of the main building prior to commencing excavation of basement area. Dig local pit or trenches if necessary to allow construction of temporary pad or strip foundation at basement level to support temporary props. Excavations to be temporarily shored as they progress down in accordance with good practice.

#### STAGE 6

23. Excavate to 1000mm below existing ground floor level removing the top level of shoring to the underpinning and main retaining walls.
24. Install propping and waling beams at high level, just below the level of the proposed concrete ground floor slab, resin anchored to retaining walls. NOTE - Contractor to set out and split the beams, providing robust end plate and bolted splice connections to suit their manual handling requirements.

#### STAGE 7

25. Excavate inside the basement to 1000mm above proposed concrete slab removing the shoring down to the level of the excavation only, keeping the bottom shoring in place.
26. Locally excavate trenches max 400mm wide to the top of slab level across the building. Put low level propping to the underpinned wall within the trenches, just above the proposed slab level. NOTE - Contractor to set out and split the beams, providing robust end plate and bolted splice connections to suit their manual handling requirements.

#### STAGE 8

27. Complete excavation inside to basement slab formation level.

28. Lay blinding concrete, place reinforcement, and wall starter bars.
29. Cast basement slab with any drainage channels if necessary.
30. When basement slab concrete has reached strength, remove the low level propping and waling beams.
31. Place reinforcement, formwork and cast the reinforced concrete walls
32. Place soffit formwork and supporting temporary works, place reinforcement and cast ground floor slab, with boxouts for the temporary steelwork.
33. Remove high level propping in basement, when concrete reaches strength.
34. Dry-pack under the existing walls to the building where they will be supported on the concrete superstructure.
35. Remove temporary needles and steel work supporting structure, and fill in the boxouts.
36. Install drained cavity.
37. Construct rear extension.
38. Complete the construction and fitting out.



## **Annex B – Movement monitoring specification**

### **1. Introduction**

The purpose of this specification is to outline the requirements for a movement monitoring system that will measure movements during underpinning and basement excavation works. Movements of the owners' property and the neighbouring property, No.8 Downside Crescent and No.12 Downside Crescent will be monitored.

### **2. Installation**

#### **2.1. Control**

Monitoring control stations are to be established around the site perimeter from which the monitoring targets can be surveyed. Additional control survey targets are to be placed outside the site's zone of influence and accurately fixed in 3 dimensions. These targets will be used to establish station coordinates prior to each survey.

#### **2.2. Reflective targets**

Monitoring points are to be installed as per the attached sketches. Exact locations are to be adjusted to ensure line of sight from survey stations. Targets are to be attached to walls using epoxy adhesive.

#### **2.3. Tilt meters**

Wireless high precision tilt sensors transmit data to the monitoring provider's office over an internet connection and can be published to a web portal with automatic alerts to the contractor at trigger levels. No tilt meters on party walls are suggested.

#### **2.4. Precise levels**

Precise level monitoring points are to be installed below each tilt-meter to monitor precise vertical movement. These are to be done head ball studs resin anchored into the wall.

### **3. Monitoring**

#### **3.1. Reflective Targets**

These are to be surveyed using two rounds of angles for each survey point and recorded. Any large deviations are to be immediately reported to the contractor.

#### **3.2. Precise levels**

Precise levelling points are to be levelled based on benchmarks and levelling runs should be based on closed loops. Any closures greater than 1mm will require measurements to be repeated.

### **4. Monitoring frequency**

Monitoring is to commence during site establishment. The initial set of baseline readings should be taken minimum 1 month before commencement of any significant structural works and then a first set of readings should be taken immediately prior to the start of any groundworks.

Thereafter monitoring should be carried out weekly during underpinning, excavation, temporary shoring, and concrete basement box construction. Once basement works are complete including the removal of all temporary works a set of readings should be taken followed by 3 more sets at intervals of 1 month.

### **5. Trigger values**

Trigger levels for neighbouring property and party wall monitoring are set as follows;

#### Vertical settlement

Threshold value is 75% of trigger value – Report to all parties. Contractor to check walls in the vicinity of the monitoring point and report any new cracking. If cracks are evident, then crack monitors are to be installed and reported on weekly. Engineer to check relative settlement from neighbouring monitoring points and determine if any further action is required.

Action values are reported in the attached plan – Stop work and report to all parties. Contractor to check walls in the vicinity of the monitoring point and report on any cracking. Engineer to check relative settlement from neighbouring monitoring points and determine what action is required.

#### Tilt

Threshold alert value 1/500 – Automatic alert issued to contractor who is to alert all parties. Contractor to check party wall for any visible defects. Engineer to determine if any further action is required.

Threshold alert value 1/350 – Automatic alert issued to contractor who is to alert all parties and stop work. Contractor to check party wall for any visible defects. Engineer to determine what further action is required.

Trigger levels for areas other than the neighbouring property and party wall are set as follows;

#### Vertical settlement

Threshold value 4mm – Report to all parties. Contractor to check walls in the vicinity of the monitoring point and report any new cracking. If cracks are evident, then crack monitors are to be installed and reported on weekly. Engineer to check relative settlement from neighbouring monitoring points and determine if any further action is required.

Action value 6mm – Stop work and report to all parties. Contractor to check walls in the vicinity of the monitoring point and report on any cracking. Engineer to check relative settlement from neighbouring monitoring points and determine what action is required.

#### Horizontal movement

Threshold value 4mm – Report to all parties. Contractor to check walls in the vicinity of the monitoring point and report any new cracking. If cracks are evident, then crack monitors are to be installed and reported on weekly. Engineer to check relative movement from neighbouring monitoring points and determine if any further action is required.

Action value 6mm – Stop work and report to all parties. Contractor to check walls in the vicinity of the monitoring point and report on any cracking. Engineer to check relative movement from neighbouring monitoring points and determine what action is required.

## 6. Reporting

The reporting will be provided in PDF format.


Each report will contain the following information:

- Executive Summary
- Date of survey,
- Weather conditions during survey,
- Surveyor responsible for the survey.
- Applicable notes and accuracies
- Tabular data highlighting exceeding specified trigger limits.
- Graphs showing vertical and horizontal movements with time.
- Location plans




TARGETS ARE IN GREEN


TRIGGER VERTICAL VALUES ARE IN RED



TARGETS ARE IN GREEN  
 TRIGGER VERTICAL VALUES ARE IN RED



Existing Rear Elevation





TARGETS ARE IN GREEN  
TRIGGER VERTICH LEVEL ARE IN RED

