



rev.      date

REMOVES NEW MIN. 20 MIN. BRICK / MIN. 7.5 MIN. BLOCK WORK IN MORTAR DESIGNATION (ii) ABOVE DPC LEVEL. NEW MIN. 50 MIN. CLASS B ENG. BRICK IN MORTAR DESIGNATION (i) BELOW DPC LEVEL.

REMOVES PROPOSED TYPE 2 STRAINERS STEEL WALL TIES BY ANGLE OR SIMILAR APPROVED.

18mm PROTECTIVE BOARD TO R.I.W. WATERPROOFING MEMBRANE

SCREENED, INSULATION AND FINISHES TO ARCHITECT'S DETAILS AND SPECIFICATION

EXISTING GROUND LEVEL

200mm THICK RC RETAINING WALL WITH R.I.W. BITUMINOUS MEMBRANE WATERPROOFING AND PAINT

PFC

SSC

250mm THICK RC RAFT FOUNDATION

50mm CONCRETE BLINDING

PROVIDE 225mm THICK CELLCORET TYPE HX 5; GRADE 13/18 ANTI-HEAVE VOID FORMER BY CORNER OR SIMILAR APPROVED

PROVIDE 75mm THICK x 250 DEEP CHAMFERED PILE COLLAR BY 'CORCOR' AROUND ALL PILES 250;

300 Ø PILE DESIGNED AND INSTALLED BY SPECIALIST PILING CONTRACTOR (TYPICAL)