

**Product Title / Range:**

**Standard Paving**  
**750 x 600 x 50mm**  
**Commercial**

**T** 01422 312000  
**F** 01422 312943  
**E** advisory.services@marshalls.co.uk  
**Print Date** 27/03/2018  
**Data Sheet No** 44

**Description**

Product type	Solid unit with pimple surface
Base material	Unpigmented concrete
Manufacturing process	Hydraulically pressed concrete
Governing standards	All data where relevant to be established in accordance with BS EN 1339 : 2003
NBS Specification	Q25 315
CE Declaration of Performance	www.marshalls.co.uk/dop

**Physical Properties**

Nominal Dimensions	750 x 600 x 50mm
Work Dimensions	748 x 598 x 50mm
Tolerances on Work Dimensions	Length $\pm 2$ mm, width $\pm 2$ mm, thickness $\pm 3$ mm
Abrasion Resistance	$\leq 23$ mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	$\leq 1.0$ kg/m <sup>2</sup> as a mean with no individual value $> 1.5$ kg/m <sup>2</sup>
Material Density	2300 kg/m <sup>3</sup> (typically)
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) : $> 45$ Mean unpolished skid resistance value (USRV) : $> 45$
Transverse/Flexural Split/Breaking	Characteristic bending strength of 4.0 MPa with no individual result less than 3.2 MPa

**Specification**

Colour	Natural
Approx unit weight	53 kg
Technical information	Reference should be made to BS 7533-8 : 2003
Emission of Asbestos	No content

**Product Title / Range:**

**Standard Paving  
750 x 600 x 50mm  
Commercial**

**T** 01422 312000  
**F** 01422 312943  
**E** [advisory.services@marshalls.co.uk](mailto:advisory.services@marshalls.co.uk)  
**Print Date** 27/03/2018  
**Data Sheet No** 44

External Fire Performance Deemed to satisfy. See commission decision 2000/553/ECU  
Reaction to fire Class A1, see commission decision 2000/605/EC

**Application**

Suitability Laid in accordance with BS 7533-4 : 2006.  
Suitable for the construction of pedestrian areas only including domestic paths and patios

**Supply**

Av. pack size 9 m<sup>2</sup>  
Av. pack weight 1060 kg  
Packaging All packs are suitable for crane off-load. Fork lift off-load on request

**Further Information**

Cleaning & Maintenance Information regarding the cleaning & maintenance of this product may be obtained on request  
Efflorescence Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking  
Weathering It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.  
Product Evolution The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details  
Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice  
Website [www.marshalls.co.uk/commercial](http://www.marshalls.co.uk/commercial)  
Contact Us For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233  
Date of issue October 2007



# Marshalls

## Product Data Sheet

Landscape House  
Premier Way  
Lowfields Business Park  
Elland, Halifax  
HX5 9HT

**Product Title / Range:**

Standard Paving  
750 x 600 x 50mm  
Commercial

T 01422 312000  
F 01422 312943  
E [advisory.services@marshalls.co.uk](mailto:advisory.services@marshalls.co.uk)  
**Print Date** 27/03/2018  
**Data Sheet No** 44

Date of issue

Issue 3