

**Project Name** 12561 STREAT MARKETS LTD, CENTRE POINT, LINK BUILDING,

**Project Number** 12561 DO/JP






**Client**






**Date** 26.10.18








**Revision** **A**



















Into Lighting Ltd  
4 O'Meara Street,  
London,  
SE1 1TE  
T: 0845 873 7013  
F: 0845 873 7018  
E: lighting@into.co.uk  
www.into.co.uk

Into Reference	Description	Guide images	Quantity
<b>GENERAL LIGHTING</b>			
<b>A</b>	<b>Track mounted adjustable spotlight for general illumination</b>		<b>94</b>
Control gear	Track mounted adjustable spotlight for general illumination		
Lamp	Integral LED driver - mains dimmable		
Optic	350mA 12W LED 2700K 90CRI 844lm		
Baffle	20° Optic		
Accessories	Gold Baffle		
Colour / Finish	Honeycombe Louvre		
Notes	WHITE		
	N/A		
<b>A1</b>	<b>General illumination to art work in double height space</b>		<b>18</b>
Control gear	Track mounted adjustable spotlight		
Lamp	Integral LED driver - mains dimmable		
Optic	350mA 12W LED 2700K 90CRI 897lm		
Baffle	34° Optic		
Accessories	Gold Baffle		
Colour / Finish	Honeycombe Louvre		
Notes	WHITE		
	N/A		
<b>C</b>	<b>Artwork illumination</b>		<b>4</b>
Control gear	IP67 Surface mounted adjustable spotlight		<b>1</b>
Lamp	Remote electronic driver 500mA 1-10V dimmable		
Accessories	500mA 7W LED 2200K 34 degree		
Accessories	Cowl		
Colour / Finish	Base plate		
Notes	Black		
	N/A		
<b>G</b>	<b>Illumination to kitchen counter</b>		<b>37</b>
Control gear	IP67 Recessed fixed downlight		<b>4</b>
Lamp	Remote electronic driver 500mA 1-10V dimmable		
Accessories	500mA 1.7W LED 2200K 12 degree		
Colour / Finish	Colour correction filter		
Notes	Stainless steel		
	N/A		
<b>G1</b>	<b>Illumination to bar counter</b>		<b>13</b>
Control gear	IP67 Recessed fixed downlight		<b>1</b>
Lamp	Remote electronic driver 500mA 1-10V dimmable		
Accessories	500mA 1.7W LED 2200K 12 degree		
Colour / Finish	Colour correction filter		
Notes	Stainless steel		
	N/A		

<b>H</b>		<b>General illumination to mezzaiane level</b>		
		Semi recessed adjustable downlight mounted within bespoke recessed channel		
		7514mm length c/w 6No spotlights		1
		1323mm length c/w 1No spotlights		1
		3300mm length c/w 2No spotlights		1
		3516mm length c/w 3No spotlights		1
		5456mm length c/w 3No spotlights		1
		5456mm length c/w 4No spotlights		1
		4117mm length c/w 2No spotlights		1
		1239mm length c/w 1No spotlights		1
		3673mm length c/w 2No spotlights		2
		2146mm length c/w 2No spotlights		1
		878mm length c/w 2No spotlights		2
		3817mm length c/w 2No spotlights		2
		839mm length c/w 2No spotlights		2
		3519mm length c/w 3No spotlights		1
		3435mm length c/w 2No spotlights		1
		2973mm length c/w 2No spotlights		1
Control gear		Remote electronic driver 700mA 1-10V dimmable		6
Lamp		700mA 2.4W LED 2700K 31 degree		
Accessories		Colour correction filter		
Colour / Finish		Black		
Notes		N/A		
<b>H1</b>		<b>General illumination to mezzaiane level</b>		
		Semi recessed adjustable downlight mounted within bespoke recessed channel		
		400mm length c/w 1No spotlights		3
Control gear		Remote electronic driver 700mA 1-10V dimmable		1
Lamp		700mA 2.4W LED 2700K 48 degree		
Accessories		Colour correction filter		
Colour / Finish		Black		
Notes		N/A		
<b>J</b>		<b>General illumination</b>		
		Recessed adjustable downlight		69
Control gear		Remote LED Driver - Mains Dimmable		
Lamp		250mA 9W LED 28° 90CRI 2700K		
Accessories		N/A		
Colour / Finish		White		
Dimensions		Bezel: 96mm Cut Out: 88mm Depth: 110mm		
Notes		<b>CONFIRMATION OF EXACT DEPTH OF CEILING REQUIRED BEFORE ORDERING</b>		
<b>K</b>		<b>Illumination to artwork</b>		
		Recessed adjustable slot downlight		10
Control gear		Remote LED Driver - Mains Dimmable		
Lamp		250mA 9W LED 40° 90CRI 2700K		
Accessories		N/A		
Colour / Finish		White		
Dimensions		Bezel: 96mm Cut Out: 88mm Depth: 110mm		
Notes		<b>CONFIRMATION OF EXACT DEPTH OF CEILING REQUIRED BEFORE ORDERING</b>		
<b>L</b>		<b>Illumination to kitchen 7 counter</b>		
		Semi recessed adjustable spotlight		4
Control gear		Remote electronic LED driver - 700mA constant current - 1-10V dimmable - to run 4-14 fittings		1
Lamp		700mA 2.4W 12Degree LED 2200K		
Accessories		Single swivel mounting plate		
Accessories		N/A		
Dimensions		30mm diameter. 23mm cut-out. 24.5mm recess depth. 51mm unit height.		
Colour / Finish		Black anodised aluminium		
Notes		N/A		

<b>M</b>	<b>Lobby illumination</b>		
	Recessed adjustable downlight		
	Remote LED Driver - Mains Dimmable		
	Lamp 250mA 9W LED 40° 90CRI 2700K		<b>4</b>
	Accessories N/A		
	Colour / Finish White		
	Dimensions Bezel: 96mm Cut Out: 88mm Depth: 110mm		
	Notes <b>CONFIRMATION OF EXACT DEPTH OF CEILING REQUIRED BEFORE ORDERING</b>		
<b>N</b>	<b>General illumination to barber area</b>		
	Semi recessed adjustable downlight mounted within bespoke recessed channel		
	4357mm length c/w 4No spotlights		<b>1</b>
	4357mm length c/w 4No spotlights		<b>1</b>
	4935mm length c/w 4No spotlights		<b>1</b>
	Control gear Remote electronic driver 700mA 1-10V dimmable		<b>1</b>
	Lamp 700mA 2.4W LED 2700K 31 degree		
	Accessories Colour correction filter		
	Colour / Finish White		
	Notes N/A		
<b>P</b>	<b>Surface mounted adjustable spotlight over stairs</b>		
	Surface mounted adjustable spotlight over stairs		
	Integral LED driver - mains dimmable		<b>3</b>
	Lamp 350mA 12W LED 2700K 90CRI 844lm		
	Optic 20° Optic		
	Baffle Black Baffle		
	Accessories Honeycombe Louvre		
	Accessories N/A		
	Colour / Finish BLACK		
	Notes N/A		
<b>LED1 GF.01</b>	<b>Linear illumination around mezzanine balustrade</b>		
	Linear flexible LED tape with silicone housing IP65 - 5m reel		
	Control gear Remote 24V 150W LED driver		<b>4</b>
	Control gear Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		<b>2</b>
	Lamp 24V 13.2W per metre LED 2200K CRI90		<b>2</b>
	Accessories Adhesive backing / 10 x Fixing clips		<b>10</b>
	Accessories 20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		
	Colour / Finish N/A		
	Dimensions 1No 19.8m approx		
	Notes All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		
<b>LED1 GF.02</b>	<b>Ground floor: Linear illumination to bar nosing / kitchen nosing</b>		
	Linear flexible LED tape with silicone housing IP65 - 5m reel		
	Control gear Remote 24V 150W LED driver		<b>7</b>
	Control gear Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		<b>4</b>
	Lamp 24V 13.2W per metre LED 2200K CRI90		<b>4</b>
	Accessories Adhesive backing / 10 x Fixing clips		<b>16</b>
	Accessories 20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		
	Colour / Finish N/A		
	Dimensions 1No 8.1m / 6.8m / 9.5m / 7m = 31.4m approx		
	Notes All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		

<b>LED1 GF.03</b>		<b>Linear illumination for counter working light</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			7
Control gear	Remote 24V 150W LED driver			7
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			7
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			16
Colour / Finish	N/A			
Dimensions	1No 5.4m / 4.7m / 5m / 3.3m / 5.5m / 2.6m / 5.4m = 31.9m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.04</b>		<b>Linear illumination to bottle step display</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			3
Control gear	Remote 24V 150W LED driver			2
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			2
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			7
Colour / Finish	N/A			
Dimensions	4No 3.2m = 12.8m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.05</b>		<b>Linear illumination to gantry</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			12
Control gear	Remote 24V 150W LED driver			7
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			7
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			28
Colour / Finish	N/A			
Dimensions	1No 6.9m / 7.9m / 8.5m / 8.1m / 5m / 2No 5.5m / 2No 4.2m = 55.8m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.06</b>		<b>Linear illumination to back bar</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			1
Control gear	Remote 24V 150W LED driver			1
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			1
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			3
Colour / Finish	N/A			
Dimensions	2No 2.9m = 5.8m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			


<b>LED1 GF.07</b>		<b>Linear illumination to display units</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			9
Control gear	Remote 24V 150W LED driver			4
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			4
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			22
Colour / Finish	N/A			
Dimensions	12No 3.6m = 43.2m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.08</b>		<b>Linear illumination to kitchen 6 counter nosing</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			2
Control gear	Remote 24V 150W LED driver			1
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			1
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			4
Colour / Finish	N/A			
Dimensions	1No 5.5m / 2.25m = 7.75m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.09</b>		<b>Linear illumination to kitchen 7 skirting</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			2
Control gear	Remote 24V 150W LED driver			1
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			1
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			4
Colour / Finish	N/A			
Dimensions	1No 6.5m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 GF.10</b>		<b>Linear illumination to perimeter lobby ceiling</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel			4
Control gear	Remote 24V 150W LED driver			2
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG			2
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps			9
Colour / Finish	N/A			
Dimensions	17.8m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			

<b>LED1 GF.11</b>		<b>Linear illumination to top of columns</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel		2	
Control gear	Remote 24V 150W LED driver		1	
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1	
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		5	
Colour / Finish	N/A			
Dimensions	2No 4.6m = 9.3m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 M.01</b>		<b>Linear illumination for counter working light</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel		1	
Control gear	Remote 24V 150W LED driver		1	
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1	
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		2	
Colour / Finish	N/A			
Dimensions	1No 3.6m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 M.02</b>		<b>Mezz: Linear illumination to bar nosing / kitchen nosing</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel		2	
Control gear	Remote 24V 150W LED driver		1	
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1	
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		5	
Colour / Finish	N/A			
Dimensions	1No 3.6m / 5.7m = 9.3m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			
<b>LED1 M.03</b>		<b>Mezz: Linear illumination to bar ganrty</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel		2	
Control gear	Remote 24V 150W LED driver		1	
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1	
Accessories	24V 13.2W per metre LED 2200K CRI90			
Accessories	Adhesive backing / 10 x Fixing clips			
	20mm x 20mm Aluminium base, mounting profile, diffuser - 2000mm, 2no end caps		4	
Colour / Finish	N/A			
Dimensions	1No 3.7m / 3.9m = 7.6m approx			
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition			










<b>LED2 GF.01</b>	<b>Linear illumination to columns</b>		
	Surface mounted linear luminaire - 2050mm		2
	Surface mounted linear luminaire - 1400mm		3
	Surface mounted linear luminaire - 2000mm		1
	Surface mounted linear luminaire - 1350mm		1
	Surface mounted linear luminaire - 2150mm		1
	Remote electronic driver 1-10V dimmable		8
Control gear	500mA 1.7W per 12 Degree 2400K LED		
Lamp	Adjustable mounting bracket / Anti glare louvre		
Accessories			
Colour / Finish	Black		
Notes	N/A		
<hr/>			
<b>LED3 GF.01</b>	<b>Linear illumination to columns - colour change</b>		
	OMITTED		
	<b>DMX CABLES TO BE WIRED TO THIS LOCATION TO ADD FITTINGS IN FUTURE</b>		
<hr/>			
<b>LED4 GF.01</b>	<b>Linear illumination to bar nosing</b>		
	Linear flexible LED tape with silicone housing IP65 - 5m reel		4
Control gear	Remote 24V 150W LED driver		2
Control gear	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		2
Lamp	24V 13.2W per metre LED 2200K CRI90		
Accessories	Adhesive backing / 10 x Fixing clips		
Colour / Finish	N/A		
Dimensions	1No 18.6m approx		
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		
<hr/>			
<b>LED4 GF.02</b>	<b>Linear illumination to bar working light</b>		
	Linear flexible LED tape with silicone housing IP65 - 5m reel		4
Control gear	Remote 24V 150W LED driver		2
Control gear	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		2
Lamp	24V 13.2W per metre LED 2200K CRI90		
Accessories	Adhesive backing / 10 x Fixing clips		
Colour / Finish	N/A		
Dimensions	1No 18.6m approx		
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		
<hr/>			
<b>LED4 GF.03</b>	<b>Linear illumination to kitchen counter</b>		
	Linear flexible LED tape with silicone housing IP65 - 5m reel		2
Control gear	Remote 24V 150W LED driver		1
Control gear	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1
Lamp	24V 13.2W per metre LED 2200K CRI90		
Accessories	Adhesive backing / 10 x Fixing clips		
Colour / Finish	N/A		
Dimensions	1No 6.5m approx		
Notes	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		

<b>LED4 GF.04</b>	<b>Linear illumination to kitchen counter - Working light</b>		
Control gear	Linear flexible LED tape with silicone housing IP65 - 5m reel		1
Control gear	Remote 24V 150W LED driver		1
Lamp	Remote 24V 192W (96W per channel) 1-10V dimmable interface LOG		1
Accessories	24V 13.2W per metre LED 2200K CRI90		
Colour / Finish	Adhesive backing / 10 x Fixing clips		
Dimensions	N/A		
Notes	1No 5m approx		
	All linear LED products are quoted against dimensions taken from an interior designer/ architects' drawings. It is the responsibility of the ordering party to ensure that the appointed main contractor verifies these dimensions are correct prior to ordering. In the event dimensions are found to be incorrect and additional linear LED product required, this will be chargeable as an addition		







#### TRACK AND ACCESSORIES

<b>TR</b>	240V 3 circuit track - 3 metre length		<b>54</b>
<b>TR</b>	240V 3 circuit track - 2 metre length		<b>2</b>
Circuit Config	3 circuits plus common neutral and earth. Neutral rated to 16A max.		
Lamp	N/A		
Accessories	T straight connectors		<b>12</b>
Accessories	L straight connectors		<b>7</b>
Accessories	3 Circuit live end		<b>13</b>
Accessories	End caps		<b>27</b>
Accessories	Adjustable 3m suspension wires - 1500mm		<b>224</b>
Colour / Finish	Black		
Notes	N/A		


#### EMERGENCY LIGHTING

<b>em</b>	<b>Emergency illumination - non-maintained</b>		
Control gear	Recessed fixed emergency luminaire		<b>23</b>
Lamp	Remote control gear c/w 3 hour emergency battery pack		
Accessories	2W LED		
Colour / Finish	N/A		
Notes	White		
	N/A		
<b>em1</b>	<b>Emergency illumination - non-maintained</b>		
Control gear	Track mounted emergency luminaire		<b>25</b>
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	240V 3W LED		
Colour / Finish	N/A		
Dimensions	Black/White/Silver		
	L: 336mm / W: 37mm / H: 57mm		
<b>em2</b>	<b>Emergency illumination - non-maintained</b>		
Control gear	Surface mounted emergency luminaire		<b>1</b>
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	2W LED		
Colour / Finish	N/A		
Dimensions	White		
Notes	Length: 150mm Width: 150mm Depth: 35mm		
	N/A		
<b>em3</b>	<b>Emergency illumination - non-maintained</b>		
Control gear	Surface mounted emergency luminaire		<b>7</b>
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	2W LED		
Colour / Finish	N/A		
Dimensions	Black		
Notes	Length: 150mm Width: 150mm Depth: 35mm		
	N/A		



<b>exit1</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Ceiling mounted emergency exit sign - White painted finish		1
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	LED		
Accessories	Ceiling Bracket - White		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 220mm / W: 300mm / D: 50mm		
Notes	ISO Format - Arrow Down		
	N/A		
<b>exit2</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Ceiling mounted emergency exit sign - White painted finish		2
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	LED		
Accessories	Ceiling Bracket - White		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 220mm / W: 300mm / D: 50mm		
Notes	ISO Format - Arrow Right		
	N/A		
<b>exit3</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Semi recessed emergency exit sign - White painted finish		2
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	LED		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 150mm / W: 288mm		
Notes	ISO Format - Arrow Down		
	N/A		
<b>exit4</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Wall mounted emergency exit sign		2
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	16 x white LED		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 185mm / W: 385mm / D: 71mm		
Notes	ISO Format - Arrow Down		
	N/A		
<b>exit5</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Semi recessed emergency exit sign - White painted finish		2
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	LED		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 150mm / W: 288mm		
Notes	ISO Format - Arrow Up		
	N/A		
<b>exit6</b>	<b>Emergency exit sign - maintained</b>		
Control gear	Semi recessed emergency exit sign - White painted finish		2
Lamp	Integral control gear c/w 3 hour emergency battery pack		
Accessories	LED		
Colour / Finish	N/A		
Dimensions	White		
LEGEND	H: 150mm / W: 288mm		
Notes	ISO Format - Arrow Right		
	N/A		

Important note      Emergency exit signs are supplied as standard with 'arrow up' for straight on direction. Should alternative arrow directions be required, this must be highlighted prior to an order being placed with Into to avoid incurring costs for signs to be changed post order. Into recommend that the responsible party or Duty Holder consult with their landlord (if applicable) risk assessment provider, fire safety engineers, local authority and insurer to confirm site specific emergency lighting requirements prior to emergency lighting being ordered.

DIMMING SYSTEM				
	<b>Dimming control system -</b>			
Control gear	Dimming control system - 18 channels of 06 amps resistive load to control mains, low voltage, cold cathode and fluorescent lighting.		5	
Accessories	10 button plate. Button operation programmed with default setting for recalling four lighting scenes plus On/Off and scene raise/lower		4	
Accessories	Key switch		1	
Colour / Finish	Stainless steel plate			