



Information

Paving Supplier To be porcelain paving, product name to be confirmed.
 London Stone, www.londonstone.co.uk, 01753 212950
 To be installed as per supplier's instructions with a fall of 1:80 away from the house.
 To be installed on 100mm deep layer of compacted MOT type 1, followed by a full mortar bed which is 30-50mm deep.
 Before laying each slab, the back should be painted with a bond bridge of SBR bonding agent and ordinary cement to improve adhesion. This bonding mixture is very difficult to remove once it has set, so extra care should be taken not to get any of the mixture on the surface of the paving slabs. Remove any splashes with a wet sponge straight away. Pointing joints to be 5mm, to be pointed with Ardex FL, colour to be advised.

Brick Supplier Brick for coping to be confirmed.
 Chelmer Valley Brick Co.
 www.chelmervalley.co.uk, 01277 219634

Trellis Contemporary slatted panel to be fitted to the left hand patio wall. To be full height to 2000mm, constructed from 45mm wide batons with a 10mm gap between slatts.

Balustrades To be frameless glass balustrades to a height of 1100mm from adjacent surface.

Hampstead Garden Design

Designer	Sarah Oxby 18 Dorchester Gardens London NW11 6BN Tel: 07838 250793
Clients' name Job title	Ashley Dunster & Anna Vidiney 95 Canfield Gardens, London NW6 3DY
Drawing title Scale Date	Layout plan 1:200 @ A3 31.10.18