

D1.05	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Underside of Lintel</div><div>Flush door</div><div>Finished Floor level</div></div><div><div><div>2.415</div><div>2.040</div></div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div> <td><div><div>Location: Internal sliding doors. Leaf size 2No 610x1981x35</div><div>Structural Opening (wxh): 2415 x 2040</div><div>Finished wall thickness: 130</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>N/A</div></div><div>Glazing type – N/A</div><div>Ironmongery:<div>– Handles (type to be agreed)</div></div><div>Notes:</div><div>No. required:<div>1</div></div></div></td> <td>D2.01 D3.01</td> <td><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Underside of Lintel</div><div>Panelled door</div><div>Finished Floor level</div></div><div><div><div>0.955</div><div>2.040</div></div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div><td><div><div>Location: Flat entrance doors. Leaf size 864x1981x44</div><div>Structural Opening (wxh): 955 x 2040 Door to have minimum 775mm clear opening</div><div>Finished wall thickness: 132</div><div>Door type: Solid core, six panel door with hardwood lipping and intumescent smoke seal(stain/varnish to client choice)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Ironmongery: 1 ½ Twin Ball Bearing Fire Door Hinges – 100 x 75 x 3mm Grade 201 Stainless Steel to BS EN grade 14 and to have CE mark – Multi-point locking system – Snib to enable opening without use of key – Perko (or similar)self-closing device – Handles (type to be agreed) – Secured by Design 3 hooks – All doors to have either half moon or contract projection door stop – 76mm Satin Nickel screw fixed door numbers</div><div>Notes: 1. All door components including the frame, glazing,intumescent fire and smoke seals, ironmongery etc to have 30 minutes fire rating. 2. Door to BS 476 part 22 and to comply with Approved Document B: 2006 edition incorporating 2010 amendments;Volume 1&2, Documents; E – for sound, F – for ventilation, L – for Thermal M – for Accessibility 3. Hinge side might vary (see floor plan) 4. Each door to have a secure doorset 5. Where provided, letter plates to have maximum aperture of 260x40mm, located to hinder the removal of keys and fitted with an internal doorflap 6. Door viewer also to be provided 7. Doorset to be fitted with a door chain or door limiter</div><div>No. required:<div>2</div></div></div></td><td>DE2.01</td><td><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div></div><div><div>Flush door</div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div><td><div><div>Location: Existing Store door</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement door</div><div>No. required:<div>1</div></div></div></td></td></td>	<div><div>Location: Internal sliding doors. Leaf size 2No 610x1981x35</div><div>Structural Opening (wxh): 2415 x 2040</div><div>Finished wall thickness: 130</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>N/A</div></div><div>Glazing type – N/A</div><div>Ironmongery:<div>– Handles (type to be agreed)</div></div><div>Notes:</div><div>No. required:<div>1</div></div></div>	D2.01 D3.01	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Underside of Lintel</div><div>Panelled door</div><div>Finished Floor level</div></div><div><div><div>0.955</div><div>2.040</div></div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div> <td><div><div>Location: Flat entrance doors. Leaf size 864x1981x44</div><div>Structural Opening (wxh): 955 x 2040 Door to have minimum 775mm clear opening</div><div>Finished wall thickness: 132</div><div>Door type: Solid core, six panel door with hardwood lipping and intumescent smoke seal(stain/varnish to client choice)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Ironmongery: 1 ½ Twin Ball Bearing Fire Door Hinges – 100 x 75 x 3mm Grade 201 Stainless Steel to BS EN grade 14 and to have CE mark – Multi-point locking system – Snib to enable opening without use of key – Perko (or similar)self-closing device – Handles (type to be agreed) – Secured by Design 3 hooks – All doors to have either half moon or contract projection door stop – 76mm Satin Nickel screw fixed door numbers</div><div>Notes: 1. All door components including the frame, glazing,intumescent fire and smoke seals, ironmongery etc to have 30 minutes fire rating. 2. Door to BS 476 part 22 and to comply with Approved Document B: 2006 edition incorporating 2010 amendments;Volume 1&2, Documents; E – for sound, F – for ventilation, L – for Thermal M – for Accessibility 3. Hinge side might vary (see floor plan) 4. Each door to have a secure doorset 5. Where provided, letter plates to have maximum aperture of 260x40mm, located to hinder the removal of keys and fitted with an internal doorflap 6. Door viewer also to be provided 7. Doorset to be fitted with a door chain or door limiter</div><div>No. required:<div>2</div></div></div></td> <td>DE2.01</td> <td><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div></div><div><div>Flush door</div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div><td><div><div>Location: Existing Store door</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement door</div><div>No. required:<div>1</div></div></div></td></td>	<div><div>Location: Flat entrance doors. Leaf size 864x1981x44</div><div>Structural Opening (wxh): 955 x 2040 Door to have minimum 775mm clear opening</div><div>Finished wall thickness: 132</div><div>Door type: Solid core, six panel door with hardwood lipping and intumescent smoke seal(stain/varnish to client choice)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Ironmongery: 1 ½ Twin Ball Bearing Fire Door Hinges – 100 x 75 x 3mm Grade 201 Stainless Steel to BS EN grade 14 and to have CE mark – Multi-point locking system – Snib to enable opening without use of key – Perko (or similar)self-closing device – Handles (type to be agreed) – Secured by Design 3 hooks – All doors to have either half moon or contract projection door stop – 76mm Satin Nickel screw fixed door numbers</div><div>Notes: 1. All door components including the frame, glazing,intumescent fire and smoke seals, ironmongery etc to have 30 minutes fire rating. 2. Door to BS 476 part 22 and to comply with Approved Document B: 2006 edition incorporating 2010 amendments;Volume 1&2, Documents; E – for sound, F – for ventilation, L – for Thermal M – for Accessibility 3. Hinge side might vary (see floor plan) 4. Each door to have a secure doorset 5. Where provided, letter plates to have maximum aperture of 260x40mm, located to hinder the removal of keys and fitted with an internal doorflap 6. Door viewer also to be provided 7. Doorset to be fitted with a door chain or door limiter</div><div>No. required:<div>2</div></div></div>	DE2.01	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div></div><div><div>Flush door</div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div> <td><div><div>Location: Existing Store door</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement door</div><div>No. required:<div>1</div></div></div></td>	<div><div>Location: Existing Store door</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement door</div><div>No. required:<div>1</div></div></div>
		DL.01/02 DL.03/05	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Flush door</div></div><div><div><div>1.750</div><div>0.750</div></div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div> <td><div><div>Location: Loft Area. Leaf size 3No 545x630x55 (site check)</div><div>Structural Opening (wxh): 1750 x 700 (site check)</div><div>Finished wall thickness: 250</div><div>Door type: Solid core timber door with hardwood lipping (stain/varnish to client choice)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>N/A</div></div><div>Glazing type – N/A</div><div>Ironmongery: 1 ½ Twin Ball Bearing Door Hinges – 100 x 75 x 3mm Grade 201 external grade Stainless Steel to BS EN grade 14 and to have CE mark – Handles (type to be agreed) – FB2 lock</div><div>Notes:</div><div>No. required:<div>2</div></div></div></td> <td>Service Riser Doors</td> <td><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div></div><div><div>Flush doors</div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div><td><div><div>Location: Service Riser</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement doors to Lower Ground Floor, Ground and First Floor – dimensions to be checked on site 2. Ironmongery as existing 3. New doors to Third Floor – dimensions to be confirmed on site</div><div>No. required:<div>3No existing 1No new</div></div></div></td><td></td></td>	<div><div>Location: Loft Area. Leaf size 3No 545x630x55 (site check)</div><div>Structural Opening (wxh): 1750 x 700 (site check)</div><div>Finished wall thickness: 250</div><div>Door type: Solid core timber door with hardwood lipping (stain/varnish to client choice)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>N/A</div></div><div>Glazing type – N/A</div><div>Ironmongery: 1 ½ Twin Ball Bearing Door Hinges – 100 x 75 x 3mm Grade 201 external grade Stainless Steel to BS EN grade 14 and to have CE mark – Handles (type to be agreed) – FB2 lock</div><div>Notes:</div><div>No. required:<div>2</div></div></div>	Service Riser Doors	<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div></div><div><div>Flush doors</div></div><div>Elevation Scale 1:50</div><div><div><div></div><div></div></div></div><div>Plan Scale 1:50</div></div> <td><div><div>Location: Service Riser</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement doors to Lower Ground Floor, Ground and First Floor – dimensions to be checked on site 2. Ironmongery as existing 3. New doors to Third Floor – dimensions to be confirmed on site</div><div>No. required:<div>3No existing 1No new</div></div></div></td> <td></td>	<div><div>Location: Service Riser</div><div>Structural Opening (wxh): As existing</div><div>Finished wall thickness: As existing</div><div>Door type: Solid core, flush door with hardwood lipping and intumescent smoke seal (painted white)</div><div>Lining: Timber (sw)</div><div>Fire rating:<div>FD30S</div></div><div>Glazing type – N/A</div><div>Notes: 1. Replacement doors to Lower Ground Floor, Ground and First Floor – dimensions to be checked on site 2. Ironmongery as existing 3. New doors to Third Floor – dimensions to be confirmed on site</div><div>No. required:<div>3No existing 1No new</div></div></div>	