

DEMOLITION SPECIFICATION

- AGREE REQUIREMENTS FOR RETAINING SHRUBS AND PLANTING WITH CLIENT PRIOR TO COMMENCING WORKS
- 2. SET ASIDE ANY MATERIALS FROM DEMOLITIONS IF SUITABLE FOR RE-USE
- 3. CAREFULLY REMOVE ALL COPINGS
- 4. RAKE OUT AND REPOINT JOINTS TO ALL SECTIONS OF WALL WHICH ARE NOT TO BE RE-BUILT, ALLOW FOR REMOVAL OF ANY PREVIOUSLY INSTALLED CORRODING METAL FIXINGS
- CAREFULLY TAKE DOWN SECTION OF WALL BETWEEN PIER 2 AND 3, INCLUDING PIERS 2 AND 3) TO 1050MM BELOW GROUND LEVEL
- ALLOW FOR REMOVAL OF SMALL SECTION OF BRICKWORK TO WEST OF PIER 2

RE-BUILD SPECIFICATION

- 1. TO INCLUDE BUTTRESSES AND PIERS TO MATCH EXISTING AS NOTED USING SALVAGED BRICKS FROM DEMOLITION WHERE POSSIBLE
- 2. RAKE OUT AND RE-POINT ALL RETAINED BRICKWORK
- 3. NEW SECTIONS OF WALL TO BE ONE BRICK THICK ENGLISH BOND
- 4. ALLOW FOR ENGINEERING BRICKS TO BE USED BELOW GROUND LEVEL AND SECOND HAND STOCKS TO MATCH EXISTING ABOVE GROUND LEVEL
- 5. FOUNDATION TO BE MASS CONCRETE TRENCH FOUNDATION
- 6. JOINTS TO BE FLUSH POINTED STRUCK AS WORK PROCEEDS
- 7. ALLOW FOR BACKFILL AND TOPSOIL TO GARDENS BOTH SIDES OF NEW SECTIONS OF WALL
- 8. SUPPLY AND LAY NEW BRICK ON EDGE COPINGS IN STOCK BRICKS
- SUPPLY AND INSTALL SS BRICK TOR MIN 300MM LONG TO BE INSERTED INTO ALL HORIZONTAL
 JOINTS AT JUNCTIONS BETWEEN NEW PIERS AND PANELS: 150MM OVERLAP TO PIER/ PANEL