

Boundary

All beam bearing to be installed at 200mm on padstone

NOTES:

This drawing is copyright of "Fred Richard & Associates" & is only to

be used by the client for planning / building control application works at the address listed below

Reproduction is only to take place with written authority.

These plans are subject to Planning & Building Regulation

law before building work commences. Any structural work where mentioned on this drawing

Approval or any other statute in

is subject to qualified structural

All FD30 doors to have 25mm door stops screwed and glued or intumescent strips. The fire doors need to be fitted with 3

throughout the internal floor area of the flat. Underfloor heating to be installed in accordance with manufacturer's instruction. Pipes for to be used for underfloor heating to be installed above the floor joists and installed in such a way not to compromise the separating floor

Timber guard rail 1.1m

and civil engineers' calculations before building works commence. All PDF drawings are provided to the specified scale and should be printed correctly. Contractor must take independent measurements and check all dimensions on site prior to commencement, ordering Underfloor floor heating to be installed materials or manufacture. To commence work before building regulations approval is entirely at contractor's own risk. FRED **RICHARD & ASSOCIATES is not** responsible for unauthorised changes made to the drawings or the consequences thereof. TERRACE ail timber deck 5m 1:50 May-2019 **FRED RICHARD & ASSOCIATES** 2 Montagu Gardens Dartford DA1 5RP 1:50 / A3 Tel: 01322477125; 07812378352

03

Website: www.fredrichardandassociates.com E-mail: info@fredrichardandassociates.com