

# Schedule of Materials

Ref: 1044-B-20-05 Material Schedule

**To be read in conjunction with planning drawings as cross referenced.**

## Elevation/Section key notes.

General materials and finishes notes:

- 1 Window: Fixed Aluminium windows. RAL TBC (dark grey – to match cladding)
- 2 Window: Thermally broken aluminium window. Generally top hung opening (except those fixed), openable with 100mm restrictor, in dark grey colour. RAL TBC
- 3 Window: Fixed Aluminium windows. RAL TBC (dark grey – to match cladding)
- 4 Window: Thermally broken aluminium window. Generally top hung opening (except those fixed), openable with 100mm restrictor, in dark grey colour. RAL TBC
- 5 Window: Fixed Aluminium windows. RAL TBC (dark grey – to match cladding)
- 6 Window: Thermally broken aluminium window. Generally top hung opening (except those fixed), openable with 100mm restrictor, in dark grey colour. RAL TBC
- 7 Window: Fixed Aluminium windows. RAL TBC (dark grey – to match cladding)
- 8 Curtain walling: Thermally broken. RAL TBC (dark grey – to match cladding/windows).  
With mid-pane blinds and fixed windows.
- 9 Window: Fixed Aluminium windows. RAL TBC
- 10 Window: Fixed Aluminium windows. RAL TBC (dark grey – to match cladding)
- 11 Window: Thermally broken aluminium window. Generally top hung opening (except those fixed), openable with 100mm restrictor, in dark grey colour. RAL TBC
- 12 Door: Thermally broken aluminium frame to PAS 24 standards. Fully glazed.
- 13 Door: Thermally broken aluminium frame to PAS 24 standards. Fully glazed.
- 14 Door: Thermally broken aluminium frame to PAS 24 standards. Fully glazed.
- 15 Spandrel Panel. Colour/finish TBC
- 16 PV panels to M+E/Energy report specification.
- 17 Roller Shutter Door to workshop, in dark grey colour. RAL TBC
- 18 Aluminium Door with Louvres to plantroom - 50mm Pitch Blades.
- 19 Feature sliding and lockable security gate in 'lacquer red' colour. 1.8m in height. RAL TBC.
- 20 Fire escape exit door clad in External Wall Type 01
- 21 Door: Thermally broken aluminium frame to Secured by Design standards (LPS1175 or STS). Fully glazed.
- 22 Fixed Bench Seating
- 23 Entrance Canopy: Steel frame structure with metal cladding as EXT-01 and recessed lighting.
- 24 Security fencing. 1.8m in height.
- 25 Brickwork painted black or black bricks in running bond, colour mortar to match.
- 26 Dark blue/black engineering brickwork to base (below DPC)
- 27 Lift overrun.
- 28 Pre-cast concrete lintel – painted black.
- 29 Powder coated aluminium signage fixed with a metal rod system. RAL TBC (Front facing in 'lacquer red' – to match sliding security gate and side depths in 'black').

EXT-01 External Wall Type 01 – Profiled metal cladding sheets. A1 rated steel, trapezoidal pattern, black in colour (RAL tbc), vertical orientation, fixed back to support rails.

EXT-02 External Wall Type 02 – Precast Concrete wall panels, painted black.