

## V91 Electrical systems - landscape

**To be read with Preliminaries/ General conditions.**

### **PRODUCTS**

#### **303 PRODUCTS STANDARDS AND APPROVALS GENERALLY**

- Standard: In accordance with BS 7671.
- CE Marking: Required.
- Cables: BASEC approved.

#### **335 LUMINAIRES GENERALLY**

- Standards: To BS EN 60598-1 and BS EN 55015.

#### **350A LIGHTING TO RAISED PLANTERS**

- Standard: To BS EN 60598-2-7.
  - Approval: Kitemark certified.
- Refer to drawing 5657\_510 D88
- Photometric performance: To BS EN 13032-1.
- Manufacturer: Iguzzini [www.iguzzini.com/](http://www.iguzzini.com/).
  - Product reference: Palco Inout Q694 (42°).
- Ingress protection to BS EN 60529: IP66.
- Body material: Aluminium.
  - Finish and colour: RAL 9005.
- Lens: Clear toughened safety glass.
- Mounting: Spike fixing to topsoil.
  - Lamp: [Light emitting diode (LED)]
  - Colour temperature: 3000.

#### **350B LIGHTING TO RAISED TREE PLANTERS**

- Standard: To BS EN 60598-2-7.
  - Approval: Kitemark certified.
- Refer to drawing 5657\_510 D69
- Photometric performance: To BS EN 13032-1.
- Manufacturer: Iguzzini [www.iguzzini.com/](http://www.iguzzini.com/).
  - Product reference: Palco Inout Q691 (24°).
- Ingress protection to BS EN 60529: IP66.
- Body material: Aluminium.
  - Finish and colour: RAL 9005.
- Lens: Clear toughened safety glass.
- Mounting: Spike fixing to topsoil.
  - Lamp: [Light emitting diode (LED)]
  - Colour temperature: 3000.

## 5657\_101 Camley Street

### 350C LIGHTING PENDANT TO PERGOLA

- Standard: To BS EN 60598-2-7.
  - Approval: Kitemark certified.
- Photometric performance: To BS EN 13032-1.
- Manufacturer: Marset [www.marset.com/](http://www.marset.com/).
  - Product reference: Soho 57.
- Ingress protection to BS EN 60529: IP44.
- Body material: Polyethylene.
  - Finish and colour: Black.
- Lens: Methacrylate opal diffuser.
- Mounting: Refer to drawing 5657\_510 D70 fixings to be determined by fabricator and coordinated with Electrical Engineer and Landscape Architect.
  - Lamp: [Light emitting diode (LED)]
  - Colour temperature: 3000.

### 350D LIGHTING TO ENTRANCE SIGN

- Standard: To BS EN 60598-2-7.
  - Approval: Kitemark certified.
- Refer to drawing 5657\_511 D71
- Photometric performance: To BS EN 13032-1.
- Manufacturer: Iguzzini [www.iguzzini.com/](http://www.iguzzini.com/).
  - Product reference: Linealuce Compact Recessed BM95.
- Ingress protection to BS EN 60529: IP67.
- Body material: Aluminium.
  - Finish and colour: 15 Grey.
- Lens: Opal toughened safety glass.
- Mounting: Recessed within pavement.
  - Lamp: [Light emitting diode (LED)]
  - Colour temperature: 3000.