


Sash spring



HARDWOOD 30 YEAR WARRANTIES	SOFTWOOD 15 15 YEAR WARRANTIES
WEATHER SEALS 10 YEAR WARRANTIES	GLAZING UNIT 10 YEAR WARRANTIES
IRONMONGERY 10 YEAR WARRANTIES	PAINT FINISH 7 YEAR WARRANTIES

PRODUCT DESCRIPTION:



Frame Depth (mm)	155
Frame material:	Engineered Softwood
Cill material:	Hardwood
Sash material:	Engineered Softwood
Glazing specification:	24 mm 4 gr -16Ar- 4GNP gr (Pilkington 4mm Tempered + 4mm Tempered Low-E, Argon gas filled gap, Ug=1.1) (warm edge spacer TGI grey) (BS EN 1279)
Rebate:	Internally Beaded 22mm wooden bars with internal spacer
Spacer Bar and Color:	Grey Warm edge TGI
U Value:	1.4 W/m ² K
Frame Color:	White RAL 9010 paint - fully factory painted with TEKNOS water based micro-porous paint
Ventilation:	Concealed Trickle vent (Titon EA 4000 - White)
Hardware:	Caldwell's Spring Balances
Hardware color:	Polished Brass
Additional hardware if agreed:	Travel restrictors or Sash Eye Ring Pull on customers demands

The engineered timber can be produced from pine, redwood, meranti or oak according to preference.


U value performance range from 1.4 W/m²K to 1.0 W/m²K, and 36db sound rating depending on the type of window glazing.

Finishing, with water based paints by TEKNOS. Customers are free to select product RAL or stain colours upon their choice.

www.windowssolutionsltd.co.uk

www.windowssolutionsltd.co.uk

Sash box



HARDWOOD 30 YEAR WARRANTIES	SOFTWOOD 15 15 YEAR WARRANTIES
WEATHER SEALS 10 YEAR WARRANTIES	GLAZING UNIT 10 YEAR WARRANTIES
IRONMONGERY 10 YEAR WARRANTIES	PAINT FINISH 7 YEAR WARRANTIES

PRODUCT DESCRIPTION:



Frame Depth (mm)	156
Frame material:	Engineered Softwood
Cill material:	Hardwood
Sash material:	Engineered Softwood
Glazing specification:	24 mm 4 gr -16Ar- 4GNP gr (Pilkington 4mm Tempered + 4mm Tempered Low-E, Argon gas filled gap, Ug=1.1) (warm edge spacer TGI grey) (BS EN 1279)
Rebate:	Internally Beaded 22mm wooden bars with internal spacer
Spacer Bar and Color:	Grey Warm edge TGI
U Value:	1.4 W/m ² K
Frame Color:	White RAL 9010 paint - fully factory painted with TEKNOS water based micro-porous paint
Ventilation:	Concealed Trickle vent (Titon EA 4000 - White)
Hardware:	Caldwell's fasteners, Sash Window Lead weights
Hardware color:	Polished Brass
Additional hardware if agreed:	Travel restrictors or Sash Eye Ring Pull on customers demands

The engineered timber can be produced from pine, redwood, meranti or oak according to preference.


U value performance range from 1.4 W/m²K to 1.0 W/m²K, and 36db sound rating depending on the type of window glazing.

Finishing, with water based paints by TEKNOS. Customers are free to select product RAL or stain colours upon their choice.

www.windowssolutionsltd.co.uk

www.windowssolutionsltd.co.uk

Flush casement



HARDWOOD 30 YEAR WARRANTIES	SOFTWOOD 15 15 YEAR WARRANTIES
WEATHER SEALS 10 YEAR WARRANTIES	GLAZING UNIT 10 YEAR WARRANTIES
IRONMONGERY 10 YEAR WARRANTIES	PAINT FINISH 7 YEAR WARRANTIES

PRODUCT DESCRIPTION:



Frame Depth (mm)	Frame 115mm, sash 56mm
Frame material:	Engineered Softwood
Openings:	Inward, outward and tilt and turn
Sash material:	Engineered Softwood
Glazing specification:	24 mm 4 gr -16Ar-4GNP gr (Pilkington 4mm Tempered + 4mm Tempered Low-E, Argon gas filled gap, Ug=1.1) (warm edge spacer TGI grey) (BS EN 1279)
Rebate:	Internally Beaded 22mm wooden bars with internal spacer
Spacer Bar and Color:	Grey Warm edge TGI
U Value:	1.4 W/m2K
Frame Color:	White RAL 9010 paint - fully factory painted with
Ventilation:	TEKNOS water based micro-porous paint
Hardware:	Concealed Trickle vent (Ttton EA 4000 - White)
Hardware color:	IPA BESLAG, friction hinges.
Additional hardware if agreed:	Polished Chrome or Brass Side hung friction hinges

The engineered timber can be produced from pine, redwood, meranti or oak according to preference.

U value performance range from 1.4 W/m2K to 1.0 W/m2K, and 36db sound rating depending on the type of window glazing.

Finishing with water based paints by TEKNOS. Customers are free to select product RAL or stain colours upon their choice.