

Optional glazing bars for standard VELUX roof windows



Depending on where you live, conservation officers will have different requirements. The black finish featured in our conservation roof window packages may not be required in your area.

By adding a glazing bar to a standard VELUX roof window with a grey exterior, you can create a traditional appearance, allowing you to take advantage of all roof window styles and sizes available (except triple glazed roof windows).

To be used for Windows:
NW3-04
NW3-05

Grey glazing bars are also available for standard VELUX roof windows

Recessed flashing



In addition to a glazing bar, you may be asked to install your roof window deeper into the roof than can be achieved with standard installation. To do this you should select a recessed flashing kit, streamlining the roof window so less protrudes above the roofline.

Recessed flashings are also available with insulation and underfelt collars and are recommended for optimum energy efficiency. Our full range of recessed flashings are available as part of our conservation roof window packages.

To be used for Windows:
NW3-04
NW3-05
NW2-04

To create your grey conservation package

- 1 Select your preferred VELUX roof window. This includes white painted, white polyurethane, pine and all operating methods. **P20-27**
- 2 Choose a flashing kit right for your roof pitch and roofing material – we recommend a recessed flashing kit. **P58-59**
- 3 Use VELUX installation products for optimum energy efficiency. **P56-57**
- 4 Add one or more conservation glazing bars of the right size to your roof windows. Remember, to match grey exteriors you should consider adding a grey glazing bar (nearest RAL 7043).