



101x38Ø GALVANISED COLOUR-COATED MILD STEEL TAPERED POLE,
 5mm WALL THICKNESS;
 BOTTOM (BURIED) 1M FINISHED BITUMINOUS PAINT,
 REMAINDER COLOUR-COATED BLACK RAL9005 OR AS
 SPECIFIED, TBA;
 (NB POLE MAY BE ECCENTRICALLY POSITIONED
 WITH MIN 100 COVER IF REQ'D)

POLE DESIGN

101x38Ø TAPERED POLES WITHIN ALL CONSERVATION AREAS;
 76Ø POLES TO BE USED ELSEWHERE -- ALL AS DWG No 868.51

POLE + WIRE HEIGHTS

TOP OF ALL POLES CROSSING ROADS TO BE 5500 ABOVE CROWN OF
 ROAD WITH A NOMINAL THICKNESS (NYLON FISHING LINE)
 SPANNING TAUT BETWEEN, EXTENDING TO FIXING STAPLE @ 2500AGL
 FOR EASE OF EMERGENCY MAINTENANCE ACCESS.
 POLES ADJACENT TO FOOTPATHS, DRIVEWAYS etc TO BE TO HEIGHT
 INDICATED ON SPECIFIC LOCATION DRAWING.
 POLES COLOUR-COATED BLACK RAL9005 OR AS SPECIFIED, TBA.

3500 x 1025DP
 CONCRETE BASE,
 TOP 175 BELOW
 EXTG FINISHED LEVEL;
 HAND DUG EXCAVATION
 TO SAFEGUARD EXTG SERVICES
 DUCTS AND TREE ROOTS

1:10 PLAN OF
 500Ø CONCRETE BASE

DRAWING REF : 868-62

CAMDEN 'ERUV' -- CONSERVATION AREA LOCATIONS

TAPERED POLE & WIRE DETAILS

ROSENFELDER ASSOCIATES
 Chartered Architects + Planning Consultants
 10-12 Perrins Court Hampstead LONDON NW3 (020) 7794 4425