

ian chalk architects

No, 19 Window Schedule

Window/Door number	Description of existing window	Description of proposed window	Retained or replace/news	Material	Glazing
Ground floor					
Z04(b)-00-W01	Double casement with bottom fan light	Double casement with bottom fan lights and fixed central pane and fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
First floor					
Z04(b)-01-W01	Double casement with bottom fan light	Double casement with bottom fan lights and fixed central pane and fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W02	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W03	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W04	Screening to lift	tbc	tbc	tbc	tbc
Z04(b)-01-W05	Crittall style window	Single casement with lower and upper fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W06	Triple casement with alternating position of fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W07	Quadruple casement with top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W08	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W09	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W10	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W11	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner

Second floor

Z04(b)-02-W01	Double casement with bottom and top fan light	Double casement with bottom fan lights and fixed central pane and fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-02-W02	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-02-W03	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-02-W04	Screening to lift	tbc	Replace	Steel	tbc
Z04(b)-02-W05	Crittall style window	Single casement with lower and upper fanlight	Replace	Steel	tbc
Z04(b)-02-W06	Triple casement with alternating position of fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-02-W07	Triple casement with alternating position of fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-01-W08	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W09	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W10	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-01-W11	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner

Third floor

Z04(b)-03-W01	Triple casement with alternating position of fan lights	Double casement with bottom fan lights and fixed central pane and fanlight	Replace	Steel	tbc
Z04(b)-03-W02	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-03-W03	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-03-W04	Screening to lift	tbc	Replace	Steel	tbc
Z04(b)-03-W05	Crittall style window	Single casement with lower and upper fanlight	Replace	Steel	tbc
Z04(b)-03-W06	Triple casement with top fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-03-W07	Triple casement with top fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	tbc
Z04(b)-03-W08	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-03-W09	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-03-W10	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner

Z04(b)-03-W11	vertically pivoting window with horizontally pivoting fanlight	vertically pivoting window with horizontally pivoting fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
---------------	--	--	---------	-------	---

Fourth floor

Z04(b)-04-W01	Triple casement with alternating position of fan lights	Double casement with bottom fan lights and fixed central pane and fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W02	Single casement with bottom and top fan light	Single casement with lower and upper fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W03	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W04	Double casement with bottom and top fan light	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W05	Crittall casement with top fan light	Single casement with lower and upper fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W06	Screening to lift	tbc	Replace	Steel	tbc
Z04(b)-04-W07	Crittall casement with top fan light	Single casement with lower and upper fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W08	Triple casement with top fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W09	Triple casement with top fan lights	Double casement with bottom fan lights and 2no. fixed central panes with fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W10	casement	casement	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W11	casement	casement	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W12	casement	casement	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-04-W13	casement	casement	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner

Fifth floor

Z04(b)-05-W01	Triple casement with alternating position of fan lights	Single casement with lower and upper fanlight	Replace	Steel	Slimlight double glazing warm edge, 18mm outer low iron, 4mm dimguard toughened laminated inner
Z04(b)-05-W02	Screening to lift	tbc	Replace	Steel	tbc