

OAK DRIFT WOOD OILED 180 X 15 MM

ENGINEERED FLOORING 180 MM X 15 MM



DESCRIPTION

PRICE CALCULATOR

Oak is a highly popular species that is a real classic and is suitable for a wide range of finishes and appearances, so that you can achieve the style you want.

The combination of light and dark shades of grey in the Drift Wood oil finish work with the surface to add depth to the timber. The cool grey tones and scattered knots add boundless character and style.

This is a distinctive floor which celebrates the natural beauty of wood with on-trend grey tones. Unlike a painted floor, the detailing of oak is there for all to see and admire. The natural, simple beauty of the oak is enhanced not smothered.

Our overlay boards are designed to be laid over a subfloor, whether concrete or an existing wood floor. Once laid, this floor looks and feels the same as all of our beautiful wood flooring but cannot be used as a structural floor.

Nail Fitting: Nail fixing is usually done via a nail gun, e.g Porta-Nailer, where a serrated nail is inserted through the tongue at 45 degrees.

Stick Down: Sticking involves the use of an adhesive to bond the wood flooring to either a concrete/screed sub floor or to a ply/chipboard sub floor.

Floating: A floating floor is not physically connected to the sub floor. Normally laid on an underlay, the floor is joined by gluing the tongue and groove together or by using a click system.

([HTTPS://NATURALWOODFLOOR.CO.UK](https://naturalwoodfloor.co.uk))

Under Floor Heating: This product is compatible for use over an electric or water under floor heating system. The maximum temperature must not exceed 27 degrees Celsius at the floor surface.

Engineered: 2 part Engineered floor with a Hardwood top surface bonded to a multilayer waterproof Russian Birch Plywood. Can be Nailed, Stuck Down, or Floated depending on the sub floor. All floors are Tongue and Groove with Ends Matched unless stated otherwise.

£52.50 + VAT

**PRODUCT CODE
OLODRO/180**

ORDER A SAMPLE

([HTTPS://NATURALWOODFLOOR.CO.UK/WP-
LOGIN.PHP?ACTION=REGISTER](https://naturalwoodfloor.co.uk/wp-login.php?action=register))

FULL TECHNICAL INFORMATION

Our engineered board has been produced using a Russian WBP birch ply, manufactured to European standard EN 326-2. The adhesive used to bond the board is an E1 category, PUR adhesive (formaldehyde free) to DIN/EN 14257 and DIN/EN 204 low emission glue which is heat and water resistant in accordance with BS EN 14342:2005+A1. The top layer is kiln dried to between 8-12% moisture content.

The formaldehyde emissions are: 0,01 ppm, pentachlorophenol emissions: <0.8 mg/kg. Thermal conductivity (W/mK) is 0,10W/mK.

Suitable for secret fixing to a ply subfloor, floating on an underlay or a fully bonded installation to a screed subfloor. The board is supplied with a micro bevel along the length of the board, factory Oiled ready to use.

*if the product is being laid in a high traffic environment then an additional coat of oil is recommended.

Product code:

OLODRO/180

Grade: Millrun

Grade, contains knots & Colour variation

Species: Oak**Group:**

Engineered Flooring

Category:

Engineered Overlay

Type of Finish:

Oiled - An additional coat is recommended.

Size: 180 x 15 mm**Width:** 180 mm**Thickness:** 15 mm**Brushed:** No**Profile:** Tongue and Groove**Specification:**

Bevelled Edge

Unit Weight: 11kg**Suitable for underfloor****heating:** Yes

Nail Fitting: Nail fixing is usually done via a nail gun, e.g Porta-Nailer, where a serrated nail is inserted through the tongue at 45 degrees.

Stick Down: Sticking involves the use of an adhesive to bond the wood flooring to either a concrete/screed sub floor or to a

Compatible for use in conjunction with underfloor heating the board complies with BS 8201:2011, rated in accordance with BS EN 13501-1, and is classified D fl -S1 when laid as a fixed floor on a structural subfloor.

ply/chipboard sub floor.

Floating: A floating floor is not physically connected to the sub floor. Normally laid on an underlay, the floor is joined by gluing the tongue and groove together or by using a click system.

Under Floor Heating: This product is compatible for use over an electric or water under floor heating system. The maximum temperature must not exceed 27 degrees Celsius at the floor surface.

Engineered: 2 part Engineered floor with a Hardwood top surface bonded to a multilayer waterproof Russian Birch Plywood. Can be Nailed, Stuck Down, or Floated depending on the sub floor. All floors are Tongue and Groove with Ends Matched unless stated otherwise.

SEE FITTING INFORMATION



Nail Fitting: Nail fixing is usually done via a nail gun, e.g Porta-Nailer, where a serrated nail is inserted through the tongue at 45 degrees.

ACCESSORIES

**Osmo Polyx-Oil Clear Satin
(3032) 2.5 Ltr**

FROM £60.83

[\(/accessories/osmo-polyx-oil-clear-satin-3032-2-5-ltr/\)](/accessories/osmo-polyx-oil-clear-satin-3032-2-5-ltr/)

Osmo Wash & Care 1 Ltr

FROM £10.83

[\(/accessories/osmo-wash-care-1-ltr/\)](/accessories/osmo-wash-care-1-ltr/)

Visit our showroom

20 Smugglers Way

Wandsworth

London

SW18 1EG

[VIEW MAP](#)

[\(/CONTACT-US\)](/CONTACT-US)

(htt
ps:/
/w
ww.
inst
agr
(htt
am.
ps:/
/w
ww.
m/n
atur
alw
ood
floo
rco
mp
any/
?
hl=
en)
(htt
ps:/
/w
ww.
face
boo
k.co
m/T
heN
atur
alW
ood
Flo
orC
o/)

ORDER A SAMPLE
(HTTPS://NATURAL
WOODFLOOR.CO.U
K/WP-LOGIN.PHP?
ACTION=REGISTER

)

Sign In

<https://naturalwoodfloor.co.uk/wp-login.php>

Customer Sign Up

<https://naturalwoodfloor.co.uk/wp-login.php?action=register>

Delivery Information

<https://naturalwoodfloor.co.uk/delivery-information/>

FAQs

<https://naturalwoodfloor.co.uk/advice/faq/>

Contact Us

<https://naturalwoodfloor.co.uk/contact-us/>

© 2019 Natural Wood Floor Company Ltd.

Terms & Conditions

<https://naturalwoodfloor.co.uk/terms-conditions/> Cookies &

Privacy Policy

<https://naturalwoodfloor.co.uk/cookies-privacy-policy/>