

Insulation - not

running through

Insulation - not

running through

Do not scale from this drawing. Use figured dimensions only. All dimensions to be checked and verified by the contractor on site.

C Pringle Richards Sharratt Ltd: Studio 4, 33 Stannary Street, London, SE11 4AA: Company registered in England No. 3189549

structure

Read this drawing in association with all other relevant contract documents and risk assessments

1:1@ A1 RF PIPEWORK SIZES

L 1:1 10 pence coin

for scale reference

Scale bar for verification only

Date Description 27 July 2018 Planning & Listed Building Consent Applications Planning & Listed Building Consent Applications 21 June 2019 16 August 2019 Planning & Listed Building Consent Applications FOR PLANNING

ABA's Servicing Strategy Drawing

Key Plan

NOTES:

LEGEND

Exposed pipework to lower ground floor ceiling

detailed notes on drawing

New riser/opening in floor

Existing beams within floor

Layout of existing walls to be removed

Existing joists within floor

Electrical riser.

Mechanical riser.

with an on site survey prior to construction.

Frankham services drawings.

to existing joists.

Conservation Officer.

Pipework dimensions are as follows:

For VRF sizes refer to drawing RS_5_J_61

Note: Beam and joist locations are assumed and are to be confirmed

The drawing is to be read in conjunction with PRS Heritage Significance drawings (HW-series drawings); Alan Baxter structural drawings and

The services distribution strategy is to avoid altering the existing fabric by

Elsewhere the integration of new services will aim to work with the grain

of the existing structure by passing services between existing timber

floor joists and with careful coordination of the routes to limit notching

Where new notches are required these will be agreed by the LB Camden

1.No 24mm ø pipe including insulation (6.5 ø RF pipe to VRF)

1.No 31mm ø pipe including insulation (13 ø RF pipe to VRF)

All horizontal distribution of pipework to not be larger than 13mm in

diameter. No insulation to run through floor timber structure.

All redundant services openings will be made good.

1. SERVICES STRATEGY - TYPICAL FLOOR

h = Span of BEAM

2. SERVICES STILATERY - SINGLE TOISTED FLOOR

re-using existing services routes and notches where possible.

Pipework from/to existing & new risers within floor void

Floor mounted VRF unit within bespoke joinery housing.

Electrical cabling from/to existing & new risers within floor void

Existing riser/opening in floor to be retained or stripped-out - refer to

41 RUSSELL SQUARE - BRITISH MUSEUM THIRD FLOOR PLAN: 41RS PROPOSED SERVICES RISERS - SHEET 02 41RS_20_Y_05.2 Drwg No: