

# **JANSEN STEEL DOORS**

## **FEATURES**

- All Doors to be manufactured from 2mm thick mild steel Jansen sections, all joints to be welded and ground to smooth finish. Jansen sections to be shot blasted, hot zinc sprayed and polyester powder coated textured finish to any BS or RAL No (All Metallic and certain silver paints at extra cost).
- Complies with Part M regulations for wheelchair access
- Custom designs on request

### **SPECIFICATION**

- » Sizes:
- Any size made to order
- » Ironmongery:
- 12mm Anti-nip stainless steel continuous hinge
- Stainless steel pull handle 225x22mm
- Stainless steel push plate internal face

#### » Alternative Frames:

- 80x40x2mm stainless steel hollow section
- . 100x50x2mm stainless steel hollow section
- » Alternative Glazing:
- Pyroshield georgian wire glass
- Laminated glass
- Obscure glass
- Double glazed sealed unit


#### » Hardware:

- LCN2035 concealed door closer
- Stainless steel kick plate internal and external
- » Options:
- Magnalock housing to be manufactured from 60x40x2mm (for M32 magnets) or 100x50x2mm (for M82 magnets) stainless steel hollow section fixed with security screws
- 2-No Magna Locks (Securitron M32 and M32C) OR
- To meet Secured by design standards 2-No Magna Locks (Securitron M62 and M62C)
- RX100 low level threshold
- Fanlights and sidelights
- » Finishes:
- Painted BS or RAL colour

#### Please Note:

All/any electrical equipment to be disconnected and connected by others. Electrical equipment supply and connected by others.










MIL 126



MIL 127

Secured by Design Secured by De

MIL 128

Pro Door Manufacture, Instatistion Mainisrance

