## **DECLARATION OF PERFORMANCE**

Category 20 comprising of

Original London Stock Weathered Original London Stock Imperial Gault





## **Group HD, Category II Handmade Clay Bricks**

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Dimensional Tolerances mm	230 x 110 x 68 - 215 x 102.5 x 65*		
	Tolerance	T1 / *TM	BS EN771-1:2011
	Range	R1 / *RM	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm2	Mean	15.7	
	Category	II	
Dimensional Stability N/mm2	NPD		
Bond Strength Fixed value N/mm2	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1		Commission Decision 2000/605/EC
Water Absorption %	21		- BS EN771-1:2011
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m3 (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

September 2018

Grindle House Farm Grindle Road Grindle, Near Shifnal Shropshire

Imperial Bricks Ltd

TF11 9JR