

12 Keats Grove

Structural Engineer's Basement Impact Assessment



Prepared by: Samuel Pickles MEng CEng MIStructE

Yousuf Azizi BSc

Reviewed by: Paul Toplis MA CEng FIStructE

Thomas Quigg MSc CEng MICE

Job Number: 28570

Date	Version	Notes/Amendments/Issue Purpose
October 2019	1	Issued for planning

Contents		Page
1	Introduction	3
2	Desk Study	3
3	Hydrology, Drainage and Flood Risk	3
4	CPG Basements - Screening, Scoping and Additional Assessments	4
5	Construction Methodology	4

Appendices:

Appendix A	Site location and Historic Maps
Appendix B	Drainage and Hydrology Maps
Appendix C	Proposed Structural Drawings and Construction Sequence
Appendix D	Structural Calculations

Accompanying Documents

Existing and Proposed Architectural Drawings	CDA
Ground Investigation and Basement Impact Assessment Report	GEA
Ground Movement Analysis	GEA
Arboriculturalist's Report	ADC

Contains Ordnance Survey material © Crown copyright. All rights reserved. Licence number 0100058197
 Contains British Geological Survey materials © NERC 2019 All rights reserved.

1 Introduction

The proposed alterations to this four storey late Georgian house include demolishing and rebuilding two wings to the house with basements under each. The wings are a relatively modern addition to the original building and have been remodelled several times over the years. The historic central part of the house has an original lower ground floor level under its entire footprint. In order to coordinate with the existing lower ground floor and raised ground floor levels, the wings will be set such that the proposed basement level is approximately 1m lower than the existing lower ground level; see site location and relevant historic maps in Appendix A.

2 Desk Study

Site History

With reference to Figure 2 and Figure 3 the site has been a house since before 1866, and is assumed to have been previously undeveloped. As can be seen, several of the houses on the street were demolished and some rebuilt in the period between the two maps being produced. Additionally, there is record of WW2 bombing in the area and that the property suffered some minor blast damage [Figure 4 and Figure 5]. A preliminary UXO Risk Assessment was carried out prior to the Site Investigation and gives recommendation that a more detailed assessment should be carried out which will be completed before construction commences.

Geology

The site is underlain by London Clay formation as was found in historic records [Figure 6] and confirmed with the site investigation carried out. The site investigation comprised trial pits and several boreholes which extended to a depth greater than the proposed excavation - ground water was not encountered.

Further information can be found in the accompanying report(s) produced by GEA which cover Geology and Hydrogeology, and includes their Interpretative Site Investigation report.

3 Hydrology, Drainage and Flood Risk

The site is not within the catchment of the Hampstead Heath Pond Chain, which is approximately 130m to the north-east of the site [Figure 7]

The site surface area is currently approximately 1510m², of which approximately 700m² is permeable. The property drains to a combined drainage system which discharges to the combined public sewer in Keats Grove. Refer to Drainage CCTV Survey drawing [Figure 8] for existing drainage arrangements and Thames Water Asset search [Figure 9]

The proposed site surface area will be unchanged (1510m²). The footprint of the proposed building footprint is ~5m² larger than the existing however this area is already hardstanding and so there will be no increase in hardstanding as a result. Refer to the accompanying existing and proposed architectural drawings.

The site is located in Flood Zone 1 and is not at risk of flooding. The site is not at risk of flooding from rivers or the sea, surface water flooding or reservoir flooding. Refer to Environment Agency Flood Risk map [Figure 10] and Surface Water Flooding map [Figure 11].

The site is not within a Critical Drainage Area.

4 CPG Basements - Screening, Scoping and Additional Assessments

Refer to GEA's accompanying reports for Screening, Scoping and Basement Impact Assessment. As identified in the aforementioned report, part of the works will be taking place within a tree root protection zone and the impact of this is assessed in the accompanying Arboricultural Report.

5 Construction Methodology

Reference should be made to Appendix C where proposed construction type and sequencing is illustrated. Supporting Calculations can be found in Appendix D.

Substructure

The basement structures will be formed in an underpinning construction method with base and ground floor slab to form a stiff concrete box. This is due to the relatively shallow depth of the excavation required and as it allows retention of existing structures. Notably, all of the walls that are to be underpinned are that of the Building Owner and therefore are not Party Structure

Superstructure

The wings will be single storey above ground and are currently proposed to be constructed in loadbearing masonry with timber and steel roof structures.

External Works

There are no retaining walls proposed in the landscaping works. The proposed basements will conflict with existing below ground drainage, hence this will be reconfigured during the works.

Codes and Standards

The works will be designed in accordance with the relevant British Standards.

Loadings

Area	Load (kN/m ²)
Floors	2.5
Roofs	0.8
Retaining - surcharge	10

Design Fire Periods

The concrete structure will be designed to provide an inherent fire resistance of 60mins. Fire protection of the single storey superstructure will be by lining/encasement to the Architect's details.

Disproportionate Collapse

Class 1 to Part A3 – no special measures required.

Calculations

Conservative geotechnical parameters for soil density, cohesion and an accidental scenario of retained water level have been adopted for the design. Heave of the clays has also been considered.

Damage Classification

A ground movement analysis has been carried out by GEA and should be referred to for the impact on the surrounding buildings. The report summarises that the anticipated movement would result in damage of Category 0 to 1 in accordance with the Burland scale and so is considered acceptable.

Appendix A

Site location and Historic Maps




Figure 1: Site location [Google maps 2019]




Figure 2: Extract from OS historic map of London 1866




Figure 3: Extract from OS historic map of London 1915




Figure 4: WW2 bomb locations [bombsight.org]




Figure 5: Bomb damage map [LCC war damage maps]




Figure 6: Site Geology [British Geological Survey – Geology of Britain Viewer accessed October 2019]

Appendix B

Drainage and Hydrology Maps



Figure 7: Hampstead Chain Catchment Boundaries [Figure 4.3 of the Hampstead Heath Ponds Project (March 2013)]




Figure 8: CCTV survey drawing




Figure 9: Extract from Thames Water Asset search




Figure 10: Extract from Environment Agency – Flood Map for Planning accessed October 2019




Figure 11: Environment Agency - Surface water flood risk map accessed October 2019

Appendix C

Proposed Structural Drawings and Construction Sequence



PROPOSED BASEMENT CONSTRUCTION AND METHOD SEQUENCE

Sequence


- 1 Demolish existing structures
- 2 Construct basement in an underpinning sequence (1,4,2,5,3), refer to underpin construction sequence below
- 3 Construct superstructure

Underpinning Construction Sequence

- A. Excavate for underpin, installing shoring as progressing
- B. Cast RC base (install drainage if required)
- C. Cast RC wall and additional strutting across
- D. Backfill
- E. Repeat until all underpins are complete
- F. Excavate and install walers inc. diagonal bracing struts to mid-height
- G. Batter down to existing foundation level and install lower waler and continue to excavate until lower level propping can be completed
- H. Excavate remaining soil, install drainage, cast base slab.
- I. Cast ground floor slab and remove temporary works



BASEMENT PLAN



SECTION

Appendix D

Structural Calculations

RETAINING WALL ANALYSIS

In accordance with EN1997-1:2004 incorporating Corrigendum dated February 2009 and the UK National Annex incorporating Corrigendum No.1

Tedds calculation version 2.9.10

Analysis summary

Description	Unit	Capacity	Applied	F o S	Result
Bearing pressure	kN/m ²	100	22.8	4.385	PASS

Design summary

Description	Unit	Provided	Required	Utilisation	Result
Stem p0 rear face - Flexural reinforcement	mm ² /m	754.0	680.7	0.90	PASS
Stem p0 - Span/Depth ratio		11.5	16.6	1.44	FAIL
Base bottom face - Flexural reinforcement	mm ² /m	1340.4	718.7	0.54	PASS
Base - Shear resistance	kN/m	135.1	46.5	0.34	PASS
Transverse stem reinforcement	mm ² /m	392.7	250.0	0.64	PASS
Transverse base reinforcement	mm ² /m	392.7	268.1	0.68	PASS

Retaining wall details

Stem type	Cantilever
Stem height	$h_{\text{stem}} = 2800$ mm
Stem thickness	$t_{\text{stem}} = 250$ mm
Angle to rear face of stem	$\alpha = 90$ deg
Stem density	$\gamma_{\text{stem}} = 25$ kN/m ³
Toe length	$l_{\text{toe}} = 3000$ mm
Base thickness	$t_{\text{base}} = 300$ mm
Base density	$\gamma_{\text{base}} = 25$ kN/m ³
Height of retained soil	$h_{\text{ret}} = 1800$ mm
Angle of soil surface	$\beta = 0$ deg
Depth of cover	$d_{\text{cover}} = 0$ mm
Height of water	$h_{\text{water}} = 1000$ mm
Water density	$\gamma_w = 9.8$ kN/m ³

In reality the stem will be propped mid height during construction and the ground slab will provide a permanent prop at the top. This simplistic analysis also neglects the stiffening due to the return walls. Overall the deflection will be very low from experience. Considered OK

Retained soil properties


Soil type	Organic clay
Moist density	$\gamma_{\text{mr}} = 18$ kN/m ³
Saturated density	$\gamma_{\text{sr}} = 20$ kN/m ³
Characteristic effective shear resistance angle	$\phi_{r,k}^t = 23$ deg
Characteristic wall friction angle	$\delta_{r,k} = 11.5$ deg

Base soil properties

Soil type	Organic clay
Soil density	$\gamma_b = 18$ kN/m ³
Characteristic effective shear resistance angle	$\phi_{b,k}^t = 23$ deg
Characteristic wall friction angle	$\delta_{b,k} = 11.5$ deg
Characteristic base friction angle	$\delta_{bb,k} = 12$ deg
Presumed bearing capacity	$P_{\text{bearing}} = 100$ kN/m ²

Loading details

Variable surcharge load	Surcharge _Q = 10 kN/m ²
Vertical line load at 3125 mm	$P_{G1} = 15$ kN/m
	$P_{Q1} = 5$ kN/m



Calculate retaining wall geometry

Base length

$$l_{\text{base}} = l_{\text{toe}} + t_{\text{stem}} = \mathbf{3250 \text{ mm}}$$

Saturated soil height

$$h_{\text{sat}} = h_{\text{water}} + d_{\text{cover}} = \mathbf{1000 \text{ mm}}$$

Moist soil height

$$h_{\text{moist}} = h_{\text{ret}} - h_{\text{water}} = \mathbf{800 \text{ mm}}$$

Length of surcharge load

$$l_{\text{sur}} = l_{\text{heel}} = \mathbf{0 \text{ mm}}$$

- Distance to vertical component

$$x_{\text{sur}_v} = l_{\text{base}} - l_{\text{heel}} / 2 = \mathbf{3250 \text{ mm}}$$

Effective height of wall

$$h_{\text{eff}} = h_{\text{base}} + d_{\text{cover}} + h_{\text{ret}} = \mathbf{2100 \text{ mm}}$$

- Distance to horizontal component

$$x_{\text{sur}_h} = h_{\text{eff}} / 2 = \mathbf{1050 \text{ mm}}$$

Area of wall stem

$$A_{\text{stem}} = h_{\text{stem}} \times t_{\text{stem}} = \mathbf{0.7 \text{ m}^2}$$

- Distance to vertical component

$$x_{\text{stem}} = l_{\text{toe}} + t_{\text{stem}} / 2 = \mathbf{3125 \text{ mm}}$$

Area of wall base

$$A_{\text{base}} = l_{\text{base}} \times t_{\text{base}} = \mathbf{0.975 \text{ m}^2}$$

- Distance to vertical component

$$x_{\text{base}} = l_{\text{base}} / 2 = \mathbf{1625 \text{ mm}}$$

For undrained soils - Annex C.1(2)

At rest pressure coefficient

$$K_0 = \mathbf{1.000}$$

Passive pressure coefficient

$$K_p = \mathbf{1.000}$$

Bearing pressure check

Vertical forces on wall

Wall stem

$$F_{\text{stem}} = A_{\text{stem}} \times \gamma_{\text{stem}} = \mathbf{17.5 \text{ kN/m}}$$

Wall base

$$F_{\text{base}} = A_{\text{base}} \times \gamma_{\text{base}} = \mathbf{24.4 \text{ kN/m}}$$

Line loads

$$F_{P_v} = P_{G1} + P_{Q1} = \mathbf{20 \text{ kN/m}}$$

Total

$$F_{\text{total}_v} = F_{\text{stem}} + F_{\text{base}} + F_{P_v} + F_{\text{water}_v} = \mathbf{61.9 \text{ kN/m}}$$

Horizontal forces on wall

Surcharge load	$F_{sur,h} = K_0 \times \cos(\delta_{r,k}) \times \text{Surcharge}_Q \times h_{eff} = 20.6 \text{ kN/m}$
Saturated retained soil	$F_{sat,h} = K_0 \times \cos(\delta_{r,k}) \times (\gamma_{sr} - \gamma_w) \times (h_{sat} + h_{base})^2 / 2 = 8.4 \text{ kN/m}$
Water	$F_{water,h} = \gamma_w \times (h_{water} + d_{cover} + h_{base})^2 / 2 = 8.3 \text{ kN/m}$
Moist retained soil	$F_{moist,h} = K_0 \times \cos(\delta_{r,k}) \times \gamma_{mr} \times ((h_{eff} - h_{sat} - h_{base})^2 / 2 + (h_{eff} - h_{sat} - h_{base}) \times (h_{sat} + h_{base})) = 24 \text{ kN/m}$
Base soil	$F_{pass,h} = -K_P \times \cos(\delta_{b,k}) \times \gamma_b \times (d_{cover} + h_{base})^2 / 2 = -0.8 \text{ kN/m}$
Total	$F_{total,h} = F_{sur,h} + F_{sat,h} + F_{water,h} + F_{moist,h} + F_{pass,h} = 60.5 \text{ kN/m}$

Moments on wall

Wall stem	$M_{stem} = F_{stem} \times X_{stem} = 54.7 \text{ kNm/m}$
Wall base	$M_{base} = F_{base} \times X_{base} = 39.6 \text{ kNm/m}$
Surcharge load	$M_{sur} = -F_{sur,h} \times X_{sur,h} = -21.6 \text{ kNm/m}$
Line loads	$M_P = (P_{G1} + P_{Q1}) \times p_1 = 62.5 \text{ kNm/m}$
Saturated retained soil	$M_{sat} = -F_{sat,h} \times X_{sat,h} = -3.7 \text{ kNm/m}$
Water	$M_{water} = -F_{water,h} \times X_{water,h} = -3.6 \text{ kNm/m}$
Moist retained soil	$M_{moist} = -F_{moist,h} \times X_{moist,h} = -20.8 \text{ kNm/m}$
Total	$M_{total} = M_{stem} + M_{base} + M_{sur} + M_P + M_{sat} + M_{water} + M_{moist} = 107.2 \text{ kNm/m}$

Check bearing pressure

Propping force	$F_{prop,base} = F_{total,h} = 60.5 \text{ kN/m}$
Distance to reaction	$\bar{X} = M_{total} / F_{total,v} = 1732 \text{ mm}$
Eccentricity of reaction	$e = \bar{X} - l_{base} / 2 = 107 \text{ mm}$
Loaded length of base	$l_{load} = l_{base} = 3250 \text{ mm}$
Bearing pressure at toe	$q_{toe} = F_{total,v} / l_{base} \times (1 - 6 \times e / l_{base}) = 15.3 \text{ kN/m}^2$
Bearing pressure at heel	$q_{heel} = F_{total,v} / l_{base} \times (1 + 6 \times e / l_{base}) = 22.8 \text{ kN/m}^2$
Factor of safety	$FoS_{bp} = P_{bearing} / \max(q_{toe}, q_{heel}) = 4.385$

Base resistance provided by friction with soil
Friction 0.33
G = 15kPa
A = 5m²/m
Friction resistance = 75kN/m
Additionally existing foundation and passive resistance will help significantly

PASS - Allowable bearing pressure exceeds maximum applied bearing pressure

RETAINING WALL DESIGN

In accordance with EN1992-1-1:2004 incorporating Corrigendum dated January 2008 and the UK National Annex incorporating National Amendment No.1

Tedds calculation version 2.9.10

Concrete details - Table 3.1 - Strength and deformation characteristics for concrete

Concrete strength class	C30/37
Characteristic compressive cylinder strength	$f_{ck} = 30 \text{ N/mm}^2$
Characteristic compressive cube strength	$f_{ck,cube} = 37 \text{ N/mm}^2$
Mean value of compressive cylinder strength	$f_{cm} = f_{ck} + 8 \text{ N/mm}^2 = 38 \text{ N/mm}^2$
Mean value of axial tensile strength	$f_{ctm} = 0.3 \text{ N/mm}^2 \times (f_{ck} / 1 \text{ N/mm}^2)^{2/3} = 2.9 \text{ N/mm}^2$
5% fractile of axial tensile strength	$f_{ctk,0.05} = 0.7 \times f_{ctm} = 2.0 \text{ N/mm}^2$
Secant modulus of elasticity of concrete	$E_{cm} = 22 \text{ kN/mm}^2 \times (f_{cm} / 10 \text{ N/mm}^2)^{0.3} = 32837 \text{ N/mm}^2$
Partial factor for concrete - Table 2.1N	$\gamma_C = 1.50$
Compressive strength coefficient - cl.3.1.6(1)	$\alpha_{cc} = 0.85$
Design compressive concrete strength - exp.3.15	$f_{cd} = \alpha_{cc} \times f_{ck} / \gamma_C = 17.0 \text{ N/mm}^2$
Maximum aggregate size	$h_{agg} = 20 \text{ mm}$
Ultimate strain - Table 3.1	$\epsilon_{cu2} = 0.0035$
Shortening strain - Table 3.1	$\epsilon_{cu3} = 0.0035$







Effective compression zone height factor	$\lambda = 0.80$
Effective strength factor	$\eta = 1.00$
Bending coefficient k_1	$K_1 = 0.40$
Bending coefficient k_2	$K_2 = 1.00 \times (0.6 + 0.0014/\epsilon_{cu2}) = 1.00$
Bending coefficient k_3	$K_3 = 0.40$
Bending coefficient k_4	$K_4 = 1.00 \times (0.6 + 0.0014/\epsilon_{cu2}) = 1.00$

Reinforcement details

Characteristic yield strength of reinforcement	$f_{yk} = 500 \text{ N/mm}^2$
Modulus of elasticity of reinforcement	$E_s = 200000 \text{ N/mm}^2$
Partial factor for reinforcing steel - Table 2.1N	$\gamma_s = 1.15$
Design yield strength of reinforcement	$f_{yd} = f_{yk} / \gamma_s = 435 \text{ N/mm}^2$

Cover to reinforcement

Front face of stem	$c_{sf} = 30 \text{ mm}$
Rear face of stem	$c_{sr} = 75 \text{ mm}$
Top face of base	$c_{bt} = 50 \text{ mm}$
Bottom face of base	$c_{bb} = 75 \text{ mm}$



Check stem design at base of stemDepth of section $h = 250$ mm**Rectangular section in flexure - Section 6.1**Design bending moment combination 1 $M = 47.4$ kNm/mDepth to tension reinforcement $d = h - c_{sr} - \phi_{sr} / 2 = 169$ mm

$$K = M / (d^2 \times f_{ck}) = 0.055$$

$$K' = (2 \times \eta \times \alpha_{cc} / \gamma_c) \times (1 - \lambda \times (\delta - K_1) / (2 \times K_2)) \times (\lambda \times (\delta - K_1) / (2 \times K_2))$$

$$K' = 0.207$$

 $K' > K$ - No compression reinforcement is requiredLever arm $z = \min(0.5 + 0.5 \times (1 - 2 \times K / (\eta \times \alpha_{cc} / \gamma_c))^{0.5}, 0.95) \times d = 160$ mmDepth of neutral axis $x = 2.5 \times (d - z) = 22$ mmArea of tension reinforcement required $A_{sr,req} = M / (f_{yd} \times z) = 681$ mm²/m

Tension reinforcement provided 12 dia.bars @ 150 c/c

Area of tension reinforcement provided $A_{sr,prov} = \pi \times \phi_{sr}^2 / (4 \times s_{sr}) = 754$ mm²/mMinimum area of reinforcement - exp.9.1N $A_{sr,min} = \max(0.26 \times f_{ctm} / f_{yk}, 0.0013) \times d = 255$ mm²/mMaximum area of reinforcement - cl.9.2.1.1(3) $A_{sr,max} = 0.04 \times h = 10000$ mm²/m

$$\max(A_{sr,req}, A_{sr,min}) / A_{sr,prov} = 0.903$$

PASS - Area of reinforcement provided is greater than area of reinforcement required

Library item: Rectangular single output

Deflection control - Section 7.4Reference reinforcement ratio $\rho_0 = \sqrt{(f_{ck} / 1 \text{ N/mm}^2)} / 1000 = 0.005$ Required tension reinforcement ratio $\rho = A_{sr,req} / d = 0.004$ Required compression reinforcement ratio $\rho' = A_{sr,2,req} / d_2 = 0.000$ Structural system factor - Table 7.4N $K_b = 0.4$ Reinforcement factor - exp.7.17 $K_s = \min(500 \text{ N/mm}^2 / (f_{yk} \times A_{sr,req} / A_{sr,prov}), 1.5) = 1.108$ Limiting span to depth ratio - exp.7.16.a $\min(K_s \times K_b \times [11 + 1.5 \times \sqrt{(f_{ck} / 1 \text{ N/mm}^2)} \times \rho_0 / \rho + 3.2 \times \sqrt{(f_{ck} / 1 \text{ N/mm}^2)} \times (\rho_0 / \rho - 1)^{3/2}], 40 \times K_b) = 11.5$ Actual span to depth ratio $h_{stem} / d = 16.6$ **FAIL - Span to depth ratio exceeds deflection control limit****Crack control - Section 7.3**Limiting crack width $w_{max} = 0.3$ mmVariable load factor - EN1990 – Table A1.1 $\psi_2 = 0.3$ Serviceability bending moment $M_{sls} = 22.3$ kNm/mTensile stress in reinforcement $\sigma_s = M_{sls} / (A_{sr,prov} \times z) = 184.2$ N/mm²

Load duration Long term

Load duration factor $k_t = 0.4$ Effective area of concrete in tension $A_{c,eff} = \min(2.5 \times (h - d), (h - x) / 3, h / 2)$

$$A_{c,eff} = 76079 \text{ mm}^2/\text{m}$$

Mean value of concrete tensile strength $f_{ct,eff} = f_{ctm} = 2.9$ N/mm²Reinforcement ratio $\rho_{p,eff} = A_{sr,prov} / A_{c,eff} = 0.010$ Modular ratio $\alpha_e = E_s / E_{cm} = 6.091$ Bond property coefficient $k_1 = 0.8$ Strain distribution coefficient $k_2 = 0.5$

$$k_3 = 3.4$$

$$k_4 = 0.425$$

In reality the stem will be propped mid height during construction and the ground slab will provide a permanent prop at the top. This simplistic analysis also neglects the stiffening due to the return walls. Overall the deflection will be very low from experience. Considered OK

Maximum crack spacing - exp.7.11

$$s_{r,max} = k_3 \times C_{sr} + k_1 \times k_2 \times k_4 \times \phi_{sr} / \rho_{p,eff} = \mathbf{461 \text{ mm}}$$

Maximum crack width - exp.7.8

$$w_k = s_{r,max} \times \max(\sigma_s - k_t \times (f_{ct,eff} / \rho_{p,eff}) \times (1 + \alpha_e \times \rho_{p,eff}), 0.6 \times \sigma_s) / E_s$$

$$w_k = \mathbf{0.255 \text{ mm}}$$

$$w_k / w_{max} = \mathbf{0.849}$$

PASS - Maximum crack width is less than limiting crack width

Rectangular section in shear - Section 6.2

Design shear force

$$V = \mathbf{66.5 \text{ kN/m}}$$

$$C_{Rd,c} = 0.18 / \gamma_c = \mathbf{0.120}$$

$$k = \min(1 + \sqrt{(200 \text{ mm} / d)}, 2) = \mathbf{2.000}$$

Longitudinal reinforcement ratio

$$\rho_l = \min(A_{sr,prov} / d, 0.02) = \mathbf{0.004}$$

$$v_{min} = 0.035 \text{ N}^{1/2}/\text{mm} \times k^{3/2} \times f_{ck}^{0.5} = \mathbf{0.542 \text{ N/mm}^2}$$

Design shear resistance - exp.6.2a & 6.2b

$$V_{Rd,c} = \max(C_{Rd,c} \times k \times (100 \text{ N}^2/\text{mm}^4 \times \rho_l \times f_{ck})^{1/3}, v_{min}) \times d$$

$$V_{Rd,c} = \mathbf{96.3 \text{ kN/m}}$$

$$V / V_{Rd,c} = \mathbf{0.690}$$

PASS - Design shear resistance exceeds design shear force

Horizontal reinforcement parallel to face of stem - Section 9.6

Minimum area of reinforcement - cl.9.6.3(1)

$$A_{sx,req} = \max(0.25 \times A_{sr,prov}, 0.001 \times t_{stem}) = \mathbf{250 \text{ mm}^2/\text{m}}$$

Maximum spacing of reinforcement - cl.9.6.3(2)

$$s_{sx,max} = \mathbf{400 \text{ mm}}$$

Transverse reinforcement provided

$$\mathbf{10 \text{ dia.bars @ } 200 \text{ c/c}}$$

Area of transverse reinforcement provided

$$A_{sx,prov} = \pi \times \phi_{sx}^2 / (4 \times s_{sx}) = \mathbf{393 \text{ mm}^2/\text{m}}$$

PASS - Area of reinforcement provided is greater than area of reinforcement required

Check base design at toe

Depth of section

$$h = \mathbf{300 \text{ mm}}$$

Rectangular section in flexure - Section 6.1

Design bending moment combination 1

$$M = \mathbf{64.4 \text{ kNm/m}}$$

Depth to tension reinforcement

$$d = h - c_{bb} - \phi_{bb} / 2 = \mathbf{217 \text{ mm}}$$

$$K = M / (d^2 \times f_{ck}) = \mathbf{0.046}$$

$$K' = (2 \times \eta \times \alpha_{cc} / \gamma_c) \times (1 - \lambda \times (\delta - K_1) / (2 \times K_2)) \times (\lambda \times (\delta - K_1) / (2 \times K_2))$$

$$K' = \mathbf{0.207}$$

K' > K - No compression reinforcement is required

Lever arm

$$z = \min(0.5 + 0.5 \times (1 - 2 \times K / (\eta \times \alpha_{cc} / \gamma_c))^{0.5}, 0.95) \times d = \mathbf{206 \text{ mm}}$$

Depth of neutral axis

$$x = 2.5 \times (d - z) = \mathbf{27 \text{ mm}}$$

Area of tension reinforcement required

$$A_{bb,req} = M / (f_{yd} \times z) = \mathbf{719 \text{ mm}^2/\text{m}}$$

Tension reinforcement provided

$$\mathbf{16 \text{ dia.bars @ } 150 \text{ c/c}}$$

Area of tension reinforcement provided

$$A_{bb,prov} = \pi \times \phi_{bb}^2 / (4 \times s_{bb}) = \mathbf{1340 \text{ mm}^2/\text{m}}$$

Minimum area of reinforcement - exp.9.1N

$$A_{bb,min} = \max(0.26 \times f_{ctm} / f_{yk}, 0.0013) \times d = \mathbf{327 \text{ mm}^2/\text{m}}$$

Maximum area of reinforcement - cl.9.2.1.1(3)

$$A_{bb,max} = 0.04 \times h = \mathbf{12000 \text{ mm}^2/\text{m}}$$

$$\max(A_{bb,req}, A_{bb,min}) / A_{bb,prov} = \mathbf{0.536}$$

PASS - Area of reinforcement provided is greater than area of reinforcement required

Library item: Rectangular single output

Crack control - Section 7.3

Limiting crack width

$$w_{max} = \mathbf{0.3 \text{ mm}}$$

Variable load factor - EN1990 – Table A1.1

$$\psi_2 = \mathbf{0.3}$$

Serviceability bending moment

$$M_{sls} = \mathbf{45.4 \text{ kNm/m}}$$

Tensile stress in reinforcement

$$\sigma_s = M_{sls} / (A_{bb,prov} \times z) = \mathbf{164.3 \text{ N/mm}^2}$$

Load duration

$$\text{Long term}$$