5.4 Kingsway Elevation - Proposed

33



Kingsway elevation



Historic facade and windows

Historic replacement windows Portland Stone

The proposals for Kingsway elevation include:

- Restoration of historic façade.
- Refurbish 65 Keeley Street entrance including new signage, lighting and historic features.
- All windows replaced with a design to match historic windows.
- Sloping plant screen added at roof level to enclose previously cluttered services.

Existing roof outline

New slim profile metal windows to match historic proportions

Bronze mansard extension retained. New windows

Mansard extension retained and re-clad at 6th floor plus new windows.

Mansard re-built plus new cladding and windows at 7th floor

Plant and core


Existing historic entrance refurbished

Out of scope

5.4 Kingsway Elevation - Proposed

The material palette proposed for the 6th and 7th floor is guided largely by the existing facade.

Currently a large extent of the facade to the existing 6th and 7th floor extensions is in a bad state or of a poor quality. We proposed to replace the facade material at 6th floor (rear of building) and entire 7th floor with a metal cladding with a bronze finish, to tie in with the 1920's extension on Kingsway elevation.








Kingsway elevation



#### 5.5 Wild Court Elevation - Existing



Wild Court Elevation









Existing Wild Court Elevation

General characteristics of the Wild Court facade can be summarised as:

- Wild Court facade features Portland stone, white glazed bricks and bronze.
- A heavy horizontal band divides the elevation between 1st and 2nd floors.
- The building was extended at 6th floor in 1925.
- The building was unsympathetically extended at 7th floor in 1989.
- All the original windows along the Wild Court elevation have been replaced.
- The plant is installed at roof level, mainly above the core structures. Currently there is no plant enclosure or screen.
- Ad hoc and cluttered plant has a negative impact on the roofscape.
- Base and middle storey facade requires restoration.
- Parts of the 1925 and all of the 1989 storeys are in a very poor condition and have reached the end of their design life.

PAYE have carried out a review of the existing façade and have identified areas where steel frame corrosion, which is at early stage, is causing cracking as explained on page 29.

1980's sloping roof extension

1920's bronze extension with projecting canopy.

1920's low quality extension to rear of building

Existing windows


Existing entrance points

Existing lift core

Services grilles

Out of scope

5.6 Wild Court Elevation - Proposed



Wild Court Elevation



The proposals for Wild Court elevation include:

- All windows replaced with a design to match historic windows.
- Sloping plant screen added at roof level to enclose previously cluttered services.
- Restoration of historic façade.


- Existing roof outline
- New slim profile metal windows to match historic proportions
- New louvres
  - UKPN access maintained
- Bronze mansard extension retained. New windows
- Mansard extension retained and re-clad at 6th floor plus new windows.

  Mansard re-built plus new cladding and windows at 7th floor
- Plant
- Out of scope

5.6 Wild Court Elevation - Proposed

The material palette proposed for the 6th and 7th floor is guided largely by the existing facade.

Currently a large extent of the facade to the existing 6th and 7th floor extensions is in a bad state or of a poor quality. We propose to replace the facade material at 6th floor (rear of building) and the entire 7th floor with a metal cladding with a bronze finish, to tie in with the 1920's extension on Kingsway elevation. The core extension on Wild Court clad will be clad in glazed white bricks to tie in with the existing facade material below.










Wild Court Elevation



Context elevation

## **6.1 Public Realm Improvements**



Proposed Space House Public Realm by Squire&Partners

This page shows the proposals for the public realm enhancements currently part of CAA House consented works as well as potential plans for pedestrianisation of Keeley Street.

The creation of a new entrance off Keeley Street connects the building to the new public space and activates this frontage.

----- Application Site

Kodak House reception space

Potential pedestrianisation / traffic calming on Keeley Street








39

Space House proposals by Squire&Partners - Planning application no. 2019/2773/P

## **6.2 Proposed Kodak House Entrance**















Kingsway Facade principles sketch

Glass

Solid / louvered

## **6.2 Proposed Kodak House Entrance**

HODAK HOUSE

2

3

1800


9

100

6

7

Elevation



Plan

- New double glazed crittal style slim line windows.
- 2. New black metal entrance canopy with integrated illuminated signage and lighting
- 3. New wall mounted circular bulb lights. Brass finish
- 4. Existing red brick facade repaired and cleaned
- 5. New metal framed, double glazed entrance doors. Black colour.
- 6. New solid metal bike entrance door. Black frame colour. Brass finish ironmongery
- 7. Fixed minimal black metal frame glazed panels
- 8. New metal pull handles with engraved lettering Brass colour
- 9. Laser cut metal signage. Brass finish
- 10. Access control panel. Black metal finish

The key principles of the proposed entrance design are:

- Projecting canopy over entrance
- Fully glazed bay to access reception
- Partially glazed bay onto stairs
- Substation access retained
- Original loading bay visually reinstated
- New lighting and signage
- New metal frame windows at upper levels to match original windows design




Key Plan




Keeley Street Elevation

## 6.3 Historic Entrance to 65 Kingsway







Proposed Elevation


The key principles of the proposed entrance design are:

- Stone sensitively cleaned
- New backlit soffit with wire grid
- New brass signage
- Historic door, gate and features retained and french polished
- Floor cleaned



7.1 Core - Opportunities and Constraints

## 01. Existing Floor Plate Analysis



- Floor plate is divided by the modern central WC's block
- 2 sets of lifts on either side of floor plate
- Arrival experience not suitable for modern office



View of typical floor


# ¥INGSWAY

## 02. Proposed Reconfiguration


- Consolidate core on northern elevation
- New lift position aligns with new entrance at ground floor
- Incorporates historic stair within core
- Combine front and back side of the building as original floorplate



Precedent image - open floor plate



7.2 Typical Proposed Office Floor



Scope of work to the typical office floor includes:

- Reconfiguration of the core with new WC's, lifts and secondary stair linking all
- 3no. columns removed per floor to facilitate core relocation and improve floor
- Modern linings removed from columns and original steel exposed and painted
- · New raised access floor installed throughout
- New windows installed on all elevations, to match historic design
- Retain and restore historic staircase
- Raft ceiling design with partly exposed services

#### Extract from Bidwells Historic Report:


The scheme seeks the removal of a small number of columns, including one towards the centre of the floor plate and two within the proposed northern core, per floor. While this will result in the loss of some historic fabric, the special interest and contribution of the columns to the significance of the building is in their cumulative appearance, creating an open plan floor space supported by steel structures rather than in the intrinsic historic value of the fabric. The proposals seek the removal of a very small proportion of these supports, retaining over twenty columns per floor, and the overall impression of a historic steel structure will remain and be better revealed following the strip back of later cladding to the columns. Therefore while the loss of the columns, as part of the original fabric of the building, will result in a degree of harm, this level is considered to be negligible and remaining within the spectrum of less than substantial harm overall. The proposals fundamentally retain the contribution of columns to the special interest of the building and are in line with proposals the Council have previously consented, including the removal of columns in the basement of the building.






Precedents Images

7.3 Ground Floor - Opportunities and Constraints



## 01. Existing Ground Floor Analysis

- One entrance from Kingsway to main reception
- Main reception is small, with limited visual presence from the street.
- B1 office at the rear of the building is confined and dark
- Blank elevation on Keeley street facade. Blocked predominantly by louvres.
- Keeley street facade impacts negatively on neighbouring spaces



## 02. Proposed Ground Floor Reconfiguration

- Create an enlarged reception.
- Historic Kingsway entrance is retained.
- Create a new Kodak House entrance from Keeley Street positioned opposite the new lifts.
- Facade is opened up and activated on Keeley Street
- B1 office directly connected to reception









Photographs of existing reception


7.4 Proposed Ground Floor Plan





Concept Plan

7.4 Proposed Ground Floor Plan



The key features and materials of the new Kodak House reception are:


- Double flight, full width bleachers with staggered steps
- Sesame lift (platform lifts integrated within bleachers)
- New passenger lifts in line with new entrance
- Plinth and reception desk
- Black metal Crittal partitions with fluted glass
- Kodak style castellated beams
- Whole building meeting facility
- Photographic studio style light fittings
- Waiting area including storage
- Exposed structural ceiling
- New signage
- Slab level alterations to allow on grade access from Keeley Street
- 3no columns removed
- High end floor finishes
- Historic ceiling retained, refurbished and adapted where necessary

48

Historic stair to first floor retained and refurbished

7.5 First Floor Historic Plans Analysis

## First Floor Plan Form Evolution



#### 1910 Plan form

- Cores located on Wild Court and Keeley St perimeters
- Reception area open to the rear of the floor plate

#### 1939 Modified Plan Form

- Rear of the floor plate is heavily subdivided
- Floor plate is split by concierge area


#### 1973 Modified Plan Form

- Fireplace is relocated.
- Rear of the floor plate is still subdivided but reconfigured

49

• Concierge area converted into WC's block

7.6 First Floor Existing Plan Analysis



Modern Marble floor.

Historic Stair and Railings

Core splitting floorplate

Historic marble clad round columns

Historic coved ceilings (asbestos)

The first floor is unique to the rest of the floors in that it retains some of the original features of the historic first floor reception area.

In analysing the existing we have identified negative and positive contributors to the space. We proposed to alter or remove the negative contributing elements.


- Modern Pendant light fittings of a dated style
- Modern Glazed screens of a dated style
- Modern Marble floor finish that is of a dated style
- # Historic Coved ceilings built with asbestos insulated boards
- ➡ Historic Marble-clad columns
- Historic stair and railings
- ➡ Historic mahogany fire place



Historic Fireplace.

7.7 Proposed First Floor Plan

51



Proposed First Floor Plan

The refurbished First Floor will provide:

- B1 office to the same standard as the floors above
- Sensitively restored stair, balustrade, marble columns
- Coved ceiling replaced like for like with non asbestos materials
- New quality floor finish within the extent of the historic reception area and on historic stair



View of First Floor . 1972



Restored Historic marble clad round columns



Coved ceilings replaced like for like



Office



Restored historic staircase



Restored historic fireplace




New quality floor finish



## **Terrace**

## 8.1 Proposed Terrace



Communal terrace area: 195 m<sup>2</sup>








53

Precedent Images

Proposed terrace plan

## 9.1 Access Provisions and DDA Compliance



#### Ground Floor Plan



#### Access

An entrance from Keeley Street has been planned to create level access to the office building. It is proposed to lower part of the existing ground floor slab and introduce 2no platform lifts to achieve this. From the reception 3no. passenger lifts will give access to all levels; the basement will only be served by two of these lifts and 1no lift will access the proposed terrace at roof level.

A stair lift on the historic stair to Wild Court is currently used for DDA access and will be maintained.

The existing historic entrance from Kingsway is going to be restored and will remain a stepped entrance in order to preserve its historic character.

The UKPN access from Keeley Street will be maintained. A separate access for bicycles is also created from Keeley Street.

A new services lift accessible from Wild Court via a protected lobby and will serve all levels from basement to seventh floor.

#### **Internal Circulation**

The existing historic staircase will be refurbished and linked to the proposed core and a new accommodation stair is proposed to the Keeley Street side of the building. Both stairs will serve all levels and will provide means of access and escape from the building. The new protected stair is accessible from basement level through to roof level via a hatch and will include for a DDA refuge at each level. The existing protected original stair is accessible from the basement level through to the seventh floor, and will be extended to the roof.

## 9.2 Cycle Parking Spaces and Facilities


The occupier facilities will be located in the basement and will include: a cycle store, male and female changing rooms including showers, lockers, sinks and WC's, an accessible WC/shower and a drying room.

#### The facilities include:

- 74 bike spaces
- 108 lockers
- 1no. Bicycle maintenance station
- 5 male and 5 female showers
- 1no. DDA WC Changing Shower
- 1no. drying room

The above figures comply with BCO, Planning and BREEAM Standards.





Basement Floor Plan









Precedent images

56


9.3 Waste Management

## **ARUP**


The development provides a combined waste and recycling storage with an area of 25 m<sup>2</sup> which will house:

- 1 No. 1,100 litre eurobins compactor for compacting paper waste;
- 4 No. 1,100 litre eurobins for compacted paper waste;
- 3 No. 1,100 litre eurobins for residual waste;
- 1 No. 1,100 litre eurobins for cardboard waste;
- 1 No. 1,100 litre eurobins for plastics waste; and
- 1 No. 360 litre eurobins for mixed metal waste.

The bins are going to be taken out to Wild Court through the services lift.



Basement Floor






-->

Waste route

## 9.4 Circulation and Fire Escape Routes





WILD CT

REALEY ST

REELEY ST

Ground Floor Plan





#### **Escape at Basement Floor**

Escape from the basement will be either via the existing historic stair to Wild Court or the new secondary stair to Keeley Street through a protected corridor.

#### **Escape at Typical Office Floor**

The existing historic stair to Wild Court and the new secondary stair to Keeley Street will provide two means of escape from all office floors to street level. If the typical office floor is split into two tenancies, additional protected corridors will need to be built so that both tenancies can access both escape routes.

#### **Escape at Ground Floor**

Escape from the ground floor will be through the reception to either Keeley Street or Wild Court via a protected corridor. The existing A3 unit will escape through the office reception.

#### **Escape at First Floor**

Escape from the first floor office will be either through the secondary stair or through the primary core.

#### **Escape at Roof Level**

Escape from roof level and terrace will be via the existing historic stair.



58

9.5 Secured by Design

Feedback was received in relation to this project from the Secured by Design officer. The meeting took place on site on 18th September 2019.

The key areas discussed were:

- Points of access to the building
- Multiple uses in the building and necessity for access and movement within the building to be addressed so that any potential cross over between uses are protected.
- Current and proposed reception design and importance of entrance(s) visibility from reception desk
- Access to the occupier facilities at basement floor
- Access to the offices
- Access to the communal terrace

The following elements of the design were suggested by Camden Council Secured by Design officer and will be implemented in further design phases: Internal

- Access control to basement floor facilities (encrypted fob) recommended and to include for door to cycle store and showers/ lockers.
- Cycle store door to be PAS24 2016
- Preference for lifts to have destination control
- Access control to both stair cores from reception and office floors required (FOB access control)
- Where escaping through different demises is required by the fire strategy
  relevant doors should be either alarmed and visually controlled with cameras
  or be supplied with magnetic locks which release only in case of fire

#### External

- GF entrance from Wild Court requires access control
- Where achievable due to the building being Listed and within a conservation area, new external doors should always be security rated to a minimum of PAS24:2016 with a minimum of two magnetic locks positioned two thirds from the top and bottom of the frame and integral within the door unit.
- The use of 'Sold Secure' products within the cycle storage area itself is recommended to allow for three points of locking (both wheels and the frame are required to be secured).

Overall there are no major issues being created by this proposal and the officer cannot forsee it causing any major issues to the local area. As long as security is considered throughout the application and that crime prevention is followed once the building is in use then the risks associated with crime should be reduced.



# Sustainability





10.1 Sustainability

61

The sustainability targets are as follows:

#### **BREEAM Excellent**

The development is being subjected to a BREEAM assessment under the 2014 Non-Domestic Refurbishment & Fit-Out Full Assessment. Various workshop sessions and reviews have taken place with the project team with the purpose to identify the key elements that will be adopted and progressed going forward. The assessment has shown that a' Very Good' rating is achievable and a route to achieve 'Excellent' has been identified. The development target is to achieve a BREEAM rating of Excellent. The project team is committed to achieving this

The project is targeting the full available score for the reduction in consumption of water i.e.

 Wat 01 Water Consumption Wat 02 Water Monitoring Wat 03 Water Leak Detection

The existing building has been thermally modelled along with the proposed scheme and this shows that there is a predicted reduction in carbon emissions of circa 25% between the existing and proposed schemes. This has been achieved primarily by the following measures:

- The use of air source heat pumps in their variable refrigerant flow format.
- The installation of LED lighting.
- The provision of lighting controls to include presence detection and daylight dimming to the perimeter zones.
- Upgraded glazing thermal performance.

#### **WELL Gold**


The project is targeting Gold accreditation.

Cundall has carried out two preliminary Core and Shell WELL assessments for the proposed redevelopment of 65 Kingsway in London. They indicated that all the preconditions are achievable.

Considerations for early design stages:

The following key considerations are recommended:

- Air Quality
- Ventilation rates, CO2 sensors, air filtration:
- VOC levels in internal finishes, Asbestos/ Lead/ PCB surveys;
- Water testing against all contaminants suggested by WELL and space allocation for water filters if required
- Daylight fenestration and solar glare control, lighting performance
- Window sizes, workstations location, internal blinds, lighting levels;
- Nourishment
- Tea point facilities and wash hand basin/ sink sizes, provision of breakout spaces;
- Fitness
- Promote staircase design, cycling and showers/ changing facilities;
- Comfort
- Designing for inclusivity and disability, self-closing doors to toilets and cleaner's cupboard;
- Acoustic testing
- Exterior noise intrusion and glazing performance;
- Internal and mechanical equipment sound levels;
- Mind
- Biophilia-planting on roof and terraces and internal planting, ceiling heights.







# **Areas**

#### EXISTING

Floor		N	IIA	GIA		Gi	EA
		m²	ft²	m²	ft²	m²	ft²
Basement	Storage / Plant	78.9	849	586.6	6,314	628.0	6,760
Ground	B1	398.3	4,287	666.9	7,179	739.2	7,957
First	B1	644.7	6,940	976.1	10,507	1,079.0	11,614
Second	B1	817.0	8,794	983.6	10,587	1,078.0	11,604
Third	B1	809.0	8,708	978.5	10,533	1,078.0	11,604
Fourth	B1	820.2	8,829	973.9	10,483	1,078.0	11,604
Fifth	B1	818.3	8,808	978.1	10,528	1,078.0	11,604
Sixth	B1	706.0	7,599	933.5	10,048	991.0	10,667
Seventh	B1	555.5	5,979	804.0	8,654	856.4	9,218
Roof		0	0	0	0	0	0
Total		5,647.9	60,794	7,881.2	84,833	8,605.6	92,631
TOTAL B1		5,569.0	59,945	7,294.6	78,519	7,977.6	85,871

#### PROPOSED

Floor		N	IIA	G	IA	GEA	
		m²	ft²	m²	ft²	m²	ft²
Basement	Commuter Facilties / Plant	0.0	0	586.6	6,314	628.0	6,760
Ground	B1	250.5	2,696	672.8	7,242	739.2	7,957
First	B1	791.5	8,520	976.1	10,507	1,079.0	11,614
Second	B1	819.7	8,823	983.6	10,587	1,078.0	11,604
Third	B1	815.8	8,781	978.5	10,533	1,078.0	11,604
Fourth	B1	806.8	8,684	973.9	10,483	1,078.0	11,604
Fifth	B1	810.2	8,721	978.1	10,528	1,078.0	11,604
Sixth *	B1	742.0	7,987	933.2	10,045	984.3	10,595
Seventh *	B1	632.7	6,810	822.0	8,848	866.0	9,322
Roof	Terrace and core	0.0	0	40.8	439	51.4	553
Total		5,669.2	61,023	7,945.6	85,526	8,659.9	93,215

TOTAL B1	5,669.2	61,023	7,359.0	79,212	8,031.9	86,455
----------	---------	--------	---------	--------	---------	--------

#### PROPOSED B1 UPLIFT AGAINST EXISTING

FLOOR		NIA U	PLIFT	GIA U	PLIFT	GEA U	IPLIFT
		m²	ft²	m²	ft²	m²	ft²
Ground Floor	B1	-147.8	-1591	0.0	0	0.0	0
First	B1	146.8	1580	0.0	0	0.0	0
Second	B1	2.7	29	0.0	0	0.0	0
Third	B1	6.8	73	0.0	0	0.0	0
Fourth	B1	-13.4	-144	0.0	0	0.0	0
Fifth	B1	-8.1	-87	0.0	0	0.0	0
Sixth	B1	36.0	388	-0.3	-3	-6.7	-72
Seventh	B1	77.2	831	18.0	194	9.6	103
Roof	Terrace and core	0.0	0	40.8	439	51.4	553
TOTAL B1 UPLIFT		100.2	1078	58.5	630	54.3	584

NOTES:
- Areas are subject to design development and will be adjusted following Building Control, Section 20, Fire Stratey, M&E and Structural input as the scheme progresses

- Measurements based on Hollis Measured Survey 2019

- Based on single occupancy floors

## **Areas**

10.1 Area Summary

The areas within this page are based on single occupancy per floor of the

Measurements are based on survey information provided (Not Validated).

# **Appendices**