

Colours confirmed by Prime 11/3/19

Channing School

Ref - P1



Manuf. / Supplier - Light Distribution

Range - WPZ

Description - IP65 impact proof LED

Control Gear - HF integral

Light Source - Various to suit lux level requirements

Colours - NA

Dimensions - 1200mm and 1500mm



Colours confirmed by Prime 11/3/19

Channing School

Ref - P2



(Plant room external wall)

Manuf. / Supplier - Light Distribution

Range - WLE

Description - IP65 wallpack

Control Gear - HF integral

Light Source - Various

Colours - Black

Dimensions - 310mm x 260mm



Colours confirmed by Prime 11/3/19

Channing School Proposal TBC by architect

Ref - EXT1



NB Silver grey finish required

Manuf. / Supplier - Light Distribution

Range - Greeny M

Description - Recessed wall mounted asymetric wall light

Control Gear - HF integral

Light Source - 200lm

Colours - Silver Grey

Dimensions - 202mm x 73mm



Colours confirmed by Prime 11/3/19

Channing School Proposal TBC by architect

Ref - EXT2



Manuf. / Supplier - Light Distribution

Range - BOL

Description - Aluminium IP65 bollard

Control Gear - HF integral

Light Source - 15W

Colours - Black

Dimensions - 1057mm x 158mm



Colours confirmed by Prime 11/3/19

Channing School

Ref - EXT3



Manuf. / Supplier - Light Distribution

Range - Nova or Cora (depending on size)

Description - IP65 asymetric flood light

Control Gear - HF integral

Light Source - Various to suit

Colours - Silver grey

Dimensions - 530mm x 250mm (large) 320mm x 190mm (small)