

Location Plan

Zaun Duo 8 fence panels installed in front of brick wall. Allow for an additional horizontal beam to close the gap between the fence and the wall.

Raised timber planter behind retaining wall

New brick retaining wall to Engineer's specification

PartM compliant steel double handrail

Marshalls corduroy hazard warning paving. Colour: TBC

Light buff coloured tarmac surface by Ulticolour or similar approved.

New macadam ball court surfacing with non-slip heavy duty acrylic coating and acrylic line markings, installed to manufacturer's specification

Marshalls Perfecta concrete step treads and risers with in-built contrasting visibility strips (colour TBC); cut to size; installed on 10mm mortar bed

A395 Reinforcing mesh, covered by not less than 50mm concrete

MOT Type 1 leveled & revised for appropriate camber

Concrete foundations Standard to BS 5328-1
Mix: designated mix not less than C20 to a minimum thickness of 150mm
A395 Reinforcing mesh, covered by not less than 50mm concrete
















Light buff coloured tarmac surface by Ulticolour or similar approved.

50 mm AluExcell edge between path and the ball court surface

Marshalls corduroy hazard warning paving. Colour: TBC

Det. 1. Typical step detail 1:25


KEY

-  Existing tree retained and protected according to the BS5837:2012.
-  New tree in the raised planter. 300mm topsoil to BS 3882:2015 above 500mm new approved free draining sandy subsoil to BS 8601:2013.
-  New shrub and perennial planting in raised planters. Topsoil to BS 3882:2015. Depth min. 600 mm.
-  New surface to MUGA: new macadam ball court surfacing with non-slip heavy duty acrylic coating and acrylic line markings.
-  Light buff coloured tarmac surface to the ramp by Ulticolour or similar approved.
-  Steps: Marshalls Perfecta chamfered natural concrete treads and risers 400x400x50mm, cut to size, with inserted contrasting visibility strips.
-  Handrail to steps and ramp: galvanised and powder coated steel to RAL9005 (jet black).
-  Marshalls corduroy hazard warning paving slabs to steps and ramp. Colour: Dark Grey (TBC)
-  New 1.2m h flat top metal railings by Alpharail or similar. Galvanised and powder coated to RAL9005 (jet black).
-  New 3m h Zaun Duo8 Sports Fencing to east, south and west elevations to the ball courts. Galvanised and powder coated Dark Blue.
-  New metal gates, width and height as shown on the drawing. Galvanised and powder coated to match fence panels.
-  Brick retaining walls to structural engineer's details.
-  New metal edging to resin bound gravel path. Flexible 50 mm h Flexible AluExcell by Kinley or similar approved.
-  Slot drain by ACO or similar approved. Indicative location TBC; to drainage engineer's details
-  Outdoor gym equipment by The Great Outdoor Gym Company

Existing levels +24.8 Proposed levels +4.27

Rev	Description	Drawn	Check	Appr	Date

Groundwork London
12 Baron Street
London N1 9LL
Tel: 020 7239 1280
Fax: 020 7278 1515
www.groundwork.org.uk/London



Project: **HS2 Improvements**

Client: **LB Camden**

Drawing Title
DETAILS SHEET 2

Drawn: MF Check: LC Appr: AP Date: 05/12/2019 Scale at A3: As shown

Status: **PLANNING**

Drawing No: **CA030_P_01AHM_009** Revision: -