



Dual Inverter
COMPRESSOR

Deluxe



High performance R32 wall-mounted unit




R32 refrigerant has a global Warming Potential (GWP) of only 675, and has been shown to have a remarkably reduced environmental impact compared to other refrigerants such as R410A. Its high efficiency is proven as just a smaller amount of R32 is required (15% less gas charge compared to R410A) with better heating performance at lower ambient temperatures whilst also using less refrigerant per kilowatt of capacity delivered.

R32 high refrigerant compression rate contributes to higher system capacity than products using R410A.

Smart diagnostics and embedded wi fi

Whenever, wherever and no matter how many air conditioners you have, you can easily access and control your air conditioners by using smart internet devices such as Android or iOS based mobile phones. Smart Diagnosis allows users to conveniently check set up, installation, troubleshooting and other information directly from a smartphone.

By using "LG Smart ThinQ" App and clicking "Start Smart Diagnosis", monitor and check diagnosis results conveniently via Wi-Fi.



Comfort Air Feature

This option conveniently sets the indoor unit louvers to a pre-set position so that outflowing air is directed away from the room's occupants.

Easy to Open

Easy horizontal sliding filter when cleaning your air conditioners in 1 step.

Easy to Clean

The filter is designed for easy handling and quick cleaning, which lengthens its lifespan.

1 Step
Detachable
Grille



Easy
Cleaning
Filter



Click the button twice :
the vane goes to the lowest
position for indirect airflow.
(Optimised airflow for heating)



Click the button once :
the vane goes to the highest
position for indirect airflow.
(Optimised airflow for cooling)

DELUXE



LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification: www.eurovent-certification.com



Embedded Wi-Fi



Smart Diagnosis



Active Energy Control



Energy Display



Dual Protection Filter



Auto Cleaning



Plasmaster Ionizer^{PLUS}



Jet Cool



2 Way Swing



Fast Heating



Gold Fin™



Comfort Air



Low Noise 19dB (9k, 12k)



Silence Mode



Quick & Easy Installation

The LG Deluxe wall mounted unit, offers a range of benefits including the inclusion of a **Plasmaster ionizer filter** to protect from odours and harmful substances. It sterilises and deodorises, reducing harmful microscopic particles, utilising over 3 million ions by infusing the air passing through the air conditioner.


They feature **Auto Cleaning** – cleaning the filter with regular airflow and removing harmful particles, preventing bacteria, mould and odours that can otherwise accumulate in an indoor unit. The **larger Skew fan**, incorporated enables the cool air flow to reach all extremities of a room, the Standard Plus **4-way swing louvres** keep the space cool and comfortable. The **Fast Cooling** feature provides an optimised high-speed airflow which can cool rooms faster while still delivering air evenly in every direction. The **'Jet Cool'** mode reduces temperatures of outflowing air to just 18 degrees C for 30 minutes with just one click. By reducing the second vortex, which decreases airflow from the air outlet, and enlarging the fan size, the amount of airflow is increased by 13 CMM.

The LG wall mounted units operate at 19dB low noise level – quieter than a library - yet still providing healthy soft air flow in the property.



The deluxe LG wall mount unit features a **Plasmaster⁺ ionizer plus** filter for healthier indoor air quality #IAQ.

How it works



Technical Information

- A system is one indoor unit with one connecting outdoor unit.

UNIT				9K	12K	18K
INDOOR				DC09RQ.NSJ	DC12RQ.NSJ	DC18RQ.NSK
Capacity	Cooling	Min/Rated/Max	kW	0.89/2.50/3.70	0.89/3.50/4.04	0.90/5.00/5.50
	Heating +7°C	Min/Rated/Max	kW	0.89/3.20/5.00	0.89/4.00/6.00	0.90/5.80/6.40
	Heating -7°C	Rated	kW	3.20	3.50	4.20
Power Input	Cooling	Rated	W	572	933	1562
	Heating +7°C	Rated	W	711	976	1611
EER			W/W	4.37	3.75	3.20
S.E.E.R. (Seasonal Energy Efficiency Ratio)				7.9	7.6	7.0
Energy Label	Cooling	(A++ to E Scale)		A++	A++	A++
	Heating	(A++ to E Scale)		A++	A++	A+
Annual Energy Consumption	Cooling		kWh	111	161	250
	Heating		kWh	852	883	1270
Sound Pressure	Cooling	Sleep	dB(A)	19	19	31
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Dimension			mm	837*308*189	837*308*189	998*345*210
Net Weight			kg	9.1	9.1	11.9
OUTDOOR				DC09RQ.UL2	DC12RQ.UL2	DC18RQ.UL2
Sound Pressure	Cooling	High	dB(A)	49	49	53
	Heating	High	dB(A)	51	51	55
Net Weight			kg	34.1	34.1	34.4
Dimension			mm	770*545*288	770*545*288	770*545*288

The product contains Fluorinated greenhouse gases (R32). R32 is under the category A2 mildly flammable refrigerants and as such are NOT SUITABLE for retrofit applications. SEER, the higher the number, the more efficiently a product will produce cooling/heating, while conserving energy.