

Construction of Bespoke Paving Slab for the Camden Walk of Fame

Aggregates included in concrete mix:

Novostones Arduin Ground (Inner circular area)

The concrete mix includes black magmatic finely grained stone from Linz am Rhein and silicon quartz.

Novostones Kingstone Ground (Outer area)

The concrete mix includes limestone from the Chiemsee area, white prismatic tectosilicate from the Eiffel mountain range, white dolomite from Andalusia, rhomboid crystals and black magmatic finely grained stone from Linz am Rhein.

Target output performance measurements

Subject	Description method	Target
Weather resistance	frost, thaw, salt resistant	$\leq 1.0 \text{ kg/m}^2$ average $\leq 1.5 \text{ kg/m}^2$ ind.
Wear resistance	wide wheel resistant	$\leq 23 \text{ mm}$
Dimension variation diagonals	measure	2 mm
Dimension variation length, width, thickness	measure	All pavers 2, 2, 2 mm
Slip/Skid resistance (minimum USRV value)	pendulum	Above 59 USRV slip potential very low

If required final tests can be completed after the stone is manufactured.



Maritime House, Basin Road North, Hove, East Sussex BN41 1WR
Tel: 01273 704970 E-mail: sales@blyko.co.uk www.blyko.co.uk

Registered Office: A division of Euromin Ltd, Pavilion View, 19 New Road, Brighton, East Sussex, BN1 1EY
Place of Registration: Incorporated in England, Registration Number 2243241



Maritime House, Basin Road North, Hove, East Sussex BN41 1WR
Tel: 01273 704970 E-mail: sales@blyko.co.uk www.blyko.co.uk