

All levels and dimensions to be checked on site prior to construction / fabrication; report discrepancies immediately. Do not scale dimensions from this drawings. This drawing is copyright protected.

REVISION			
A	9.3.20.	REDRAWN	DA
B	2.4.20.	Roof Edge protection illustrated.	DA



Internal Wall Infill Construction:
[1 hour fire rated]

- Remove exisg. windows.

Infill assembly:

- Zinc, layers 12.5mm BG fireline board
- Internal lining either side of,
- 70mm metal studs @ 600mm centres
- secured to the prepared exisg. masonry structural opening.
- Seal the perimeter edges of the plasterboard / masonry abutment both sides with intumescent mastic to maintain a 1 hour fire rating.

Fire Door perimeter partitioning:

- as per infill assembly above between new fire door and existing masonry opening.
- refer to Threesixty Architecture drawing 18170GA_32_002.

TENDER

SCALE	DATE	DRAWN	CHECKED
1:50	Jan'20	DA	

PROJECT
SHURGARD SELF STORAGE
CAMDEN, LONDON
N7 9LG

DRAWING
Section AA
As Proposed

Threesixty
Architecture

10 MONTROSE STREET
GLASGOW
G1 1RE

0141 229 7575
www.360architecture.com

DRAWING NO.

18170GA_21_001B