










**Appendix B** - Schedule of proposed light fittings

**Appendix B - Schedule of proposed light fittings**

Ref	Description	Manufacturer	Picture	Location
ST	Cygnus ST IP65 LED and conventional source post top lantern with conical die cast aluminium body and clear UV stabilised polycarbonate diffuser. With symmetrical distribution having zero upward light.	Whitecroft Cygnus ST	EXTERNAL LIGHTING 	Exterior
UE	CENTURION IP65 – Surface mounted IP65 LED perimeter security luminaire with covered top diffuser to limit and control upward light. Black, 1x36W LED 4000k, 3hr maintenance	Whitecroft Centurion IP65	SECURITY PERIMETER 	Exterior
VE	KOLO IP65 HOOD – Surface mounted IP65 LED circular luminaire with covered top diffuser to limit and control upward light. Black, 1x14W LED 4000k, 3hr maintenance	Whitecroft Kolo Hood IP65	EXTERNAL ENTRANCES 	Exterior
W	MARINE SD shallow depth IP68 In Ground LED uplighter with die cast aluminium housing, 316 marine grade stainless steel bezel and adjustable wide beam distribution.  Clear thermal shock resistant tempered glass. Supplied with integral driver. Stainless steel, 1x20W, 4000k	Whitecroft Marine SD	EXTERNAL LANDSCAPE 	Exterior

<p>X</p>	<p>Starline Flex is a linear LED tape with self-adhesive backing. 3000K, IP67 with body, 390lm/m, CRI &gt; 85, Efficiency 78 lm/cw.</p>	<p>Whitecroft Starline Flex IP67</p>	<p>EXTERNAL BENCHES</p> 	<p>Exterior</p>
<p>Y</p>	<p>MARINE LF IP67 In Ground LED fixed uplighter with die cast housing, 316 grade stainless steel bezel and asymmetric distribution.  Clear thermal shock resistant tempered glass. White LED 464 lumens 3.8W Requires dedicated driver. Stainless Steel, 1x3W, 4000k</p>	<p>Whitecroft Marine LF IP67</p>	<p>EXTERNAL LANDSCAPE</p> 	<p>Exterior</p>
<p>Z</p>	<p>BROADWALK QUAD IP54 wall recessed LED luminaire for low level applications. With nylon body, die cast aluminium frame and plexiglass diffuser with grille.</p>	<p>Whitecroft Broadwalk Quad IP54</p>	<p>EXTERNAL LIGHTING</p> 	<p>Exterior</p>
<p>LL</p>	<p>LED LINE IP67 recessed LED luminaire for low level applications. With die cast aluminium housing and diffused optics.</p>	<p>Whitecroft LED LINE IP67</p>	<p>EXTERNAL LIGHTING</p> 	<p>Exterior</p>
<p>Q</p>	<p>ECLIPSE IP54 rated Wall light c/w GU10 led lamp, aluminium body, RAL 9005 black finish</p>	<p>ORLIGHT ECLIPSE IP54</p>	<p>BALCONY LIGHTING</p> 	<p>Balcony</p>