



- DOUBLE LEAF SWING DOOR OPEN OUTWARD.

- THE DOOR CAN ALWAYS BE OPENED FROM THE INSIDE IN THE DIRECTION OF ESCAPE. THE DOOR CAN ONLY BE OPENED FROM OUTSIDE USING THE KEY, WHEREBY THE LATCH AND BOLT ARE PULLED BACK.

PLEASE NOTE:
OUR WINDOWS, DOORS AND CURTAIN WALL, RAINSCREEN
CLADDING SYSTEMS INCLUDING THEIR ANCILLARY ITEMS
COMPLY TO THE APPROPRIATE CURRENT BSEN STANDARDS
HOWEVER THE PRODUCTS AND SYSTEMS WE USE IN SOME
CASES WILL INCORPORATE SOME LIMITED COMBUSTIBLE
MATERIALS PERMISSIBLE IN CURRENT APPROVED H M
GOVERNMENT DOCUMENT B : 2013 AND GUIDANCE NOTES
PUBLISHED BY THE CWCT REFERENCE TN98.

IT WILL BE DEEMED UNLESS AGREED IN WRITING THAT THE RESPONSIBILITY REST WITH THE CLIENT, ARCHITECTS, CDM DESIGNERS, FACADE CONSULTANTS OR THE FIRE CONSULTANTS TO MAKE SURE OUR PRODUCTS AND SYSTEMS COMPLY WITH THE EMPLOYERS REQUIREMENTS AND/OR LOCAL BUILDING CONTROL APPROVALS. THE SAME CAN BE SAID FOR ANY FIRE RATED GLAZING INTERNALLY OR EXTERNALLY INCLUDING ANY FIRE RATED DOORS IN ANY ROUTE OF ESCAPE

DRAWINGS, SPECIFICATIONS AND CALCULATIONS ARE SUBMITTED BY SUKL IN ACCORDANCE WITH RELEVANT CLAUSES OF THE SUBCONTRACT FOR COMMENT AND OR APPROVAL AS REQUIRED BY THE SUBCONTRACT AND DEFINED BY THE MAIN CONTRACT. ANY COMMENT OR APPROVAL OF THE DRAWINGS RETURNED TO SUKL DOES NOT RELIEVE SUKL OF HIS RESPONSIBILITIES UNDER THE SUBCONTRACT.

SPECIFICATION

DOOR SYSTEM

DOOR SYSTEM - ALUPROF MB-70 CASEMENT STANDARD ALUMINIUM DOORS
SYSTEM IN ACCORDANCE WITH ALUPROF TEST DATA & SPECIFICATIONS TO
CURRENT BS & EN STANDARDS.

IRONMONGERY

- 19242311 ALUPROF - Linco Rosette Stainless Steel
- 80004016 Cylinder insert 3560 mm
- 80004017 WALKA - 3/4" round rod 6682 - function E
- 80004023 WALKA - Round rod 2400 mm
- 80004024 WALKA - Stripper with guide
- 80004025 WALKA - Top rod
- 80009048 FUHR - Carry bar 1250 mm
- 80009051 WALKA - Part 24x24x25 mm
- 80009053 WALKA - Panic keep P24x3 mm
- 80009054 WALKA - Rod - last part top
- 80009055 WALKA - Panic door P24x3 - rod last part
- 80009056 WALKA - Floor keep
- 80009057 WALKA - Bottom rod
- 80009059 WALKA - Part 2x3 mm
- 80009060 ECO SCHULTE - Rosette Stainless Steel
- 80009063 ECO SCHULTE - Touch bar 1250 mm Stainless Steel
- 80009094 Run-up wedge
- 80105468 WALKA - 3-leaf hinge Wk, spacing 92 mm typical 10716
- 80105491 WALKA - Mounting set for 3-leaf hinge: 47 mm drill
- 80105492 Six-leaf hinge 7024 mm
- 80105493 Insert with a rod guide
- 80722210 Bolt Mx25 mm
- 80722211 DORMA TS 93 90 CONTUR LOCK CLOSER
- 80722212 SLIDE RAILS FOR DORMA TS 93 CLOSER
- 80722213 ECO EPN 2000 II PANIC BAR

OPERATION -

- SIDE HUNG OPEN OUT
- MECHANICAL OPENING

GLAZING -

GLASS SPEC. DG 02: - 35mm THICK DOUBLE GLAZED UNIT COMPRISING

OUTER:	4mm PLAINCLAR CLEAR HEAT STRENGTHENED GLASS 1.52mm PVB INTERLAYER 4mm PLAINCLAR CLEAR HEAT STRENGTHENED GLASS WITH COOL LITE SKN 165 II HIGH PERFORMANCE TO FACE 4.
CAVITY:	16mm BLACK TGI SPACER, 90% ARGON FILLED DUAL POLYSULPHIDE EDGE SEAL CONSTRUCTION .
INNER :	4mm PLAINCLAR CLEAR HEAT STRENGTHENED GLASS 1.52mm PVB INTERLAYER 4mm PLAINCLAR CLEAR HEAT STRENGTHENED GLASS

WEIGHT = 43 Kg/m² U-VALUE = 1.0W/m²K LT-VALUE = 58%
G-VALUE = 0,32

FINISHES -

- PROFILES

EXTERNAL - ALL VISIBLE SURFACES TO BE FINISHED TO QUALICOAT CLASS 2, PPC RAL 7016 MATT (30% GLOSS) 60 MICRONS INTERPON D 2525 TO CURRENT BS & EN STANDARDS

INTERNAL - ALL VISIBLE SURFACES TO BE FINISHED TO QUALICOAT CLASS 2,
PPC RAL 7016 MATT (30% GLOSS) 60 MICRONS INTERPON D 2525 TO CURRENT
BS & EN STANDARDS

- GASKETS - BLACK
- HANDLE - FINISH STAINLESS STEEL (ASH123.38.12200.SS F1.120)

Lendlease TO REMOVE AND REINSTATE ALL INTERNAL AND EXTERNAL FINISHES AND FIXTURES TO ALLOW STRUCTURA TO CARRY OUT WORKS TO THE CURTAIN WALLING TO AGREED DETAILS. Lendlease TO MAKE GOOD AS NECESSARY, IF REQUIRED. STRUCTURAL OPENINGS AND INTERNAL FINISHES TO THE EMPLOYER'S REQUIREMENTS.


ANY NEW SUPPORTING STRUCTURES AND STEEL WORK OR ANY BUILDERS WORK OUTSIDE OF STRUCTURA'S REMIT IS TO BE CARRIED OUT BY Lendlease.

PROTECTION AND FINAL BUILDERS CLEAN IS TO BE CARRIED OUT BY Lendlease.

UNLESS ITEMS/ELEMENTS ARE NOTED BY SUK, THEY WILL BE

BY OTHERS.

-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
REV	DATE	REVISION	INT



Structura UK Ltd
Unit 1, Oakcroft road,
Chessington, Surrey. KT9 1RH
Tel. 020 8397 4361
Fax. 020 8391 5805
E Mail info@structura.co.uk

Location

Location CAMDEN TOWN HALL
LONDON WC1H 9JE

Title TONBRIDGE WALK ELEVATION
MANUAL DOOR DG-EX-20 VERTICAL SECTION DETAIL 01.00

Client LENDLEASE
20 TRITON ST. REGENT'S PLACE LONDON NW1 3BA

Drwn MC	Date 31.07.2020	Chckd AF	Scale NTS@A
---------	-----------------	----------	-------------

CTH-SUK-G0-DR-25-X-022

24067-D-120

Reason for Issue
APPROVAL