



MK

Dimensions in mm



Mounting feet

To fix Axial/VAR cased fans on ceiling, wall or floor. Made from galvanised sheet steel or hot dipped galvanised steel. Fixing holes fit casing flanges. Set includes a pair of feet, nuts and bolts.


Note:

If motors of high weight are installed, an extension duct (VR...) is recommended to move the centre of gravity within the mounting feet. Mount feet on the outer flange.

Type	Ref. No.	A	B	C	Weight in kg
MK 200-225	1446	310	208/220	20	1.5
MK 250-280	1447	340	227/245	20	1.7
MK 315-355	1448	380	281/300	25	2.2
MK 400-450	1449	360	311/335	25	2.6
MK 500-560	1450	570	383/415	25	5.3
MK 630	1333	600	465	30	8.5
MK 710	1372	670	515	35	10.5
MK 800	1373	680	565	35	15.5
MK 900	1374	760	625	35	18.0
MK 1000	1375	840	690	35	19.5

SDD-U

Dimensions in mm



Anti vibration pads

The rubber mounting pads SDD-U are suitable as a base for installation of fans on flat, horizontal surfaces. They reduce the direct noise and vibration transmission to the building structure.

One set consists of 4 elements, which are positioned individually under the corners of the fan unit. Maximum compression: 40 kg/pad = total 160 kg.

SDD-U Ref. No. 5627

SDD

Dimensions in mm


SDD 1-3




SDD 1F, 4-10





SDD 1



SDD 2



SDD 3



SDZ

Dimensions in mm


SDZ 1-3




SDZ 1F, 4-9





SDZ 1



SDZ 2



SDZ 3



Anti vibration mounts for compression

To reduce noise and vibration transmission of fans installed on horizontal surfaces. Simple installation in combination with feet MK (accessory). Select size according to fan weight (see table).

Rubber elements are suitable for small to middle weights and ambients up to +60 °C. Spring elements are suitable for higher temperatures above +60 °C (e.g. smoke extraction).

Anti vibration mounts for suspension

To reduce noise and vibration transmission of fans installed hanging from ceilings. Specification as model SDD.

Important note for installation!

Make sure that fan system is well balanced (centre of gravity of heavy motor may cause uneven loading of mounts).

Type	Ref. No.	Maximum fan weight in kg	H Height in mm	Spring element	Contents 1 set = 4 pieces
SDD 1	1452	80	*		
SDD 1F	1942	70	112 - 82	•	
SDD 2	1453	180	*		
SDD 3	1367	750	*		
SDD 4	1944	130	112 - 86	•	
SDD 5	1924	210	112 - 86	•	
SDD 6	1926	400	112 - 80	•	
SDD 7	1928	580	112 - 82	•	
SDD 8	1930	900	112 - 82	•	
SDD 9	1934	1300	112 - 85	•	
SDD 10	1951	1800	112 - 88	•	

* shown in dimensional drawing

Type	Ref. No.	Maximum fan weight in kg	H Height in mm	Spring element	Contents 1 set = 4 pieces
SDZ 1	1454	60	*		
SDZ 1F	1943	70	190 - 220	•	
SDZ 2	1455	160	*		
SDZ 3	1366	300	*		
SDZ 4	1945	130	190 - 216	•	
SDZ 5	1925	210	190 - 216	•	
SDZ 6	1927	400	190 - 221	•	
SDZ 7	1929	580	190 - 220	•	
SDZ 8	1931	900	190 - 220	•	
SDZ 9	1935	1300	190 - 217	•	

* shown in dimensional drawing