

Hard Landscape Legend

Proposed site boundary

Proposed Willow play structures

Existing flag paving to be retained. New reinforced grey concrete block flag paving 450x600x63mm to be laid alongside existing paving as required to complete footpath. To be laid butt jointed with concrete base at 150mm staggered bond as supplied by Marshalls

Proposed Keyblok paving 200x100x60mm, colour Charcoal, laid flexible butt jointed, as supplied by Marshalls, or similar

Proposed exposed aggregate concrete surface at 100mm depth laid to manufacture specification as supplied by Pepcon Itd

Proposed asphalt surfacing with Bituchem NatraTex surface course in 'Cotswold' with clear binder and decorative aggregate. Available from NatraTex or similar. Tel: 01594 826768, www.natratex.co.uk

Existing asphalt surface

Proposed pre-cast bespoke concrete planters, 1.2m high. Free draining into ground to avoid need for additional drainage

Proposed bench locations, to be FSC 'Inline Seat' in hardwood and steelwith black powder coated finish to metal framework as supplied by Woodscape or similar Proposed 1.25m high Sentry Residential metal railings and gate as supplied by Jacksons or similar

Proposed 1.25m high Sentry Residential metal railings and gate as supplied by Jacksons or similar

Proposed visitor CaMden cycle stands ,galvanised as supplied by Broxap or similar

External finish levels

Proposed surface edging to be level laid with a single row of granite conservation aggregate setts in charcoal, to be 100 x 100mm as supplied from Marshalls or similar

Proposed locations for exterior lighting, to be Kirium Mini as supplied by DW Windsor or similar. To be coordinated with an M & E consultant

Proposed locations for exterior lighting, to be Aventis eyelid as supplied by DW Windsor or similar. To be coordinated with an M & E consultant

Soft Landscape Legend

Existing trees to be retained and protected during construction

Proposed tree planting within soft landscape. See detail

Proposed specimen shrub planting

Proposed *Buxus* (box) hedge planting to be planted in a single row at 300mm centres and maintained at 500mm height

Proposed native hedge planting to be planted in a double staggered row 300mm apart and at 500mm centres in each row. To be maintained at 1m height

Proposed mixed planting to receive 75mm bark mulch after planting operations

Proposed drive to be 38mm Pre-Grown Golpla Grass Paver and 150mmCellweb to be laid to suppliers specification as supplied by geosyn.co.uk

Proposed grass areas to receive good quality amenity grass turves laid in line with good horticultural practices

			\mathbf{T}
G	19.09.17	Client comments	СВ
F	11.08.17	Client comments	СВ
E	22.11.16	Client comments	JS
D	07.07.16	Amend existing tree position	JNT
С	09.05.16	Amend planter details	JS
В	08.04.16	Client comments	JS
A	22.02.16	Update for VE	JS
Rev	Date	Details	Drawn



Rodbourne Rail Business Centre, Grange Lane, Malmesbury, SN16 OES Tel: 01666 825646

Courtyard House, Mill Lane, Godalming, GU7 1EY Tel: 01483 425714

Suite 6, Crescent House, Yonge Close, Eastleigh, SO50 9SX Tel: 02382 026300

> 9 Brownlow Road, Cambridge, CB4 3NG Tel: 07825 868654

> > email: mail@acdenv.co.uk www.acdenvironmental.co.uk

Lovell Partnerships Limited

scheme:	Regent's Park Estates
	Rydell Water (Former One
	Stop)
client:	Lovell Partnerships Ltd
drawing:	Hard Landscape Proposals
date:	September 2015
scale:	1:100@A1
drawing no:	LOV20033-12G
drawn:	JNT checked: JS
	Environmental Ltd. All rights described in ovright. Designs and Patents Act 1988 have

Chapter IV of the Copyright, Designs and Patents Act 1988 have been generally asserted: 2011. Copyright of this plan remains with ACD until all fees have been paid in full.