

В

С

D

F

Do not scale

	500										
-	30										
<u>\</u>											
<b>,</b>											
						Z					

Μ

Ν

0

I J K L

0

 $\begin{pmatrix} 4 \end{pmatrix}$ 

40021

Elevation

Etch Pattern - Offset pattern on 2 plys of glass

1:2

┝┍╌┓

20 10

2

5 laminates of 12 mm heat strengthened low iron glass, laminated with sentry glass interlayer. Inner surface of 2 plys surfaced etched with pattern —

Stainless steel cap mechanically fixed top and bottom and bonded with structral silicone Cable channel -


Fin is to be edge lit from either side with 2 LED strips. The light source is to be within an extrusion, and the extrusion bonded to the edge of the glass, such that the light from the LED goes only into the glass edge it is illuminating. -

Edge detail should be considered so that direct view of the LED is limited and that colour mixing of the RGB LED is not visible.

Offset etch pattern


Section 7 Horizontal section through Edge detail 1:2

G









		+					 	1290	)			
	3410											
	300			tch ran						Et	tche	• ed
FFL +28.000 m	250											
A		а , , , , , , , , , , , , , , , , , , ,	A 		₹ 	·			· · · · · · · · · · · · · · · · · · ·	1 J- . 2 		