

Installation Type	Unit of Measure	Capacity/Flow rate (1)	Use Factor (2)	Fixed use (litres/person/day) (3)	Litres/person/day = [(1)x(2)] + (3) (4)
WC (single flush)	Flush Volume (litres)		4.42	0.00	0
WC (dual flush)	Full flush Volume (litres)	5.8	1.46	0.00	8.47
	Part flush Volume (litres)	3	2.96	0.00	8.88
WC (multiple fittings)	Average effective flushing Volume (litres)		4.42	0.00	0
Taps (excluding kitchen/utility room taps)	Flow rate (litres/min)	5.10	1.58	1.58	9.64
Bath (where shower also present)	Capacity to overflow(litres)	139.00	0.11	0.00	15.29
Shower (where bath also present)	Flow Rate(litres / minute)	8.00	4.37	0.00	34.96
Bath Only	Capacity to overflow(litres)		0.50	0.00	0
Shower Only	Flow Rate (litres/minute)		5.60	0.00	0
Kitchen/Utility room sink taps	Flow rate (litres/minute)	8.85	0.44	10.36	14.25
Washing Machine	(Litres/kg dry load)	6.42	2.1	0.00	13.48
Dishwasher	(Litres/place setting)	0.76	3.6	0.00	2.74
Waste disposal unit	(Litres/use)	☐ Present	3.08	0.00	0
Water Softener	(Litres/person/day)		1.00	0.00	0
	(5)	Total Calculated use (litres/person/day) =SUM(column 4)			107.71
	(6)	Contribution from greywater (litres/person/day)			0
	(7)	Contribution from rainwater (litres/person/day)			0
	(8)	Normalisation factor			0.91
	(9)	Total internal water consumption = [(5)-(6)-(7)]x(8) (litres/person/day)			98.02
	(10)	External water use			5.0
	(11)	Total water consumption (Building Regulation 17.K) =(9)+(10)(litres/person/day)			103.0

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

WC Type	Effective Flushing volume* (litres) (a)		Quantity (No.) (b)	Total per Fitting Type = (a)x(b) (c)
Multiple Fittings?	☐			
Dual Flush?	☒			
	Full Flushing volume x 0.33	Part Flushing volume x 0.67	(a)	
1	5.8	3	3.924	1
Total (Sum of all Quantities) (d)			1	
Total (Sum of all totals per fitting type) (e)				3.92
Average effective flushing volume (litres)=(e)/(d)				3.92
Calculate				

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Bath Fitting Type	Capacity to overflow(litres) (a)	Quantity (No.) (b)	Total per Fitting Type =(a)x(b) (c)
Are there any showers present?	☒		
1	139	1	139.00
2			
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			139.00
Average capacity to overflow(litres) = [(e)/(d)]			139.00
Maximum Capacity to overflow (litres) (f)			139.00
Weighted Average capacity to overflow(litres) = [(f)x0.7]			97.30
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Tap Fitting Type	Flow rate (litres/min) (a)	Quantity (No.) (b)	Total per Fitting Type =(a)x(b) (c)
1	5.1	1	5.10
2			
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			5.10
Average flow rate (litres/min) = [(e)/(d)]			5.10
Maximum flow rate (litres/min) (f)			5.10
Weighted Average flow rate (litres/min) = [(f)x0.7]			3.57
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Type of Dishwasher	Litres per place setting (a)	Quantity (No.) (b)	Total per Fitting Type =(a)x(b) (c)
1	0.76	1	0.76
2			
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			0.76
Average litres per place setting = [(e)/(d)]			0.76
Maximum litres per place setting (f)			0.76
Weighted Average litres per place setting = [(f)x0.7]			0.53
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Tap Fitting Type	Flow rate (litres/min) (a)	Quantity (No.) (b)	Total per Fitting Type = (a)x(b) (c)
1	8.85	1	8.85
2			
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			8.85
Average flow rate (litres/min) = [(e)/(d)]			8.85
Maximum flow rate (litres/min) (f)			8.85
Weighted Average flow rate (litres/min) = [(f)x0.7]			6.20
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Shower fitting Type	Flow rate (litres/min) (a)	Quantity (No.) (b)	Total per Fitting Type =(a)x(b) (c)
Are there any Baths Present?	☒		
1	8	1	8.00
2			12.00
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			8.00
Average flow rate (litres/min) = [(e)/(d)]			8.00
Maximum flow rate (litres/min) (f)			8.00
Weighted Average flow rate (litres/min) = [(f)x0.7]			5.60
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)

Type of washing machine	Litres per kilogram of dry load (a)	Quantity (No.) (b)	Total per Fitting Type = (a)x(b) (c)
1	6.42	1	6.42
2			
3			
4			
5			
6			
Total (Sum of all Quantities) (d)		1	
Total (Sum of all totals per fitting type) (e)			6.42
Average litres per kilogram of dry load = [(e)/(d)]			6.42
Maximum litres per kilogram of dry load (f)			6.42
Weighted Average litres per kilogram of dry load = [(f)x0.7]			4.49
Calculate			

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (dual flush)	Gerbrit 109.051.00.1	17.35
Taps	Crosswater Mike Pro monobloc	9.64
Baths (shower(s) present)	Ideal Standard Tesi Watersaving Single Ended Bath - T000901	15.29
Showers (bath(s) present)	Idealrain M1 Shower Kit	34.96
Kitchen Taps	TAP3562 Lamona Garda S	14.25
Washing Machines	AEG L7WE7631B1	13.48
Dishwasher	AEG FSB42607Z	2.74



©WRC plc 2021

[Terms and Conditions](#)
[System Requirements](#)