

GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS ON (MAINTAINED).

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE

EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

THE CEILING GRID LAYOUT IS INDICATIVE ONLY AND LIGHTING INSTALLATION SHOULD BE CO-ORDINATED FULLY ON SITE PRIOR TO INSTALLATION.

THE ELECTRICAL CONTRACTOR SHALL PROCURE, SUPPLY, INSTALL, TEST, COMMISSION AND SET TO WORK A COMPLETE, FULLY OPERATIONAL LIGHTING AND LIGHTING CONTROL

ALL LIGHTING SHALL HAVE CLEARANCE FROM ANY INSULATION AS HIGHLIGHTED WITHIN THE MANUFACTURES HAND BOOK.

THE LUMINARE HEAT DISSIPATING AREAS SHALL NOT HAVE THE AIR

ALL REFLECTORS, COVERS OR VISUAL AREAS SHALL BE CLEAN AND FREE FROM DIRT PRIOR TO LIGHTING LEVELS COMMISSIONED.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR ALL LUMINAIRES, ACCESSORIES, PLUG-INS, MOUNTING KITS AND POWER SUPPLIES WERE NECESSARY COMPLYING TO CURRENT BUILDING REGULATIONS, SO AS TO (Ra) LESS THAN 60. ENSURE A COMPLETE AND OPERATIONAL INSTALLATION.

LOCATION OF ALL SWITCHING TO BE IN ACCORDANCE WITH BS 8300 AND BUILDING REGULATIONS APPROVED DOCUMENT M.

THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE TESTING AND COMMISSIONING OF THE EMERGENCY LIGHTING INSTALLATION IN ACCORDANCE WITH REQUIREMENTS OF BS 5266 -CODE OF PRACTICE FOR EMERGENCY LIGHTING AND SHALL PROVIDE

THE LIGHTING OPERATION TIMES SHALL BE CONFIRMED BY THE USER TO ALLOW FOR COMMISSIONING AND NECESSARY DEMONSTRATIONS OF

ALL LIGHTING SPECIFIED IS IN ACCORDANCE WITH THE GUIDANCE CONTAINED IN REGARDS ENERGY EFFECTIVE LIGHTING DESIGN AND

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR 5A RATED SOCKET OUTLETS AND ALL FEATURE AND DECORATIVE LIGHTING.

IN EXPOSED CEILING AREAS THE ELECTRICAL CONTRACTOR SHALL ALLOW FOR USING GALVANISED STEEL CONDUIT AND TRUNKING SYSTEMS WHICH PROPRIETARY FITTINGS AND CONCEAL SUPPORTS IN FINISH AND LAYOUT AGREED WITH THE INTERIOR DESIGNER. ENSURE CABLING IS CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE EMERGENCY LIGHTING INSTALLATION, SUPPLIED, INSTALLED AND COMMISSION UNDER THE ELECTRICAL CONTRACT SHALL BE SELF CONTAINED INDEPENDENT EMERGENCY LIGHTING LUMINAIRES CONSISTING OF EITHER RECESSED OR SURFACE MOUNTED TO SUIT CEILING MAKE UP, 3 HOUR NON-MAINTAINED MICROPOINT LED DOWN LIGHTS, WALL MOUNTED BEAM LUMINAIRES AS NOTED WITHIN THE LUMINAIRE SCHEDULE CONNECTED TO THE LOCAL LIGHTING CIRCUITS

EMERGENCY LIGHTING IS TO BE PROVIDED OUTSIDE AND NEAR EXITS, WITHIN THE REQUIRED EMERGENCY ALARM CALL POINTS TO CURRENT REGULATIONS AND WIRING SHALL MATCH THAT DESCRIBED FOR THE GENERAL LIGHTING INSTALLATION.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON THE DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENe 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT)

LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM. CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

ALL EXTERNAL LIGHTING IS TO BE ZONED SO THAT CERTAIN CIRCUITS CAN BE SWITCHED OFF AT PRE-DETERMINED TIMES TO PROVIDE A CURFREW PERIOD AS REQUIRED BY THE END USER.

TYPE A DISTRIBUTION BOARDS SHALL BE USED FOR THE EXTERNAL

CONDUIT ROUTES SHALL BE PROVIDED THROUGHT THE BUILDING STRUCTURE TO THE EXTERNAL FACADES TO SUPPORT THE EXTERNAL LIGHTING SCHEME. CONDUITS SHALL BE GALVANISED STEEL AND BE ROUTED BACK TO THE RELEVANT EXTERNAL LIGHTING BOARD. WHERE LIGHTING IS GROUND MOUNTED AROUND THE EXTERNAL PERIMETER OF THE BUILDING, ARMOURED CABLING SHALL BE ROUTED AT APPROPRIATE DEPTHS AND PROTECTED AS REQUIRED UNDER CURRENT REGULATIONS. CAST IN CABLE DUCTS / SLEEVES SHALL BE PROVIDED WHERE CABLES EXIT THE BUILDING. DUCTED CABLE ROUTES SHALL BE PROVIDED TO SERVE EXTERNAL LIGHTING.

THE ELECRICAL CONTRACTOR IS TO INSTALL ADEQUATE LIGHTING FOR THE SAFE PASSAGE OF PEOPLE TO AND FROM THE BUILDING AND ENHANCE THE SECURITY OF THE BUILDING IN ACCORDANCE WITH THE LANDSCAPE DESIGNERS ASPIRATIONS. THE INSTALLATION SHALL COMPRISE LED LUMINAIRES, ASSOCIATED CIRCUITS, CONTAINMENT AND CONTROL DEVICES TO ILLUMINATE THE FOLLOWING EXTERNAL AREAS

MAIN BUILDING ENVELOPE,

- MAIN BUILDING ENTRANCE AVERAGE 100 LUX, ROOF TERRACE & AMENITY AREAS - AVERAGE 30 LUX,
- UNDERGROUND CAR PARKING AREAS AVERAGE 30 LUX, COURTYARD SPACE,
- MAIN ENTRANCE DOOR, SECONDARY ACCESS DOORS AND ALL FIRE EXITS

CODE FOR SUSTAINABLE HOME CREDIT ENe6 EXTERNAL LIGHTING IS TO SYSTEM, IN-LINE WITH THE ASPIRATIONS AND DETAIL OF ALL NOTES AND BE SOUGHT INCLUDING COMPLIANCE WITH CIBSE LIGHTING GUIDE 6 -"THE OUTDOOR ENVIRONMENT"

> ALL EXTERNAL LIGHTING (EXCEPT FOR SAFETY AND SECURITY LIGHTING) CAN BE AUTOMATICALLY SWITCHED OFF BETWEEN 2300 HRS AND 0700 HRS. THIS IS ACHIEVED VIA TIMER FOR ALL EXTERNAL LIGHTING SET TO THE APPROPRIATE HOURS. ADJUSTABLE TIMESWITCH AND DAYLIGHT SENSOR - SCENE SETTING PLATE AND 365/24/7 TIMER AD PHOTOCELL. PIR CONTROLS SHALL BE AFFORDED TO THE CAR PARK LIGHTING

> ALL EXTERNAL LUMINAIRES SHALL HAVE A LUMINOUS EFFICACY OF AT LEAST 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP HAS A COLOUR RENDERING INDEX (Ra) GREATER THAN OR EQUAL TO 60 OR MIN 60 LAMP LUMENS/CIRCUIT WATT WHEN LAMP HAS A COLOUR RENDERING INDES

> ALL EXTERNAL LIGHT FITTINGS FOR SIGNS AND UPLIGHTING ARE TO HAVE A LUMINIOUS EFFICACY OF AT LEAST 60 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS GREATER THAN OR EQUAL TO 25W OR MIN 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS LESS THAN 25W.

THE ELECTRICAL CONTRACTOR IS TO INSURE THAT ALL CONTROLS ARE LINKED TO THE BUILDINGS CENTRAL BMS SYSTEM. IT IS THE INTENTION FOR THE EXTERNAL LIGHTING TO BE FULLY AUTOMATED, HOWEVER OVERRIDE CONTROL SHALL BE PROVIDED ON THE BMS SYSTEM. ALLOWING PROGRAMMED OPERATING TIMES OF GROUP LUMINAIRES.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE.

THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING. CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

e 11	_			1:100					
C B A REV	MAY.21 FEB.21 DEC.20 DATE	SBD U TENDE ISSUEE DESCR	IPDATE FO R ISSUE) FOR REV PTION	R REVIEW				CS CS DR	
		C	a	ld	V	Æ			
AF R	RCHITECT	ARC	HITECT	ſS					
Jo N		PLE 2	ASANT						
F 4	203								
P 4 E E E	RAWING LECTF EVEL XTERI BLOCK	RICAL 00 NAL L D1	SERV _IGHTIN & D2	ICES NG	INST	ALLA	TION		
	RAWING LECTF EVEL XTERN BLOCK	RICAL 00 NAL L D1	SERV _IGHTIN & D2 	ices Ng - 00 -	INST. - N2	ALLA - E	tion - 11	4 -	C



ON (MAINTAINED).

SYSTEM.

DRAWINGS.

CONTROLS.

CABLES.

Scale

GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE

EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

THE CEILING GRID LAYOUT IS INDICATIVE ONLY AND LIGHTING INSTALLATION SHOULD BE CO-ORDINATED FULLY ON SITE PRIOR TO INSTALLATION.

THE ELECTRICAL CONTRACTOR SHALL PROCURE, SUPPLY, INSTALL, TEST, COMMISSION AND SET TO WORK A COMPLETE, FULLY OPERATIONAL LIGHTING AND LIGHTING CONTROL

ALL LIGHTING SHALL HAVE CLEARANCE FROM ANY INSULATION AS HIGHLIGHTED WITHIN THE MANUFACTURES HAND BOOK.

THE LUMINARE HEAT DISSIPATING AREAS SHALL NOT HAVE THE AIR FLOW OBSTRUCTED IN ANY WAY.

ALL REFLECTORS, COVERS OR VISUAL AREAS SHALL BE CLEAN AND FREE FROM DIRT PRIOR TO LIGHTING LEVELS COMMISSIONED.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR ALL LUMINAIRES, ACCESSORIES, PLUG-INS, MOUNTING KITS AND POWER SUPPLIES WERE NECESSARY COMPLYING TO CURRENT BUILDING REGULATIONS, SO AS TO ENSURE A COMPLETE AND OPERATIONAL INSTALLATION.

LOCATION OF ALL SWITCHING TO BE IN ACCORDANCE WITH BS 8300 AND BUILDING REGULATIONS APPROVED DOCUMENT M. THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE

TESTING AND COMMISSIONING OF THE EMERGENCY LIGHTING INSTALLATION IN ACCORDANCE WITH REQUIREMENTS OF BS 5266 -CODE OF PRACTICE FOR EMERGENCY LIGHTING AND SHALL PROVIDE THE NECESSARY DOCUMENTATION:

THE LIGHTING OPERATION TIMES SHALL BE CONFIRMED BY THE USER TO ALLOW FOR COMMISSIONING AND NECESSARY DEMONSTRATIONS OF

ALL LIGHTING SPECIFIED IS IN ACCORDANCE WITH THE GUIDANCE CONTAINED IN REGARDS ENERGY EFFECTIVE LIGHTING DESIGN AND SPECIFICATION.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR 5A RATED SOCKET OUTLETS AND ALL FEATURE AND DECORATIVE LIGHTING.

IN EXPOSED CEILING AREAS THE ELECTRICAL CONTRACTOR SHALL ALLOW FOR USING GALVANISED STEEL CONDUIT AND TRUNKING SYSTEMS WHICH PROPRIETARY FITTINGS AND CONCEAL SUPPORTS IN FINISH AND LAYOUT AGREED WITH THE INTERIOR DESIGNER. ENSURE CABLING IS CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE EMERGENCY LIGHTING INSTALLATION, SUPPLIED, INSTALLED AND COMMISSION UNDER THE ELECTRICAL CONTRACT SHALL BE SELF CONTAINED INDEPENDENT EMERGENCY LIGHTING LUMINAIRES CONSISTING OF EITHER RECESSED OR SURFACE MOUNTED TO SUIT CEILING MAKE UP, 3 HOUR NON-MAINTAINED MICROPOINT LED DOWN LIGHTS, WALL MOUNTED BEAM LUMINAIRES AS NOTED WITHIN THE LUMINAIRE SCHEDULE CONNECTED TO THE LOCAL LIGHTING CIRCUITS

EMERGENCY LIGHTING IS TO BE PROVIDED OUTSIDE AND NEAR EXITS, WITHIN THE REQUIRED EMERGENCY ALARM CALL POINTS TO CURRENT REGULATIONS AND WIRING SHALL MATCH THAT DESCRIBED FOR THE GENERAL LIGHTING INSTALLATION.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON TH DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENe 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT)

LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM, CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

ALL EXTERNAL LIGHTING IS TO BE ZONED SO THAT CERTAIN CIRCUITS CAN BE SWITCHED OFF AT PRE-DETERMINED TIMES TO PROVIDE A CURFREW PERIOD AS REQUIRED BY THE END USER.

TYPE A DISTRIBUTION BOARDS SHALL BE USED FOR THE EXTERNAL LIGHTING SUPPLIES.

CONDUIT ROUTES SHALL BE PROVIDED THROUGHT THE BUILDING STRUCTURE TO THE EXTERNAL FACADES TO SUPPORT THE EXTERNAL LIGHTING SCHEME. CONDUITS SHALL BE GALVANISED STEEL AND BE ROUTED BACK TO THE RELEVANT EXTERNAL LIGHTING BOARD. WHERE LIGHTING IS GROUND MOUNTED AROUND THE EXTERNAL PERIMETER OF THE BUILDING, ARMOURED CABLING SHALL BE ROUTED AT APPROPRIATE DEPTHS AND PROTECTED AS REQUIRED UNDER CURRENT REGULATIONS. CAST IN CABLE DUCTS / SLEEVES SHALL BE PROVIDED WHERE CABLES EXIT THE BUILDING. DUCTED CABLE ROUTES SHALL BE PROVIDED TO SERVE EXTERNAL LIGHTING.

THE ELECRICAL CONTRACTOR IS TO INSTALL ADEQUATE LIGHTING FOR THE SAFE PASSAGE OF PEOPLE TO AND FROM THE BUILDING AND ENHANCE THE SECURITY OF THE BUILDING IN ACCORDANCE WITH THE LANDSCAPE DESIGNERS ASPIRATIONS. THE INSTALLATION SHALL COMPRISE LED LUMINAIRES, ASSOCIATED CIRCUITS, CONTAINMENT AND CONTROL DEVICES TO ILLUMINATE THE FOLLOWING EXTERNAL AREAS

- MAIN BUILDING ENVELOPE, • MAIN BUILDING ENTRANCE - AVERAGE 100 LUX,
- ROOF TERRACE & AMENITY AREAS AVERAGE 30 LUX, • UNDERGROUND CAR PARKING AREAS - AVERAGE 30 LUX,
- COURTYARD SPACE, MAIN ENTRANCE DOOR,
- SECONDARY ACCESS DOORS AND ALL FIRE EXITS

CODE FOR SUSTAINABLE HOME CREDIT ENe6 EXTERNAL LIGHTING IS TO SYSTEM, IN-LINE WITH THE ASPIRATIONS AND DETAIL OF ALL NOTES AND BE SOUGHT INCLUDING COMPLIANCE WITH CIBSE LIGHTING GUIDE 6 -"THE OUTDOOR ENVIRONMENT"

> ALL EXTERNAL LIGHTING (EXCEPT FOR SAFETY AND SECURITY LIGHTING) CAN BE AUTOMATICALLY SWITCHED OFF BETWEEN 2300 HRS AND 0700 HRS. THIS IS ACHIEVED VIA TIMER FOR ALL EXTERNAL LIGHTING SET TO THE APPROPRIATE HOURS. ADJUSTABLE TIMESWITCH AND DAYLIGHT SENSOR - SCENE SETTING PLATE AND 365/24/7 TIMER AD PHOTOCELL. PIR CONTROLS SHALL BE AFFORDED TO THE CAR PARK LIGHTING

> ALL EXTERNAL LUMINAIRES SHALL HAVE A LUMINOUS EFFICACY OF AT LEAST 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP HAS A COLOUR RENDERING INDEX (Ra) GREATER THAN OR EQUAL TO 60 OR MIN 60 LAMP LUMENS/CIRCUIT WATT WHEN LAMP HAS A COLOUR RENDERING INDES (Ra) LESS THAN 60.

> ALL EXTERNAL LIGHT FITTINGS FOR SIGNS AND UPLIGHTING ARE TO HAVE A LUMINIOUS EFFICACY OF AT LEAST 60 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS GREATER THAN OR EQUAL TO 25W OR MIN 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS LESS THAN 25W.

THE ELECTRICAL CONTRACTOR IS TO INSURE THAT ALL CONTROLS ARE LINKED TO THE BUILDINGS CENTRAL BMS SYSTEM. IT IS THE INTENTION FOR THE EXTERNAL LIGHTING TO BE FULLY AUTOMATED, HOWEVER OVERRIDE CONTROL SHALL BE PROVIDED ON THE BMS SYSTEM. ALLOWING PROGRAMMED OPERATING TIMES OF GROUP LUMINAIRES.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE.

THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING, CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

D	MAY 21	SBD UPDATE FOR REVI	FW	20	1 1
<u>с</u>	FFB 21	PLANNING ISSUE			
	FFB 21	TENDER ISSUE			
	DEC 20	ISSUED FOR REVIEW			
		Calc	lwe		
A F	RCHITECT	ARCHITECTS			
	MOUNT PHASE	PLEASANT 2			
2	4203				
	1203 ELECTRI EVEL (EXTERN BLOCK	ICAL SERVICES DO AL LIGHTING B & C	5 INSTALLA	TION	
	PRAWING ELECTRI EVEL (EXTERN BLOCK PRAWING NO.	ICAL SERVICES DO AL LIGHTING B & C /REVISION CAL - ZZ - 00	installa - W2 - E	tion - 115 -	D

NEWTOWNBREDA BELFAST BT8 6AW EMAIL: admin@caldwellconsulting.net



GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS ON (MAINTAINED).

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE SYSTEM.

EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON THE DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENe 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT)

LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA CABLES.

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM, CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

COURTYARD SPACE,



ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE. THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING,

CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE



THE REPORT OF THE PARTY OF THE

GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS ON (MAINTAINED).

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE SYSTEM.

EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

THE CEILING GRID LAYOUT IS INDICATIVE ONLY AND LIGHTING INSTALLATION SHOULD BE CO-ORDINATED FULLY ON SITE PRIOR TO INSTALLATION.

THE ELECTRICAL CONTRACTOR SHALL PROCURE, SUPPLY, INSTALL, TEST, COMMISSION AND SET TO WORK A COMPLETE, FULLY OPERATIONAL LIGHTING AND LIGHTING CONTROL SYSTEM, IN-LINE WITH THE ASPIRATIONS AND DETAIL OF ALL NOTES AND • SECONDARY ACCESS DOORS AND ALL FIRE EXITS DRAWINGS.

ALL LIGHTING SHALL HAVE CLEARANCE FROM ANY INSULATION AS HIGHLIGHTED WITHIN THE MANUFACTURES HAND BOOK.

THE LUMINARE HEAT DISSIPATING AREAS SHALL NOT HAVE THE AIR FLOW OBSTRUCTED IN ANY WAY.

ALL REFLECTORS, COVERS OR VISUAL AREAS SHALL BE CLEAN AND FREE FROM DIRT PRIOR TO LIGHTING LEVELS COMMISSIONED.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR ALL LUMINAIRES, ACCESSORIES, PLUG-INS, MOUNTING KITS AND POWER SUPPLIES WERE NECESSARY COMPLYING TO CURRENT BUILDING REGULATIONS, SO AS TO ENSURE A COMPLETE AND OPERATIONAL INSTALLATION.

LOCATION OF ALL SWITCHING TO BE IN ACCORDANCE WITH BS 8300 AND BUILDING REGULATIONS APPROVED DOCUMENT M.

THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE TESTING AND COMMISSIONING OF THE EMERGENCY LIGHTING INSTALLATION IN ACCORDANCE WITH REQUIREMENTS OF BS 5266 -CODE OF PRACTICE FOR EMERGENCY LIGHTING AND SHALL PROVIDE THE NECESSARY DOCUMENTATION:

THE LIGHTING OPERATION TIMES SHALL BE CONFIRMED BY THE USER TO ALLOW FOR COMMISSIONING AND NECESSARY DEMONSTRATIONS OF CONTROLS.

ALL LIGHTING SPECIFIED IS IN ACCORDANCE WITH THE GUIDANCE CONTAINED IN REGARDS ENERGY EFFECTIVE LIGHTING DESIGN AND SPECIFICATION.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR 5A RATED SOCKET OUTLETS AND ALL FEATURE AND DECORATIVE LIGHTING.

IN EXPOSED CEILING AREAS THE ELECTRICAL CONTRACTOR SHALL ALLOW FOR USING GALVANISED STEEL CONDUIT AND TRUNKING SYSTEMS WHICH PROPRIETARY FITTINGS AND CONCEAL SUPPORTS IN FINISH AND LAYOUT AGREED WITH THE INTERIOR DESIGNER. ENSURE CABLING IS CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE EMERGENCY LIGHTING INSTALLATION, SUPPLIED, INSTALLED AND COMMISSION UNDER THE ELECTRICAL CONTRACT SHALL BE SELF CONTAINED INDEPENDENT EMERGENCY LIGHTING LUMINAIRES CONSISTING OF EITHER RECESSED OR SURFACE MOUNTED TO SUIT CEILING MAKE UP, 3 HOUR NON-MAINTAINED MICROPOINT LED DOWN LIGHTS, WALL MOUNTED BEAM LUMINAIRES AS NOTED WITHIN THE LUMINAIRE SCHEDULE CONNECTED TO THE LOCAL LIGHTING CIRCUITS

EMERGENCY LIGHTING IS TO BE PROVIDED OUTSIDE AND NEAR EXITS, WITHIN THE REQUIRED EMERGENCY ALARM CALL POINTS TO CURRENT REGULATIONS AND WIRING SHALL MATCH THAT DESCRIBED FOR THE GENERAL LIGHTING INSTALLATION.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON THE DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENE 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT)

LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA CABLES.

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM, CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

ALL EXTERNAL LIGHTING IS TO BE ZONED SO THAT CERTAIN CIRCUITS CAN BE SWITCHED OFF AT PRE-DETERMINED TIMES TO PROVIDE A CURFREW PERIOD AS REQUIRED BY THE END USER.

TYPE A DISTRIBUTION BOARDS SHALL BE USED FOR THE EXTERNAL LIGHTING SUPPLIES.

CONDUIT ROUTES SHALL BE PROVIDED THROUGHT THE BUILDING STRUCTURE TO THE EXTERNAL FACADES TO SUPPORT THE EXTERNAL LIGHTING SCHEME. CONDUITS SHALL BE GALVANISED STEEL AND BE ROUTED BACK TO THE RELEVANT EXTERNAL LIGHTING BOARD. WHERE LIGHTING IS GROUND MOUNTED AROUND THE EXTERNAL PERIMETER OF THE BUILDING, ARMOURED CABLING SHALL BE ROUTED AT APPROPRIATE DEPTHS AND PROTECTED AS REQUIRED UNDER CURRENT REGULATIONS. CAST IN CABLE DUCTS / SLEEVES SHALL BE PROVIDED WHERE CABLES EXIT THE BUILDING. DUCTED CABLE ROUTES SHALL BE PROVIDED TO SERVE EXTERNAL LIGHTING.

THE ELECRICAL CONTRACTOR IS TO INSTALL ADEQUATE LIGHTING FOR THE SAFE PASSAGE OF PEOPLE TO AND FROM THE BUILDING AND ENHANCE THE SECURITY OF THE BUILDING IN ACCORDANCE WITH THE LANDSCAPE DESIGNERS ASPIRATIONS. THE INSTALLATION SHALL COMPRISE LED LUMINAIRES, ASSOCIATED CIRCUITS, CONTAINMENT AND CONTROL DEVICES TO ILLUMINATE THE FOLLOWING EXTERNAL AREAS

MAIN BUILDING ENVELOPE,

- MAIN BUILDING ENTRANCE AVERAGE 100 LUX, ROOF TERRACE & AMENITY AREAS - AVERAGE 30 LUX,
- UNDERGROUND CAR PARKING AREAS AVERAGE 30 LUX,
- COURTYARD SPACE, MAIN ENTRANCE DOOR,

CODE FOR SUSTAINABLE HOME CREDIT ENe6 EXTERNAL LIGHTING IS TO BE SOUGHT INCLUDING COMPLIANCE WITH CIBSE LIGHTING GUIDE 6 -"THE OUTDOOR ENVIRONMENT"

ALL EXTERNAL LIGHTING (EXCEPT FOR SAFETY AND SECURITY LIGHTING) CAN BE AUTOMATICALLY SWITCHED OFF BETWEEN 2300 HRS AND 0700 HRS. THIS IS ACHIEVED VIA TIMER FOR ALL EXTERNAL LIGHTING SET TO THE APPROPRIATE HOURS. ADJUSTABLE TIMESWITCH AND DAYLIGHT SENSOR - SCENE SETTING PLATE AND 365/24/7 TIMER AD PHOTOCELL. PIR CONTROLS SHALL BE AFFORDED TO THE CAR PARK LIGHTING

ALL EXTERNAL LUMINAIRES SHALL HAVE A LUMINOUS EFFICACY OF AT LEAST 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP HAS A COLOUR RENDERING INDEX (Ra) GREATER THAN OR EQUAL TO 60 OR MIN 60 LAMP LUMENS/CIRCUIT WATT WHEN LAMP HAS A COLOUR RENDERING INDES (Ra) LESS THAN 60.

ALL EXTERNAL LIGHT FITTINGS FOR SIGNS AND UPLIGHTING ARE TO HAVE A LUMINIOUS EFFICACY OF AT LEAST 60 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS GREATER THAN OR EQUAL TO 25W OR MIN 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS LESS THAN 25W.

THE ELECTRICAL CONTRACTOR IS TO INSURE THAT ALL CONTROLS ARE LINKED TO THE BUILDINGS CENTRAL BMS SYSTEM. IT IS THE INTENTION FOR THE EXTERNAL LIGHTING TO BE FULLY AUTOMATED, HOWEVER OVERRIDE CONTROL SHALL BE PROVIDED ON THE BMS SYSTEM. ALLOWING PROGRAMMED OPERATING TIMES OF GROUP LUMINAIRES.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE.

THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING, CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

В	FEB.21	TENDER ISSUE	CS	LW
A	DEC.20	ISSUED FOR REVIEW	CS	LW
REV	DATE	DESCRIPTION	DR	СК
		Caldwell		
a F	RCHITECT RYDER	ARCHITECTS		
J	ОВ			
N	IOUNT	PLEASANT		
F	PHASE	2		
4	203			
D E E	rawing LECTR BLOCK	ICAL SERVICES INSTALLATION D – LEVEL 06		
Г 	COF L	EVEL EXTERNAL LIGHTING		
D	rawing no. PP2 –	CAL – ZZ – 06 – M2 – E – 11	7 – [}
s 1	cale/Prin :100@	ted At Date Drawn Checki A1 NOV'20 CS LW	ED	
Ur Ne	NIT 6 FORE	STGROVE BUSINESS PARK TEL: 02890699720 FAX EDA BELFAST BT8 6AW EMAIL: admin@caldwel	(:028906 Ilconsultin	41625 ig.net





SYSTEM. EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

THE CEILING GRID LAYOUT IS INDICATIVE ONLY AND LIGHTING INSTALLATION SHOULD BE CO-ORDINATED FULLY ON SITE PRIOR TO INSTALLATION.

THE ELECTRICAL CONTRACTOR SHALL PROCURE, SUPPLY, INSTALL, TEST, COMMISSION AND SET TO WORK A COMPLETE, FULLY OPERATIONAL LIGHTING AND LIGHTING CONTROL SYSTEM, IN-LINE WITH THE ASPIRATIONS AND DETAIL OF ALL NOTES AND DRAWINGS.

ALL REFLECTORS, COVERS OR VISUAL AREAS SHALL BE CLEAN AND FREE FROM DIRT PRIOR TO LIGHTING LEVELS COMMISSIONED.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR ALL LUMINAIRES, ACCESSORIES, PLUG-INS, MOUNTING KITS AND POWER SUPPLIES WERE NECESSARY COMPLYING TO CURRENT BUILDING REGULATIONS, SO AS TO ENSURE A COMPLETE AND OPERATIONAL INSTALLATION.

CONTROLS.

SPECIFICATION.

IN EXPOSED CEILING AREAS THE ELECTRICAL CONTRACTOR SHALL ALLOW FOR USING GALVANISED STEEL CONDUIT AND TRUNKING SYSTEMS WHICH PROPRIETARY FITTINGS AND CONCEAL SUPPORTS IN FINISH AND LAYOUT AGREED WITH THE INTERIOR DESIGNER. ENSURE CABLING IS CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE EMERGENCY LIGHTING INSTALLATION, SUPPLIED, INSTALLED AND COMMISSION UNDER THE ELECTRICAL CONTRACT SHALL BE SELF CONTAINED INDEPENDENT EMERGENCY LIGHTING LUMINAIRES CONSISTING OF EITHER RECESSED OR SURFACE MOUNTED TO SUIT CEILING MAKE UP, 3 HOUR NON-MAINTAINED MICROPOINT LED DOWN LIGHTS, WALL MOUNTED BEAM LUMINAIRES AS NOTED WITHIN THE LUMINAIRE SCHEDULE CONNECTED TO THE LOCAL LIGHTING CIRCUITS

EMERGENCY LIGHTING IS TO BE PROVIDED OUTSIDE AND NEAR EXITS, WITHIN THE REQUIRED EMERGENCY ALARM CALL POINTS TO CURRENT REGULATIONS AND WIRING SHALL MATCH THAT DESCRIBED FOR THE GENERAL LIGHTING INSTALLATION.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON THE DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENe 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT)

CABLES.

GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS ON (MAINTAINED).

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE

ALL LIGHTING SHALL HAVE CLEARANCE FROM ANY INSULATION AS HIGHLIGHTED WITHIN THE MANUFACTURES HAND BOOK.

THE LUMINARE HEAT DISSIPATING AREAS SHALL NOT HAVE THE AIR FLOW OBSTRUCTED IN ANY WAY.

LOCATION OF ALL SWITCHING TO BE IN ACCORDANCE WITH BS 8300 AND BUILDING REGULATIONS APPROVED DOCUMENT M.

THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE TESTING AND COMMISSIONING OF THE EMERGENCY LIGHTING INSTALLATION IN ACCORDANCE WITH REQUIREMENTS OF BS 5266 -CODE OF PRACTICE FOR EMERGENCY LIGHTING AND SHALL PROVIDE THE NECESSARY DOCUMENTATION:

THE LIGHTING OPERATION TIMES SHALL BE CONFIRMED BY THE USER TO ALLOW FOR COMMISSIONING AND NECESSARY DEMONSTRATIONS OF

ALL LIGHTING SPECIFIED IS IN ACCORDANCE WITH THE GUIDANCE CONTAINED IN REGARDS ENERGY EFFECTIVE LIGHTING DESIGN AND

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR 5A RATED SOCKET OUTLETS AND ALL FEATURE AND DECORATIVE LIGHTING.

LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM, CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

ALL EXTERNAL LIGHTING IS TO BE ZONED SO THAT CERTAIN CIRCUITS CAN BE SWITCHED OFF AT PRE-DETERMINED TIMES TO PROVIDE A CURFREW PERIOD AS REQUIRED BY THE END USER.

TYPE A DISTRIBUTION BOARDS SHALL BE USED FOR THE EXTERNAL LIGHTING SUPPLIES.

CONDUIT ROUTES SHALL BE PROVIDED THROUGHT THE BUILDING STRUCTURE TO THE EXTERNAL FACADES TO SUPPORT THE EXTERNAL LIGHTING SCHEME. CONDUITS SHALL BE GALVANISED STEEL AND BE ROUTED BACK TO THE RELEVANT EXTERNAL LIGHTING BOARD. WHERE LIGHTING IS GROUND MOUNTED AROUND THE EXTERNAL PERIMETER OF THE BUILDING, ARMOURED CABLING SHALL BE ROUTED AT APPROPRIATE DEPTHS AND PROTECTED AS REQUIRED UNDER CURRENT REGULATIONS. CAST IN CABLE DUCTS / SLEEVES SHALL BE PROVIDED WHERE CABLES EXIT THE BUILDING. DUCTED CABLE ROUTES SHALL BE PROVIDED TO SERVE EXTERNAL LIGHTING.

THE ELECRICAL CONTRACTOR IS TO INSTALL ADEQUATE LIGHTING FOR THE SAFE PASSAGE OF PEOPLE TO AND FROM THE BUILDING AND ENHANCE THE SECURITY OF THE BUILDING IN ACCORDANCE WITH THE LANDSCAPE DESIGNERS ASPIRATIONS. THE INSTALLATION SHALL COMPRISE LED LUMINAIRES, ASSOCIATED CIRCUITS, CONTAINMENT AND CONTROL DEVICES TO ILLUMINATE THE FOLLOWING EXTERNAL AREAS

- MAIN BUILDING ENVELOPE, MAIN BUILDING ENTRANCE - AVERAGE 100 LUX.
- ROOF TERRACE & AMENITY AREAS AVERAGE 30 LUX, • UNDERGROUND CAR PARKING AREAS - AVERAGE 30 LUX,
- COURTYARD SPACE,
- MAIN ENTRANCE DOOR, SECONDARY ACCESS DOORS AND ALL FIRE EXITS

CODE FOR SUSTAINABLE HOME CREDIT ENe6 EXTERNAL LIGHTING IS TO BE SOUGHT INCLUDING COMPLIANCE WITH CIBSE LIGHTING GUIDE 6 -"THE OUTDOOR ENVIRONMENT"

ALL EXTERNAL LIGHTING (EXCEPT FOR SAFETY AND SECURITY LIGHTING) CAN BE AUTOMATICALLY SWITCHED OFF BETWEEN 2300 HRS AND 0700 HRS. THIS IS ACHIEVED VIA TIMER FOR ALL EXTERNAL LIGHTING SET TO THE APPROPRIATE HOURS. ADJUSTABLE TIMESWITCH AND DAYLIGHT SENSOR - SCENE SETTING PLATE AND 365/24/7 TIMER AD PHOTOCELL. PIR CONTROLS SHALL BE AFFORDED TO THE CAR PARK LIGHTING

ALL EXTERNAL LUMINAIRES SHALL HAVE A LUMINOUS EFFICACY OF AT LEAST 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP HAS A COLOUR RENDERING INDEX (Ra) GREATER THAN OR EQUAL TO 60 OR MIN 60 LAMP LUMENS/CIRCUIT WATT WHEN LAMP HAS A COLOUR RENDERING INDES (Ra) LESS THAN 60.

ALL EXTERNAL LIGHT FITTINGS FOR SIGNS AND UPLIGHTING ARE TO HAVE A LUMINIOUS EFFICACY OF AT LEAST 60 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS GREATER THAN OR EQUAL TO 25W OR MIN 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS LESS THAN 25W.

THE ELECTRICAL CONTRACTOR IS TO INSURE THAT ALL CONTROLS ARE LINKED TO THE BUILDINGS CENTRAL BMS SYSTEM. IT IS THE INTENTION FOR THE EXTERNAL LIGHTING TO BE FULLY AUTOMATED, HOWEVER OVERRIDE CONTROL SHALL BE PROVIDED ON THE BMS SYSTEM. ALLOWING PROGRAMMED OPERATING TIMES OF GROUP LUMINAIRES.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE.

THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING, CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

						_
В	FEB.21	TENDER	R ISSUE		CS	l
Α	DEC.20	ISSUED	FOR REVIEW		CS	
REV	DATE	DESCRI	PTION		DR	
		C		We		
ai F	RCHITECT RYDER	ARCI	HITECTS			
J N F 4	ов ЛОUNT PHASE F023	PLE 2	ASANT			
D E E	RAWING ELECTF EVEL EXTERI	RICAL 08 E NAL L	SERVICES 3LOCK C .IGHTING	INSTALLA	TION	
D M	rawing n PP2 –	o./Revisio CAL -	ис – ZZ – 08	- M2 - E	- 118 -	B
s 1	cale/Pri :100@	NTED AT ⊉A 1	Date NOV'20	Drawn CS	Checked LW	
Un Ne		estgrov reda Be	'E BUSINESS PARI LFAST BT8 6AW	K TEL: 0289069	9720 FAX:028906	541 na.





ON (MAINTAINED). SYSTEM.

EACH EMERGENCY LUMINAIRE SHOULD BE COMPLETE WITH A STICK ON REFERENCE LABEL THAT SHOULD CORRELATE WITH THE AS INSTALLED RECORD DRAWINGS.

DRAWINGS.

CONTROLS.

SPECIFICATION.

IN EXPOSED CEILING AREAS THE ELECTRICAL CONTRACTOR SHALL ALLOW FOR USING GALVANISED STEEL CONDUIT AND TRUNKING SYSTEMS WHICH PROPRIETARY FITTINGS AND CONCEAL SUPPORTS IN FINISH AND LAYOUT AGREED WITH THE INTERIOR DESIGNER. ENSURE CABLING IS CO-ORDINATED IN A NEAT AND TIDY MANNER.

THE EMERGENCY LIGHTING INSTALLATION, SUPPLIED, INSTALLED AND COMMISSION UNDER THE ELECTRICAL CONTRACT SHALL BE SELF CONTAINED INDEPENDENT EMERGENCY LIGHTING LUMINAIRES CONSISTING OF EITHER RECESSED OR SURFACE MOUNTED TO SUIT CEILING MAKE UP, 3 HOUR NON-MAINTAINED MICROPOINT LED DOWN LIGHTS, WALL MOUNTED BEAM LUMINAIRES AS NOTED WITHIN THE LUMINAIRE SCHEDULE CONNECTED TO THE LOCAL LIGHTING CIRCUITS

EMERGENCY LIGHTING IS TO BE PROVIDED OUTSIDE AND NEAR EXITS, WITHIN THE REQUIRED EMERGENCY ALARM CALL POINTS TO CURRENT REGULATIONS AND WIRING SHALL MATCH THAT DESCRIBED FOR THE GENERAL LIGHTING INSTALLATION.

THE ELECTRICAL CONTRACT IS TO PROVIDE AN EXTERNAL LIGHTING INSTALLATION COMPRISING FLICKER FREE LED FEATURE LIGHTING VIA BOLLARDS AND RECESSED UPLIGHTS ETC AS INDICATED ON THE DRAWINGS AND LUMINAIRE SCHEDULES. (MEETING ENe 6 - CAPABLE OF ONLY ACCEPTING LAMPS HAVING A LUMINOUS EFFICACY GREATER THAN 40 LUMINS PER CIRCUIT WATT CONTROLLED BY PUSH BUTTON TIME SWITCHES/PIR SENSORS OR EQUIVALENT) LIGHTING IS TO BE CONTROLLED VIA A TIME CLOCK/ PHOTOCELL AND HOA. WIRED CIRCUITS FOR LANDSCAPE LIGHTING SHALL BE IN XLPE/SWA

CABLES.

GENERAL & EMERGENCY LIGHTING NOTES

THE EMERGENCY / ESCAPE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 5266-1: 2016, BS 1838: 2013

THE LIGHTING INSTALLATION SHALL COMPLY IN FULL WITH THE REQUIREMENTS OF BS 7671 18 EDITION.

THE INTERNAL OVER DOOR EMERGENCY LUMINAIRES SHALL BE WIRED TO OPERATE WHEN LOCAL LIGHTING IS

THE LIGHTING CONTROLS MANUFACTURER, WITH ASSISTANCE FROM THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE COMMISSIONING OF THE

THE CEILING GRID LAYOUT IS INDICATIVE ONLY AND LIGHTING INSTALLATION SHOULD BE CO-ORDINATED FULLY ON SITE PRIOR TO INSTALLATION.

THE ELECTRICAL CONTRACTOR SHALL PROCURE, SUPPLY, INSTALL, TEST, COMMISSION AND SET TO WORK A COMPLETE, FULLY OPERATIONAL LIGHTING AND LIGHTING CONTROL SYSTEM, IN-LINE WITH THE ASPIRATIONS AND DETAIL OF ALL NOTES AND • SECONDARY ACCESS DOORS AND ALL FIRE EXITS

ALL LIGHTING SHALL HAVE CLEARANCE FROM ANY INSULATION AS HIGHLIGHTED WITHIN THE MANUFACTURES HAND BOOK.

THE LUMINARE HEAT DISSIPATING AREAS SHALL NOT HAVE THE AIR FLOW OBSTRUCTED IN ANY WAY.

ALL REFLECTORS, COVERS OR VISUAL AREAS SHALL BE CLEAN AND FREE FROM DIRT PRIOR TO LIGHTING LEVELS COMMISSIONED.

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR ALL LUMINAIRES, ACCESSORIES, PLUG-INS, MOUNTING KITS AND POWER SUPPLIES WERE NECESSARY COMPLYING TO CURRENT BUILDING REGULATIONS, SO AS TO ENSURE A COMPLETE AND OPERATIONAL INSTALLATION.

LOCATION OF ALL SWITCHING TO BE IN ACCORDANCE WITH BS 8300 AND BUILDING REGULATIONS APPROVED DOCUMENT M.

THE ELECTRICAL CONTRACTOR SHALL CARRY OUT THE TESTING AND COMMISSIONING OF THE EMERGENCY LIGHTING INSTALLATION IN ACCORDANCE WITH REQUIREMENTS OF BS 5266 -CODE OF PRACTICE FOR EMERGENCY LIGHTING AND SHALL PROVIDE THE NECESSARY DOCUMENTATION:

THE LIGHTING OPERATION TIMES SHALL BE CONFIRMED BY THE USER TO ALLOW FOR COMMISSIONING AND NECESSARY DEMONSTRATIONS OF

ALL LIGHTING SPECIFIED IS IN ACCORDANCE WITH THE GUIDANCE CONTAINED IN REGARDS ENERGY EFFECTIVE LIGHTING DESIGN AND

THE ELECTRICAL CONTRACTOR IS TO INCLUDE FOR 5A RATED SOCKET OUTLETS AND ALL FEATURE AND DECORATIVE LIGHTING.

WIRED CIRCUITS SERVING LUMINAIRES FIXED TO THE BUILDING ARE TO BE IN SINGLE CORE LOW SMOKE ZERO HALOGEN (LSZH) CABLES ENCLOSED WITHIN A METALLIC CONDUIT AND TRUNKING SYSTEM, CONTROLLED VIA TIMECLOCK WITH PHOTOCELL (DUST TO DAWN) AND HAND/OFF/AUTO SWITCHING LOCATED ADJACENT TO THE RELEVANT EXTERNAL LIGHTING BOARD (LOCATION TO BE AGREED). INTERPOSING MULTI-POLE CONTACTORS SHALL BE PROVIDED AS NECESSARY.

ALL EXTERNAL LIGHTING IS TO BE ZONED SO THAT CERTAIN CIRCUITS CAN BE SWITCHED OFF AT PRE-DETERMINED TIMES TO PROVIDE A CURFREW PERIOD AS REQUIRED BY THE END USER.

TYPE A DISTRIBUTION BOARDS SHALL BE USED FOR THE EXTERNAL LIGHTING SUPPLIES.

CONDUIT ROUTES SHALL BE PROVIDED THROUGHT THE BUILDING STRUCTURE TO THE EXTERNAL FACADES TO SUPPORT THE EXTERNAL LIGHTING SCHEME. CONDUITS SHALL BE GALVANISED STEEL AND BE ROUTED BACK TO THE RELEVANT EXTERNAL LIGHTING BOARD. WHERE LIGHTING IS GROUND MOUNTED AROUND THE EXTERNAL PERIMETER OF THE BUILDING, ARMOURED CABLING SHALL BE ROUTED AT APPROPRIATE DEPTHS AND PROTECTED AS REQUIRED UNDER CURRENT REGULATIONS. CAST IN CABLE DUCTS / SLEEVES SHALL BE PROVIDED WHERE CABLES EXIT THE BUILDING. DUCTED CABLE ROUTES SHALL BE PROVIDED TO SERVE EXTERNAL LIGHTING.

THE ELECRICAL CONTRACTOR IS TO INSTALL ADEQUATE LIGHTING FOR THE SAFE PASSAGE OF PEOPLE TO AND FROM THE BUILDING AND ENHANCE THE SECURITY OF THE BUILDING IN ACCORDANCE WITH THE LANDSCAPE DESIGNERS ASPIRATIONS. THE INSTALLATION SHALL COMPRISE LED LUMINAIRES, ASSOCIATED CIRCUITS, CONTAINMENT AND CONTROL DEVICES TO ILLUMINATE THE FOLLOWING EXTERNAL AREAS

- MAIN BUILDING ENVELOPE.
- MAIN BUILDING ENTRANCE AVERAGE 100 LUX, ROOF TERRACE & AMENITY AREAS - AVERAGE 30 LUX,
- UNDERGROUND CAR PARKING AREAS AVERAGE 30 LUX,
- COURTYARD SPACE, MAIN ENTRANCE DOOR,

CODE FOR SUSTAINABLE HOME CREDIT ENe6 EXTERNAL LIGHTING IS TO BE SOUGHT INCLUDING COMPLIANCE WITH CIBSE LIGHTING GUIDE 6 -"THE OUTDOOR ENVIRONMENT"

ALL EXTERNAL LIGHTING (EXCEPT FOR SAFETY AND SECURITY LIGHTING) CAN BE AUTOMATICALLY SWITCHED OFF BETWEEN 2300 HRS AND 0700 HRS. THIS IS ACHIEVED VIA TIMER FOR ALL EXTERNAL LIGHTING SET TO THE APPROPRIATE HOURS. ADJUSTABLE TIMESWITCH AND DAYLIGHT SENSOR - SCENE SETTING PLATE AND 365/24/7 TIMER AD PHOTOCELL. PIR CONTROLS SHALL BE AFFORDED TO THE CAR PARK LIGHTING

ALL EXTERNAL LUMINAIRES SHALL HAVE A LUMINOUS EFFICACY OF AT LEAST 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP HAS A COLOUR RENDERING INDEX (Ra) GREATER THAN OR EQUAL TO 60 OR MIN 60 LAMP LUMENS/CIRCUIT WATT WHEN LAMP HAS A COLOUR RENDERING INDES (Ra) LESS THAN 60.

ALL EXTERNAL LIGHT FITTINGS FOR SIGNS AND UPLIGHTING ARE TO HAVE A LUMINIOUS EFFICACY OF AT LEAST 60 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS GREATER THAN OR EQUAL TO 25W OR MIN 50 LAMP LUMENS/CIRCUIT WATT WHEN THE LAMP WATTAGE IS LESS THAN 25W.

THE ELECTRICAL CONTRACTOR IS TO INSURE THAT ALL CONTROLS ARE LINKED TO THE BUILDINGS CENTRAL BMS SYSTEM. IT IS THE INTENTION FOR THE EXTERNAL LIGHTING TO BE FULLY AUTOMATED, HOWEVER OVERRIDE CONTROL SHALL BE PROVIDED ON THE BMS SYSTEM. ALLOWING PROGRAMMED OPERATING TIMES OF GROUP LUMINAIRES.

ALL LIGHTING SHALL BE PROVIDED IN ACCORDANCE WITH THE ARCHITECTS DETAILS AND FINISHES AND SHALL BE INSTALLED SO TO ALLOW FUTURE ACCESS TO ALL POWER SUPPLIES AND LAMPS FOR FUTURE MAINTENANCE.

THE CONTRACTOR SHALL ENSURE THAT ALL EXTERNAL LIGHTING, CONTAINMENT, SWITCHGEAR, LUMINAIRES, CABLING AND ACCESSORIES ARE INCLUDED FOR WITHIN THEIR TENDER QUOTATION.

									_
В	FEB.21	TENDER	R ISSUE					CS	L
А	DEC.20	ISSUED	FOR REVIEW					CS	L
REV	DATE	DESCRI	PTION					DR	C
			i 🛥		1			L	
							5 []		
			an			V			
F	RYDER	ARCI	HITECTS						
J	OB								
Ν	IOUNT	PLE	ASANT						
F	PHASE	2							
Ζ	1023								
D							TION		
E		RICAL	SERVICE	5	INS	ALLA	TION		
L	EVEL	10							
E	EXTERI	NAL L	IGHTING						
D	RAWING N	0./REVISIO	N						
M	IPP2 -	CAL -	- 22 - 1	0	- M2	- E	- 11	9 –	B
S	CALE / PRI	NTED AT	DATE		DRAWN		Снеск	ED	
1	:50@/	41	NOV'20		CS		LW		
U١	NIT 6 FOR	RESTGROV	E BUSINESS P	ARK	TEL:	0289069	9720 Fax	<:028906	541
Ne	EWTOWNB	reda Be	lfast BT8 6	SAW	Eм	AIL: adn	nin@caldwe	llconsultir	ng.

