

SPPARC DOOR SCHEDULE
1808-SPP-01-DR-A-P-31-XX-01-50

Project: Percy Street
Project No: 1808 Rev C01
Date: 07.09.2021
Issued for: Planning Condition 4 d)

DOOR NO.	FLOOR LEVEL	LOCATION	DESCRIPTION	DOOR TYPE	STRUCTURAL OPENING (W X H)	FIRE RATING	FIRE LINKED	HANDLE	LOCK	DOOR & FRAME FINISH	HINGES	CLOSER	ACCESSORIES	COMMENTS
D-B1-01	Basement Level	EXTERNAL VAULT	EXISTING VAULT ACCESS HATCH TO BE RETAINED	17	940 x 1780 mm	/	/	H.07	L.03	DF.05	BH.02	/	/	
D-B1-02	Basement Level	EXTERNAL VAULT	EXISTING VAULT ACCESS HATCH TO BE RETAINED	17	940 x 1780 mm	/	/	H.07	L.03	DF.05	BH.02	/	/	
D-B1-03	Basement Level	EXTERNAL VAULT	RETAINED AS EXISTING	17	940 x 1795 mm	/	/	H.07	L.03	DF.05	BH.02	/	/	
D-B1-04	Basement Level	EXTERNAL CUPBOARD	RETAINED AS EXISTING	8	1180 x 1750 mm	/	/	H.07	L.03	DF.05	BH.02	/	/	
D-B1-05	Basement Level	MAIN ENTRANCE DOOR	RETAINED AS EXISTING	11	1180 x 2295 mm	/	/	H.07	L.02	DF.05	BH.02	/	/	
D-B1-06	Basement Level	ELEC STORE	RETAINED AS EXISTING	8	1100 x 2520 mm	/	/	H.03	/	DF.05	BH.02	/	/	
D-B1-07	Basement Level	STORE	SOLID CORE DOOR	5	620 x 2105 mm	FD30S	/	H.01	/	DF.01	BH.01	/	/	
D-B1-08	Basement Level	RISER DOOR	SOLID CORE DOOR	6	620 x 2105 mm	FD30S	/	H.06	/	DF.01	BH.01	/	/	
D-B1-09	Basement Level	HALL	DOUBLE LEAF CRITAL STYLE GLAZED DOOR	14	1500 x 2100 mm	FD30S	/	H.05	/	DF.04	BH.03	/	/	FIRE RATING OF GLAZED DOORS SAID TO BE INHERINTLY 30MINS STANDARD
D-B1-10	Basement Level	WC	SOLID CORE DOOR WITH PANELS	3	810 x 2100 mm	FD30S	/	H.01	L.01	DF.01	BH.01	/	/	
D-B1-11	Basement Level	WC	SOLID CORE DOOR WITH PANELS	3	810 x 2100 mm	FD30S	/	H.01	L.01	DF.01	BH.01	/	/	
D-B1-12	Basement Level	HALL	SINGLE LEAF CRITAL STYLE GLAZED DOOR	4	960 x 2100 mm	FD30S	/	H.05	/	DF.04	BH.03	/	/	FIRE RATING OF GLAZED DOORS SAID TO BE INHERINTLY 30MINS STANDARD
D-B1-13	Basement Level	STORE	SOLID CORE DOOR	5	620 x 2105 mm	FD30S	/	H.01	/	DF.01	BH.01	/	/	
D-B1-14	Basement Level	HALL SEPERATION	SOLID CORE DOOR	11	940 x 2100 mm	FD30S	YES	H.01	/	DF.01	BH.01	/	/	ENTRY SYSTEM BY OTHERS
D-B1-15	Basement Level	WC	SOLID CORE DOOR	2	810 x 2100 mm	FD30S	/	H.01	L.01	DF.01	BH.01	/	/	
D-B1-16	Basement Level	COAT STORE	SOLID CORE DOOR	1	675.5 x 1415 mm	FD30S	/	H.06	/	DF.01	BH.05	/	/	
D-B1-17	Basement Level	UNDER STAIR STORAGE	SOLID CORE DOOR	1	675.5 x 1415 mm	FD30S	/	H.06	/	DF.01	BH.05	/	/	
D-B1-18	Basement Level	COMMS ROOM	SOLID CORE DOOR	2	610 x 2100 mm	FD30S	/	H.01	/	DF.08	BH.01	/	/	
D-B1-19	Basement Level	COMMS ROOM	SOLID CORE DOOR	2	610 x 2100 mm	FD30S	/	H.01	/	DF.08	BH.01	/	/	
D-B1-20	Basement Level	WC	SOLID CORE DOOR	2	810 x 2100 mm	FD30S	/	H.01	L.01	DF.08	BH.01	/	/	
D-0G-01	Ground Floor Level	MAIN ENTRANCE	SOLID CORE DOOR	7	1180 x 2295 mm	/	YES	H.04	L.02/L.05	DF.06	BH.01	CL.01	K.01/K.02	ENTRY SYSTEM BY OTHERS
D-0G-02	Ground Floor Level	BOARDROOM DOOR	RETAINED AS EXITING AND RE SWUNG	11	975 x 1910 mm	/	YES	H.01	/	DF.01	BH.01	CL.02	DS.01	
D-0G-03	Ground Floor Level	LIBRARY DOOR	RETAINED AS EXITING AND RE SWUNG	11	960 x 1885 mm	/	YES	H.01	/	DF.01	BH.01	CL.02	DS.01	
D-0G-04	Ground Floor Level	KITCHEN DOOR	SOLID CORE DOOR WITH GLAZED PANELS	15	820 x 1840 mm	FD30S	YES	H.01	/	DF.01	BH.01	/	/	
D-0G-05	Ground Floor Level	LIBRARY RISER	PLASTERBOARD FACING SOLID CORE RISER DOOR WITH CONCEALED FRAME	12.1	490 x 2100 mm	FD30S	/	H.06	/	DF.03	BH.06	/	/	
D-0G-06	Ground Floor Level	LIBRARY DOOR	DOUBLE LEAF SOLID CORE DOOR	8	810 x 2100 mm	/	/	H.06	/	DF.01	BH.01	/	/	
D-0G-07	Ground Floor Level	LIBRARY DOOR	RETAINED AS EXISTING	11	1095 x 2000 mm	/	/	H.01	/	DF.01	BH.01	/	DS.01	
D-0G-08	Ground Floor Level	STORE	RETAINED AS EXISTING	11	490 x 2105 mm	/	/	H.06	/	DF.01	BH.01	/	/	
D-0G-09	Ground Floor Level	RISER DOOR	RETAINED AS EXISTING	11	490 x 2105 mm	FD30S	/	H.06	/	DF.01	BH.05	/	/	EXISTING DOOR TO BE FIRE PROTECTED
D-0G-10	Ground Floor Level	BOARDROOM DOOR	RETAINED AS EXISTING	11	1095 x 2000 mm	/	/	H.01	/	DF.01	BH.01	/	DS.01	
D-0G-11	Ground Floor Level	BOARDROOM DOOR	RETAINED AS EXISTING (FIXED CLOSED)	11	1055 x 2000 mm	/	/	/	/	DF.01	BH.02	/	/	
D-0G-12	Ground Floor Level	EXTERNAL BASEMENT STREET ACCESS GATE	RETAINED AS EXISTING	20	800 x 1375 mm	/	YES	/	/	DF.07	BH.02	/	/	KEY LOCK TO BE REMOVED AND GATE TO OPEN AUTOMATICALLY IN CASE OF FIRE
D-01-01	First Floor Level	MAIN ROOM	RETAINED AS EXISTING	11	1000 x 2150 mm	/	YES	H.01	/	DF.01	BH.01	CL.02	DS.01	
D-01-02	First Floor Level	EXTERNAL TERRACE	EXTERNAL SOLID CORE DOOR WITH GLAZED ELEMENTS	10	1075 x 2416 mm	/	YES	H.08	L.04	DF.01	BH.01	/	/	REQUIRES AUTOMATED OPENING RE AOV REQUIREMENTS
D-01-03	First Floor Level	REAR ROOM	RETAINED AS EXITING AND RE SWUNG	11	870 x 2270 mm	/	YES	H.01	/	DF.01	BH.01	CL.02	DS.01	PORTION OF DOOR BASE TO BE REMOVED AS TO ALLOW FOR (APPROX 70mm) RAISED FLOOR TO REAR OFFICE
D-01-04	First Floor Level	MAIN ROOM/ REAR ROOM	RETAINED AS EXITING AND RE SWUNG	8	2370 x 2545 mm	/	/	H.09	/	DF.01	BH.04	/	/	
D-01-05	First Floor Level	REAR ROOM RISER DOOR	SOLID CORE DOOR CONCEALED IN JOINERY	12	620 x 2100 mm	FD30S	/	H.06	/	DF.01	BH.06	/	/	DOOR TO MATCH JOINERY WITH FIRE RATED BACKING
D-01-06	First Floor Level	ACCESS AND MAINTENNACE DOOR TO TERRACE	OPENING ELEMENT OF BALUSTRADE	16	850 x 1000 mm	/	/	/	/	/	/	/	/	IRONMONGERY BY SPECIALIST
D-02-01	Second Floor Level	FRONT OFFICE SPACE	RE USE AS EXISTING (Former Third Bedroom/ Front Left)	13	780 x 2500 mm	/	YES	H.02	/	DF.05	BH.05	CL.02	DS.01	
D-02-02	Second Floor Level	WC	RE USE AS EXISTING (Former Second Bedroom/ Front Right)	13	750 x 2500 mm	/	YES	H.02	L.01	DF.05	BH.05	CL.02	/	
D-02-03	Second Floor Level	STORE BENEATH STAIR	SOLID CORE DOOR	1	675.5 x 1415 mm	FD30S	YES	H.06	/	DF.01	BH.05	/	/	
D-02-04	Second Floor Level	REAR OFFICE	DOUBLE LEAF CRITAL STYLE GLAZED DOOR	21	1500 x 2310 mm	FD30S	YES	H.05	/	DF.04	/	/	DS.01	IRONMONGERY BY MANUFACTURER
D-02-05	Second Floor Level	REAR OFFICE/FRONT OFFICE	CRITAL STYLE GLAZED DOOR	22	815 x 2310 mm	FD30S	/	H.05	/	DF.04	/	/	DS.01	IRONMONGERY BY MANUFACTURER
D-02-06	Second Floor Level	FRONT OFFICE	CRITAL STYLE GLAZED DOOR	21	815 x 2310 mm	FD30S	YES	H.05	/	DF.04	/	/	DS.01	IRONMONGERY BY MANUFACTURER
D-02-07	Second Floor Level	REAR ROOM RISER DOOR	SOLID CORE DOOR CONCEALED IN JOINERY	12	620 x 2320 mm	FD30S	/	H.06	/	DF.01	BH.05	/	/	DOOR TO MATCH JOINERY WITH FIRE RATED BACKING
D-02-08	Second Floor Level	APARTMENT ENTRANCE	SOLID CORE DOOR WITH PANELS	26	920 x 2170	FD30S	/	/	/	/	/	/	/	
D-03-01	Third Floor Level	MEETING ROOM	CRITAL STYLE GLAZED DOOR	23	885 x 2480 mm	FD30S	YES	H.05	/	DF.04	/	/	DS.01	IRONMONGERY BY MANUFACTURER
D-03-02	Third Floor Level	WC	RETAIN AS EXISTING (Former/ current Bathroom)	9	910 x 2100 mm	FD30S	YES	H.02	L.01	DF.05	BH.05	/	/	
D-03-03	Third Floor Level	PRINTING ROOM DOOR	RE USE AS PER EXISTING (Former L3 pivot/Master bed)	24	1095 x 2490 mm	/	/	H.06	/	/	/	/	/	
D-03-04	Third Floor Level	BRAINSTORM ROOM	CRITAL STYLE GLAZED DOOR	23	885 x 2480 mm	FD30S	YES	H.05	/	DF.04	/	/	DS.01	IRONMONGERY BY MANUFACTURER
D-03-05	Third Floor Level	PRINTING AREA RISER DOOR	SOLID CORE DOOR CONCEALED IN JOINERY	12	620 x 2480 mm	FD30S	/	H.06	/	DF.01	BH.05	/	/	DOOR TO MATCH JOINERY WITH FIRE RATED BACKING
D-03-06	Third Floor Level	ROOF ACCESS (A&M only)	RE USE AS PER EXISTING (Former L3 WC)	13	800 x 2500	FD30S	/	/	/	/	/	/	/	
D-03-07	Third Floor Level	REAR OFFICE	CRITAL STYLE GLAZED DOOR	25	885 x 2480 mm	FD30S	/	/	/	/	/	/	/	
D-0R-01	Roof Level	ROOF ACCESS	METAL BALUSTRADE AND ASSOCIATED DOOR	19	900 x 800 mm	/	YES	/	/	DF.07	/	/	/	IRONMONGERY BY SPECIALIST MANUFACTURER
D-0R-02	Roof Level	REMOVABLE LOUVRES	PLANT	18	/	/	/	/	L.02	DF.04	/	/	/	IRONMONGERY BY SPECIALIST MANUFACTURER

DOOR FURNITURE SCHEDULE / SPECIFICATION

Project: Percy Street
Project No: 1808 PS Rev C01
Date: 07.09.2021
Issued for: CONSTRUCTION
