## Discharge of Ground Source Heat Pump Condition 22

## Branch Hill House, New Hampstead, London

Prepared for Almax Group 7<sup>th</sup> October 2021



# envision



Revision	Date			
A - First Issue	01/10/2021			
B – Minor Revision	07/10/2021			
Author	Signature			
Olabisi Sobowale	Gottett			
Checked & Authorised	Signature			
Ciaran Dorrity BEng (Hons) NDEA	lina los			

## DISCLAIMER

The opinions and interpretations presented in this report represent our best technical interpretation of the data made available to us. However, due to the uncertainty inherent in the estimation of all parameters, we cannot, and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, cost damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents, or employees.

Except for the provision of professional services on a fee basis, Envision Energy does not have a commercial arrangement with any other person or company involved in the interests that are the subject of this report.

Envision cannot accept any liability for the correctness, applicability, or validity for the information they have provided, or indeed for any consequential costs or losses in this regard. Our efforts have been made on a "best endeavours" basis and no responsibility or liability is warranted or accepted by Envision Energy Ltd.

London Office 0207 486 0680

Milton Keynes Office 01908 062819

Oxford Office 01865 598698

contact@envisioneco.com



## **CONTENTS**

PREFA	ICE	3
1.	SUMMARY OVERVIEW	4
APPEN	NDIX I – KENSA GSHP SERVICING, MAINTENANCE, WARRANTY OVERVIEW	7
	NDIX II – KENSA PLANT INFORMATION	8
APPEN	NDIX III – DRAWINGS	9
APPEN	NDIX IV – HEAT PUMP - METERING	.0



## PREFACE

### **NON-DISCLOSURE**

This document contains confidential information. In consideration of Envision Energy disclosing such confidential information this document should be held and maintained in confidence and should only be disclosed to:

- 1. The client
- 2. Professional advisors to the client
- 3. The Local Authority for the site location
- 4. The Environment Agency
- 5. Clients permitted assignees established by written assignment; and
- 6. Professional advisors of permitted assignees.

This document is issued only to the organisations stated above and on the understanding that this practice is not held responsible for the action of others who obtain any unauthorised disclosures of its contents or place any reliance on any part of its findings, fact, or opinions, be they specifically stated or implied.

The confidential information in this document shall only be used for the intended purpose.

## **FREEDOM OF INFORMATION**

Copies of this document may come into the possession of organisations designated under the Freedom of Information Act 2000. Organisations designated in the 'Act' are requested to respect the above statements relating to confidentiality and copyright.

#### ENQUIRIES

Any enquiries regarding this document shall be directed to ENVISION ENERGY LTD, telephone 01908 062819, email <u>contact@envisioneco.com</u>

#### COPYRIGHT © ENVISION ENERGY LTD

The material presented in this report is confidential. This report has been prepared for the exclusive use of the Client and shall not be distributed or made available to any other company or person without the knowledge and written consent of the Client or Envision Energy Ltd.



## 1. SUMMARY OVERVIEW

1.1 Envision has been appointed by Almax Group to discharge Condition 22 of planning permission 2019/6354/P for the installed ground source heat pumps (GSHP(s)) which requires:

"Prior to commencements of works, details, drawings, and data sheets showing the location, Seasonal Performance Factor of at least 2.5 and Be Green stage carbon saving of the ground source heat pumps and associated equipment to be installed on the building, shall have been submitted to and approved by the Local Planning Authority in writing. The measures shall include the installation of metering details including estimated costs to occupants and commitment to monitor performance of the system post construction. A site-specific lifetime maintenance schedule for each system, including safe access arrangements, shall be provided. The equipment shall be installed in full accordance with the details approved by the Local Planning Authority and permanently retained and maintained thereafter.

1.2 This note and appendices explains how the above conditions for GSHPs installed on the site have been met during Stage 3+ design.

## **Summary of Results**

- 1.3 In accordance with Condition 22 and following design development at RIBA Stage 3, the development is expected to achieve a Seasonal Performance factor of 3.29, greater than the required value of at least 2.5. This finding is explained further in this report.
- 1.4 For the 'Be Green' stage carbon saving of GSHPs, a 'Discharge of Energy & Sustainability conditions' report has been prepared and submitted alongside this report. It is shown to offset 39.22 tonnes of CO2 per annum.
- 1.5 The metering details will include estimated costs to applicants and display metering that will be recorded annually to monitor the performance of the system post-construction. This also allows for ease in keeping up with regular maintenance per annum and aligns with policies in the 'Be Seen' stage of the energy hierarchy from the London Plan Policy SI 2 'Minimising greenhouse gas emissions'.
- 1.6 The development is therefore deemed to be in full accordance with Condition 22 of planning permission 2019/6354/P and approved by the Local Planning Authority in writing.

envision

## **GSHP** Technical Information

- 1.7 The GSHPs and associated equipment to be installed in this development are from the Kensa series ground source heat pumps and a Kensa GSHP Servicing Maintenance Warranty Overview prepared and provided in Appendix I details the overview of servicing, maintenance, and warranty for a Kensa shared GSHP system.
- 1.8 The GSHP used has an ambient shared ground loop array which runs in very deep boreholes drilled into the ground and each apartment will have its own individual heat pump/hot water cylinder. This means that although the loop is shared across all apartments, tenants manage and pay their own bills.
- 1.9 The heat pump/hot water cylinder(s) will be installed in the tenants' demise MEP cupboards, with pipework to the required rooms for hot water and heating services. Detailed further in Appendix I is the full lifetime maintenance schedule, with the technical information for the GSHPs and the associated equipment prepared and provided in Appendix II.
- 1.10 All information in this report has been provided by Kensa who are designing the ambient loop pipework, hydraulics, boreholes, heat pump sizing and cylinder sizing.

## Proposed ambient loop pipework route.

- 1.11 The ambient loop pipework from the ground loop array will connect to multiple demises. The routes for the pipework ensures that staircases and lift shafts are avoided and the pipework does not pass through multiple demises. The MEP cupboard in the tenants' demise will be utilised for installing the heat pumps.
- 1.12 Pipework is distributed from the external ground loop array, into the plantroom and at high level via the risers to each apartments' MEP cupboard.
- 1.13 The locations of the heat pumps are provided in Appendix III.



## **Seasonal Performance Factor**

- 1.14 To obtain an actual Seasonal Performance Factor (SPF) of at least 2.5, the total energy output and total energy inputs will be measured via appropriate metering. Dividing the total output by the input will provide the actual in use SPF. As part of the London Plan 'Energy Assessment Guidance' with regards to heat pumps, a 'high specification of energy efficiency' is expected to ensure that the system 'operates efficiently and to reduce peak electricity demand'. The expected SPF value calculated by Kensa for their system is 3.29.
- 1.15 This shows that following design development at RIBA Stage 3, the development is expected to achieve a Seasonal Performance factor of 3.29, greater than the required value of at least 2.5 for Condition 22.

## 'Be Green' carbon saving

1.16 For the 'Be Green' stage carbon saving of GSHPs, an energy report has been prepared and submitted with the planning. It is shown to offset 39.22 tonnes CO2 per annum.

## 'Be Seen' energy monitoring guidance and measures for performance monitoring

- 1.17 In accordance with the 'Be Seen' post construction monitoring requirement of London Plan Policy SI 2 'Minimising GHG emissions', for a minimum of 5 years, monitoring and annual reporting of energy demand and carbon emissions will be measured as part of the energy strategy. To monitor the performance of the GSHPs, measures including a heat pump specific electric meter and heat meter will be installed as per the drawing in Appendix IV.
- 1.18 The monitoring will provide insight into the SPF and if it increases or decreases during usage and real tenant occupancy. It will also ensure that the actual carbon performance is meeting the expected performance approved during the planning stage, aligning with the 'Be Seen' policy.
- 1.19 The metering details will include estimated costs to occupants and display metering that will be recorded annually to monitor the performance of the system post-construction. This also allows for ease in keeping up with regular maintenance per annum.
- 1.20 The estimated costs to occupants will include the fuel used in the system, incentives, electricity sales (if applicable), plant replacement, an annual maintenance schedule, and overhead costs. These are shown below in Figure 1.1.

Unit	Average Running Cost	Incentives	Electricity Sales	Estimated Plant Replacement (@year 20)	Annual Maintenance (Approx.)	Annual Overheads (Approx.)
Typical Unit	£392.65	N/A	N/A	£3,000	£300	£100

#### Fig 1.1 – Average Running Costs



APPENDIX I – KENSA GSHP SERVICING, MAINTENANCE, WARRANTY OVERVIEW



**APPENDIX II – KENSA PLANT INFORMATION** 



## **APPENDIX III – DRAWINGS**



**APPENDIX IV – HEAT PUMP - METERING**