



Glazing 1	PLANICLEAR 4 mm
Cavity 1	Argon 90% 14 mm
Glazing 2	PLANITHERM XN PLANICLEAR 3 mm PVB STANDARD 0.38 mm PLANICLEAR 3 mm

Notes: 4 (14 Argon 90) 33.1 PLANITHERM XN, Ug=1,1

LUMINOUS FACTORS EN410 (2011-04)

Light Transmittance (TL)	81 %
Outdoor Reflectance (RLe)	11 %
Indoor Reflectance (RLi)	12 %

THERMAL TRANSMISSION EN673-2011

Ug	1.1 W/(m ² .K)
Angle relative to the vertical	0 °

MANUFACTURING SIZES

Nominal Thickness	24.38 mm
Weight	25.4 kg/m ²

ACOUSTICS EN 12758

Rw (C;Ctr)	N/A
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

SAFETY CLASS EN 12600

Pendulum Body Resistance	NPD/2B2
--------------------------	---------

ENERGY FACTORS EN410 (2011-04)

Transmittance (TE)	56 %
Outdoor Reflectance (Ree)	27 %
Indoor Reflectance (Rei)	23 %
Absorptance A1 (AE1)	7 %
Absorptance A2 (AE2)	11 %

SOLAR FACTORS EN410 (2011-04)

Solar Factor (g)	0.65
Shading Coefficient (SC)	0.75

COLOR RENDERING

Transmission (Ra)	98
Reflection (Ra)	97

ANTI-BURGLARY EN 356

Burglar Resistance	NPD
--------------------	-----