📌 bam	T	ba	m
-------	---	----	---

 x^{N}

 \mathbf{x}_{i}

Sample/Benchmark Approval

Form: Rev:

	Kings Cross	S3				Project No	: HLN0284
Submitted by:	BAM Service	s Engineerir	ng			Date	: 19-01-2022
Submitted to:	BAM Constru	ction				Ref No	: MEP/E/043
Туре:	Sample	e: X	Benchma	ark:	Mock	c-up:	<i>b</i>
Description: X Public realm	C Type Luminair	e					
Location for Ir BAM Project (e Location aft roject Office,	er Inspection:	
To be Built int	o the Works?	Yes] If YES Lo	ocation:	All areas		
Applicable Ce	rtification(s) (e.g.	BS, BBA cert e	ətc)				
AAC LEARST ST							In all relevant
	specifications. Te		omittal Ref:	BAMse-1	SE-0056 atta	ached.	
drawings and	specifications. Te Guthrie		omittal Ref:		SE-0056 atta		19/01/2022
drawings and Signed: <u>W</u> Project Team	specifications. Te Guthrie Comments: Js A	B C	Name:	BAMse-7 W Guthr Re-se	SE-0056 atta	Date:	
drawings and Signed: W Project Team Approval Statu	specifications. Te Guthrie Comments: us A	B C	Name:	BAMse-7 W Guthr Re-se	SE-0056 atta	Date:	
drawings and Signed: <u>W</u> Project Team	specifications. Te Guthrie Comments: us A oved; B – Approved v oved By: Na	B C with Comments	Name:	BAMse-T W Guthr Re-st	SE-0056 atta	Required	
drawings and Signed: W Project Team Approval Statu Legend: A – Appro Sample Appro Signed:	specifications. Te Guthrie Comments: us A oved By: ved By: Na Queg Na	B C vith Comments ame: Loca	Name: Name: ; C - Rejected ((CAU)) COME 2	BAMse-T W Guthr Re-su	SE-0056 atta	Required Date:	 ate: 𝒇((0?)/-

Figure 1.

	Light Source: Type: Wattage: Colour Temperature:	LED 19W 3000K	Light Source Ordering Manufacturer: Reference:	Information: N/A N/A
	Colour Rendering:	Ra 80+	Qty. per luminaire:	1no,
	Base: Lamp Lumens: (Im) Efficacy: (Im/W) Rated Life: Colour Consistency:	Integral LED 2700 lm N/A 100,000 hrs (L80B10 for LED) 2 MacAdam ellipse (LED only)	Notes:	Integral
12	Driver/ Ballast:		Driver Ordering Inform	
	Driver/Ballast type: IP Rating:	Integral N/A	Manufacturer: Catalogue Number:	N/A N/A
	Elec. Input:	230VAC	Max. quantity of	
	Output:	N/A	luminaires per driver:	N/A
	Maximum Current/Load Dimming Range: Control Protocol: Size: (if remote)	N/A 100% - 1% DALI N/A	Notes:	N/A
10	Weight: (if remote)	N/A		

Figure 2-

10	
Sheet Ref No: MEPE 043	an in the
Sample & Location: 53 Site office Company: IGUZZINI XC Lum	inatre
Signature/Date: WW 196	1/22
HLN 0284 King's Cross S3	ham

🕸 bam

Figure 3 –



Figure 4 –





Figure 5 –

