

Date

Name

Client

Project name

Quote#



Type/Quantity

25/02/2022 03:58:09

Specification Sheet

LOGIC S 24V 93055 13967 9330

[Weblink](#)



Cutout shape/size:  112 x 112 mm

Recessed depth: 125 mm

Available colors: ALU ANODIZED (13967 9330 ANO)

INCL.CABLE H05 RN-F 2 x 1mm² 0,5m

1 x LED 7,1W / CRI>90 / 3000K / 812lm

REFLECTOR WFL-55°

EXCL.LED POWER SUPPLY 24V-DC (non-dimmable)

INCL.IP68 CONNECTOR 3P

IEC 60598-2-13 : max.150kg 25N/cm²

ESG 5mm

Other CRI or KELVIN on request

LED Technics: Light source: 812 lm // 7 W // 115 lm/W
Luminaire: 710 lm // 8 W // 87 lm/W

24V-DC

Class: III

Weight: 1.1 KG

Protection level: IP67

Minimum distance: n.a.

Energy Class: E

Options: GENIE BOX 80 S / 90 S
CBOX

Requirements: LED POWER SUPPLY 24V-DC


For detailed installation instructions, please consult the manual. [13967_XXX0_HAND.pdf](#)

LOGIC S 24V 93055
13967 9330

Related references


LED POWER SUPPLIES

[Weblink / Specs sheet](#)



LED POWER SUPPLY 24V-DC / 150W
300 89 24 150
100-240V / 0/50-60Hz
Number of luminaires: 21

[Weblink / Specs sheet](#)




LED POWER SUPPLY 24V-DC / 24W
21012 0160
220-240V / 50-60Hz
Number of luminaires: 3

Related references

GROUND MOUNTING BOXES

[Weblink / Specs sheet](#)




GENIE BOX 80 S / 90 S
213 19 08

Related references

WATERPROOF CONNECTION PARTS

[Weblink / Specs sheet](#)



CBOX
216 12 00

LOGIC S 24V 93055
13967 9330

Related project picture of product family:

