BESPOKE CONCRETE PRODUCTS

CONCRETE MIX DESIGN SHEET

| PRODUCT | BCP WH02A - C40/50 |
|-------------------------------|-------------------------|
| DATE | 31/04/22 |
| CLIENT | Classic Masonry Limited |
| PROJECT 21 Maresfield Gardens | |
| Order No. | 2439 |

| Exposure Classes | XC4; XS1; XF3 |
|--------------------------------------|---|
| Characteristic Strength | 50N/mm2 |
| Minimum Cement Content | 380kg/m3 |
| Maximum Water/Cement Ratio | 0.38 |
| Type and class of cement combination | CEM I |
| Aggregate size | 10mm |
| Chloride Content | CI 0, 20 |
| Finish | Staircase - polished the etched. Other items etched |

Notes: all materials are fully in accordance with the relevant BS and EN standards.

| 300kg | White cement 52.5N to BS EN 197-1 |
|------------|--|
| 150kg | GGBS (Ecocem) |
| 1080 kg | 4 - 10mm White Limestone (Derbyshire) |
| 650 kg | Crushed white limestone - R6 (4mm to dust) |
| 50kg | Yellow Building Sand (Sherburn, Co Durham) |
| 2250ml | Plasticiser - Viscocrete 25MP |
| none | Rapid Strength - not required |
| none | Air Entrainment - not required |
| 170 litres | Water (depending on Moisture in Sand and Aggregates) |