



Liven Jansen &lt;liven@charltonbrown.com&gt;

## FW: Abby Rose - Vehicle Movements (In Relation To Spring Walk Wall)

**Mark Edgar** <mark@southdownssafety.co.uk>  
 To: Liven Jansen <liven@charltonbrown.com>  
 Cc: David Hayes <david.hayes@trenchco.co.uk>

28 April 2022 at 13:49

Hi Liven,

Please find the table below which shows the number of spoil removal vehicle movements for each size of construction vehicle.

As you can see, using the "smaller" vehicle would result in 3x the number of vehicle movements, obviously the use of any vehicle smaller than those detailed (i.e., a narrow-bodied vehicle) would result in a vastly increased number of vehicle movements to those detailed within the table.

TOTAL m <sup>3</sup> OF SPOIL TO BE REMOVED		1800m <sup>3</sup>		
VEHICLE DESCRIPTION	VEHICLE LENGTH	VEHICLE WIDTH	VEHICLE CAPACITY (m <sup>3</sup> )	NUMBER OF REQUIRED MOVEMENTS
a. 4 Axle Rigid Spoil	10.66m	2.49m	12	150
b. 2 Axle Rigid Spoil	6.97m	2.40m	4	450

Please let me know if you need anything further from me with regards to this issue.

Kind regards,

Mark Edgar

Planning Support Consultant

[South Downs Safety Ltd](#)

E: [mark@southdownssafety.co.uk](mailto:mark@southdownssafety.co.uk)

M: 07545 898 726



Company Registration No. 8018675