


<b>TITLE:</b> <b>The Conservation Rooflight®</b> > A roof window range suitable for pitched roofs between 17.5° and 65° > Detail applicable ONLY to rooflight models with integral casement timber linings <b>Warm Roof   Slate Tile   Lead Soakers</b> <b>'Between the rafter' installation detail</b>	<b>DWG NO.:</b> CR_WRSF_LS_A	<b>SHEET NO.:</b> 1 OF 2	<b>REVISION:</b> <div style="font-size: 2em; font-weight: bold; text-align: center;">A</div>	 <b>the Rooflight Company</b> <i>The Professionals' Choice</i> w: www.therooflightcompany.co.uk t: 01993 833 108 e: info@therooflightcompany.co.uk
	<b>SCALE:</b> 1:5 @ A3 DO NOT SCALE	<b>DATE:</b> 24/07/2014	New at first issue DB:EH CB:PD	
This is a suggested installation detail which may not be exactly applicable to all situations and constructions. It is not a detailed or constructional proposal. Installers and designers are advised to check their own details for compliance with all currently applicable Local Authority by-laws, Acts of Parliament and British / ISO standards.			All information contained within this drawing is copyright © and design right of the Rooflight Company. The intellectual property rights of the products detailed within this drawing and embedded 3D models are owned by the Rooflight Company.	