



LOGIC 40 R MOON 93015

13956 9310



[Link da web](#)



Formato/tamanho recortado:  43 mm

Profundidade de encastramento: 85 mm

Cores disponíveis: ALUMINIO ANODIZADO (13956 9310 ANO)

1 x LED 3,9W / CRI>90 / 3000K / 385lm

REFLECTOR SP-15°

INCL. 1 x CABLE H05 RN-F 2 x 1mm² 0,5m

EXCL. LED POWER SUPPLY 350mA-DC

IEC 60598-2-13 : max. 150kg 25N/cm²

ESG 6mm

Other CRI or KELVIN on request

Technics LED: Fonte de luz: 385 lm // 3 W // 98 lm/W
Luminária: 85 lm // 5 W // 19 lm/W

Classe: III

Peso: 0.2 KG

Nível de proteção: IP67

Distância mínima: n.a.

Opções: LOGIC 40 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Requisitos: LED POWER SUPPLY 350mA-DC DIM

Para obter instruções de instalação detalhadas, por favor consulte o manual. [13956_XXX0_HAND.pdf](#)



NOTE: Supplier to provide 2700K colour temperature to all light fittings

OBLIX R 70 930

15121 9300



Weblink



Available colors: DARK GREY (15121 9300 N)

1 x LED 7,1W / CRI>90 / 3000K / 812lm
INCL.LED POWER SUPPLY 350mA-DC
Other CRI or KELVIN on request

LED Technics: Light source: 812 lm // 7 W // 115 lm/W
Luminaire: 587 lm // 8 W // 72 lm/W

120-240V / 50-60Hz

Class: II

Weight: 4.3 KG
Protection level: IP55
Minimum distance: n.a.


Options: PIN 3
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual. [15121 XXXX HAND.pdf](#)

NOTE: Supplier to provide 2700K colour temperature to all light fittings

SPIX M 93030

29715 9330



Available colors:	DARK GREY (29715 9330 N)
ADJUSTABLE 90°/360° 1 x LED 3,9-8,2W / CRI>90 / 3000K / 385-677lm LENS FL-30° EXCL.LED POWER SUPPLY 350-700mA-DC Other CRI or KELVIN on request	
LED Technics:	Light source: 677 lm // 8 W // 83 lm/W Luminaire: 9 W
Class:	III
Weight:	0.5 KG
Protection level:	IP65
Minimum distance:	n.a.
Energy Class:	G
Accessories:	KAP STRIPER
Requirements:	LED POWER SUPPLY 350 / 500 / 700mA-DC DIM
For detailed installation instructions, please consult the manual. 29715_XXX0_HAND.pdf	



NOTE: Supplier to provide 2700K colour temperature to all light fittings

ENTERO SQ-S X 92720

28539 9220



WebLink



0-20°/355°



Cutout shape/size:  76 x 76 mm

Recessed depth: 110 mm

Thickness of mounting surface: 12,5 or 25

Available colors: BLACK (28539 9220 B)
WHITE (28539 9220 W)

ADJUSTABLE 0-20°/355°

1 x LED 5,8-8,6W / CRI>90 / 2700K / 753-1041lm

REFLECTOR FL-20°

EXCL.LED POWER SUPPLY 350-500mA-DC

LED Technics: Light source: 1041 lm // 8 W // 121 lm/W
Luminaire: 630 lm // 10 W

Class: III

Weight: 0.285 KG

Protection level: IP65

Minimum distance: n.a.

Accessories: ENTERO S HONEYCOMB
ENTERO S LINEAR SPREAD LENS
ENTERO S SPREAD LENS
ENTERO S SOFTENING LENS
ENTERO S GLASS SBL

Requirements: LED POWER SUPPLY 350 / 500mA-DC DIM

For detailed installation instructions, please consult the manual: [28539_XXX0_HAND.pdf](#)

NOTE: Supplier to provide 2700K colour temperature to all light fittings